

CERTIFICATE OF COMPLIANCE

Certificate Number E60425
Report Reference E60425-20050718
Date 2022-January-03

Issued to: PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8
Blomberg 32825 DE

This is to certify that
representative samples of TERMINAL BLOCKS - COMPONENT
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL1059 and CAN/CSA C22.2 No. 158-10 Terminal Blocks

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number E60425
Report Reference E60425-20050718
Date 2022-January-03

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Component terminal blocks, Cat. Nos. MCO1.5 followed by /1 or 2 digit number, and by Suffix -GL or -GR, followed by -3.81.

Socket - Cat. Nos. MCO 1.5 followed by /3, /4 or /5 and by Suffix -G1L or -G1R, followed by -3.5 for use with Model MC1.5 header.

Header - Cat. No. MCO1.5 followed by one or two digit number, followed by -GL or -GR, followed by -3.81, followed by -SI, followed by -BK, followed by any alphanumeric code.

Cat. Nos. MSTBO followed by Suffix 2.5 followed by /single digit number, followed by -GL, -GR, may be followed by -5.08.

Cat. Nos. MSTBO followed by Suffix 2.5 followed by /single digit number; followed by -G1L or -G1R; followed by OO, KO, or OK; followed by P+F, may be followed by -5.08.

Cat. Nos. MSTBO followed by Suffix 2.5 followed by /single digit number, followed by -G1L, or -G1R, with or without -THR, may be followed by -5.08.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>