

Certificate of Compliance

Certificate Number:

UL-US-2424650-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITTB(S), PTO, etc	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424650-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2424669-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Block

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITTB(S), PTO, etc	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424669-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2424706-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Block

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITTB(S), PTO, etc	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424706-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2424717-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Block

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITTB(S), PTO, etc	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424717-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2424723-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Block

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITTB(S), PTO, etc	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424723-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2424716-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Block

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITTB(S), PTO, etc	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424716-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2424718-3

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059 - Terminal Block

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBKKB2.5-PV, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
PTTB 4-PE, PITTB 4-PE(@@), All PIT(S), PITTB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex. - PT, PITTB(S), PTO, etc	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBO 6 W35, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
RBOC 12/8, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
ST2.5-L/L/N, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
T 4-QUATTRO, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

Terminal blocks may not be shipped with all terminals removed.	
TB10 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB10 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB16 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB35-PE EI, TB35-PE I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

TB6 I, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/S-Ben, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2424718-3
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-L60425-618711-
02406791-3

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-618711-02406791-3
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6)	Terminal Blocks - Component
BT 14	Terminal Blocks - Component
BT 14-F	Terminal Blocks - Component
BT 2.0(6)	Terminal Blocks - Component
BT 3.5(6)	Terminal Blocks - Component
BT 5.5(6)	Terminal Blocks - Component
BT 5.5-F(6)	Terminal Blocks - Component
BTH 1.25(6)	Terminal Blocks - Component
BTH 2.0(6)	Terminal Blocks - Component
BTH 3.5(6)	Terminal Blocks - Component
BTO 1.25(6)	Terminal Blocks - Component
BTO 14	Terminal Blocks - Component
BTO 14-F	Terminal Blocks - Component
BTO 2.0(6)	Terminal Blocks - Component
BTO 3.5(6)	Terminal Blocks - Component
BTO 38	Terminal Blocks - Component
BTO 38-F	Terminal Blocks - Component
BTO 5.5(6)	Terminal Blocks - Component
BTO 5.5-F(6)	Terminal Blocks - Component
BTP 1.25(6)	Terminal Blocks - Component
BTP 2.0(6)	Terminal Blocks - Component
BTP 3.5(6)	Terminal Blocks - Component
G5(1)	Terminal Blocks - Component
GTF76/230	Terminal Blocks - Component
GTF76/48	Terminal Blocks - Component
K10(2)	Terminal Blocks - Component
K16, K16/E	Terminal Blocks - Component
K2.5(2)	Terminal Blocks - Component
K25, K25/E	Terminal Blocks - Component
K3(2)	Terminal Blocks - Component
K4(2)	Terminal Blocks - Component
K4-TG(2)	Terminal Blocks - Component
K5(2)	Terminal Blocks - Component
MBK	Terminal Blocks - Component
MBK10	Terminal Blocks - Component
MBK2.5/E	Terminal Blocks - Component
MBK2.5/E-PE	Terminal Blocks - Component
MBK3	Terminal Blocks - Component
MBK3/E-Z-PE	Terminal Blocks - Component
MBK5, MBK5/E	Terminal Blocks - Component
MBK5/E-FS	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-618711-02406791-3
Report reference E60425-19760420
Date 2025-02-14

MBK5/E-FS/FS	Terminal Blocks - Component
MBKKB2.5-PV	Terminal Blocks - Component
PLA 5/X-7.5 -ZB, PLA 5/X-7.5 -ZF, PLH 5/X-7.5 -ZB, PLH 5/X-7.5 -ZF	Terminal Blocks - Component
PTTB 4-PE, PITTB 4-PE(@@)	Terminal Blocks - Component
QTC1.5, -TG (#), -QUATTRO, -TWIN, /1P	Terminal Blocks - Component
RBO 3 SP/SP	Terminal Blocks - Component
RBO 6 W35	Terminal Blocks - Component
RBOC 12/8	Terminal Blocks - Component
SPT-MODULAR 1237697: SPT 2.5/X-V-5.0	Terminal Blocks - Component
SSK/N0525-LB1(3)	Terminal Blocks - Component
SSK0525-TG(3)	Terminal Blocks - Component
SSK110(3)	Terminal Blocks - Component
SSK116(3)	Terminal Blocks - Component
SSK125(3)	Terminal Blocks - Component
SSK135(3)	Terminal Blocks - Component
SSK5(3)	Terminal Blocks - Component
ST-1N4007	Terminal Blocks - Component
ST-BE	Terminal Blocks - Component
ST-BE-VIERPOL	Terminal Blocks - Component
ST-Si(4)	Terminal Blocks - Component
ST2.5-L/L/N	Terminal Blocks - Component
T 4-QUATTRO	Terminal Blocks - Component
TB10 EI	Terminal Blocks - Component
TB10 I	Terminal Blocks - Component
TB16 EI	Terminal Blocks - Component
TB35-PE EI, TB35-PE I	Terminal Blocks - Component
TB4-2L-HESILED 60 (5x20) I lower level	Terminal Blocks - Component
TB6 EI	Terminal Blocks - Component
TB6 I	Terminal Blocks - Component
UDK 3 / TB 2,5-QUATTRO C, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4 / TB 4-QUATTRO C, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-618711-02406791-3
Report reference E60425-19760420
Date 2025-02-14

multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
UDK4	Terminal Blocks - Component
UDK4-ILA1000	Terminal Blocks - Component
UDK4-ILA500	Terminal Blocks - Component
UDK4-ULA(5)	Terminal Blocks - Component
UGSK/S	Terminal Blocks - Component
UGSK6	Terminal Blocks - Component
URDK6	Terminal Blocks - Component
URTK/S	Terminal Blocks - Component
URTK/S-Ben	Terminal Blocks - Component
URTK/S-Ben 10, URTK/S-BEN 10-TK	Terminal Blocks - Component
URTK/SP	Terminal Blocks - Component
URTK/SS	Terminal Blocks - Component
URTK6	Terminal Blocks - Component
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250, LA 250 f/b (5x20) w/wo 120KOHM	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419389-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419389-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419397-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419397-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419392-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419392-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419386-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419386-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419394-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419394-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419405-0

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419405-0
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2419399-3

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CAN/CSA C22.2 No. 158 -Terminal Blocks

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BT 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BT 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 2.0(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTH 3.5(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 1.25(6), Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 14, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
BTO 14-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 38, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 38-F, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
BTO 5.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTO 5.5-F(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 1.25(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 2.0(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
BTP 3.5(6), Followed by 1.5/5-ST-3.81, followed by - KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
G5(1), With or without suffixes BK, BU or GNYE.	Terminal Blocks - Component
GTF76/230, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
GTF76/48, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K10(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K16, K16/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K2.5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K25, K25/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
K3(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K4-TG(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
K5(2), Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.	Terminal Blocks - Component
MBK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK10, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK2.5/E-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK3/E-Z-PE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	
MBK5, MBK5/E, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
MBK5/E-FS/FS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
SSK/N0525-LB1(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK0525-TG(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK110(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK116(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK125(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK135(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
SSK5(3), With suffix -LED 24 N, LED 60 N, LED 250 N.	Terminal Blocks - Component
ST-1N4007, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

ST-BE, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-BE-VIERPOL, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
ST-Si(4), Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UDK 4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK3, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

UDK4-ILA1000, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ILA500, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4-ULA(5), Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.	Terminal Blocks - Component
UGSK/S, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UGSK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URDK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2419399-3
Report reference E60425-19760420
Date 2025-02-14

URTK/S-Ben 10, URTK/S-BEN 10-TK, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SP, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK/SS, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
URTK6, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-L60425-618911-
02406791-3

Report Reference:

E60425-19760420

Issue Date:

2025-02-14

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2023-12

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-618911-02406791-3
Report reference E60425-19760420
Date 2025-02-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BT 1.25(6)	Terminal Blocks - Component
BT 14	Terminal Blocks - Component
BT 14-F	Terminal Blocks - Component
BT 2.0(6)	Terminal Blocks - Component
BT 3.5(6)	Terminal Blocks - Component
BT 5.5(6)	Terminal Blocks - Component
BT 5.5-F(6)	Terminal Blocks - Component
BTH 1.25(6)	Terminal Blocks - Component
BTH 2.0(6)	Terminal Blocks - Component
BTH 3.5(6)	Terminal Blocks - Component
BTO 1.25(6)	Terminal Blocks - Component
BTO 14	Terminal Blocks - Component
BTO 14-F	Terminal Blocks - Component
BTO 2.0(6)	Terminal Blocks - Component
BTO 3.5(6)	Terminal Blocks - Component
BTO 38	Terminal Blocks - Component
BTO 38-F	Terminal Blocks - Component
BTO 5.5(6)	Terminal Blocks - Component
BTO 5.5-F(6)	Terminal Blocks - Component
BTP 1.25(6)	Terminal Blocks - Component
BTP 2.0(6)	Terminal Blocks - Component
BTP 3.5(6)	Terminal Blocks - Component
G5(1)	Terminal Blocks - Component
GTF76/230	Terminal Blocks - Component
GTF76/48	Terminal Blocks - Component
K10(2)	Terminal Blocks - Component
K16, K16/E	Terminal Blocks - Component
K2.5(2)	Terminal Blocks - Component
K25, K25/E	Terminal Blocks - Component
K3(2)	Terminal Blocks - Component
K4(2)	Terminal Blocks - Component
K4-TG(2)	Terminal Blocks - Component
K5(2)	Terminal Blocks - Component
MBK	Terminal Blocks - Component
MBK10	Terminal Blocks - Component
MBK2.5/E	Terminal Blocks - Component
MBK2.5/E-PE	Terminal Blocks - Component
MBK3	Terminal Blocks - Component
MBK3/E-Z-PE	Terminal Blocks - Component
MBK5, MBK5/E	Terminal Blocks - Component
MBK5/E-FS	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-618911-02406791-3
Report reference E60425-19760420
Date 2025-02-14

MBK5/E-FS/FS	Terminal Blocks - Component
SSK/N0525-LB1(3)	Terminal Blocks - Component
SSK0525-TG(3)	Terminal Blocks - Component
SSK110(3)	Terminal Blocks - Component
SSK116(3)	Terminal Blocks - Component
SSK125(3)	Terminal Blocks - Component
SSK135(3)	Terminal Blocks - Component
SSK5(3)	Terminal Blocks - Component
ST-1N4007	Terminal Blocks - Component
ST-BE	Terminal Blocks - Component
ST-BE-VIERPOL	Terminal Blocks - Component
ST-Si(4)	Terminal Blocks - Component
UDK 3 / TB 2,5-QUATTRO C, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK 4 / TB 4-QUATTRO C, All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.	Terminal Blocks - Component
UDK4	Terminal Blocks - Component
UDK4-ILA1000	Terminal Blocks - Component
UDK4-ILA500	Terminal Blocks - Component
UDK4-ULA(5)	Terminal Blocks - Component
UGSK/S	Terminal Blocks - Component
UGSK6	Terminal Blocks - Component
URDK6	Terminal Blocks - Component
URTK/S-Ben 10, URTK/S-BEN 10-TK	Terminal Blocks - Component
URTK/SP	Terminal Blocks - Component
URTK/SS	Terminal Blocks - Component
URTK6	Terminal Blocks - Component



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

File E60425	Vol. 1	Sec. 1	Page 1	Issued: 1976-04-20
	Vol. 4	Sec. 5		Revised: 2025-02-13
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		

and Report

DESCRIPTION

PRODUCT COVERED:

USR, CNR - Types G5 followed by Suffixes /2, /3, /4, /6, /12, /2B. Types K2.5 with or without Suffixes /E, /M; Type K3 with or without Suffixes /E, /M; Types K4 with or without Suffixes -TG, /E, /M; Type K5 with or without Suffixes /E, /M; Type K10 with or without Suffixes /E, /M; Type K16, K16/E, K25, K25/E. Types MBKKB2.5, MBKKB2.5-PV. Types MBK with or without Suffixes 2.5/E, 3, 5, 5/E, 5/E-FS, 5/E-FS/FS, 10. Types SSK with or without Suffixes 0525-TG, 110, 116, 125, 135, 5, /N 0525-L/B1, may be followed by Kri. Fuse block Type ST-Si may be followed by Suffixes LED12, LED24, LED60, LA250, followed by Suffix -UK4, Type UDK3 **or TB 2,5-QUATTRO C**, with or without suffix 120 KOHM. Types UDK4 **or TB 4-QUATTRO C** with or without Suffixes -ILA500, -ILA1000, ULA-12RD/0-U, -ULA230RD/0-U, ULA-24RD/0-U, -ULA24GN/0-U, -ULA-48RD/0-U, ULA-60RD/0-U, -ULA230, -ULA500, -ULA/EK: Types URTK/S, /S-Ben, /S-Ben 10, /SS, /SP. Types UGSK/S, GTF76/230, GTF76/48. Types ST-BE, ST-BE-VIERPOL, ST-1N4007. Types URDK6, URTK6, UGSK6.

USR, CNR - Barrier Types terminal block BT 1.25, BT 2.0, BT 3.5, BTO 1.25, BTO 2.0, BTO 3.5, BTP 1.25, BTP 2.0, BTP 3.5, BTH 1.25, BTH 2.0, BTH 3.5 with or without Suffix -F. BT 5.5, BT 5.5-F, BTO 5.5, BTO 5.5-F, BT 14, BT 14-F, BTO 14, BTO 14-F, BTO 38, BTO 38-F.

Protective conductor terminal blocks, Cat. Nos. MBK2.5E-PE, MBK3/E-Z-PE.

Note -

USR - Products designated USR have been investigated using US requirements as noted in the Test Record.

CNR - Products designated CNR have been investigated using Canadian requirements as noted in the Test Record.

GENERAL:

These are single pole terminal blocks for rail mounting. They may be grouped together to form multipole units of unlimited length. These devices are intended for general industrial applications. The pressure wire connectors are suitable for field and factory wiring within the ratings specified. Fuse block Type ST-Si is suitable for factory wiring only, since this block is a plug-in component used in combination with specific terminal blocks covered by this report.

Ratings - Type	Wire Range AWG-Cu	Max Current, A	Max V	Torque (lb-in)
G5 with Suffixes	Nos. 26-10	30	300	5-7
K2.5 with or without Suffixes	Nos. 30-14	15	300	5-7
K3 with or without Suffixes	Nos. 28-12	20	600	5-7
K4/E, K4/M	Nos. 28-12	20	600	5-7
K4-TG	Nos. 28-12	20	300	5-7
K5 with or without Suffixes	Nos. 26-10	30	600	5-7
K10 with or without Suffixes	Nos. 26-8	50	600	11-15
K16, K16/E	Nos. 24-6	65	600	11-15
K25, K25/E	Nos. 22-4	85	600	18-25
MBK	Nos. 30-14	15	300	5-7
MBK2.5/E	Nos. 30-12	20	300	5-7
MBK3/E-Z-PE	Nos. 30-12	-	-	5-7
MBK3	Nos. 28-12	20	600	5-7
MBKKB2.5, -PV	Nos. 30-12	20	300	5-7
UGSK/S	Nos. 26-8	50	600	11-15
GTF76/230	Nos. 26-8	50	250	11-15

File E60425	Vol. 1	Sec. 1	Page 1A	Issued: 1976-04-20
	Vol. 4	Sec. 5		Revised: 2025-02-13
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		

and Report

Ratings -

Type	Wire Range AWG-Cu	Max Current, A	Max Voltage (V)	Torque (lb-in)
GTF76/48	Nos. 26-8	50	50	11-15
MBK5, MBK5/E	Nos. 26-10	30	600	5-7
MBK5/E-FS, -FS/FS	Nos. 26-10	5	300-	5-7
MBK10	Nos. 26-8	50	600	11-15
SSK0525-TG	Nos. 28-12	20	300	5-7
SSK110	Nos. 26-8	50	600	11-15
SSK116	Nos. 24-6	65	600	11-15
SSK125	Nos. 22-4	85	600	18-25
SSK135	Nos. 18-2	115	600	30-50
SSK5	Nos. 26-10	30	600	5-7
SSK/N0525-L/B1	Nos. 28-12	20	600	5-7
ST-Si Series	-	10	300-	-
UDK3 or TB 2,5-QUATTRO C	Nos. 30-12	20	300/	5-7
UDK4 or TB 4-QUATTRO C	Nos. 30-10	(2)	600-	5-7
UDK4-ILA500	Nos. 30-10	0.5	600-	5-7
UDK4-ILA1000	Nos. 30-10	1.0	600-	5-7
UDK4-ULA with suffixes	Nos. 30-10	(2)	600-	5-7
URTK/S, /S-Ben	Nos. 26-8	50	300	11-15
URTK/SS	Nos. 28-12	20	300	5-7
URTK/S-Ben 10, URTK/S-Ben 10-TK	Nos. 26-8	57 (3)	600	10-16
URTK/SP	Nos. 26-8	45	300	13-16
ST-BE	Nos. 30-14	10	300	5-7
ST-BE-VIERPOL	Nos. 30-14	10	300	5-7
ST-1N4007	Nos. 30-14	1	300	5-7
URDK6	Nos. 26-8	50	300	15
URTK6	Nos. 26-8	50	300	15
UGSK6	Nos. 26-8	50	300	15

- (1) Field-wiring: Nos. 18-2, Factory-wiring: Nos. 18-1/0
- (2) Field-wiring: 30 A max, Factory-wiring: 35 A max
- See spacings table for current limitations.
- (3) 50 A max for field-wiring applications

and Report

Ratings:

Type	Wire Range (Copper, Str/Sol)	Current (A)	Voltage (V)	Torque (Nm)	UG
BT 1.25	26-16	10	600	0.6 - 1.0	B,C
BT 2.0	26-14	15	600	1.0 - 1.3	B,C
BT 3.5	26-10	30	600	1.4 - 2.0	B,C
BTO 1.25	26-16	10	600	0.6 - 1.0	B,C
BTO 2.0	26-14	15	600	1.0 - 1.3	B,C
BTO 3.5	26-10	30	600	1.4 - 2.0	B,C
BTP 1.25	26-16	10	300	-	B,C
BTP 2.0	26-14	15	600	-	B,C
BTP 3.5	26-12	20	600	-	B,C
BTH 1.25	26-16	10	300	0.6 - 1.0	B,C
BTH 2.0	26-14	15	600	1.0 - 1.3	B,C
BTH 3.5	26-12	20	600	1.4 - 2.0	B,C
BT 1.25-F	26-16	10	600	0.6 - 1.0	B,C
BT 2.0-F	26-14	15	600	1.0 - 1.3	B,C
BT 3.5-F	26-10	30	600	1.4 - 2.0	B,C
BTO 1.25-F	26-16	10	600	0.6 - 1.0	B,C
BTO 2.0-F	26-14	15	600	1.0 - 1.3	B,C
BTO 3.5-F	26-10	30	600	1.4 - 2.0	B,C
BTP 1.25-F	26-16	10	300	-	B,C
BTP 2.0-F	26-14	15	600	-	B,C
BTP 3.5-F	26-12	20	600	-	B,C
BTH 1.25-F	26-16	10	300	0.6 - 1.0	B,C
BTH 2.0-F	26-14	15	600	1.0 - 1.3	B,C
BTH 3.5-F	26-12	20	600	1.4 - 2.0	B,C
BT 5.5	24-8	40	600	1.4 - 2.0	B,C
BT 5.5-F	24-8	40	600	1.4 - 2.0	B,C
BTO 5.5	24-8	40	600	1.4 - 2.0	B,C
BTO 5.5-F	24-8	40	600	1.4 - 2.0	B,C

Strip length for BTP 1.25 is 8-9 mm.

Strip length for BTP 2.0 is 10-12 mm.

Strip length for BTP 3.5 is 10-12 mm.

8 AWG wire used is compact copper stranded

Ratings (Continued): -

Type	Wire Range (Copper, Str/Sol)	Current (A)	Voltage (V)	Torque (Nm)	UG
BT 14	20 - 6	60	600	2.6 - 3.7	B,C
BT 14-F	20 - 6	60	600	2.6 - 3.7	B,C
BTO 14	20 - 6	60	600	2.6 - 3.7	B,C
BTO 14-F	20 - 6	60	600	2.6 - 3.7	B,C
BTO 38	20 - 2	100	600	10 - 13.5	B,C
BTO 38-F	20 - 2	100	600	10 - 13.5	B,C

6, 2 AWG wire used is compact copper stranded

The terminal blocks tabulated below have optional 3-phase short circuit current ratings. The Terminal Blocks must be protected by the max ampere and Class of overcurrent protective device noted below.

Cat. No.	Suitable Conductors kcmil/AWG Str.		Overcurrent Protection Fuse Required Class/Max Amp Rating						SCCR, RMS Sym A	Volts Max
	Line	Load	J	T	RK1	RK5	G	CC		
UDK 4 or TB 4- QUATTRO C	14-10 Cu	14- 10 Cu	60	60	-	-	30	30	100,000	600

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in products where the acceptability is determined by Underwriters Laboratories Inc.

Conditions of Acceptability -

1. The mounting suitability shall be determined in the end-use.
2. The insulating bodies are molded of Recognized Component polymeric materials (QMFZ2). Identification of these plastic materials by manufacturer's name, Grade designation, maximum operating temperature, and flame rating are specified in the "Section General" pages in this Procedure. The acceptability of these materials shall be judged in the end use application.
3. These devices are suitable for general industrial use, within the above ratings.
4. These devices may be suitable for other than general industrial use providing spacings insulating materials, etc., are acceptable in the end-use.
- 4A. The pressure wire connectors for all Cat. Nos. comply with field-wiring requirements in UL 486E Standard for Equipment Wiring Terminals.
5. The tightening torque for field wiring pressure wire connector terminals is recorded in the Ratings section of this Report. This torque value shall be marked on the end-use product for those categories which require torque markings for field terminated conductors.
6. Types MBK5/E-FS and -FS/FS have male quick-connect terminals. The suitability of connections to these terminals shall be determined in the end-use. The quick-connect terminals are for factory-wiring only.
7. **The suitability of jumpers used with Types MBK5/E-FS, -FS/FS, K4-TG, UK4-TG and SSK0525-TG; shall be determined in the end-use.**
8. **The connectors of Type G5/2-B are combined.**

File E60425	Vol. 1	Sec. 1	Page 2A	Issued: 1976-04-20
	Vol. 4	Sec. 5		Revised: 2017-12-01
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		

and Report

9. The suitability of the internal circuitry of ST-SiLED, ST-SiLA, UDK4-ULA, and UDK4-ILA series terminal blocks have not been investigated and shall be determined in the end-use.

10. Fuse block Type ST-Si is a plug-in component intended for use with terminal block Cat. Nos. K4-TG, SSK0525-TG and UK4-TG. The contact terminals of the ST-Si series devices are to be factory wired only and the suitability of the connection shall be determined in the end-use.

11. Type ST-Si devices are intended for 5 mm by 20 mm miscellaneous fuses. The suitability of the fuses shall be determined in the end-use. They are not intended for branch circuit protection. Markings concerning fuse replacement and location should be considered in the end-use products.

12. Cat. Nos. URTK/SP, URTK6, UGSK6, employ a thermoplastic cupped washer as part of the sliding-link disconnect screw. The suitability of this construction (thermoplastic sandwiched between screwhead and current bar) has not been evaluated and shall be judged in the end-use equipment.

13. Grounding type terminal blocks, Cat. Nos. MBK2.5/E-PE, MBK3/E-Z-PE comply with short time current requirements in UL 467 Standard for Grounding and Bonding Equipment.

The Grounding terminals comply with requirements for protective conductor terminal blocks, in UL 1059 Standard for Terminal Blocks.

14. Cat. Nos. GTF76/230 and GTF76/48 - The suitability of the neon lamps and LED's, including rating, marking, mechanical securement, and insulating sleeving shall be determined in the end-use equipment.

15. Types ST-BE, ST-BE-VIERPOL, ST-1N4007 component holder plug-in blocks for use with the manufacturer's terminal blocks which accommodate fused or non-fused plug-in disconnect modules. The mounting suitability shall be determined in the end-use equipment.

16. The suitability of electrical components used with plug-in component holders Types ST-BE, ST-BE-VIERPOL, ST-1N4007 shall be evaluated in the end-use equipment.

17. Terminal block types BT, BTO and BTH series are intended to be used with suitable prepared conductors and are intended for use with certified pressure terminal connectors.

18. The terminal block types BT 5.5, BT 5.5-F, BTO 5.5, BTO **5.5-F**, **BT 14**, **BT 14-F**, **BTO 14**, and **BTO 14-F** are intended to be used with Listed pressure terminal connectors, such as ring and fork types, on the end of the conductor before attachment to the wiring terminals of the terminal block.

and Report

Nomenclature:

1.	$\frac{K}{I}$	$\frac{5}{II}$	$\frac{/M}{III}$
----	---------------	----------------	------------------

I. Mounting Foot Construction Variations

MBK - Suitable for 15 mm wide mounting rail

K - Suitable for 35 mm wide mounting rail.

MBKKB - Suitable for both 15 mm wide and 35 mm wide mounting rail.

II. Max Wire Range Capacity

2.5 - No. 12 AWG

3,4 - No. 12 AWG

5 - No. 10 AWG

10 - No. 8 AWG

16 - No. 6 AWG

25 - No. 4 AWG

35 - No. 1/0 AWG

III. /M-10 section snap-in block, snap-lock provided for every other section.

/E - 1 section snap-in block. Snap-lock provided for each section.

None - 10 - section slide-in block. Provisions or angled mounting.

/E-FS - Pressure wire connector on line side, .110 in (2.8 mm) quick-connectors on load side.

/E-FS/FS - .110 in (2.8 mm) quick-connectors on both sides.

/E-PE - Grounding type version of Cat. No. MBK2.5/E

/E-Z-PE - (Cat. No. MBK3/E-Z-PE). Same as MBK2.5/E-PE except

higher

profile housing.

File E60425	Vol. 1	Sec. 1	Page 3A	Issued: 1976-04-20
	Vol. 4	Sec. 5		Revised: 2001-08-24
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		
	and Report			

2.	<u>SSK</u>	<u>110</u>	<u>Kri</u>
	I	II	III

I. SSK - Melamine or polyester Grade RFK insulating base

II. Wire Range Capacity

110 - 18-8 AWG
 116 - 18-6 AWG
 125 - 18-4 AWG
 135 - 18-2 AWG
 /N0525-L/B1 - 22-12 AWG
 5 - 18-10 AWG
 0525-TG - 22-12 AWG

III. Kri - Manufacturer's code marking for insulating block material.

3.	<u>A</u>	<u>UDK 4</u>	<u>-ULA</u>	<u>-48</u>	<u>RT</u>	<u>/O-U</u>
	A	B	C	D	E	F

A - Basic Construction

B - Wire AWG Area Capacity

3 - 3 mm²
 4 - 4 mm²
 (Items C through F for UDK4 series only)

C - Optional. Light Circuit Variations.

-ULA - Voltage indication circuitry
 -ILA - Current indication circuitry

File E60425	Vol. 1	Sec. 1	Page 3B	Issued: 1976-04-20
	Vol. 4	Sec. 5		Revised: 2013-06-06
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		

and Report

D - Electrical Ratings of Light Circuitry. Not used with Suffix/EK (Item F) below.

- 12 - 12 V LED (with Suffix -ULA only)
- 24 - 24 V LED (with Suffix -ULA only)
- 48 - 48 V LED (with Suffix -ULA only)
- 60 - 60 V LED (with Suffix -ULA only)
- 230 - 230 V Neon light (with Suffix -ULA only)
- 230 - 230 V LED (with Suffix -ULA only)
- 500 - 500 V neon light (with Suffix -ULA only)
- 500 - 500 mA Neon light (with Suffix -ILA only)
- 1000 - 1000 mA Neon light (with Suffix -ILA only)

E - Light Circuit Type

- With Suffix GN or RD - LED indicator
- Without Suffix GN or RD - Neon light indicator

F - Light Circuitry Location

- /O-U - Light indication between left side terminal and right side terminals. (Used with Suffix RT or RD only).
- /EK - Light indication between left side terminal and bus bar. (Used with Suffix -ULA only).

4. $\frac{G5}{I}$ $\frac{12}{II}$

- I. Basic Designation
 - II. Number of poles: 2, 3, 4, 6, 12
- G5/2B is identical to the G5 series except the former employs a common bus bar bridging the wire connectors as shown in Fig. 14, Page 19.

5. $\frac{ST-Si}{A}$ $\frac{LED}{B}$ $\frac{24}{C}$ $\frac{-UK4}{D}$

A - Basic Construction

B - Optional LED - LED indicator

LA - Neon light indicator

C - When Suffix LED is used:

- 12 - Two - 12 V LED's in series with 1.8 kilohm resistor
- 24 - Two - 24 V LED's in series with 3.9 kilohm resistor
- 24 - Two - 24 V LED's in series with 120 kilohm resistor**
- 60 - Two - 60 V LED's in series with 11.0 kilohm resistor
- 230 - Two 230 V LED's in series with 150 kilohm resistor

When Suffix LA is used:

- 250 - One - 250 V neon light in series with 272 kilohm resistor.
- 500 - One 500 V neon light in series with 1 milliohm resistor

D - Basic designation of terminal blocks used with this plug-in fuseholder.

File E60425 Vol. 1 Sec. 1 Page 3C Issued: 1976-04-20
 Vol. 4 Sec. 5 Revised: 2017-07-28
 Vol. 5 Sec. 1
 Vol. 7 Sec. 1
 Vol. 8 Sec. 1
 Vol. 11 Sec. 1
 Vol. 16 Sec. 1
 Vol. 17 Sec. 2
 Vol. 22 Sec. 11
 and Report

6. URTK /S
 A B

A - Basic Designation - single pole terminal blocks employing pressure wire connectors, and sliding link disconnects.

B - Construction Variations -

 /SS - Provides M3 terminal screw
 /S - Provides M4 terminal screw with modified connector body and insulating block
 /S-Ben - Provides M4 hollow cylindrical-shaped screw head for 4 mm dia test plug
 /S-Ben 10 - Same as S-Ben except modified connector body and insulating block
 /SP - Disconnect (sliding link) with M4 terminal screws and M4 test plug socket.

Nomenclature:

A	B	C
X0	X1	F

A - Basic Construction (X0)

 BT - Barrier type with both sides having screw connection (closed enclosure)

 BTO - Barrier type with both sides having screw connection (open enclosure)

 BTP- Barrier type with both sides push in connection provision.

 BTH- Barrier type with one side push in and second side screw type connection provision.

B - Connection Capacity (X1): 1.25, 2.0, 3.5

C - w/wo suffix -F: Flange type for mounting purposes

 Corrosion Protection - All parts are of corrosion resistant material or are suitably plated to resist corrosion.

File E60425

Vol. 1 Sec. 1
Vol. 4 Sec. 5
Vol. 5 Sec. 1
Vol. 7 Sec. 1
Vol. 8 Sec. 1
Vol. 11 Sec. 1
Vol. 16 Sec. 1
Vol. 17 Sec. 2
Vol. 22 Sec. 11
and Report

Page 3C1A

Issued: 1976-04-20

New: 2017-11-30

Nomenclature:

A	B	C
X0	X1	X2

A - Basic Construction (X0)

BT - Barrier type with both sides having screw connection
(closed enclosure)

BTO - Barrier type with both sides having screw connection
(open enclosure)

B - Connection Capacity (X1): 5.5

C - w/wo suffix (X2) -F - for flange type mounting purpose.

With all colour variants are possible and the can be added at any position of nomenclature.

Note: In nomenclature we can use /,- and space in between every suffix.

BT 5.5	BTO 5.5
BT 5.5-F	BTO 5.5-F

File E60425	Vol. 1	Sec. 1	Page 3C1B	Issued: 1976-04-20
	Vol. 4	Sec. 5		New: 2017-12-01
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		
	and Report			

Nomenclature:

BT	14	-F
X0	X1	X2

A - Basic Construction (X0)

BT - Barrier type with both sides having screw connection
(closed enclosure)

BTO - Barrier type with both sides having screw connection
(open enclosure)

B - Connection Capacity (X1): 14

C - w/wo suffix (X2) -F - article with flange type provision for mounting.

With all colour variants are possible and the can be added at any position of nomenclature

Note: In nomenclature we can use /,- and space in between every suffix.

BT 14	BTO 14
BT 14-F	BTO 14-F

File E60425	Vol. 1	Sec. 1	Page 3C1C	Issued: 1976-04-20
	Vol. 4	Sec. 5		Revised: 2025-02-13
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		

and Report

Nomenclature:

BTO	38	-F
X0	X1	X2

A - Basic Construction (X0)

BTO - Barrier type with both sides having screw connection
(open enclosure)

B - Connection Capacity (X1): 38

C - w/wo suffix (X2) -F - article with flange type provision for mounting.

With all colour variants are possible and the can be added at any position of nomenclature

Note: In nomenclature we can use /,- and space in between every suffix.

BTO 38	BTO 38-F
--------	----------

Nomenclature: URTK/S-BEN 10-TK

URTK	X0	X1
A	B	C

A: URTK:

B: with or without suffix (X0)

X0: /S BEN 10: Same as S-Ben except modified connector body and insulating block

C: with or without suffix(X1):

-TK : with knurled screw, for operating the disconnect slider

With all colour variants are possible and that can be added at any position of nomenclature

Note: In nomenclature we can use /,- and space in between every suffix.

URTK/S-BEN 10-TK

File E60425	Vol. 1	Sec. 1	Page 3C1D	Issued: 1976-04-20
	Vol. 4	Sec. 5		New: 2025-02-13
	Vol. 5	Sec. 1		
	Vol. 7	Sec. 1		
	Vol. 8	Sec. 1		
	Vol. 11	Sec. 1		
	Vol. 16	Sec. 1		
	Vol. 17	Sec. 2		
	Vol. 22	Sec. 11		
	and Report			

Nomenclature: TB 2,5-QUATTRO C, TB 4-QUATTRO C

TB	X0	X1	X2
A	B	C	D

A: TB: Feed through terminal block
 B: with or without suffix (X0)
 X0: Size of correlation to the cross-section (X0) : 2.5, 4
 C: with or without suffix(X1):
 -QUATTRO C: One level housing, four terminals
 D: with or without suffix(X2):
 -C: C stays for Copper alloy
 With all colour variants are possible and that can be added at any position of nomenclature

Note: In nomenclature we can use /,- and space in between every suffix.

TB 2,5-QUATTRO C	TB 4-QUATTRO C
------------------	----------------