

CERTIFICATE OF COMPLIANCE

Certificate Number E310982
Report Reference E310982-20150511
Date 2022-February-08

Issued to: PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8
Blomberg 32825 DE

This is to certify that
representative samples of TUBING, EXTRUDED INSULATING - COMPONENT
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 224, CSA C22.2 No. 198.1-06, Standard for Safety for Extruded Insulating Tubing.

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E310982
Report Reference E310982-20150511
Date 2022-February-08

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Tubing, Extruded Insulating: Flexible Heat Shrinkable Polyolefin Tubing produced with the following specifications and ratings

Cat. No.
WMS(XY)(AB),
E-WMS XX (...)R,
E-WMS XX (...)RL,
E-WMS XX (...)RXL, E-WMS XX (...)R YE,
E-WMS XX (...)RL YE, E-WMS XX (...)RXL YE

(AB) will be footnoted "BM:XXXX", which is replaced by two alpha characters followed by two numeric characters.

Note: E-WMS XX (...)R, E-WMS XX (...)RL, E-WMS XX (...)RXL, E-WMS XX (...)R YE, E-WMS XX (...)RL YE, and E-WMS XX (...)RXL YE are alternate designations for Cat. No. WMS(XY)(AB)

(...) – may be any alphanumeric combination, including one or more digits, indicating the dimensions of the label.

XX – may be any alphanumeric combination, including one or more digits, indicating the diameter of the cable.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>