

WML ...

Cable Marker Labels for Thermal Transfer Printers



CLIPLINE

Data Sheet

103141_en_01

© PHOENIX CONTACT - 02/2008

1 Description

WML cable marker labels consist of a labeling field and transparent protective foil.

The protective foil is wound over the labeling and provides permanent protection against dirt and abrasion.

The labels do not increase the cross section and the conductor can also be drawn through cable ducts, for example, when fitted later.



Make sure you always use the latest documentation.
It can be downloaded at www.download.phoenixcontact.com.

A conversion table is available on the Internet at
www.download.phoenixcontact.com/general/7000_en_00.pdf.



This data sheet is valid for all products listed on the following page:

2 Ordering Data

Cable Marker Labels

Description	Type	Order No.	Pcs./Pck.
Cable marker labels for THERMOMARK S1 ... and THERMOMARK X1 ... thermal transfer printers			
Labeling field: 25 mm x 19 mm, up to 14 mm Ø, 1 roll = 1500 labels, color: white	WML 14 (25x19)R	0817536	1
Labeling field: 25 mm x 19 mm, up to 14 mm Ø, 1 roll = 1500 labels, color: yellow	WML 14 (25x19)R YE	0817549	1
Labeling field: 38 mm x 19 mm, up to 14 mm Ø, 1 roll = 1000 labels, color: white	WML 14 (38x19)R	0817552	1
Labeling field: 12 mm x 12 mm, up to 18 mm Ø, 1 roll = 2500 labels, color: white	WML 18 (12x12)R	0817507	1
Labeling field: 25 mm x 38 mm, up to 36 mm Ø, 1 roll = 500 labels, color: white	WML 36 (25x38)R	0817510	1
Labeling field: 25 mm x 10 mm, up to 5 mm Ø, 1 roll = 3000 labels, color: white	WML 5 (25x10)R	0817523	1
Labeling field: 13 mm x 13 mm, up to 6 mm Ø, 1 roll = 7000 labels, color: white	WML 6 (13x13)R	0816252	1
Cable marker labels for THERMOMARK X1 ... thermal transfer printers			
Labeling field: 25 mm x 19 mm, up to 12 mm Ø, 1 roll = 3000 labels, color: white	WML 12 (25x19)RL	0817594	1
Labeling field: 25 mm x 25 mm, up to 22 mm Ø, 1 roll = 3000 labels, color: white	WML 22 (25x25)RL	0817604	1
Labeling field: 13 mm x 10 mm, up to 3 mm Ø, 1 roll = 5000 labels, color: white	WML 3 (13x10)RL	0817565	1
Labeling field: 13 mm x 13 mm, up to 7.5 mm Ø, 1 roll = 10,000 labels, color: white	WML 7,5 (13x13)RL	0817578	1
Labeling field: 25 mm x 13 mm, up to 7.5 mm Ø, 1 roll = 5000 labels, color: white	WML 7,5 (25x13)RL	0817581	1

Compatible Output Devices

Description	Type	Order No.	Pcs./Pck.
Thermal transfer printer, including power supply unit, connecting cable, Windows® printer drivers, operating instructions	THERMOMARK X1	5145274	1
Starter set, complete for THERMOMARK X1, comprising: CMS-MARK-WIN labeling software, THERMOMARK X1 thermal transfer printer, ink ribbon, and roll of labels	THERMOMARK X1-KIT	5145287	1
Thermal transfer printer, including power supply unit, connecting cable, Windows® printer drivers, operating instructions	THERMOMARK S1	5145313	1
Starter set, complete for THERMOMARK S1, comprising: CMS-MARK-WIN labeling software, THERMOMARK S1 thermal transfer printer, ink ribbon, and roll of labels	THERMOMARK S1-KIT	5145326	1
Starter set, complete for THERMOMARK S1, comprising: CMS-MARK-WIN labeling software, THERMOMARK S1 thermal transfer printer, ink ribbon, and roll of labels	THERMOMARK S1-KIT-USA	5145452	1

Compatible Ink Ribbon

Description	Type	Order No.	Pcs./Pck.
Ink ribbon, length: 300 m, width: 110 mm, ink color: black	THERMOMARK-RIBBON 110	5145384	1

3 Technical Data

General Data

Material	Polyvinyl (free from cadmium, halogen, and silicone)
Temperature range	-40°C ... +70°C
Area of application	Suitable for outdoor use
Wipe resistance of the inscription	According to DIN EN 61010-1/VDE 0411-1 (only in association with the Phoenix Contact components listed under "Ordering Data")
Labeling method	Thermal transfer, manual
Material thickness	0.12 mm
RoHS-compliant	Yes