

XCFR8.E60425 - Terminal Blocks Certified for Canada - Component

Terminal Blocks Certified for Canada - Component

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstrasse 8

Blomberg, 32825 Germany

E60425

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
TDPT 4 - SC	24-10	Sol/str	0.6-0.8	600	30	B, C	2(105),4
				300	10	D	
				600	10	D	
TDPT 16 - SC	20-10 8-6	Sol/str Compact str	1.4 - 1.7	600	58	B, C	2(105),4
				300	10	D	
				600	5	D	
TDPT 2,5 - SC	24-12	Sol/str	0.5 - 0.6	300	20	B	2(105),4
				150	20	C	
				300	10	D	
TDPT 4 - SP	24-10	Sol/str	N/A	600	30	B, C	2(105),4
				300	10	D	
				600	10	D	
TDPT 16 - SP	20-10 8-6	Sol/str Compact str	N/A	600	58	B, C	2(105),4
				300	10	D	
				600	5	D	
TDPT 2,5 - SP	24-12	Sol/str	N/A	300	20	B	2(105),4
				150	20	C	
				300	10	D	
FRONT-FMC 1.5/D28-FF-6.35-R, FRONT-FMC 1.5/D32-FF-6.35-R	20-16 sol/str	Cu	N/A	300	6	B, D	2(115)
FRONT-FMC 1.5/D28-MF-6.35, FRONT-FMC 1.5/D32-MF-6.35	N/A	—	N/A	300	6	B, D	2(115)
AXL SE	12 sol/str	Cu	N/A	150	12	C	2(80),4

TW50 followed by one or two digit numbers, w/wo suffixes, may be followed by CUT.	8 - 1/0	Cu	6-8	600	150	C	2(115),4,5
TW95 followed by one or two digit numbers, w/wo suffixes, may be followed by CUT.	4 - 3/0	Cu	12-15	600	200	C	2(115),4,5
UW 50-16/11-MPI	16-1/0	Cu	8-9	600	131	C	2(120), 4
	6-2/0	Cu	8-9	600	151	C	2(120), 4
	16-4	Cu	3-3.5	600	76	C	2(120), 4
UW, followed by V or blank, followed by 50, may be followed by suffixes -F, -POT, -POT/S, -POT-F/S, may be followed by /S.	6 - 2/0	Cu	6 - 8	600	151	B,C	2(115),4,5
UW 95-35/10-MPI	6-2/0	Cu	8-9	600	151	C	2(120), 4
	2-4/0	Cu	10-12	600	201	C	2(120), 4
	14-2	Cu	3-3.5	600	101	C	2(120), 4
UW, followed by V or blank, followed by 95; may be followed by suffixes -F, -POT, -POT/S, -POT-F/S, may be followed by /S.	4 - 3/0	Cu	10 - 12	600	200	B,C	2(115),4,5
UW 150-50/12-MPI	2-300 kcmil	Cu	12-14	600	256	C	2(120), 4
	6-2/0	Cu	8-9	600	2x151	C	2(120), 4
	4-3/0	Cu	8-9	600	176	C	2(120), 4
PWO 16-UW	14 - 4	Cu	N/A	600	66	B, C	2(105)
16-UW	10-4	Cu	22-26	600	66	B, C	2(105)
PWO 16-UW/S	14 - 4	Cu	N/A	600	66	B, C	2(105)
16-UW/S	10-4	Cu	22-26	600	66	B, C	2(105)
UW(V) 16/X XDP3-F (3)	10 - 4	Cu	22-26	1000	85	C	2(105)
UISLKG35	2-18	Cu	2	N/A	N/A	B, C	2(105),4
HSCH 2.5	N/A	N/A	N/A	150	8	B	2(105)
HSCH 2.5 THR (2)	N/A	N/A	N/A	150	8	B	2(130)
HSCH 2.5	N/A	N/A	N/A	300	8	D	2(105)
HSCH 1.5	N/A	N/A	N/A	150	8	B	2(105)
HSCH 1.5 THR	N/A	N/A	N/A	150	8	B	2(130)
HSCP-SP 2.5	24-16 sol	Cu	N/A	150	8	B	2(105)
HSCP-SP 2.5	24-14 str	Cu	N/A	150	8	B	2(105)
HSCP-SP 2.5	24-16 sol	Cu	N/A	300	8	D	2(105)
HSCP-SP 2.5	24-14 str	Cu	N/A	300	8	D	2(105)
HSCTV-SP 2.5	24-16 sol	Cu	N/A	150	8	B	2(105)

	24-14 str	Cu	N/A	150	8	B	2(105)
	24-16 sol	Cu	N/A	300	8	D	2(105)
	24-14 str	Cu	N/A	300	8	D	2(105)
HSCP-SP 1.5	20-10	Cu	5-6	600	8	B	2(105), 4
HSCP-SP MIX	Signal:						
	24-16 sol/str	Cu	N/A	150	8	B	2(105), 4
	Power:						
	24-16 sol	Cu	N/A	150	8	B	2(105), 4
	24-14 str	Cu	N/A	150	8	B	2(105), 4
	24-16 sol	Cu	N/A	300	8	D	2(105), 4
	24-14 str	Cu	N/A	300	8	D	2(105), 4
TB2.5-L/LB-PV I	20-12	Cu	0.5-0.6	300 600	20 5	B, C, D	2(105)
TB2.5-2L EI , TB2.5-2L I	20-12	Cu	0.4-0.5	300	20	B,C	2(105), 4
			0.4-0.5	600	5	C	
TB4-TWIN EI	20-12	Cu	0.5-0.6	300	20	B, C	2(105), 4
TB4-TWIN I	20-12	Cu	0.5-0.6	600	5	B, C, D	2(105), 4
TB4-2L EI,	20-10	Cu	0.5-0.6	300	30	B, C	2(105), 4
TB4-2L I	20-10	Cu	0.5-0.6	600	5	D	
TB4-L/LB-PV I	20-10	Cu	0.6-0.7	300 600	30 5	B, C, D	2(105)
TB4-HEDI EI, TB4-HEDI I, TB4-HEDI I MS	20-10	Cu	5-6	600	15	B, C	2(105), 4
TB4-HESI (5X20)EI, TB4-HESI (5X20)I, TB4-HESI (5X20) I MS	20-10	Cu	5-6	600	6.3	B, C	2(105), 4
TB4-HESILED24 (5X20) EI, TB4-HESILED24 (5X20) I, TB4-HESILED24 (5X20) I MS	20-10	Cu	5-6	600	6.3	B, C	2(105), 4
TB4-HESILED60 (5X20) EI, TB4-HESILED60 (5X20) I, TB4-HESILED60 (5X20), I MS	20-10	Cu	5-6	600	6.3	B, C	2(105), 4
TB4-HESILA250 (5X20) EI, TB4-HESILA250 (5X20) I, TB4-HESILA250 (5X20) I MS	20-10	Cu	5-6	600	6.3	B, C	2(105), 4
TB4-QUATTRO EI, TB4-QUATTRO I, TB4-QUATTRO I MS	20-10	Cu	0.5-0.6	300	30	B, C	2(105), 4
	20-10	Cu	0.5-0.6	600	5	D	

TB6 RTK, TB6 RTK I, TB6 RTK EI, TB6 RTK I MS	16-8	Cu	12-13	300	50	B, C	2(105), 4
TB6 RTK N	18-8	Cu	1.2-1.5	300	50	B, C	2(105)
TB6-T EI, TB6-T I, TB6-T-NP I	16-8	Cu	1.4-1.5	600	30	B,C	2(105)
UT 16-PE/S	16-4	Cu	2.25-3	600	N/A	B, C, D	2(105)
UT 35-PE/S	16-2	Cu	3.2-3.7	600	N/A	B, C, D	2(105)
TB3-PE I	20-12	Cu	4-5	N/A	N/A	B, C, D	2(105)
TB35-PE EI, TB35-PE-I	8-2	Cu	3.-3.7	N/A	600	B,C,D	2(105)
USLKG 35 N	8-2	Cu	3-3.5	N/A	600	B,C,D	2(105)
TB16 EI, TB 16 I, TB16 CHI	10-4	Cu	2.5-3	600	76	B,C	2(105)
PC 6/ 2(3)-ST-BUS-7,62	6 (Line)	Str (1)	3 Nm	600	65	B, C (3)	2(115), 4
	6 (Line)	Str (1)	3 Nm	600	65	F (2)	2(115), 4
	N/A (Load)	N/A	N/A	600	30 (4)	B, C (3)	2(115), 4
	N/A (Load)	N/A	N/A	600	30 (4)	F (2)	2(115), 4
PC 6/ 2(3)-G(-G1U)-7,62	N/A	N/A	N/A	600	35	F (2)	2(115), 4
	N/A	N/A	N/A	300	35	B, C	2(115), 4
	N/A	N/A	N/A	600	5	D	2(115), 4
LPT2.5/X-5.0, LPTA2.5/X-5.0	24-12	Cu	N/A	300	20	B	2(115), 4
	24-12	Cu	N/A	300	10	D	2(115), 4
	24-12	Cu	N/A	320	20	F (2)	2(115), 4
	24-12	Cu	N/A	300	10	G (2)	2(115), 4
LPC 2.5/X-ST-5.08, LPC 2.5/X-STF-5.08, LPC 2.5/X-ST-5.08-LR	26-12	Cu	N/A	300	16	B	2(115), 4
	26-12	Cu	N/A	300	10	D	2(115), 4
BCW-500X10-2 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-3 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-4 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-5 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)

BCW-500X10-6 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-7 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-8 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-9 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-10 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-11 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-12 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-13 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-14 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-15 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)
BCW-500X10-16 GN	14-24, Sol/Str	Cu	0.4	300	15	B, D ^A	2(105)

Notes:

- (1) - To be used only with conductors with PVC insulation, with or without nylon jacket, 19 strands, types: MTW, THHW, THW, THW-2, THHN, THWN-2, TW, TWN and CSA types TW, TWU, TWN75, TW75, TWU75, T90.
- (2) - Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification only.
- (3) - The combination of Plugs used in Usage Group B and C applications with the Headers designated "-G1U" shall be limited to the following ratings: • Plug: 300 volts, 65 A; Header: 300 V, 20 A • Plug: 600 volts, 65 A; Header: 600 V, 5 A (based on Usage Group D)
- (4) - Current rating applicable only with header type PC 6/ 2(3)-G(-G1U)-7,62.

PTPOWER 35	14-2	Cu	N/A	1000	115	C	2(120)
PTPOWER 35-PE	14-2	Cu	N/A	1000	-	C	2(120)
PTPOWER 35-F	14-2	Cu	N/A	1000	115	C	2(120)
PTPOWER 50	8-1/0	Cu	—	1000	140	C	2(120)
PTPOWER 50 P	8-1/0	Cu	—	1000	140	C	2(120)
PTPOWER 50-F	8-1/0	Cu	—	1000	140	C	2(120)

PTPOWER 50 P-F	8-1/0	Cu	—	1000	140	C	2(120)
PTPOWER 50-PE	8-1/0	Cu	—	1000	N/A	C	2(120)
AGK 10-PTPOWER	20 (sol/str)-6	Cu	—	1000	57	C	2(120)
PTPOWER 95	4-4/0	Cu	—	1000	230	C	2(120)
PTPOWER 95 P	4-4/0	Cu	—	1000	230	C	2(120)
PTPOWER 95-F	4-4/0	Cu	—	1000	230	C	2(120)
PTPOWER 95-F-P	4-4/0	Cu	—	1000	230	C	2(120)
PTPOWER 95-PE	4-4/0	Cu	—	1000	—	C	2(120)
PTPOWER 150	1-300 kcmil	Cu	—	1000	270	C	2(120)
PTPOWER 150 P	1-300 kcmil	Cu	—	1000	270	C	2(120)
PTPOWER 150-F	1-300 kcmil	Cu	—	1000	270	C	2(120)
PTU 2.5-TWIN	26-12 (sol/str)	Cu	0.5-0.6	600	20	B, C	2(115)
	26-12 (sol/str)	Cu	0.5-0.6	600	5	D	2(115)
PTU 2.5	26-12 (sol/str)	Cu	0.5-0.6	600	20	B, C	2(115)
	26-12 (sol/str)	Cu	0.5-0.6	600	5	D	2(115)
PTU 2.5-PE	26-12 (sol/str)	Cu	0.5-0.6	N/A	—	B, C, D	2(115)
PTU 2.5-TWIN-PE	26-12 (sol/str)	Cu	0.5-0.6	N/A	—	B, C, D	2(115)
PTU 4-TWIN	24-10 (sol/str)	Cu	0.6-0.8	600	30	B, C	2(115)
	24-10 (sol/str)	Cu	0.6-0.8	600	5	D	2(115)
PTU 4	24-10 (sol/str)	Cu	0.6-0.8	600	30	B, C	2(115)
	24-10 (sol/str)	Cu	0.6-0.8	600	5	D	2(115)
PTU 4-PE	24-10 (sol/str)	Cu	0.6-0.8	N/A	—	B, C, D	2(115)
PTU 4-TWIN-PE	24-10 (sol/str)	Cu	0.6-0.8	N/A	—	B, C, D	2(115)

PTV 2.5	26-12 (Sol/Str)	Cu	2	600	20	B,C	2(115), 4
PTV 2.5-PE	26-12 (Sol/Str)	Cu	2	N/A	N/A	B,C	2(115), 4
PTV 2.5-TWIN	26-12 (Sol/Str)	Cu	2	600	20	B,C	2(115), 4
PTV 2.5-TWIN-PE	26-12 (Sol/Str)	Cu	2	N/A	N/A	B,C	2(115), 4
PTV 2.5-QUATTRO	26-12 (Sol/Str)	Cu	2	600	20	B,C	2(115), 4
PTV 2.5-QUATTRO-PE	26-12 (Sol/Str)	Cu	2	N/A	N/A	B,C	2(115), 4
Note: (1) Multiple wire rating of two No. 10-20 AWG Cu. sol/str wires of same size for field and factory wiring.							
Note: (2) May be followed by suffixes -00/00 to -99/99 describing color of spring actuators or -0000 to -9999 describing color of insulation housing.							
PTVC 2.5-MT	26-12 (Sol/Str)	Cu	2	300	20	B	2(115), 4
				300	10	D	2(115), 4
PTVC 2.5-TG	26-12 (Sol/Str)	Cu	2	300	20	B	2(115), 4
				300	10	D	2(115), 4
PTVME 6/S, PTVME 6/S-P	26-10 (Sol/Str)	Cu	2	600	30	B,C	2(115)
	26-10 (Sol/Str)	Cu	2	1000	30	F(++)	2(115)
FIBO-SMD-S-LEISTE.....(°)	—	—	—	50	10	B, C	2(105)
FIBO-P-SP1,5-SINGLE-PWR...(+) (°°)	16-26 Sol 16-24 str	Cu	—	50	10	B, C	2(115), 4, 5
FIBO-P-SP-TWIN.....(+) (°°)	16-26 sol 16-24 str	Cu	—	50	6	B, C	2(115), 4, 5
AMTECH 1.5/40-ST-S	26-14	Cu	0.34 - 0.68	300	8	B, D	2 (130)
AMTECH 1.5/4-ST-S EK 24V	26-14	Cu	0.79	24	12	B, C	2(130)
AMTECH 1.5/4-ST-S EK 230V	26-14	Cu	0.79	300	12	B, C	2(130)
MSB 2.5	28-18	Cu	—	600	20	B, C	2(105)
MSB 2.5-F	28-18	Cu	—	600	20	B, C	2(105)
MSB 2.5-M	28-18	Cu	—	600	20	B, C	2(105)
MSB 2.5-NS 35	28-18	Cu	—	600	20	B, C	2(105)
MSB 2.5-RZ	28-18	Cu	—	600	20	B, C	2(105)
MSDB 2.5	28-18	Cu	—	600	20	B, C	2(105)

MSDB 2.5-F	28-18	Cu	—	600	20	B, C	2(105)
MSDB 2.5-M	28-18	Cu	—	600	20	B, C	2(105)
MSDB 2.5-NS 35	28-18	Cu	—	600	20	B, C	2(105)
MSDB 2.5-RZ	28-18	Cu	—	600	20	B, C	2(105)
MSBV 2.5	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSBV 2.5-F	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSBV 2.5-M	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSBV 2.5-NS 35	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSDBV 2.5	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSDBV 2.5-F	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSDBV 2.5-M	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSDBV 2.5-NS 35	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSDBV 2.5-RZ	28-18	Cu	—	600	20(3)	B, C, D	2(105)
MSB2.5-PE	28-12	Cu	—	—	—	B, C, D	2(105), 4
MSB2.5-NS35-PE	28-12	Cu	—	—	—	B, C, D	2(105), 4
RT 4-T, RTO 4-T-TC, RT 4-T-P/P	N/A	Cu	10-20	600	30	B, C	2(105), 5
PC6-16-G1 HT	N/A	Cu	N/A	300	66	B	2(130)
	N/A	Cu	N/A	300	66	C	2(130)
	N/A	Cu	N/A	600	5	D	2(130)
QTTCB1.5PE, QTTCB1.5/2P-PE	24-16	Cu	N/A	N/A	N/A	B, C	2(105)
QTC2.5, QTC2.5-TWIN , QTC2.5-QUATTRO	20-14	Cu	N/A	600	15	B, C	2(105)
QTC2.5-PE, QTC2.5-TWIN-PE, QTC2.5-QUATTRO-PE	20-14	Cu	N/A	N/A	N/A	B, C	2(105)
QTC2.5-HESI (5X20), QTC2.5-HESILED 24, QTC2.5-HESILED 60, QTC2.5-HESILA 250	20-14	Cu	N/A	300	15	B, C	2(105)
QTC2.5-HEDI, QTC2.5-MT, QTC2.5-TG	20-14	Cu	N/A	300	15	B, C	2(105)
QTC2.5-HEDI, QTC2.5-TG(#)	20-14	Cu	N/A	300	10	B, C	2(105)
QP1.5w/wo suffixes/1-L, /1-M, /1-R	24-16	Cu	N/A	300/600	10/5	B, C	2(105)

QP1.5f/b /1 or /2 digit No	24-16	Cu	N/A	300/600	10/5	B, C	2(105)
Note: (#) Cat. Nos. with Suffix -TG followed by Suffixes P-FU 5X20 and P-FU 6X32 followed by -5, LED 24-5, LED 60-5 or LA 250-5; Suffixes FP (5X20) with or without 24, 60, or 250.							
Note: (+) May be used also with metric prepared conductors (ferrules) 0.25 - 1.25 mm ²							
Note: (++) Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification only.							
Note: (°) Series Pin Array FIBO, followed by -SMD-S-LEISTE, followed by -4P, -12P, 20P or 36P, followed by -2R, -3R, -5R or -9R.							
Note: (°°) Series Axio Connector FIBO, followed by -P-SP or -PS-SP, followed by 1.5 or blank, followed by -single or -twin, followed by -LV or blank, followed by -PWR, DO2, DO3, DI04, DI2 or FKT, followed by alphanumeric code.							
UKH50 (1), UKH50(IB) (1)	6-1/0	Cu	7.9	600	150	B, C	2(105)
UKH70, UKH70-F	6-3/0	Cu	15.2 - 19.7	1000	192	B, C	2(105), 4
UKH95 (2), UKH95-F (2)	2-4/0	Cu	19.7	600	230	B, C	2(105)
UKH 70/4X10	For 70: 4 to 3/0 AWG	Cu	8-10 Nm	1000	176	C	2(115)
	For 4x10: 16 to 6 AWG	Cu	1.4-1.5 Nm	1000	65	C	2(115)
UKH 70/4X10-PE	For 70: 4 to 3/0 AWG	Cu	8-10 Nm	1000	—	C	2(115)
	For 4x10: 16 to 6 AWG	Cu	1.4-1.5 Nm	1000	—	C	2(115)
UKH 70 PE/S	4-2/0 AWG	Cu	8-10 Nm	600	—	B,C	2(115)
RBO 8, may be followed by -WD, may be followed by a one or two digit No.	N/A	Cu	15-20	1000	175	C	2(105),5
RBO 6/WA50	2 AWG	Cu	6-8 Nm	600	115	B,C	2(120)
RBO 6/WA70	1/0 AWG	Cu	6-8 Nm	600	150	B,C	2(120)
RBO 8/WA120	3/0 AWG	Cu	15-20 Nm	600	200	B,C	2(120)
RBO 12/WA185	300 kcmil	Cu	25-30 Nm	600	285	B,C	2(120)
RBO 16/WA240	350 kcmil	Cu	30-35 Nm	600	310	B,C	2(120)
RBO 5 W16	N/A	Cu	2-2.2	300	45	B, C	2(120)
				600	5	D	2(120)
FTB 2.5-F	28-12	Cu	NA	300	20	B,C	2(105)
				300	10	D	2(105)

FTB 2.5-NS35	28-12	Cu	NA	300	20	B,C	2(105)
				300	10	D	2(105)
FTDB 2.5-F	28-12	Cu	NA	300	20	B,C	2(105)
				300	10	D	2(105)
FTDB 2.5-NS35	28-12	Cu	NA	300	20	B,C	2(105)
				300	10	D	2(105)

Note: (1) Multiple wire rating of two No. 8-6 AWG same size str. wires for factory wiring only

Note: (2) Multiple wire rating of two No. 2-4 AWG same size str. wires for factory wiring only

Note: (3) These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single cirCuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.

FRONT1.5-V-3.81	14-30	Cu	2.5	300	10	B, D	2(115)
FRONT2.5H	12-30	Cu	3.5 to 4.5	300	10	B, D	2(105)
FRONT2.5H-SA5	12-30	Cu	3.5 to 4.5	300	24	B, D	2(105)
FRONT2.5H-SA10	12-30	Cu	3.5 to 4.5	300	24	B, D	2(105)
FRONT2.5V	12-30	Cu	3.5 to 4.5	300	10	B, C	2(105)
FRONT2.5V-SA5	12-30	Cu	3.5 to 4.5	300	10	B, D	2(105)
FRONT2.5H-SA10	30-12	Cu	3.5 to 4.5	300	10	B, D	2(105)
EP-FRONT2.5-H/SA10	30-12	Cu	3.5 to 4.5	300	10	B, D	2(105)
EP-FRONT2.5H(2)	12-30	Cu	3.5 to 4.5	300	10	B, D	2(105)
FRONT4H-6.35	10-24	Cu	4.5 to 5.5	300	30	B, D	2(105)
FREC2.5/X-ST-5.0	30-12	Cu	5-7	300	10	B, D	2(105)

Note: (2) Followed by SA10/4BK.

FRONT4V-6.35	10-24	Cu	4.5 to 5.5	300	30	B, D	2(105)
FRONT4H-7.62	10-24	Cu	4.5 to 5.5	300	30	B, D	2(105)
FRONT4V-7.62	10-24	Cu	4.5 to 5.5	300	30	B, D	2(105)
UK-FRONT4	10-24	Cu	4.5 to 5.5	300	30	B, D	2(105)
UK-FRONT4-PE	10-24	Cu	4.5 to 5.5	—	—	B, D	2(105)
FRONT-SFL2.5(1)	12-30	Cu	3.5 to 4.5	300	4	B, D	2(105)
FREC2.5/X-ST-5.0	30-12	Cu	3.5 to 4.5	300	4	B, D	2(105)

Note: (1) Followed by suffixes /D32, /F32, /F48 with or without /ZB, or /ZD.

VBST4-FS(6-2.8-0.8)ST4	10-30	Cu	0.56-0.79	300	20	B, C	2(105)
VBSTB4-FS(6-2.8-0.8)	10-30	Cu	0.56-0.79	300	20	B, C	2(105)
MSTBC2.5(1) (3)	30-12	Cu	—	300	10	B, D	2(105)
ICC2.5(2)	30-12	Cu	—	300	10	B, D	2(105)
MSTBC2.5/X-STZF-10.16-1, -2	2-18/16-14	Cu	N/A	60	10	B, C	2(105)
ICC2.5/X-STZF-10.16-1, -2	2-18/16-14	Cu	N/A	60	10	B, C	2(105)
Note: (1) Followed by /one or two digit number suffix -ST, -STZ, -STZF or -STZFD, and by -5.08, with or without -R.							
Note: (2) Followed by /one or two digit number, Suffix -STZ, -STZD or -STZF, and by -5.08.							
Note: (3) All MSTBC2.5 models can be assembled with contacts crimped with stranded and flexible, Cu wires sizes: 20-18AWG or 16 - 14AWG.							
ZFK1.5(4)	14-26	Cu	N/A	300	—	B, C	2(105)
ZFK1.5PE(4)	14-26	Cu	N/A	—	—	B, C	2(105)
ZKKB1.5(4)	26-14	Cu	N/A	600	15	B, C	2(105)
ZFK2.5(4)	12-26	Cu	N/A	600	20	B, C	2(105)
ZFK2.5-PE(4)	12-26	Cu	N/A	—	—	B, C	2(105)
ZFK2.5-MT(4)	12-26	Cu	N/A	300	15	B, C	2(105)
ZDMTK2.5(4)	26-12	Cu	N/A	300	10	B, C	2(105)
ZDMTK2.5-TWIN(4)	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKK2.5-MT(4)	26-12	Cu	N/A	300	15,20	B, C	2(105)
ZFK2.5-TWIN(4)	12-26	Cu	N/A	600	20	B, C	2(105)
ZFK2.5-TWIN-PE(4)	12-26	Cu	N/A	—	—	B, C	2(105)
Note: (4) All may be followed by suffix BU.							
ZFKI2.5(4)	12-26	Cu	N/A	600	20	B, C	2(105)
ZFKI2.5-PE(4)	12-26	Cu	N/A	—	—	B, C	2(105)
ZFDK2.5(4)	12-26	Cu	N/A	600	20	B, C	2(105)
ZFDK2.5-MT(4)	12-26	Cu	N/A	300	15	B, C	2(105)
ZFDKI2.5-PE(4)	12-26	Cu	N/A	—	—	B, C	2(105)
ZFKKB2.5(4)	12-26	Cu	N/A	600	20	B, C	2(105)
ZFK4(4)	10-24	Cu	N/A	600	30	B, C	2(105)
ZFK4-HESI	10-24	Cu	N/A	600	10	B, C	2(105)

ZFK4-HESILED	10-24	Cu	N/A	600	10	B, C	2(105)
ZFK4-HESILA	10-24	Cu	N/A	600	10	B, C	2(105)
Note: (4) All may be followed by suffix BU.							
ZFK4-PE(4)	12-24	Cu	N/A	—	—	B, C	2(105)
ZFK4-TG(4)	10-24	Cu	N/A	600	15	B, C	2(105)
ZFKI4(4)	10-24	Cu	N/A	600	30	B, C	2(105)
ZFKI4PE(4)	12-24	Cu	N/A	—	—	B, C	2(105)
ZFK4-TWIN(4)	24-10	Cu	N/A	600	30	B, C	2(105)
ZFK4-TWIN-PE(4)	24-10	Cu	N/A	—	—	B, C	2(105)
ZGSK4	24-10	Cu	N/A	300	30	B, C	2(105)
ZRTK4	24-10	Cu	N/A	300	30	B, C	2(105)
ZFKK4(4)	24-10	Cu	N/A	600	30	B, C	2(105)
ZFKD4-PE(4)	24-10	Cu	N/A	—	—	B, C	2(105)
ZFKKB4(4)	24-10	Cu	N/A	600	30	B, C	2(105)
ZFK6(4)	20-8	Cu	N/A	600	50	B, C	2(105)
ZFK6-PE	8-20	Cu	N/A	600	N/A	B, C	2(105)
ZFK6-DREHSI(5X20)(4)	20-8	Cu	N/A	600	20	B, C	2(105)
ZFK6-DREHSI(6X32)(4)	20-8	Cu	N/A	600	20	B, C	2(105)
Note: (4) All may be followed by suffix BU.							
LPT 16/1-10.00	18-4	Cu	N/A	600	72	B,C	2(105),4
	18-4	Cu	N/A	1000	72	F(2)	2(105),4
LPT 16/X-10.00 w/wo -ZB or-ZF w/wo P may be followed by two digit number	18-4	Cu	N/A	600	66	B,C	2(105),4
	18-4	Cu	N/A	1000	66	F(2)	2(105),4
LPT 16/X-15.00 w/wo -ZB or-ZF w/wo P may be followed by two digit number	18-4	Cu	N/A	600	72	B,C	2(105),4
	18-4	Cu	N/A	1000	72	E,F(2)	2(105),4
ZFKDS(1)	26-12	Cu	N/A	300	10	B, D	2(105)
ZFKDSA(1)	26-12	Cu	N/A	300	10	B, D	2(105)
ZFKDSA1.5-7.62(4)	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKKDS(1)	12-26	Cu	N/A	300	10	B, C	2(105)
ZFKKKDSA(1)	12-26	Cu	N/A	300	10	B, C	2(105)
ZFK3DS(1)	12-26	Cu	N/A	300	10	B, C	2(105)

ZFK3DSA(1) ZFK3DSA1.5-5.08- 8 WJBD:13-B01	12-26	Cu	N/A	300	10	B, C	2(105)
ZFK3DS1.5/18-BK5650288	26-12	Cu	N/A	300	10	B, C	2(105)
ZFK3DS1.5/18-BK5650288	26-12	Cu	N/A	300	10	B, C	2(105)
ZFK4DS1.5-5.08	26-12	Cu	N/A	300	10	B, C	2(105)
ZFK4DSA1.5-6.08	26-12	Cu	N/A	300	10	B, C	2(105)
ZFDK2.5-MT	12-26	Cu	N/A	300	15	B, C	2(105)
ZFKDS1.5C-5.0	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKDSA1.5C-6.0	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKKDS1.5C-5.0	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKKDSA1.5C-5.0L	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKKDS1.5C-6.0R	26-12	Cu	N/A	300	10	B, C	2(105)
Note: (1) Followed by suffixes 1.5 and -5.08 or -6.08, all may be followed by suffix BU.							
Note: (2) All Cat. Nos. are with or without suffixes -4, -M, -NS35, all may be followed by suffix BU.							
Note: (2) Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification only.							
Note: (4) All may be followed by suffix BU.							
MZB1.5(2)	26-14	Cu	5-7	600	15	B, C	2(105)
MZFK1.5(4)	26-14	Cu	5-7	600	15	B, C	2(105)
MZFK1.5-PE(4)	26-14	Cu	N/A	N/A	N/A	B, C	2(105)
MZDB1.5(4)	26-14	Cu	5-7	600	15	B, C	2(105)
MZB1.5-PE(4)	26-14	Cu	N/A	N/A	N/A	B, C	2(105)
MZB1.5-NS35-PE(4)	26-14	Cu	N/A	N/A	N/A	B, C	2(105)
ZFK6(5)	20-8	Cu	N/A	600	20	B, C	2(105)
ZEC1.0(7)	26-16	Cu	N/A	300	8	D	2(105)
ZEC1.5(8)(9)	26-14	Cu	N/A	300	10	B, D	2(105)
ZEC1.0 f/b 1 or 2 digit number, f/b -LPV, -3.5	N/A	Cu	N/A	150	8	B	2(105)
ZEC1.5/X-ST-7.5 with suffixes NZ:292416, NZ:292417	26-14	Cu	N/A	600	10	B, D	2(105)
ZDIK1.5(6)	26-14	Cu	N/A	300	15	B, C	2(105)
ZEC1.5 f/b 1 or 2 digit number, f/b -LPV, -5.0, w/wo C and 1 or 2 digit number	N/A	Cu	N/A	300	10	B, D	2(105)

ZEC 1.5 f/b 1 or 2 digit number, f/b -LPV, -7,5, w/wo Cand 1 or 2 digit number	N/A	Cu	N/A	300	10	B, D	2(105)
Note: (1) Followed by suffixes -1.5 and -5.08, may be followed by suffix BU.							
Note: (2) All Cat. Nos. are with or without suffixes -F, -M, -NS35, all may be followed by suffix BU.							
Note: (4) All may be followed by suffix BU.							
Note: (5) Followed by suffixes -DREHSILED24 or -FREHSILSA250 and by (5x20)or (6.3x32).							
Note: (6) Followed by suffixes -LA24RD/O-M or -LA24GN/O-M.							
Note: (7) Followed by /1 or /2 digit number, followed by -ST-3.5, C1R1 and a 1 or 2 digit number.							
Note: (8) Followed by /1 or /2 digit number, followed by -ST, -5.0 or -7.5, may be followed by C, followed by alphanumerical code, may be followed by R, followed by alphanumerical code.							
Note: (9) Followed by /2 digit number, followed by -ST, followed by -5.0, followed by W/C. Multidrive Bracket Assembly part number 8101442, is an assembly of Cat. No. ZEC1.5/2-ST-5.0W/C terminal blocks.							
Note: (10) X represents followed by 1 or 2 digit numbers.							
ZVIOK1.5(6)	26-14	Cu	N/A	300	15	B, C	2(105)
ZFKK1.5-MSTBV-5.08, ZFKK1.5-MSTBV-5.08-PE/F	26-14	Cu	N/A	300	15	B, C	2(105)
ZFKK1.5-ICV-5.08	26-14	Cu	N/A	300	15	B, C	2(105)
ZFKK1.5-ICV-5.08-PE/F	26-14	Cu	N/A	—	—	B, C	2(105)
ZFK1.5-TWIN(4)	26-14	Cu	N/A	300	15	B, C	2(105)
ZFDK1.5(4)	26-14	Cu	N/A	300	15	B, C	2(105)
ZFKK1.5(4)	26-14	Cu	N/A	300	10	B, C	2(105)
ZFKDS1(7)	26- 16	Cu	N/A	300	10	B, C	2(105)
ZFKDSA1(7)	26- 16	Cu	N/A	300	10	B, C	2(105)
ZFL1/5-TWIN-PE	26-14	Cu	N/A	—	—	B, C	2(105)
ZFKDS2.5-5.08	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKDS2.5-5.08-L	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKDSA2.5-6.08-R	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKKDS2.5-5.08	26-12	Cu	N/A	300	10	B, C	2(105)

ZFKKDS2.5-5.08-L	26-12	Cu	N/A	300	10	B, C	2(105)
ZFKKDS2.5-6.08-R	26-12	Cu	N/A	300	10	B, C	2(105)
ZFDK1.5-PE	26-14	Cu	N/A	—	—	B, C	2(105)
MZFKK1.5	26-14	Cu	N/A	600	15	B, C	2(105)
MZFKK1.5-PV	24-14	Cu	N/A	600	15	B, C	2(105)
MZFKKB1.5	26-14	Cu	N/A	600	15	B, C	2(105)
MZFKK1.5	26-14	Cu	N/A	600	15	B, C	2(105)
ZPV1.5/2.5(8/1)	24-10	Cu	N/A	300	15	B, D	2(105)
ST4, ST4/1P	28-10	Cu	N/A	600	30	B, C	2(105)
ST4-PCB/X-G-6.2, ST4-PCBV/X -G-6.2	—	Cu	N/A	600	20	B, C	2(105)
ST4-PCB/X-G-6.2, ST4-PCBV/X -G-6.2	—	Cu	N/A	600	20	B, C	2(105)
ST4-TWIN	28-10	Cu	N/A	600	30	B, C	2(105)
ST4-QUATTRO, -U, /2P/4CP	28-10	Cu	N/A	600	30	B, C	2(105)
STTB4	28-10	Cu	N/A	300	30	B, C	2(105)
STTB4-PV	28-10	Cu	N/A	300	30	B, C	2(105)
ST4-PE, ST4/1P-PE	28-10	Cu	N/A	N/A	N/A	B, C	2(105)
ST4-PE/3L	28-10	Cu	N/A	(#)	(##)	B, C	2(105)
ST4-TWIN-PE	28-10	Cu	N/A	N/A	N/A	B, C	2(105)
ST4-QUATTRO-PE, ST4-QUATTRO/2P-PE	28-10	Cu	N/A	N/A	N/A	B, C	2(105)
STTB4-PE	28-14	Cu	NA	—	—	B, C	2(105)

Note: (4) All may be followed by suffix BU.

Note: (6) Followed by suffixes -LA24RD/O-M or LA24GN/O-M.

Note: (7) Followed by suffixes -V and/or -W and by -3.81 or -6-35.

ST1.5	26-14	Cu	N/A	300	15	B, C	2(105)
STTB1.5, -PV	26-14	Cu	N/A	300	15	B, C	2(105)
ST1.5-QUATTRO	26-14	Cu	N/A	300	15	B, C	2(105)
ST1.5/S-QUATTRO	28-16	Cu	N/A	300, 600	10, 5	B, C, D	2(105)
ST1.5-TWIN	26-14	Cu	N/A	300	15	B, C	2(105)
ST1.5-PE	26-14	Cu	N/A	—	—	B, C	2(105)
STTB1.5-PE	26-14	Cu	N/A	—	—	B, C	2(105)
ST1.5-QUATRTO-PE	26-14	Cu	N/A	—	—	B, C	2(105)

ST1.5-TWIN-PE	26-14	Cu	N/A	—	—	B, C	2(105)
STS4-TWIN, STS4-TWIN/L, STS4, -BU	28-10	Cu	N/A	600	30	B, C	2(105)
STS4-QUATTRO	28-10	Cu	N/A	600	30	B, C	2(105)
STS4-TWIN-PE, STS4-PE	28-10	Cu	N/A	—	—	B, C	2(105)
STS4-QUATTRO-PE	28-10	Cu	N/A	—	—	B, C	2(105)
ST4-HESI (5x20)	28-10	Cu	N/A	300	10	B, C	2(105)
ST4-HESILED 24 (5X20)	28-10	Cu	N/A	300	10	B, C	2(105)
ST4-HESILED 24 I(5X20)	28-10	Cu	N/A	300	10	B, C	2(105)
ST4-HESILED 60 (5X20)	28-10	Cu	N/A	300	10	B, C	2(105)
ST4-HESILA/HESILED 250 (5X20)	28-10	Cu	N/A	300	10	B, C	2(105)
ST4-HESI (6.3x32)	28-10	Cu	N/A	300	15	B, C	2(120)
ST4-HESILED24(6.3x32)	28-10	Cu	N/A	300	15	B, C	2(120)
ST4-HESILED60 (6.3X32)	28-10	Cu	N/A	300	15	B, C	2(120)
ST4-HESILA250(6.3x32)	28-10	Cu	N/A	300	15	B, C	2(120)
SP4, SP4/1 or /2 digit number, w/wo Suffixes -L, -M, -R, w/wo Suffix BU or GNYE	24-10	Cu	N/A	600	30	B, C	2(120)
ST4-MT, -MTD, -TG	28-10	Cu	N/A	300	10	B, C	2(120)
ZFKDS4-7.5/X	24-10	Cu	N/A	300/ 300(1)	30	B, C	2(105)
ZFKDS4-9	24-10	Cu	N/A	300/ 300(1)	30	B, C	2(105)
ZFKDS4-10/X	24-10	Cu	N/A	300/ 600(2)	30	B, C	2(105)
ZFKDS4-12.5/X	24-10	Cu	N/A	600	30	B, C	2(105)
ST4/FSI/C	28-10	Cu	N/A	300	30	B, C	2(105)
ST4/FSI/C-LED12	28-10	Cu	N/A	300	30	B, C	2(105)
ST4/FSI/C-LED24	28-10	Cu	N/A	300	30	B, C	2(105)
ZFKDS407.6GNYE	24-10	Cu	N/A	—	—	B, C	2(105)
ZFKDS4-10GYNE	24-10	Cu	N/A	—	—	B, C	2(105)
ZFKDSA4-9GNYE	24-10	Cu	N/A	—	—	B, C	2(105)
ZFKDSA4-9	24-10	CU	N/A	300/ 150/ 300	30/ 30/ 10	B, C, D	2(105)
MZB-RZ, -BU	24-14	Cu	N/A	600	15	B, C	2(105)
MZDB-RZ, -BU	24-14	Cu	N/A	600	15	B, C	2(105)

ABD4 f/b /1 or /2 digit number, and by -ST-7.62	20-10	Cu	N/A	600	25	B, C	2(105)
ZFKDS10-10.00	24-6	Cu	N/A	300/150	10/65	B, C, D	2(105)
ZFKDSA10-11.7	24-6	Cu	N/A	300/150	10/65	B, C, D	2(105)
ZFKDS10-15.00	24-6	Cu	N/A	600	65	B, C	2(105)
ZFKDSA10-16.7	24-6	Cu	N/A	600	65	B, C	2(105)
SC4 followed by /1 or /2 digit number, w/wo -NS, -RZ, and/or /1-L	28-10	Cu	N/A		30	B, C	2(105)
SGSK6	18-8	Cu	N/A	300	40	B, C	2(105)
SRTK6	18-8	Cu	N/A	300	40	B, C	2(105)
SRDK6	18-8	Cu	N/A	300	40	B, C	2(105)
STTBS4	28-10	Cu	N/A	300 600	30 5	B, C, D	2(105)
STTBS4-PV	28-10	Cu	N/A	300 600	30 5	B, C, D	2(105)
STTBS4-MT	28-10	Cu	N/A	300 600	16 5	B, C, D	2(105)
STTBS4-TG	28-10	Cu	N/A	300 600	16 5	B, C, D	2(105)
STTBS4-PE	28-10	Cu	N/A	N/A	N/A	B, C, D	2(105)
DMKDS2.5	30-14	Cu	5-7	300	10	B, D	2(105)
DMKDS-FS#,-FSI#	—	Cu	—	300	10	B, D	2(105)
FL#(4)	—	—	—	300	10	B, D	2(105)
KDS4#(3)	30-10	Cu	5-7	300	30	B, D	2(105)
KDSP1.5/X(3)	30-14	Cu	5-7	300	15	B, D	2(105)
KDSP4/X(3)	30-10	Cu	5-7	300	30	B, D	2(105)
MKDS1#(3)	30-16	Cu	2.5	300	10(**)	B, D	2(105)
MKDS1.5/X#(3), -5.08	30-14	Cu	5	300	10	B, D	2(105)
MKDS1.5/(3)-10.00	30-14	Cu	5	600	15	B, C	2(105)
MKDS1.5/(3)-10.16	30-14	Cu	5	600	15	B, C	2(105)
MKDSO1.5 (5)	28-16	Cu	0.28	300	8	B	2(115)
MKDS 10/X-10.16	20-6	Cu	1.2-1.5	300	76	C	2(120)
					10	D	

Note: (3) Followed by /one or two digit number.

Note: (4) Followed by 3, or 3, and suffix -H, -S, -SH, -V, -VS, -7.5.

Note: (5) Followed by /3, /4 or /5, followed by -R or -L.

Note: # May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, may be followed by Suffix -HT and/or -PIN 1.65, may be followed by 2AP.

Note: (**) 13.5 Amp max for use with Stranded wire only

MK3DS1/X-3.81 (13)	30-16	Cu	2.5	300	10	B, D	2(105)
MKDS3/X	30-12(10)	Cu	5-7	300	10	B, D	2(105)
MKDSA3/X-3.81	30-12(10)	Cu	5-7	300	10	B, D	2(105)
MKDS3/X-B5.08, MKDS3/X-BK,-BU,-GNYE	30-12(10)	Cu	5-7	300	10	B, D	2(105)
MKDS5/X#(3)11, MKDSV5/(3)(11)	30-10	Cu	5-7	300	30	B	2(105)
	30-10	Cu	5-7	150	15	D	2(105)
	30-10	Cu	5-7	300	10	D	2(105)
MKDS5/X 2-9.5 SZS, MOD	30-10	Cu	5-7	300	30	B	2(105)
	30-10	Cu	5-7	300	30	C	2(105)
	30-10	Cu	5-7	600	5	D	2(105)
MKDS5/2-6.35 BEIGE Z1L	30-10	Cu	5-7	300	30	B	2(120)
	30-10	Cu	5-7	150	15	D	2(120)
	30-10	Cu	5-7	300	10	D	2(120)
MKDS5 (8A)	30-10	Cu	5-7	300	30	B, C	2(105)
MKDSV5 (8A)	30-10	Cu	5-7	300	30	B, C	2(105)
MKDS5HV (8A) (9B)	30-10	Cu	5-7	300 (10)	30	B, C	2(105)
MKDSV5HV (8A) (9B)	30-10	Cu	5-7	300	30	B, C	2(105)
MKDS5 (9A), (9B)	30-10	Cu	5-7	600	30	B, C	2(105)
MKDSV5 (9A)	30-10	Cu	5-7	600	30	B, C	2(105)
MKDS5HV (9A) (9B)	30-10	Cu	5-7	600	30	B, C	2(105)
MKDSV5HV (9A) (9B)	30-10	Cu	5-7	600	30	B, C	2(105)
MKDSO5/3(4)	30-10	Cu	5-7	300	30	B, C	2(105)

Note: (3) Followed by /one or two digit number.

Note: (4) Followed by -L or -R, and 6.35, with or without -BK.							
Note: (6) 15A factory-wiring. Also covered for multiple wire combination of 2 No. 18 AWG Cu. str. for field and factory-wiring.							
Note: (13) Multiple wire combination of three No. 26, 24, or No. 22 AWG Cu. stranded wires for field and factory-wiring.							
Note: # May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, may be followed by Suffix -HT and/or PIN 1.65.							
Note: (8A) Followed by Suffixes /2 or /3 and -9.5 or -9.52 w/wo -HT, ISO TS.							
Note: (9A) Followed by Suffixes /2 or /3 and -9.5 or -9.52 and by Suffix Z.							
Note: (9B) Followed by suffix SZS.							
Note: (10) Two No. 16-24 AWG Cu. str wires for field and factory-wiring.							
Note: (11) May be followed by suffixes -6.35, -7.62, may be followed by suffix -HT and/or -PIN 1.65.							
MKDSO2.5/X-L,-R	30-12	Cu	5-7	300 150 300	20 15 10	B D D	2(105)
MKDSO2.5HV/3L-7.5, MKDSO2.5HV/3R-7.5, MKDSO2.5HV/2L-7.5, MKDSO2.5HV/2R-7.5	30-12	Cu	5-7	300 600(+)	20 5	B, D	2(105)
Note: (+) Meets 600V spacing at field wiring terminals only.							
SMKDSNF1.5X(5)	30-14	Cu	45	300	10	B, D	2(105)
MKDS5/2-7.62, (9B) MKDS5/2-7.62, (9B) MKDS5/3-7.62#	30-10	Cu	5-7	300	30	B, D	2(105)
Note: (5) Followed by 5.08, with or without BK.							
MKDSN1.5, MKDSNB1.5#(3)	30-14	Cu	45	300	10	B, D	2(105)
MKDSN2.5(3)# (9B)	30-12	Cu	5-7	300 150 300	20 15 10	B D D	2(105)
MKDSN2.5 P21	30-12	Cu	5-7	300 150 300	20 15 10	B D D	2(105)
MKDS1.5/2,/3 N-5.08	30-14	Cu	5	300	10	B, D	2(105)
MKDSFW1.5(3)#	30-14	Cu	2.5	300	10	B, D	2(105)

MK3DSN1.5/X# (13)	30-14	Cu	45	300	10	B, D	2(105)
MK3DSNMH/X#	30-14	Cu	45	300	10	B, D	2(105)
GMKDSN1.5/X#	30-14	Cu	45	300	10	B, D	2(105)
SMKDSN1.5#(3)	30-14	Cu	45	300	10	B, D	2(105)
UEG (9)	30-12	Cu	5-7	300	10	B,D	2(105)
UEGM22.5,25,40/1,40/2	30-12	Cu	5-7	300	10	B, D	2(105)
UEGH(8)	30-12	Cu	5-7	300	10	B, D	2(105)
MKDS5HV(-ZB, -ZF)-6.35 (9B)	30-10	Cu	5-7	600	30	B, C	2(105)
MKDS5NHV(-ZB, -ZF)-6.35 (9B)	30-10	Cu	5-7	600	30	B, C	2(105)
MKDS5NHV P35	30-10	Cu	5-7	600	30	B	2(105)
MKDS5NHV(-ZM)-6.35 (9B)	30-10	Cu	5-7	150	30	C	2(105)
MPT0.5 foll. by /1 or /2 digit No., and 5.08, (-1, -2)	30-20	Cu	1	300	6	B, D	2(105)
BC-508X10 (3)	30-14 (11)	Cu	4.5	300	10	B, D	2(105)
BC-508X14 (3)	30-14	Cu	5	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BC-508X18 (3)	30-12	Cu	5-7	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BCA-508X18-#(3)	30-12	Cu	5-7	300	15	B	2(105)
	2 No.24-16 STR	Cu	5-7	300	15	B	2(105)
	30-12	Cu	5-7	150	15	D	2(105)
	2 No.24-16 STR	Cu	5-7	150	15	D	2(105)
	30-12	Cu	5-7	300	15	D	2(105)
	2 No.24-16 STR	Cu	5-7	300	15	D	2(105)
BCP-508 (14)	30-12	Cu	3.5	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BCH-508H (15)	—	—	—	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)

BCH-508V (15)	—	—	—	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BC-500X10 (3)	30-14 (11)	Cu	4.5	300	10	B, D	2(105)
BC-500X14 (3)	30-14	Cu	5	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BCA-500X15 (3)	30-14	Cu	5	250	15	B	2(105)
	30-14	Cu	5	300	10	D	2(105)
BCA-500X18(3)	30-12(10)	Cu	5-7	300	15	B	2(105)
	30-12(10)	Cu	5-7	150	15	D	2(105)
	30-12(10)	Cu	5-7	300	10	D	2(105)
BCA-508X15(3)	30-14	Cu	5	250	15	B	2(105)
	30-14	Cu	5	300	10	D	2(105)
BC-500X18 (3)	30-12	Cu	5-7	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BCP-500 (14)	30-12	Cu	3.5	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BCH-500H (15)	—	—	—	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BCH-500V (15)	—	—	—	300	15	B	2(105)
				150	15	D	2(105)
				300	10	D	2(105)
BC-350X9 (3)	30-16	Cu	0.28	300	10	B	2(105)
	30-16	Cu	0.28	300	10	D	2(105)
BC-381X9 (3)	30-16	Cu	0.28	300	10	B	2(105)
						D	2(105)
BCH-350H (14)	—	—	—	250	8	B	2(105)
	—	—	—	300	8	D	2(105)
BCH-350V (14)	—	—	—	250	8	B	2(105)
	—	—	—	—	—	—	—

	—	—	—	300	8	D	2(105)
BCH-381H (14)	—	—	—	250	8	B	2(105)
				300	8	D	2(105)
BCH-381V (14)	—	—	—	250	8	B	2(105)
				300	8	D	2(105)
BCP-350 (14)	30-14	Cu	0.25	250	8	B	2(105)
	30-14	Cu	0.25	300	8	D	2(105)
BCP-381 (14)	30-14	Cu	2.2	250	8	B	2(105)
				300	8	D	2(105)
BCDH-500 f/b H, HF, HS (3)	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
BCDH-508 f/b H, HF, HS (3)	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
BCVP-350R(12), BCVP-350W (12)	30-14	Cu	4	300	8	B	2(105)
	30-14	Cu	4	300	8	D	2(105)
BCVP-381R(12), BCVP-381W (12)	30-14	Cu	4	300	8	B	2(105)
	30-14	Cu	4	300	8	D	2(105)
BCVP-500R(12)(3)	30-12	Cu	5-7	300	12	B	2(105)
BCVP-500W(12)(3)	30-12	Cu	5-7	300	10	D	2(105)
BCVP-508R(12)(3)	30-12	Cu	5-7	300	12	B	2(105)
BCVP-508W(12)(3)	30-12	Cu	5-7	300	10	D	2(105)

Note: (3) Followed by /one or two digit number.

Note: (5) Followed by /2 through /12, and -5.08 may be followed by PIN2.1 w/wo BK.

Note: (7) With or without suffix /K and/or -DP, -GYNE, or WH.

Note: (8) followed by suffixes 22.5, 25, 27.5, 40, 42.5, or 45 with or without /1, or /2, and/or SMD.

Note: (9) Followed by suffixes 20, 30/1 or 30/2, with or without KMGY SO32.

Note: (9B) May be followed by suffix SZS.

Note: (13) Multiple wire combination of three No. 26, 24, or No. 22 AWG Cu. stranded wires for field and factory-wiring.

Note: (14) w/wo F followed by - one or two digit number.

Note: (15) w/wo F, S followed by - one or two digit number, w/wo CD.

Note: # May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, may be followed by Suffix -HT and/or -PIN 1.65.

Note: (11) Multiple wire combination of (2) 18AWG Cu stranded conductors for field and factory wiring.

MPT0.5/X#-2.54	30-20	Cu	1.0	125	6	B	2(105)
VDFK4(7)	30-10	Cu	5-7	300	30	B, D	2(105)
VDFK6(7)	8-26	Cu	15	300, 150(12) 300/600	50, 50, 10/5	B, C, D	2(105)
GSMKDSN1.5/X#	30-14	Cu	45	300	10	B, D	2(105)
MKKDS1#(3)	30-16	Cu	2.5	300	10	B, D	2(105)
SMKDS1#(3)(9)	30-16	Cu	2.5	300	10	B, D	2(105)
SMKDS1.5(/2, /3)-3.05 SMKDSV1.5(/2, /3)-3.05	30-16	Cu	2.5	300	10	B, D	2(105)
EPTS 2.5/32-V-5.08 NGFT IO; EPTS 2.5, followed by /4 through /32, followed by -V followed by 5.08 NGFT GND	26-12	Cu	N/A	300	2	D	2(105)
MKDSP1.5#(3), -5.08	30-14	Cu	5	300	10	B, D	2(105)
MKDSP2.5#(3)	30-12	Cu	5-7	300	10	B, D	2(105)
MKDSP10/2-10.16, MKDSP10/3-10.16	20-6	Cu	15	300	60	B, C	2(105)
MKDSP10N/X-10.16 (9B)	20-6	Cu	15	300	60	B, C	2(105)
	20-6	Cu	15	600	5	D	2(105)
MKDSP10HV/1 or /2-digit number, -10.16 (9B)	20-6	Cu	15	300, 600	60, 5	B, C, D	2(105)
MKDSP10HV/1 or /2-digit number, -12.7 (9B)	20-6	Cu	15	600	60	B, C	2(105)
MKDS10HV/1 or 2-digit number, -ZB, or -ZF, -10.16 w/wo SZS	20-6	Cu	15	600	60	B, C	2(105)
MKDS10HV/1 or 2-digit number, -B, or -F, -10.16 w/wo SZS	20-6	Cu	15	300	60	B	2(105)
	20-6	Cu	15	150	60	C	2(105)
	20-6	Cu	15	300	10	D	2(105)
EMKDS2.5#(3)	30-12	Cu	5-7	300	10	B, D	2(105)
EMKDS1.5(3)#	30-14	Cu	2.5	300	10	B, D	2(105)
MKDSD1.5/X(3)#	30-14	Cu	2.2	300	10	B, D	2(105)

MKDS2.5/X-5.08	30-12	Cu	5-7	300 150 300	20 15 10	B D D	2(105)
MKDS2.5#(3)	30-12, (2)18AWG str	Cu	5-7	300	20	B, D	2(105)
MKDSFW1.5/X#(3)	30-14	Cu	5	300	10	B, D	2(105)
MKDSW3/X#(3)	30-12(10)	Cu	5-7	300	10	B, D	2(105)
MKKDS5/X#(3)	30-10	Cu	5-7	300	30	B, C	2(105)
MKKDSN1.5#(3)	30-14	Cu	45	300	10	B, D	2(105)
MKKDSN1.5/X(3)	30-14	Cu	4.5	300	10	B, D	2(105)
MKKDSNH1.5(3)(4)	30-14	Cu	45	300	10	B, D	2(105)
MKDSP25/X-15.00, w/wo -F, -FL, -FR or S, w/wo T20L	20-10,	Cu	2.5	600	30	B, C	2(105)
	8-2	Cu	4.5	600	115	B, C	2(105)
	8-2	Cu	4.5	600	125(8)	B, C	2(105)
MKDSP25/6-15.00 3-4-B	8 str(13)	Cu	2.5	600	48	B,C	2(105)
	4 str(13)	Cu	2.5	600	80	B,C	2(105)
	10 sol/str(14)	Cu	2.5	N/A	N/A	B,C	2(105)
	6 str (14)	Cu	2.5	N/A	N/A	B,C	2(105)
MKDSP 95 (*)	6-3/0	Cu	88.5	600	200	B, C	2(120), 4
MKDSP 50/X-17.5 (+)	16-2/0	Cu	5.5	600	160	B, C	2(120), 4

Note: (3) Followed by /one or two digit number.

Note: (6) 15A max. for factory-wiring only. Also covered for multiple wire combination of 2 No. 18 AWG Cu. str for field and factory-wiring.

Note: (8) 125A for factory-wiring only.

Note: (9) May be followed by suffix BK, HT, VO.

Note: (10) Two No. 16-24 AWG Cu. str wires for field and factory-wiring

Note: # May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, may be followed by Suffix, -HT and/or -PIN 1.65.

Note: (12) May be suitable for 300V Use Group "C" when factory-wired solder terminals are suitably insulated or isolated to provide required spacings from terminal to terminal.

Note: (13) Ratings applicable for poles 1, 2, 5 and 6.

Note: (14) PCTB approval applicable for poles 3 and 4 (between the bridged poles only).

(*) Followed by /1 through 5, followed by -20.00, followed by -F or -FL, followed by two letters denoting color or blank.

Note: (+) May be followed by -F or HEX5 and by two letters denoting color or blank.

UKH50(IB)	6-1/0	Cu	70	600	150	B, C	2(105)
UKH95	2-4/0	Cu	175	600	230	B, C	2(105)
DFK-MSTB(1)(2)	—	Cu	N/A	600	12	B, D	2(105)
DFK-MSTB(1)(6)	—	Cu	N/A	300	15	B, D	2(105)
DFK-MSTBA(1)(6)	—	Cu	N/A	300	15	B, D	2(105)
DFK-MSTBVA(1)(6)	—	Cu	N/A	300	15	B, D	2(105)
FRONT-MSTB(1)(3)	30-12	Cu	5-7	600	15	B, D	2(105)
FRONT-MSTB(1)((7)	30-12	Cu	5-7	300	15	B, D	2(105)
MDSTB(1)(4)	—	Cu	N/A	300	15	B, D	2(105)
MDSTBV(1)(4)	—	Cu	N/A	300	12	B, D	2(105)
MDSTBV(1)(2)	—	Cu	N/A	300	12	B, D	2(105)
MDSTBVA(1)(2)	—	Cu	N/A	300	12	B, D	2(105)
MDSTBVA(1)(4)	—	Cu	N/A	600	12	B, D	2(105)
MDSTBVH(1)(4)	—	Cu	N/A	600	12	B, D	2(105)
MDSTBVH(1)(2)	—	Cu	N/A	300	12	B, D	2(105)
MDSTBVHA(1)(4)	—	Cu	N/A	600	12	B, D	2(105)
MDSTBVHA(1)(2)	—	Cu	N/A	300	12	B, D	2(105)
MDSTBW(1)(4)	—	Cu	N/A	300	15	B, D	2(105)
MDSTBW(1)(2)	—	Cu	N/A	300	15	B, D	2(105)
MSTB(1)(2)(16)	N/A	N/A	N/A	300	10	B	2(105)
	N/A	N/A	N/A	150	10	D	2(105)
	N/A	N/A	N/A	300	8	D	2(105)
MSTB(1)(5)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
MSTB(1)(8)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MSTB(1B)(3)	30-12(14)	Cu	0.6	300	16	B, D	2(105)
MSTB(1)(1B)(9)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
MSTBP(1)(1B)(5)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
MSTBP(1)(1B)(8)	30-12(14)	Cu	0.6	300	15	B, D	2(105)

MSTB, MSTBP, MSTBT, SMSTB, MVSTBN, MVSTBR, MVSTBW, TMSTBP with suffix -ST, -STF, -10.16	30-12 (14)	Cu	0.6	300	15	B	2(105)
	30-12 (14)	Cu	0.6	300	12	C	2(105)
	30-12 (14)	Cu	0.6	600	5	D	2(105)
MSTB, MSTBP, MSTBT, SMSTB, MVSTBN, MVSTBR, MVSTBW, TMSTBP with suffix HC, -ST, -STF, -10.16	30-12 (14)	Cu	0.6	300	15	B	2(105)
	30-12 (14)	Cu	0.6	300	12	C	2(105)
	30-12 (14)	Cu	0.6	600	5	D	2(105)
Note: (14) Two No. 16-24 AWG Cu. str wires for field and factory-wiring.							
MSTBT(1)(1B)(5)	30-12(10)	Cu	0.6	600	15	B, D	2(105)
MSTBT(1)(5)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MSTB(1)(1A)(6)(7)	—	Cu	N/A	600	16	B, D	2(105)
MSTB(1)(1A)(3)(7)	—	Cu	N/A	300	16	B, D	2(105)
MSTBA(1)(1A)(6)(7), -THT	—	Cu	N/A	600	16	B, D	2(105)
MSTBA(1)(1A)(3)(7)	—	Cu	N/A	300	16	B, D	2(105)
MSTBAG(1)(1A)(6)(7)	—	Cu	N/A	600	16	B, D	2(105)
MSTBAG(1)(1A)(3)(7)	—	Cu	N/A	300 150 300	15 15 10	B D D	2(105)
MSTBV(1)(1A)(6)(7)	—	Cu	N/A	600	15	B, D	2(105)
MSTBV(1)(1A)(3)(7)	—	Cu	N/A	300	15	B, D	2(105)
MSTBVW(1)(2)(7)	—	Cu	—	300	15	B, D	2(105)
Note: (1) Suffix 2.5, followed by /one or two digit number.							
Note: (1A) With or without suffixes HC and/or L.							
Note: (2) Suffixes -ST, -STD, -STF or -STZ, followed by -5.08, w/wo -AB, -AU, -LR, and/or -SO.							
Note: (3) Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03.							
Note: (5) Suffixes -ST, -STD, -STF or -STZ, followed by -10.16-1 or -10.6-2, w/wo -AB, -AU -LR, -P+F, -DOM, and/or -SO.							
Note: (6) Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03.							
Note: (7) May be followed by PXX							
MSTBVA(1)(1A)(6)(17), -THT	—	Cu	N/A	600	12	B, D	2(105)

MSTBVA(1)(1A)(2)(17)	—	Cu	N/A	300	12	B, D	2(105)
A-MSTBV(1)(1A)(6)(17)	—	Cu	N/A	600	12	B, D	2(105)
A-MSTBV(1)(1A)(2)(17)	—	Cu	N/A	300	12	B, D	2(105)
A-MSTBVA(1)(1A)(6)(17)	—	Cu	N/A	600	12	B, D	2(105)
A-MSTBVA(1)(1A)(2)(17)	—	Cu	N/A	300	12	B, D	2(105)
EMSTBVA(1)-G-5.08(17)	—	Cu	N/A	300	12	B, D	2(105)
MSTBVAG(1)(1A)(6)(17)	—	Cu	N/A	600	12	B, D	2(105)
MSTBVAG(1)(1A)(2)(17)	—	Cu	N/A	300	12	B, D	2(105)
MSTBW(1)(1A)(6)(17)	—	Cu	N/A	600	16	B, D	2(105)
MSTBW(1)(1A)(2)(17)	—	Cu	N/A	300	16	B, D	2(105)
MVSTBN(1)(1B)(7)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
MVSTBN(1)(1B)(3)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MVSTBR(1)(1B)(7)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
MVSTBR(1)(1B)(3)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MVSTBW(1)(1B)(7)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
MVSTBW(1)(1B)(3)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MVSTBR(1B)(8)	30-12(14)	Cu	0.6	300	16	B, D	2(105)
MVSTBW(1B)(8)	30-12(14)	Cu	0.6	300	16	B, D	2(105)
MVSTBR ASI/ 4-ST-5.08 (16)	2 No. 16 Str (15)	Cu	N/A	300	2	B, D	2(105)
MVSTBW ASI/ 4-ST-5.08 (16)	2 No. 16 Str (15)	Cu	N/A	300	2	B, D	2(105)

Note: (1) Suffix 2.5, followed by /one or two digit number.

Note: (1A) With or without suffixes HC and/or L.

Note: (1B) Suffixes 2.5, followed by HC, followed by / one or two number.

Note: (2) Suffixes -G, -GB, -G0.5, -GF or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03.

Note: (3) Suffixes -ST, -STD, or -STF, followed by -5.08, w/wo -KM, -AU, -LR, -BK, -GY and/or -ABGY, -DOM.

Note: (6) Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03.

Note: (7) Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY.

Note: (14) Two No. 16-24 AWG Cu. str wires for field and factory-wiring

Note: (15) ASI-Cable 2 No. 1.5 mm2 (2 No. 16 AWG)

Note: (16) May be followed by -KM, -AU, -LR, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN.

Note: (17) May be followed by PXX, which designate free pin length below PWB, PIN XX or PXX, where the XX is for one or two digit numbers.

SMSTB(1)(10)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
SMSTB(1)(8)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
SMSTB(1)(2)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
SMSTB(1)(9)	—	Cu	N/A	600	15	B, D	2(105)
SMSTB(1)(3)	—	Cu	N/A	300	15	B, D	2(105)
SMSTBA(1)(9)	—	Cu	N/A	600	15	B, D	2(105)
SMSTBA(1)(3)	—	Cu	N/A	300	15	B, D	2(105)
FKCT(1)(10)	26-12	Cu	N/A	300	10A and rated 16A if includes Suffix-HC	B, D(for 10A)	2(105)
FKC, FKCS(1)(10)	26-12	Cu	N/A	300	10A and rated 16A if includes Suffix-HC	B, D(for 10A)	2(105)
TFKC(1)(4)	26-12	Cu	N/A	300	10A and rated 16A if includes Suffix-HC	B, D(for 10A)	2(105)
FKIC, FKICS(1),(5),(10)	26-12	Cu	N/A	300	10A and rated 16A if includes Suffix-HC	B, D(for 10A)	2(105)
FKCVR(1)(10)	26-12	Cu	N/A	300	10A and rated 16A if includes Suffix-HC	B, D(for 10A)	2(105)

FKCVW(1)(10)	26-12	Cu	N/A	300	10A and rated 16A if includes Suffix-HC	B, D(for 10A)	2(105)
TMSTBP(1)(11)	30-12(14)	Cu	0.6	600	15	B, D	2(105)
TMSTBP(1)(4)	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MSTBO(1)(12)	—	Cu	N/A	600	8	B, D	2(105)
MSTBO(1)(3)	—	Cu	N/A	600	8	B, D	2(105)
MSTBO(1)(5)	—	Cu	N/A	300	8	B, D	2(105)
				300	10	D	
				50	12	D	
MSTBO2.5/X followed by, -GL, w/wo -5.08	—	Cu	N/A	300	12	B	2(105)
				300	10	D	
				150	12	D	
MSTBO2.5/X followed by -G1L, -G1R, w/wo -5.08, THR, 00, OK, KO, P+F	—	Cu	N/A	300	16	B	2(105)
				300	10	D	
				150	15	D	
MSTB2.5/2-GFL-5.08	—	Cu	—	300	15	B, D	2(105)
MSTB2.5/2-STFL-5.08	30-12(14)	Cu	0.6	300	15	B, D	2(105)
MVSTBR2.5/X-STF-10.16-1, -2	30-12(14)	Cu	0.6	600	10	B, C	2(105)
CC,CCA, CCVA, CCV(1),(13)	—	Cu	N/A	300	16	B	2(130)
					10	D	
	—	Cu	N/A	150	15	D	2(130)
CC, CCV (1)(15)	—	Cu	N/A	300	16	B	2(130)
					10	D	
	—	Cu	N/A	150	15	D	2(130)
MSTB2.5 HC (16)	30-12	Cu	5-7	300	16	B	2(105), 4
				300	10	D	
				150	15	D	
FRONT-MSTB2.5 (16)	30-12	Cu	5-7	300	15	B	2(105), 4
				300	10	D	
				150	15	D	
TVMSTB (1)-ST-5.08, TVMSTB (1)-STF-5.08	30-12	Cu	2	300	10	B, C	2(105), 4
FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5,08 with or without -LR	26-12	Cu	N/A	300	12	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)

DFK-MSTB2.5/X f/b -G, -GF	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
EMSTBV2.5/X f/b -G, -GF, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN.	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
FKC2.5/X f/b -ST, -STF, -STZ, -STB w/wo -5.08	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCS2.5/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCT2.5/X f/b -ST, -STF, -STZ, w/w -LIFT	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCVR2.5/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCVW2.5/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKC2.5HC/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	16	B	2(105)
	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCS2.5HC/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	16	B	2(105)

	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCT2.5HC/X f/b -ST, -STF, -STZ, w/w -LIFT	26-12	Cu	N/A	300	16	B	2(105)
	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCVR2.5HC/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	16	B	2(105)
	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKCVW2.5HC/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	16	B	2(105)
	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKIC2.5/X-TB	26-12	Cu	N/A	300	12	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKIC2.5/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKICS2.5/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	10	B	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKIC2.5HC/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	16	B	2(105)
	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FKICS2.5HC/X f/b -ST, -STF, -STZ	26-12	Cu	N/A	300	16	B	2(105)
	26-12	Cu	N/A	150	15	D	2(105)
	26-12	Cu	N/A	300	10	D	2(105)
FRONT-MSTB2.5/X f/b -ST, -STF	30-12	Cu	0.6-0.8	300	15	B	2(105)
	30-12	Cu	0.6-0.8	150	15	D	2(105)
	30-12	Cu	0.6-0.8	300	10	D	2(105)
MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, and/or -10-1 or 10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, and/or -10-1 or 10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT W/OPENING, and/or -10-	N/A	N/A	N/A	300	12	B	2(105)

1 or 10-2	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT W/OPENING, and/or -10-1 or 10-2	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT W/OPENING, and/or -10-1 or 10-2	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT W/OPENING, and/or -10-1 or 10-2	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT W/OPENING, and/or -10-1 or 10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-1 or -10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT W/OPENING and/or -10-1 or -10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT W/OPENING and/or -10-1 or -10-2	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT W/OPENING and/or -10-1 or -10-2	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)

	N/A	N/A	N/A	600	5	D	2(105)
MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT W/OPENING and/or -10-1 or -10-2	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT W/OPENING and/or -10-1 or -10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTB2.5/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
Type MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
Type MSTBTP f/b 2.5, f/b /one or two digit number, f/b -ST or -STF	30-12	Cu	0.6	300	12	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	12	B	2(105)
	30-12	Cu	0.6	150	12	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	12	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTBP2.5/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	15	B	2(105)

	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MVSTBN2.5/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MVSTBW2.5/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)

	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTB2.5HC/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	16	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTBP2.5HC/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	16	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F	30-12	Cu	0.6	300	16	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTBT2.5HC/2-STP, MSTBT2.5HC/3-STP, MSTBT2.5HC/4-STP	30-12	Cu	0.6	300	16	B	2(105),4
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105),4
	30-12	Cu	0.6	150	15	D	2(105),4
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105),4
	30-12	Cu	0.6	300	10	D	2(105),4

	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105),4
MVSTBN2.5HC/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	16	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MVSTBR2.5HC/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	16	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MVSTBW2.5HC/X f/b -ST, -STF, -STZ	30-12	Cu	0.6	300	16	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	16	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)

	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)
	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)
	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	12	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	12	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)
	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)

	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)
	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)
	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)

	N/A	N/A	N/A	300	10	D	2(105)
MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, - GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBO2.5/2, MSTBO2.5/3, MSTBO2.5/4 f/b -G1PL, -G1PR	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, - THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)

	N/A	N/A	N/A	300	10	D	2(105)
MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	16	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)

	N/A	N/A	N/A	600	5	D	2(105)
MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	12	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
QC1.5/X f/b -ST, -STF	24-16	Cu	N/A	300	10	B	2(105)
	24-16	Cu	N/A	300	10	D	2(105)
SMSTB2.5/X-G	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
SMSTBA2.5/X-G	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
SMSTB2.5/X-ST f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
SMSTB2.5/X-G f/b -10-1, 10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	12	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
SMSTBA2.5/X-G f/b -10-1, 10-2	N/A	N/A	N/A	300	15	B	2(105)
	N/A	N/A	N/A	150	15	D	2(105)
	N/A	N/A	N/A	300	10	D	2(105)
	N/A	N/A	N/A	600	5	D	2(105)
SMSTB2.5/X-ST f/b 10-1, 10-2	30-12	Cu	0.6	300	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	12	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	12	D	2(105)

	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
	30-12	Cu	0.6	600	5	D	2(105)
	2 No. 24-16 STR	Cu	0.6	600	5	D	2(105)
TMSTBP2.5/X f/b -ST, -STF w/wo P+F	30-12	Cu	0.6	250	15	B	2(105)
	2 No. 24-16 STR	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	2 No. 24-16 STR	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
	2 No. 24-16 STR	Cu	0.6	300	10	D	2(105)
TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F	30-12	Cu	0.6	300	15	B	2(105)
	30-12	Cu	0.6	150	15	D	2(105)
	30-12	Cu	0.6	300	10	D	2(105)
TVFKC1.5/X-ST (17)	24-16	Cu	N/A	300	8	B	2(105)
	24-16 SOL	Cu	N/A	300	10	B	2(105)
	24-16	Cu	N/A	300	8	D	2(105)
	24-16 SOL	Cu	N/A	300	10	D	2(105)
TVFKCL1.5/X-ST	24-16	Cu	N/A	300	8	B	2(105)
	24-16 SOL	Cu	N/A	300	10	B	2(105)
	24-16	Cu	N/A	300	8	D	2(105)
	24-16 SOL	Cu	N/A	300	10	D	2(105)
CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR.	N/A	Cu	N/A	300	10	B, D	2(105)
PSPT2.5/X-ST (/X is followed by /2, /3 or /4)	24-14 sol/str	Cu	N/A	300	15	B	2(105)
	24-14 sol/str	Cu	N/A	150	15	D	2(105)
	24-14 sol/str	Cu	N/A	300	10	D	2(105)
FKCOR2.5/X, FKCOW2.5/X followed by -ST, -STF, -5,08 with or without -LR	26-12	Cu	N/A	300	12	B	2(105)

	26-12	Cu	N/A	300	10	D	2(105)
GMSTBT (10)	24-12	Cu	4.4-5.3	600	16	B, C	2(130)
GMSTBT 2.5 HV/3-ST-7.25 KMGY PA2	24-12	Cu	4.4-5.3	1000	16	E	2(115), 4
GMSTBO (11)	N/A	N/A	N/A	300	16	B	2(130)
	N/A	N/A	N/A	150	16	C	2(130)
	N/A	N/A	N/A	300	10	D	2(130)
GMSTBO 2.5 HV/3, f/b -GL or -GR, f/b -7.25 THR PA1.3	N/A	N/A	N/A	1000	16	E	2(130)
FRONT-GMSTB(1)(2)	30-12	Cu	5-7	300	15	B, D	2(105)
GMSTB(1)(2)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GMSTB(1)(3)	30-12(8)	Cu	5-7	600	15	B, D	2(105)
GMSTB(1C)(5)(14)	30-12	Cu	5-7	600	20	B, C	2(105)
GMSTB(1B)(3)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GMSTB(1)(3)	30-12(8)	Cu	5-7	300	16	B, D	2(105)
GMSTBP(1)(5)	30-12(8)	Cu	5-7	600	15	B, D	2(105)
GMSTBP(3)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GMSTB(1)(4)	—	Cu	N/A	600	15	B, D	2(105)
GMSTB(1)(6)	—	Cu	N/A	300	15	B, D	2(105)
GMSTBA(1B)(4)	—	Cu	N/A	600	15	B, D	2(105)
GCCA(1B)(7)	—	Cu	N/A	600	15	B, D	2(105)
GMSTBV(1)(4)	—	Cu	N/A	600	15	B, D	2(105)
GMSTBV(1)(6)	—	Cu	N/A	300	15	B, D	2(105)
GMSTBVA(1B)(4)	—	Cu	N/A	600	15	B, D	2(105)
GMSTBVA(1)(6)	—	Cu	N/A	300	16	B, D	2(105)
GMSTBAS2.5/4-G-7.62	—	Cu	—	600	15	B, D	2(105)
FKCN2.5 (9)	24-14 SOL/STR	Cu	N/A	300	10	B, D	2(105)
GMSTB (1B)(3A)	—	Cu	N/A	300	15	B, D	2(105)
GMSTBA (1B)(3A)	—	Cu	N/A	300	20	B, D	2(105)
GMSTBV (1B)(3A)	—	Cu	N/A	300	15	B, D	2(105)
GMSTBVA (1B)(3A)	—	Cu	N/A	300	20	B, D	2(105)
GMSTB(1B)(13)	—	Cu	N/A	300	15	B, D	2(105)
GMSTBA(1B)(13)	—	Cu	N/A	300	15	B, D	2(105)
GMSTBV(1B)(13)	—	Cu	N/A	300	15	B, D	2(105)

GCCA(1B)(3A)	—	Cu	N/A	300	20	B, D	2(105)
GMSTB (16)	26-12	Cu	—	300	10	B, D	2(105)
GMVSTBR 2.5 f/X w/wo-ST,f/b-7.62, f/b -PA13 SO	30-12	Cu	5-7	600	15	B, C	2(105)

Note: (16): f/X f/b -ST, STF, f/b -7.5, -7.62, w/wo RDB.							
Note: (17) May be followed by RDB.							
GMVSTBR(1)(5)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GMVSTBW(1)(5)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GMSTB(1B)(3)	30-12(8)	Cu	5.7	300	16	B, D	2(105)
GMVSTBR(1B)(5)	30-12(8)	Cu	5.7	300	16	B, D	2(105)
GMVSTBR(1)(6)	30-12(8)	Cu	5-7	600	15	B, C	2(105)
GMVSTBW(1)(6)	30-12(8)	Cu	5-7	600	15	B, C	2(105)
UGMSTBHK(1)(7)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GMSTBHK(1)(7)	30-12(8)	Cu	5-7	300	15	B, D	2(105)
GFKC (1) -ST, -STF, -STF-SH(9) (10)	26-12	Cu	N/A	300	10	B, D	2(105)
GFKIC (1) -ST(9)	26-12	Cu	N/A	300	15	B, D	2(105)
Note: (1) Suffix 2.5, followed by /one or two digit number.							
Note: (1B) Suffixes 2.5, followed by HC, followed by / one or two number.							
Note: (5) Suffixes -ST or -STF, w/wo -7.62.							
Note: (6) Suffixes HV, followed by -ST or -ST-7.62 or /8-STGY3XEB2							
Note: (7) Suffixes /10-G, w/wo -7.62.							
Note: (8) Two No. 16-24 AWG Cu. str wires for field and factory-wiring							
Note: (9) Followed by suffix -7.5 or -7.62							
Note: (10) May be followed by RDB or RAE.							
GIC, GICV(1)(2) with HC	—	Cu	N/A	250 150 300	16 15 10	B D D	2(105)
GIC, GICV(1)(2)	—	Cu	N/A	250 150 300	12 12 10	B D D	2(105)
GIC (1)(3)	30-12(15)	Cu	5-7	250 150 300	12 12 10	B D D	2(105), 4

GIC, (1)(3) with HC	30-12(15)	Cu	5-7	300 150 300	16 15 10	B D D	2(105), 4
GIC(1)(3) with HCV	30-12(15)	Cu	5-7	600	16 suffix -HC	B, C	2(105), 4
IC,ICV, AICV (1)(4) with HC	—	Cu	N/A	250 150 300	16 15 10	B D D	2(105)
IC, ICV(1)(7)	—	Cu	N/A	250	12	B	2(105)
	—	Cu	N/A	150	12	D	2(105)
	—	Cu	N/A	300	10	D	2(105)
IC, ICV(1)(5)	30-12(15)	Cu	5-7	250 150 300	16 15 10	B D D	2(105), 4
IC, ICV(1)(5) with HC	30-12(15)	Cu	5-7	250 150 300	16 15 10	B D D	2(105), 4
MSTBH(6)	—	Cu	N/A	300	15	B, D	2(105)
MSTBHK(6)	30-12	Cu	25-7	300	15	B, D	2(105)
MSTBHKT(6)	30-12	Cu	5-7	300	15	B, D	2(105)
Note: (1) Suffixes 2.5, followed by /one of two-digit number.							
Note: (2) Suffixes with or without HC or HCV, followed by -G, -GF, followed by -7.62.							
Note: (3) Suffixes with or without HC or HCV, followed by -ST, -STF, -STGF, followed by -7.62.							
Note: (4) Suffixes -G, -GF, followed by -5.08.							
Note: (5) Suffixes -ST, -STF, -STGF, followed by -5.08.							
Note: (6) Suffixes 2.5, followed by /10G, followed by -5.08.							
Note: (7) Suffixes -G, -GF, -GFL or -GFR, followed by -5.08.							
UMSTBHK(6)	30-12	Cu	5-7	300	15	B, D	2(105)
UMSTBHKT(6)	30-12	Cu	5-7	300	15	B, D	2(105)
MSTBU(1)(7)	30-12(15)	Cu	5-7	300	15	B, D	2(105)
MVSTBU(1)(8)(11)	—	Cu	N/A	300	15	B, D	2(105)
MVSTBU(1)(9)(14)	30-12(15)	Cu	5-7	300	15	B, D	2(105)

MSTBVK(1)(10)	—	Cu	N/A	300	15	B, D	2(105)
Note: (1) Suffixes 2.5, followed by /one of two-digit number.							
Note: (6) Suffixes 2.5, followed by /10G, followed by -5.08.							
Note: (7) Suffixes -ST, -STD, followed by -5.08, w/wo -FL.							
Note: (8) Suffixes -GB, -GFB, followed by -5.08.							
Note: (9) Suffixes -STF, followed by -5.08.							
Note: (10) Suffixes -G, -GF, followed by -5.08.							
Note: (11) Suffixes -STSO CEAG, STFSO CEAG followed by -5.08.							
Note: (14) Cat. No. MVSTBU2.5 additionally has a multiple wire rating of 2 No. 16 AWG Cu. stranded wires for field and factory-wiring.							
Note: (15) Two No. 16-24 AWG Cu wires for field and factory-wiring							
MVSTBK(1)(11)	30-12(15)	Cu	5-7	300	15	B, D	2(105)
UMSTBVK(1)(10)	—	Cu	N/A	300	15	B, D	2(105)
UMSTBVK(1)(11)	30-12(15)	Cu	5-7	300	15	B, D	2(105)
UMSTBVK2.5/X-STF- 10.16-1, -2	30-12(15)	Cu	5-7	600	10	B, C	2(105)
UMSTBVK2.5/X-GF 10.16-1, -2	—	Cu	N/A	60	10	B, C	2(105)
SKLB(12)	—	Cu	N/A	300	10	B, D	2(105)
SKLB(13)	30-12	Cu	5-7	300	10	B, D	2(105)
Note: (1) Suffixes 2.5, followed by /one of two-digit number.							
Note: (10) Suffixes -G, -GF, followed by -5.08.							
Note: (11) Suffixes -ST, -STF, followed by -5.08.							
Note: (12) Suffixes 2.5, /12.							
Note: (13) Suffixes 2.5, /12, followed by -ST.							

Note: (15) Two No. 16-24 AWG Cu. str wires for field and factory-wiring

USLKG1.5N	26-14	Cu	0.22-0.25	600	N/A	B, C	2(105)
USLKG2.5, TB 2.5-PE EI	24-12	Cu	0.6-0.8	600	N/A	B, C	2(105)
USLKG2.5N, USLKG2.5N-1	24-12	Cu	0.6-0.8	600	N/A	B, C	2(105)
USLKG3, -1	24-12	Cu	0.6-0.8	600	N/A	B, C	2(105)
USLKG3N	24-12	Cu	0.6-0.8	600	N/A	B, C	2(105)
USLKG4, -1	24-12	Cu	0.5-0.6	600	N/A	B, C	2(105)
USLKG5, -1, TB 4-PE EI	24-10	Cu	0.6-0.8	600	N/A	B, C	2(105)
USLKG6N, -1, TB 6-PE EI	24-8	Cu	1.5-1.8	600	N/A	B, C	2(105)
USLKG10, -1, TB 10-PE EI	20-8	Cu	1.5-1.8	600	N/A	B, C	2(105)
USLKG10N, -1	20-6	Cu	1.5-1.8	600	N/A	B, C	2(105)
USLKG16, -1	20-6	Cu	1.5-1.8	600	N/A	B, C	2(105)
TB 16-PE EI, TB 16-PE I	20-6	Cu	2.5-3	600	N/A	B,C	2(105)
USLKG35, -1, TB 35-PE EI	18-1/0	Cu	3.2-3.7	600	N/A	B, C	2(105)
USLKG50, USLKG50IB	1/0-6	Cu	8	600	N/A	B, C	2(105)
USLKG95	2-4/0	Cu	20	600	N/A	B, C	2(105)
UISLKG16, -1	12-4	Cu	1.5-1.8	600	N/A	B, C	2(105)
USLKG16N, -1	22-4	Cu	1.5-1.8	600	N/A	B, C	2(105)
UKK5-PE	24-10	Cu	0.6-0.8	600	N/A	B, C	2(105)
UKKB5-PE	24-10	Cu	0.6-0.8	600	N/A	B, C	2(105)
IDC0.3/X-3.81	22-28	Cu	N/A	300	5	B, D	2(130), 4
GMKDS3, followed by one or two digit number; may be followed by -7.62	12-30(5)	Cu	5-7	300	15	B, D	2(105)
GMKDS3, followed by one or two digit number; may be followed by -7.62	12-30(5)	Cu	5-7	300	15	B, D	2(105)
GMKDSP3, followed by one or two digit number; may be followed by -7.62	12-30(5)	Cu	5-7	300	15	B, D	2(105)
GMKDSP3, followed by one or two digit number; may be followed by -7.62	12-30(5)	Cu	5-7	300	15	B, D	2(105)
GSMKDS3, followed by one or two digit number; may be followed by -7.62	12-30(5)	Cu	5-7	300	15	B, D	2(105)
GSMKDS3/3(2)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MKDSF3/2(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MKDSF3/3(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MKDSF3/4(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)

MKDSF3/8(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MKDSF3/12(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MKDSF3/2-S01(1)	12-30(5)	Cu	5-7	300	10	B, D	2(105)
MKDSF3/3-S01(1)	12-30(5)	Cu	5-7	300	10	B, D	2(105)
Note: (1) May be followed by -5.08.							
Note: (2) May be followed by -7.62.							
Note: (5) Two No. 16-24 AWG Cu. str wires for field and factory-wiring							
MKDSF3/4-S01(1)	12- 30(5)	Cu	5-7	300	10	B, D	2(105)
MKDSF3/8-S01(1)	12- 30(5)	Cu	5-7	300	10	B, D	2(105)
MKDSF3/12-S01(1)	12- 30(5)	Cu	5-7	300	10	B, D	2(105)
MKDSFW3/2	12- 30(5)	Cu	5	300	16	B, D	2(105)
MKDSFW3/3	12- 30(5)	Cu	5	300	16	B, D	2(105)
MKDSP3/2(1)	12- 30(5)	Cu	5	300	15	B, D	2(105)
MKDSP3/3(1)	12- 30(5)	Cu	5	300	15	B, D	2(105)
SMKDS1.5/2(3)	14- 30	Cu	5-7	300	10	B, D	2(105)
SMKDS1.5/3(3)	14- 30	Cu	5	300	10	B, D	2(105)
Note: (1) For factory-wiring, wire range is extended to No. 28 AWG.							
Note: (1) May be followed by -5.08.							
Note: (3) May be followed by -5.08, -6.35 or -9.5.							
Note: (5) Two No. 16-24 AWG Cu. str wires for field and factory-wiring							
SMKDS2.5/2(3)	30-12	Cu	5-7	300	15	B, D	2(105)
SMKDS2.5/3(3)	30-12	Cu	5-7	300	15	B, D	2(105)
SMKDS3/2(3)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
SMKDS3/3(3)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
SMKDS5/2(3)	10-30	Cu	5-7	300	30	B, D	2(105), 4
SMKDS5/2-9.5	10-30	Cu	5-7	300	30	B, C	2(105), 4
SMKDS5/3(3)	10-30	Cu	5-7	300	30	B, D	2(105), 4
SMKDS5/3-9.5	10-30	Cu	5-7	300	30	B, C	2(105), 4

SMKDSP1.5(1)(3)	14-30	Cu	5	300	15	B, D	2(105)
SMKDSFU2.5/X-5.08	14-30	Cu	5-7	300	10	B, D	2(105)
DFLK-D(1)Sub/B	12-30	Cu	5-7	125	2.5	B	2(105)
DFLK-D(1)Sub/S	12-30	Cu	5-7	125	2.5	B	2(105)
Note: (1) Followed by one or two-digit number.							
Note: (3) May be followed by -5.08, -6.35.							
Note: (5) Two No. 16-24 AWG Cu. str wires for field and factory-wiring							
FFKDS, FFKDSA w/wo suffix 1 f/b /H1, /H2, /V1, V2, f/b 5.08 or 7.62	24-16	Cu	N/A	300	10	B, D	2(115)
FFKDS, FFKDSA w/wo suffix 1 f/b /H, /V, f/b 2.54 or 5.08	26-18	Cu	N/A	150	6	B, D	2(115)
FFKDS, FFKDSA w/wo suffix 1 f/b /H, /V, f/b 3.81 or 6.35	26-16	Cu	N/A	300	10	B, D	2(115)
MFKDSP-5.08	22-18	Cu	N/A	300	7	B, D	2(105)
Note: (1) With or without suffix 1, followed by -5.08 or -7.62, may be followed by suffixes /SA and/or 5.08 or 10.16.							
Note: (2) With or without suffix 1, followed by suffix /H1, /H2, /V1 or /V2, followed by -5.08 or -7.62.							
Note: (3) Followed by /2, /3, /4, /6 or /7, followed by -5.08							
Note: (4) Additional wire sizes of No. 14-12 AWG Sol.							
Note: (5) With or without 1, followed by /H or /V, followed by -2.54 or -5.08.							
Note: (6) 13.5 max., for factory-wiring.							
Note: (7) With or without suffix -MT, followed by -5.08 or -7.62.							
Note: (8) 10A max. 300V, 5A max. 600V, also 13A max. factory wiring at 150V.							
Note: (9) With or without 1, followed by /H, or /V, followed by -3.81, or -6.35.							
Note: (10) 11 max, for factory-wiring.							
UK6.3-HESi(1)	26-8	Cu	11-13	600	10	B, C	2(105)

Note: (1) With or without suffixes -LED followed by 24, or suffix -LA followed by 250 or 500.

DIKI.5(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DIKD1.5(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DIKD1.5-2D	14-30	Cu	5-7	300	15	B, D	2(105)
DIKD1.5-TG	14-30		5-7	300	15	B, D	2(105)
DIKD1.5-PV(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DOKI.5(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DOK1.5(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DOKD1.5-2D(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DOK1.5-TG(1)	14-30	Cu	5-7	300	15	B, D	2(105)
DOKD1.5-TG	14-30	Cu	5-7	300	15	B, D	2(105)
DLK2.5-PE	14-30	Cu	5-7	300	15	B, D	2(105)
DLK4-PE	10-30	Cu	5-7	600	30	B, D	2(105)
DLKB2.5-PE	14-30	Cu	5-7	300	15	B, D	2(105)

Note: (1) May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -24GN, -60GN, -220, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.

VIOK1.5(2)(1)	14-30	Cu	5-7	300	15	B, D	2(105)
VIOK1.5-2D(1)	14-30	Cu	5-7	300	15	B, D	2(105)
VIOK1.5-3D-PE(1)	14-30	Cu	5-7	300	15	B, D	2(105)
USEN14	2-20	Cu	35-40	600	16	B, C	2(105)
USEN18	2-20	Cu	35-40	600	63	B, C	2(105)
HDFK4, HDFKV4, HDFKV4 SLS (1)	10-30	Cu	5-7	300 300	30 10	B D	2(105), 4
HDFK10, HDFK10-T, HDFKV10, HDFKV10-T	6-24	Cu	11-20	300 150 300	65 65 10	B C D	2(105), 4
HDFKV10-TWIN, HDFKV10-TWIN T (1)	6-24	Cu	11-20	300 300 150	65 10 65	B D C	2(105), 4
HDFK10-VP-HV (1)	24-6	Cu	11-20	600	65	B, C	2(105), 4
HDFK 10-VP M3 HOLE	24-6	Cu	11-20	300	20	B	2(105),4
					10	D	
HDFK 10 -VP/Z M3 HOLE	24-6	Cu	11-20	300	20/10	B/D	2(105),4
HDFK 10-VP M3 HOLE	18-12	Cu	4.5	300	20	B	2(105),5
					10	D	

HDFK 10 -VP/Z M3 HOLE	18-12	Cu	4.5	300	20/10	B/D	2(105),5
HDFKV10-VP-HV, HDFKV10-TWIN-HV (1)	24-6	Cu	11-20	600	65	B, C	2(105), 4
HDFK10-HV, HDFKV10-HV (1)	24-6	Cu	11-20	600	65	B, C	2(105), 4
HDFK16, HDFK 16-VP, HDFK16-T, HDFKV16, HDFKV16-T	4-20	Cu	18	600	85	B, C	2(105), 4
HDFKV16 SLS, HDFKV16 T (1)	4-20	Cu	18	600	85	B, C	2(105), 4
HDFKV16-VP SLS, HDFKV16-VP T (1)	4-20	Cu	18	600	85	B ,C	2(105), 4
HDFK(V)4-GNYE	10-30	Cu	5-7	—	—	B, D	2(105), 4
HDFK(V)10- GNYE	6-24	Cu	11-20	—	—	B, D	2(105), 4
Note: (1) With or without Suffix V, followed by Suffix 4, 4A, 4I, 10, 10A, 10I, 16, 16A, 16I, with or without Suffixes -HV, -VP, -VP-HV, -TWIN, -TWIN-DP, -TWIN-HV, -TWIN-VP-HV, SLS or T or AMK or Z.							
MKKDS1.5(1)	14-30	Cu	5.0	300	10	B, D	2(105)
MKKDS3(1)(3)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MKKDSH3(1)	12-30(5)	Cu	5-7	300	20	B, D	2(105)
MKKDSW3(1)	12-30(5)	Cu	5-7	300	20	B, D	2(105)
MK3DS3(1)(3)	12-30(5)	Cu	5.0	300	15	B, D	2(105)
Note: (1) May be followed by /2, /3, and/or -5.08.							
Note: (3) Multiple wire combination for field and factory-wiring, 2 No. 16 AWG sol/str. Solid and stranded wires are not intermixed.							
Note: (5) Two No. 16-24 AWG Cu. wires for field and factory-wiring							
MK3DS1.5(1)	14-30(5)	Cu	5-7	300	10	B, D	2(105)
MK3DS1.5(4)	14-30(5)	Cu	5.0	300	10	B, D	2(105)
MK4DS1.5(4)	14-30	Cu	5.0	300	10	B, D	2(105)
MK3DS3/18(2)	12-30(5)	Cu	5-7	300	10	B, D	2(105)
MKK3DSG3(1)(3)	12-30(5)	Cu	5-7	300	10	B, D	2(105)
MK3DSH3(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
MK3DSMH3(1)	12-30(5)	Cu	5-7	300	15	B, D	2(105)
Note: (1) May be followed by /2, /3, and/or -5.08.							
Note: (2) Followed by -36, or -52, and -5.08.							
Note: (3) Multiple wire combination for field and factory-wiring, 2 No. 16 AWG sol/str. Solid and stranded wires are not intermixed.							

Note: (4) Followed by suffixes /2, or /3, and by -5.08, with or without suffixes -A-GNYE, -BC, or -BCD.

Note: (5) Two No. 16-24 AWG Cu. str wires for field and factory-wiring

G10/2 thru /5	6-24(A)	Cu	11-20 (Lb-in) (1.24 – 2.26 Nm)	600	65	B, C	2(105)
				600	5	D	2(105)

Note: (A) Additional wire rating of 2 No. 8 AWG Cu. str., 65A max. factory wiring only.

UK3N	12-28	Cu	5-7	600	20	B, C	2(105)
UK5N-(E), UK5N CB	10-30(#) (##)	Cu	5-7	600	30	B, C	2(105)
UK6N-(E)	8-26 (1)	Cu	13-16	600	50	B, C	2(105)
UK6-FSI/C, -LED12, -LED24, -LED60,	26-8	Cu	15	300	30	B, C	2(105)
UK10N-(E)	6-24	Cu	11-20	600	65	B, C	2(105)
UK16N	4-22	Cu	13-16	600	85	B, C	2(105)
UIK16	4-12	Cu	13-16	300	85	B, C	2(105)
				600	5	D	2(105)
UIK 16 SLS	4-12	Cu	13-16	300	85	B, C	2(105)
				600	5	D	2(105)
UIK35	2-18	Cu	30-50	600	115	B, C	2(105)
UIK 35 SLS	2-18	Cu	30-50	600	115	B, C	2(105)
UK25	4-22	Cu	18-25	600	85	B, C	2(105)
UK35-(E)	1/0-18	Cu	30-50	600	150	B, C	2(105)
UK35-PE/N	1/0-18	Cu	30-50	600	150	B, C	2(105)
MBK3/E-Z	28- 12	Cu	0.6-0.8	300	20	B, C	2(105)
				600	5	D	2(105)

Note: (1) Additional multiple wire combination rating of two No. 12-18 AWG Cu. str. for field and factory-wiring, same size wires.

Note: (#) Additional wire combination rating of two No. 14 AWG Cu stranded wires.

Note: (##) Additional multiple wire rating of three No. 18 AWG Cu. stranded for field and factory-wiring.

Note: (+) 130A max for factory wiring only.

MBK6/E	8-26	Cu	1.5-1.8	300	50	B, C	2(105)
				600	5	D	2(105)

MBK5/E-Z	26-10	Cu	0.6-0.8	300	30	B, C	2(105)
				600	5	D	2(105)
MBK5/E-Z,PE	26-14	Cu	0.6-0.8	—	—	B, C	2(105)
MSLKG6	8-26	Cu	1.5-1.8	N/A	N/A	B, C	2(105)
UK1.5N	30-14	Cu	0.22-0.25	300	15	B, C	2(105)
				600	5	D	2(105)
UK2.5N	12-30	Cu	0.6-0.8	300	20	B, C	2(105)
				600	5	D	2(105)
UK3	12-28	Cu	0.6-0.8	600	20	B, C	2(105)
UK4	12-28	Cu	0.6-0.8	600	20	B, C	2(105)
	2 No. 14 Str	Cu	0.6-0.8	600	20	B, C	2(105)
UK4-SD	10-20	Cu	0.6-0.8	300	10	B, C	2(105)
				600	5	D	2(105)
UK5	10-26(#)	Cu	0.6-0.8	600	30	B, C	2(105)
	2 No. 14 Str	Cu	0.6-0.8	600	30	B, C	2(105)
UK5N-MT	20-10	Cu	0.6-0.8	600	15	B, C	2(105)
				600	5	D	2(105)
UK5N-TG	20-10	Cu	0.6-0.8	600	15	B, C	
				600	5	D	2(105)
UK5-MTD N	20-10	Cu	0.6-0.8	600	15	B, C	2(105)
UK10	8-26	Cu	1.5-1.8	600	50	B, C	2(105)
UK16	6-24	Cu	1.5-1.8	600	65	B, C	2(105)
TB4-SD	10-20	Cu	0.6-0.8	300	10	B, C	2(105)
				600	5	D	2(105), 4
PS 6-DI-SD	—	Cu	—	300	NA	B, C	2(105)
PS 6-CT-SD	20-14	Cu	0.5-0.6	300	10	B, C	2(105)
				600	5	D	2(105)
PS 6-VT-SD	20-14	Cu	0.5-0.6	300	10	B, C	2(105)
				600	5	D	2(105)
USK4	12-28	Cu	0.6-0.8	600	20	B, C	2(105)
USK10	8-26	Cu	1.5-1.8	600	50	B, C	2(105)
USK16	6-24	Cu	1.5-1.8	600	65	B, C	2(105)

UHSK/S2000	26-10	Cu	1.5-1.8	1000	50	—	2(105)
				600	50	C	2(105)
UKK5 Series, UKK 5-LA, UKK 5-LA 24 RD/U-O, UKK 5-LA 60 RD/U-O	26-14	Cu	0.6-0.8	300	30	B, C	2(105)
				600	5	D	2(105)
UKK5, UKKB 5 KAN	26-8	Cu	0.6-0.8	300	30	B, C	2(105)
				600	5	D	2(105)
UKK5-HESI(5x20) w/wo LED 12,LED 24,LED 48 LED 60 or LA 250 w/wo suffix I	26-10	Cu	0.6-0.8	300	Upper level 15 Lower level 30	B, C	2(105)
				600	Upper level 5 Lower level 5	D	2(105)
UKK5-HESI(6.3x32) w/wo LED 12,LED 24,LED 48 LED 60 or LA 250	26-10	Cu	0.6-0.8	300	Upper level 15 Lower level 30	B, C	2(105)
				600	Upper level 5 Lower level 5	D	2(105)
UKK5-DIO/O-U	26-10	Cu	0.6-0.8	300	30	B, C	2(105)
				600	5	D	2(105)
UKK5-DIO/U-O	26-10	Cu	0.6-0.8	300	30	B, C	2(105)
				600	5	D	2(105)
UKK5-DIO/UL-UR	26-10	Cu	0.6-0.8	300	Upper level 30 Lower level 1	B, C	2(105)
				600	Upper level 5 Lower level 1	D	2(105)
UKK5-2DIO/O-UL/UR-UL	26-10	Cu	0.6-0.8	300	Upper level 30 Lower level 1	B, C	2(105)
				600	Upper level 5 Lower level 1	D	2(105)
UKK3, UKKB3, UKKB3 SO, UKKB3 KAN	10-28	Cu	0.6-0.8	300	20	B, C	2(105)
				600	5	D	2(105)

UKKB10	6-24	Cu	1.2-1.8	300	65	B, C	2(105)
				600	5	D	2(105)
UKKB10-2.5	6-24	Cu	Upper 0.6-0.8, Lower 1.5-1.8	300	65	B, C	2(105)
				600	5	D	2(105)
UKKB10-2.5PV	6-24	Cu	Upper 0.6-0.8, Lower 1.5-1.8	300	65	B, C	2(105)
				600	5	D	2(105)
USK4	12-28	Cu	0.5-0.8	600	20	B, C	2(105)
USK10	8-26	Cu	1.5-1.5	600	50	B, C	2(105)
USK16	6-24	Cu	1.5-1.8	600	65	B, C	2(105)
TT-UK5 w/suffixes /12, /24, /48, /60, 100 and by AC or DC	26-10	Cu	0.6-0.8	12-110	30	B, C	2(105)
	2 No. 14 STR	Cu	0.6-0.8	12-110	30	B, C	2(105), 4
URK-ND, -ND2	24-6	Cu	1.5-1.8	600	65	B, C	2(105)
UK 6-T	26-8	Cu	1.5-1.6	600	30	B, C	2(105)
UK 6-T-P, UK 6-TK-P	26-8	Cu	1.5-1.6	600	30	B, C	2(105)
UKD 6	26-8	Cu	1.5-1.6	600	30	B, C	2(105)
Note: (1) Top level terminals are rated No. 12-30 AWG Cu sol/str (field/factory-wiring), 20A, 600v, 7-lb-in. torque							
Note: (2) May be followed by suffixes -LA60RD/U-O, or LA230.							
Note: (3) Lower level terminals rated 30A max; fused upper level rated 15A max.							
Note: (3A) Additional multiple wire rating of two No. 16-28 AWG Cu. stranded for field and factory-wiring , same size wires only.							
SDKK6(4)	24-8	Cu	15	600	26	B, C	2(105)
UDMTK5-TWIN-P/P	26-12	Cu	0.6-0.8	300	8	B, D	2(105)
UDMTK5-P/P	26-12 sol/str	Cu	0.6-0.8	300	8	B, D	2(105)
UDK-RELG	30-12	Cu	0.6-0.8	300	20	B, C	2(105)
UDK4-TG	30-12	Cu	0.6-0.8	300	15	B, C	2(105)
UK5-MTK-P/P	22-12	Cu	0.5-0.6	300	15	B, C	2(105)
				600	5	D	2(105)
UK5-MTK	22-12	Cu	0.5-0.6	300	15	B, C	2(105)
				600	5	D	2(105)
UDK4-MTK	30-10	Cu	0.6-0.8	600	15	B, C	2(105)

				600	5	D	2(105)
UDK-MTK-P/P	30-10	Cu	0.6-0.8	300	15	B, C	2(105)
				600	5	D	2(105)
UKK5-MTK-P/P w or wo LA 60RD/O-U or LA 24RD/O-U	Upper Level 26-12	Cu	0.6-0.8	300	15	B, C	2(105)
	Lower Level 26-12	Cu	0.6-0.8	300	25	B, C	2(105)
UKK5-MTKD(++)	26-12	Cu	0.6-0.8	600	15	B, C	2(105)
	Lower Level 26-12	Cu	0.6-0.8	300	25	B, C	2(105)
Note: (++) May be followed by 24 or 60, may be followed by RT/O-U.							
Note: (4) Followed by one or two digit number, with or without suffixes OBEN, UNTEN and or NZ							
UKK5-T	Upper Level 26-12	Cu	0.6-0.8	300	15	B, C	2(105)
	Lower Level 26-12	Cu	0.6-0.8	300	25	B, C	2(105)
UKK5-TG	Upper Level 26-12	Cu	0.6-0.8	300	15	B, C	2(105)
	Lower Level 26-12	Cu	0.6-0.8	300	25	B, C	2(105)
UKK 5-TG OHNE P	Upper Level 26-12	Cu	0.6-0.8	300	15	B,C	2(105)
	Lower Level 26-12	Cu	0.6-0.8	300	25	B,C	2(105)
	26-12	Cu	0.6-0.8	600	5	D	2(105)
UKK 5-TG OHNE P	Upper Level 26-12	Cu	0.6-0.8	300	15	B,C	2(105)
	Lower Level 26-12	Cu	0.6-0.8	300	25	B,C	2(105)
	26-12	Cu	0.6-0.8	600	5	D	2(105)
URELG(1),PMTK, -RD	30-12	Cu	0.6-0.8	300	20	B, C	2(105)

Note: (1) Followed by 2, 3 or 4.							
UK10-DREHSI(1)	6-24	Cu	1.5-1.8	300	20	B, C	2(105)
Note: (1) Followed by suffixes LA, LA/K, K, LED or LED/K, followed by 12, 24, 60, or 250, followed by (5x20), (5x25) or (6.3x32), with or without suffixes -TE.							
IMC1.5/X-ST-3.81, STGF-3.81	14-30	Cu	4	300	8	B, D	2(115)
MCO1.5/X-GL,-GR-3.81	—	Cu	—	300	8	B, D	2(105)
MCO1.5/X-G1L, -G1R-3.5	—	Cu	—	300	8	B, D	2(105)
MCO1.5/X-GL-3.81-SI	—	Cu	—	300	8	B,D	2(105)
MC1.5/X-ST(1), -ST1(1)	14-30	Cu	0.22-0.25 Nm	300	8	B, D	2(115)
MC1.5/X-STZ, -STZF(1)	14-30	Cu	0.22-0.25 Nm	300	8	B, D	2(115)
MC1.5/X-STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13	14-30	Cu	0.22-0.25 Nm	300	8	B, D	2(115)
MC1.5/X-STF(1), -ST1F(1)	14-30	Cu	0.22-0.25 Nm	300	8	B, D	2(115)
MCVR1.5/X-ST, -STF(1)	14-30	Cu	4	300	8	B, D	2(115)
MCVR1.5/X-STFL(1)	14-30	Cu	4	300	8	B, D	2(115)
MCVR1.5/X-STFR(1)	14-30	Cu	4	300	8	B, D	2(115)
MCVW1.5/X-ST(1)	14-30	Cu	4	300	8	B, D	2(115)
MCVW1.5/X-STF(1)	14-30	Cu	4	300	8	B, D	2(115)
MCVW1.5/X-STFL(1)	14-30	Cu	4	300	8	B, D	2(115)
MCVW1.5/X-STFR(1)	14-30	Cu	4	300	8	B, D	2(115)
FRONT-MC1.5/X-ST(2)	14-30	Cu	2-2.2	300	8	B, D	2(115)
FRONT-MC1.5/X-STF(2)	14-30	Cu	2-2.2	300	8	B, D	2(115)
PLW 16-6 (*)	14-6+	Cu	—	600	40	B, C	2(120)
	16-8#	Cu	—				
PTRE 6-2	20 - 8	Cu	N/A	600@	20	B, C	2(105)
				300^	10	D	2(105)
				600^	5	D	2(105)
PTWE 6-2	20 - 8	Cu	N/A	600@	20	B, C	2(105)
				300^	10	D	2(105)
				600^	5	D	2(105)
UTRE 6-2	24 - 8	Cu	1.5-1.8 Nm	600@	30	B, C	2(105)
				300^	10	D	2(105)

				600^	5	D	2(105)
UTWE 6-2	24 - 8	Cu	1.5-1.8 Nm	600@	30	B, C	2(105)
				300^	10	D	2(105)
				600^	5	D	2(105)
UTWE 6	24 - 8	Cu	1.5-1.8 Nm	600@	30	B, C	2(105)
				300^	10	D	2(105)
				600^	5	D	2(105)
RSCWE 6-3, may be followed by /X, AUX, /X AUX	20-8	Cu	1.5-1.8Nm	600	31	B, C	2(105)
					5	D	2(105)
FIP-3	—	Cu	—	600	31	B, C	2(105)
RSCWE 6-3/nSL	20-8	Cu	1.5-1.8Nm	600	31	B, C	2(105)
FTP	—	Cu	—	600	31	B, C	2(105)
FWP	—	Cu	—	600	31	B, C	2(105)
FTP-2 L, FTP-2 M, FTP-2 S, FTP-3/n SL	—	Cu	—	600	31	B, C	2(105)
Note: (1) Followed by suffix -3.5, -3.81 or -5.08, may be followed by -LR.							
Note: (2) Followed by -3.81, may be followed by SOX (X is a one digit number).							
Note: (*) Followed by /one or two digit number, followed by suffix -10.							
Note: (+) Outside terminals.							
Note: (#) Inside terminals.							
Note: (@) With Mounting plate							
Note: (^) without Mounting plate							
MCV1.5, IMCV1.5/X(5)	N/A	Cu	N/A	300	8	B, D	2(115)
SMC1.5/X(8)	N/A	Cu	N/A	300	8	B, D	2(115)
MC1.5/X, IMC1.5/X(5)	N/A	Cu	N/A	300	8	B, D	2(115)
MCD1.5/X, MCD1.5(2)(1)	N/A	Cu	N/A	300	8	B, D	2(115)
MCDV1.5/X(2)(1)	N/A	Cu	N/A	300	8	B, D	2(115)
IMC1.5/X-G-3.81	—	Cu	—	300	8	B, D	2(105)
IMCV1.5/X-G-3.81	—	Cu	—	300	8	B, D	2(105)

IMC1.5/X-G-3.5	—	Cu	—	300	8	B, D	2(105)
IMCV1.5/X-G-3.5	—	Cu	—	300	8	B, D	2(105)
MCO1.5/X-GL,-GR-3.81	—	Cu	—	300	8	B, D	2(105)
MCVU1.5/X GFD-3.81	14-30	Cu	2	300	8	B, D	2(115), 4
MCVK1.5/X(2)(1)	14-30	Cu	4	300	8	B, D	2(115), 4
MCVDU1.5/X(2)(1)	N/A	Cu	N/A	300	8	B, D	2(115)
DFK-MC1.5/X(2)(1)	N/A	Cu	N/A	300	8	B, D	2(115)
EMC1.5/X-G, GF-3.5	N/A	Cu	N/A	600	8	B, C	2(115)
EMC1.5/X-G, GF-3.81	N/A	Cu	N/A	300	8	B, C	2(115)
EMCV1.5/X-G, GF-3.5	N/A	Cu	N/A	300	8	B, C	2(115)
EMCV1.5/X-G, GF-3.81	N/A	Cu	N/A	300	8	B, C	2(115)
MCC1/X-ST-3.81	(3)	Cu	N/A	300	(4)	B, D	2(105), 4
MCC1/X-STF-3.81	(3)	Cu	N/A	300	(4)	B, D	2 (105), 4
MCC1/X-STZ-3.81	(3)	Cu	N/A	300	(4)	B, D	2(105), 4
MCC1/X-STZF-3.81	(3)	Cu	N/A	300	(4)	B, D	2(105), 4
MCC0.5-ST-2.54	26-18 str	Cu	N/A	150	6(9)	B, D	2 (115)
PSC1.5(/3 or /5)-F	30-14	Cu	4	300	8	B, D	2(105), 4
PSC1.5(/3 or /5)-M,-PE	N/A	N/A	N/A	300	8	B, D	2(105), 4
FMC1.5/X-ST, -STF, -STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13, -STFZ1, -STFZ2, -STFZ3, -STFZ4, -STFZ11, -STFZ12, -STFZ13 followed by -3.5, w/wo -RF	24-16	Cu	N/A	150	8	B	2(105)
			N/A	50(7)	8	C	2(105)
FMC1.5/X-ST, -STF, -STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13, -STFZ1, -STFZ2, -STFZ3, -STFZ4, -STFZ11, -STFZ12, -STFZ13 followed by -3.81, w/wo -RF	24-16	Cu	N/A	300	8	B	2(105)
			N/A	50(7)	8	C	2(105)
IFMC1.5/X followed by -ST, -STF, followed by -3.5, -3.81, w/wo -RF or -RN	24-16	Cu	N/A	150	8	B	2(105), 4
FMCD1.5/X-ST, or -STF followed by -3.5,	24-16	Cu	N/A	300	8	B, D	2(105), 4
MCDN1.5/X(6), MCDNV1.5/X(6),	—	Cu	N/A	150	8	B, D	2(105), 4
FK-MCP1.5/X-ST, -STF, -STW or -STZW, -STZ, -STZ1, -STZ2, -STZ3 (1) f/b G1 and -3.5 and P14THR, P26THR, RNP14THR or RNP26THR	16-28	Cu	N/A	300	8	B, D	2(105), 4
TFMC1.5/X f/b -ST or -STF and by -3.5	24-16	Cu	N/A	300 50 (7)	8	B	2(105), 4
FMC0.5/X-ST-2.54 w/wo CX	26-20	Cu	N/A	150	6	B	2(105)
	26-20	Cu	N/A	150	5	B	2(105)

	26-20	Cu	N/A	50 (7)	6	C	2(105)
MC0.5/X, MCV0.5/X f/b -G-2.54 f/b P14, P20, P26 f/b THR, SMD f/b R24, R44, R56, R72 w/wo CX	N/A	N/A	N/A	150	6	B	2(105)
	N/A	N/A	N/A	50 (7)	6	C	2(105)
DFMC0.5/X-ST-2.54 w/wo -RF or CX	26-20	Cu	N/A	150	6	B	2(105)
	26-20	Cu	N/A	150	5	B	2(105)
	26-20	Cu	N/A	50 (7)	6	C	2(105)
DMC0.5/X, DMCV0.5/X f/b -G1, —G1SH or G1SHL, -2.54 f/b P14, P20, P26 f/b THR, SMD f/b R24, R44, R56, R72 w/wo CX	N/A	N/A	N/A	150	6	B	2(105)
	N/A	N/A	N/A	50 (7)	6	C	2(105)
DMCC0.5 followed by /one or two digit number followed by ST, may be followed by -SH 7,0, -SKL 4,8, or -SHL 7,0, followed by -2.54	26-18	Cu	N/A	150	6 (9)	B, D	2(105), 415750
Note: (1) Followed by -3.5 or -3.81, w/wo P20, P26, may be followed by -LR or BUGY or SOX.							
Note: (2) Followed by suffix one or two digit number, -G, -G1, -G2, -GF, -G1F, -GL, -GR, -GFL, -GFR, -GFD, -G0, GW, G1W, with or without HT, -THR, TR, S01, or PIN2.							
Note: (3) No. 24-22 AWG Cu, stranded with MCC-MT0.25-0.5 crimp contact; No. 20-18 AWG Cu. stranded with MCC-MT0/.5-1 crimp contact							
Note: (4) 5A max. with MCC-MT0.25-0.5 crimp contact; 8A max. with MCC-MT0.5-1 crimp contact.							
Note: (5) May be followed by HP, followed by /1 or /2 digit number, followed by suffix -G, -GF, -GL, -GFL, -GR, -GEF, -GFR, -GSF, GO, -GW; followed by suffix -3.5 or -3.81 or 5.08, may be followed by -LR, may be followed by suffix -RN, may be followed by two-digit color-code, may be followed by P14, P20, P26, maybe followed by AU, THT, THR, CPXX, SOX or R.							
Note: (6) Followed by -G1, and by -3.5, or -3.81.							
Note: (7) For usage group C the 50V voltage rating is applicable only for factory wiring.							
Note: (8) Followed by -G, -GF, followed by -3.81 with or without HT or CPXX, XX.							
Note: (9) Current rating only with header cat. no. MC(V)0.5/.. -G-2.54.							
Note: (%) Current rating only with cat. no. DMC0(V).5/X .							
TRK1.5,-N,-S, TRK1.5-S01,-S02,-FS, TRK1.5-Blau Sol	22-14	Cu	7	300	15	B, C	2(105)
TRK2.5,TRK2.5-FS	22-12	Cu	7	600	20	B, C	2(105)
TRK2.5N(-GY,-FS-GY,-OG,-FS-OG), TRK2.5BU Sol	22-12	Cu	7	600	20	B, C	2(105)

TRK4,-FS,-Blau Sol	16-10	Cu	11	600	30	B, C	2(105)
TRKS4,TRKS4-FS	30-10	Cu	5-7	600	30	B, C	2(105)
TRKS4-PE	30-10	Cu	2(105)	600	—	B, C	2(105)
TRKS4-Si	30-10	Cu	5-7	600	8	B, C	2(105)
TRKS4-Si/K	30-10	Cu	5-7	600	8	B, C	2(105)
TRK1.5/2(1)	22-14	Cu	7	300	15	B, C	2(105)
TRK1.5/3(1)	22-14	Cu	7	300	15	B, C	2(105)
Note: (1) With or without suffixes -N, -FS, -N-FS followed by OG.							
TRKS4/1-Si(6.3x32),(5x30)	30-10	Cu	5-7	600	10	B, C	2(105)
TRKS4/3GY,OR	30-10	Cu	5-7	600	30	B, C	2(105)
TRK10	10-6	Cu	11	600	55	B, C	2(105)
TRK10 Blau Sol	10-6	Cu	11	600	55	B, C	2(105)
VTRK(Z)4,-GY,-OG	30-10	Cu	5-7	300	30	B, C	2(105)
VTRK(Z)4-SI/C,-GY,-OG	30-10	Cu	5-7	300	10	B, C	2(105)
TRK2.5-Si	22-12	Cu	7	300	8	B, C	2(105)
TRKSD4,-FS	30-10	Cu	5-7	600	30	B, C	2(105)
ZTRK4	24-10	Cu	N/A	600	30	B, C	2(105)
ZTRK4-SI	24-16	Cu	N/A	300	10	B, C	2(105)
DFK4-PE	30-10	Cu	5-7	N/A	N/A	B, D	2(105)
DFK-WW(1x1)	28-12	Cu	5-7	300	10	B, D	2(105)
DFK-TP(1.6x0.8)	28-12	Cu	5-7	300	10	B, D	2(105)
DFK-TP(2.4x0.8)	28-12	Cu	5-7	300	10	B, D	2(105)
DFK/DP-2.8	28-12	Cu	5-7	300	15	B, D	2(105)
DFK/DP-4.8	28-12	Cu	5-7	300	15	B, D	2(105)
DFK-4.8	28-12	Cu	5-7	300	15	B, D	2(105)
DFK-2.8FRONT 2.5	28-12	Cu	5-7	300	15	B, D	2(105)
DFK/DP-2.8FRONT 2.5	28-12	Cu	5-7	300	15	B, D	2(105)
DFK4	10-30	Cu	5-7	300	15	B, D	2(105)
DFK/DP4	10-30	Cu	5-7	300	15	B, D	2(105)
MBK5/E-, TG	28-12	Cu	0.5-0.6	300	20	B, C	2(105)
				600	5	D	2(105)
UK2.5(1)	30-12	Cu	0.6-0.8	600	20	B, C	2(105)

				600	5	D	2(105)
UK3(1)	30-12	Cu	0.5-0.6	300	20	B, C	2(105)
UK3-TWIN	30-12	Cu	0.5-0.6	300	20	B	2(105)
				150	20	C	2(105)
				300	10	D	2(105)
UK4(1)	28-12	Cu	0.6-0.8	300	20	B, C	2(105)
UXKK4	28-12	Cu	0.6-0.8	600	20	B, C	2(105)
Note: (1) Followed by suffix B, -(E), -MSTB-5.08, -MVSTB-5.08, -MVSTB-5.08-LA 24 RD, -MVSTB-5.08, -PLUS, -T, -TG, -T-P/P or -TWIN.							
UK5-TWIN	30-10	Cu	0.6-0.8	300	30	B, C	2(105)
				150	35	C	2(105)
				300	10	D	2(105)
UK5-HESI(1)	26-10	Cu	0.6-0.8	600	12	B, C	2(105)
UK5-HESI(2)	26-10	Cu	0.6-0.8	600	16	B, C	2(105)
UK10TWIN	24-6	Cu	1.5-1.8	300	65	B, C	2(105)
				600	5	D	2(105)
UK10-PLUS	24-6, 24-6, 30-12	Cu	1.5-1.8, 1.5-1.8, 0.6-8	300	I/P-65, O/P-65, O/P-20	B, C	2(105)
				600	5	D	2(105)
UK3-TWIN-PE	30-12	Cu	0.5-0.6	NA	—	B, C, D	2(105)
Note: (1) With or without suffix (5x20), -T OG, LED24, LED24-2MA, LED60, LA250, or LA500; with or without suffix -E or N.							
Note: (2) With or without suffix N, LED 24 N, LED 60 N, LED 250 N.							
UK5-TWIN-PE	30-10	Cu	0.6-0.8	NA	NA	B, C, D	2(105)
UK10-TWIN-PE	24-6	Cu	1.5-1.8	NA	NA	B, C, D	2(105)
UK10-PLUS-PE	24-6, 24-6, 30-12	Cu	1.5-1.8, 1.5-1.8, 0.6-8	NA	NA	B, C	2(105)
UK3D-MSTBV-5.08(2)	30-12	Cu	0.5-0.6	300	I/P-20 O/P (CB)-20 Plug-12 max	B, C	2(105)
				300	10	D	2(105)

UKK3-MSTB-5.08	30-12	Cu	0.5-0.6	300	10	B	2(105)
				300	10	D	2(105)
UKK3-MSTB-5.08-PE	30-12	Cu	0.5-0.6	N/A	N/A	B, D	2(105)
USKR-FSR(3)	28-12	Cu	0.6-0.8	600	20	B, C	2(105)
Note: (2) With or without suffixes -LA24RD.							
Note: (3) Followed by suffix (4-2.8-0.8).							
TSPC5/X-ST, -STF or -STCL, followed by -7.62	24-8	Cu	—	600	31	B, C	2(105)
Note: (1) Followed by /one or two-digit number followed by -ST, -STF followed by -7.62.							
PCVK4-7.62(2)	30-10	Cu	4.4-5.3	600	30	B, C	2(105)
UPCV3K4-G-7.62	30-10	Cu	4.4-5.3	300	30	B, C	2(105)
PCC4/X-ST-7.62(A)	20-18 16-14 16-14(A)	Cu	—	600	10	B, C	2(105)
PC4/X w/ suffixes -G -GF, -GFL, -GFR, -GU, followed by -7.62, -15.24-1, or 15.24-2	—	—	—	300(4)	30	B, C	2(105)
DFK-PC4/X-G-7.62-LOE or -FS48	—	—	—	300, 600	30, 5	B, C, D	2(105)
DFK-PC4/X-GF-7.62	—	—	—	300, 600	30, 5	B, C, D	2(105)
PCV4 w/ suffixes -G -GF, -GFL, -GFR, -GU, followed by -7.62, -15.24-1, or 15.24-2	—	—	—	300(4)	30	B, C	2(105)
PCO4/X f/b -G f/b -7.62 w/wo BK	N/A	N/A	N/A	300	20	B, C	2(105)
PC4 f/b /X(1)-7.62	30-10	Cu	4.4-5.3	300(4)	30	B, C	2(105)
PC4 f/b HV, f/b /X(1)-7.62, w/wo suffix RAE	30-10	Cu	4.4-5.3	600	30	B, C	2(105)
PC4 w/wo HV, f/b /X(1)-15.24-1	30-10	Cu	4.4-5.3	600	30	B, C	2(105)
PC4 w/wo HV f/b /X(1)-15.24-2	30-10	Cu	4.4-5.3	600	30	B, C	2(105)
PC5/X w/Suffixes -ST, -ST1, -ST2, -STF, -STF1, -STF-SH, -STF-SH1, -STF-SHL, -STF-SHL1, -STCL, -STCL1, -STFL, -STFL1, STFR, -STFR1, or -STTL followed by -7.62, w/wo RAE. (&)	24-8; (2) 24- (2)12	Cu	7	600	41	B, C	2(105)
PC5/X-STF1-15.24	24-8; (2) 24- (2)12	Cu	7	600	41	B	2(105)
	24-8; (2) 24- (2)12	Cu	7	1000	41	C	2(105)
PCV5/X-GF-15.24	-	Cu	-	300	41	B	2(105)

	-	Cu	-	1000	41	C	2(105)
	-	Cu	-	600	5	D	2(105)
PC5/X w/suffixes -G, -GF, -GSF, -GU, -GFU, followed by -7.62, w/wo THT(3)	—	Cu	—	300 150 600 150	41 41 5 10	B C D D	2(105)
PC 5/..-G-7,62 PIN3,4	—	Cu	—	300 150 600 150	41 41 5 10	B C D D	2(105)
PCV5/X w/suffixes -G, -GF, followed by -7.62, w/wo THTPC 5/..-G-7, 62	—	Cu	—	300 150 600	41 41 5	B C D	2(105)
SPC5/X w/Suffixes -ST, -STF, -STF-SH, STF-SHL, -STTL or -STCL, followed by -7.62 - STF,foll. by -7.62, w/wo -SH (&)	24-8	Cu	—	600	35	B, C	2(105)
ISPC5 f/b one or two-digit number w/suffixes -STF, -STGF, or -STGCL, followed by -7.62	24-8	Cu	7	600	35	B, C	2(105)
IPC5 f/b /1 or /2-digit No.,and by -ST, -STF, -STGF, -STF-SH, -STGF-SH or -STGCL, and by -7.62	24-8	Cu	7	600	41	B, C	2(105)
IPC5, IPCV5 f/b /1 or /2-digit No., and by -G, -GF, -GU, or -GFU, and by -7.62	—	Cu	—	300(1A)	41	B, C	2(105)
DFK-PC5/X f/b -G, -GF, -GU, -GFU, -GF-SH, -GFU-SH f/b -7.62	—	Cu	—	300 600	41 5	B, C D	2(105)
Cat. No. DFK-PC5 followed by /one or two-digit number, and by -ST, -STF Or -STF-SH; followed by -7.62.	28-4	Cu	4.4-5.3	600	41	B, C	2(105)
SPTC 5/X FI-8.5	20-10 sol/str	Cu	—	300	24	C	2(120),4
SPTC 5/X-TBUS-8.5	—	—	—	300	24	C	2(120),4
PLTT 2.5/ 3-5.0-SC... (5)	24-12 sol/str	Cu	0.5 Nm	300	20	B	2(105),4
PLTT 2.5/ 3-5.0-SC... (5)	24-12 sol/str	Cu	0.5 Nm	150	15	D	2(105),4
PLTT 2.5/ 3-5.0-SC... (5)	24-12 sol/str	Cu	0.5 Nm	300	10	D	2(105),4
PLTT 2.5/ 3-5.0-SP... (5)	24-12 sol/str	Cu	—	300	20	B	2(105),4
PLTT 2.5/ 3-5.0-SP... (5)	24-12 sol/str	Cu	—	150	15	D	2(105),4
PLTT 2.5/ 3-5.0-SP... (5)	24-12 sol/str	Cu	—	300	10	D	2(105),4

Note: (A) 2 crimp barrel sizes.							
Note: (1) Followed by -ST, -STF, -SH, -STFL, -STF-SHL, or -STFR, w/wo Suffix RAE..							
Note: (1A) May be used at 600V where PC board is conformal coated or equivalent to meet 600V spacing at solder pins.							
Note: (2) Multiple wire rating for field and factory-wiring of 3 No. 16 AWG Cu. stranded wires.							
Note: (3) Cat. No. PC5 headers are intended for use with either the Cat. No. PC5 or SPC5 detachable terminal blocks. The suitability of each combination of header and detachable terminal block has been determined by temperature rise tests.							
Note: (4) May be used for 600V applications where the suitability of spacings at the factory wiring terminals comply with the end use equipment. The suitability shall be determined in the end-use.							
Note: (5) May be followed by 1 to 30 character alphanumeric suffix (any combination of letters and/ or numbers) indicating optional alternate poles, colors, partial assemblies, coding and laser prints.							
Note: (&) Terminal Block PC5 series suitable for use with headers PC4, PCV4 and PCO4 and when used, the ampere rating for the combination is 30A, the maximum rating assigned to the terminal block headers.							
Note: When used with PC5 detachable terminal block, the ampere rating for the combination is 41 A, the max. rating assigned for both the header and terminal block.							
Note: When used with SPC5 detachable terminal block, the ampere rating for the combination is 35 A, the max. rating assigned for the terminal block.							
UDK3-PE	12-30	Cu	5-7	N/A	N/A	B, C	2(105)
UDK4-PE	10-30	Cu	5-7	N/A	N/A	B, C	2(105)
KDS10	24-6	Cu	11-15	300	65	B, C, D	2(105)
KDS10/SO	24-6	Cu	11-15	300	65	B, C, D	2(105)
KDS10-PE	24-6	Cu	11-15	—	—	B, C, D	2(105)
KDS10-PE/SO	24-6	Cu	11-15	—	—	B, C, D	2(105)
QT1.5, -BU, -MT, -TG	16-22	Cu	N/A	600	10	B, C	2(130)
QT1.5-PE	16-22	Cu	N/A	N/A	N/A	B, C	2(130)
QT1.5-TWIN,-BU	16-20	Cu	N/A	600	10	B, C	2(130)
QT1.5-TWIN-PE	16-20	Cu	N/A	600	N/A	B, C	2(130)
QT2.5	14-18	Cu	N/A	600	15	B, C	2(105)

QT2.5-BU, -MT	14-18	Cu	N/A	600	15	B, C	2(105)
QT2.5-PE	14-18	Cu	N/A	600	15	B, C	2(105)
QT2.5-TG	14-18	Cu	N/A	600	1.5	B, C	2(105)
QT2.5-TWIN	14-18	Cu	N/A	600	15	B, C	2(105)
QT2.5-TWIN-BU	14-18	Cu	N/A	600	15	B, C	2(105)
QT2.5-TWIN-PE	14-18	Cu	N/A	600	15	B, C	2(105)
QTU1.5/4	(@)	Cu	5-7	600	10	B, C	2(105)
QTU1.5/4-PE	(@)	Cu	5-7	N/A	N/A	B, C	2(105)
QTTUB1.5/4	(@)	Cu	5-7	600	10	B, C	2(105)
QTU2.5/4	(@@)	Cu	5-7	600	15	B, C	2(105)
QTU2.5/4-PE	(@@)	Cu	5-7	N/A	N/A	B, C	2(105)
QTTUB2.5/4	(@@)	Cu	5-7	600	15	B, C	2(105)
Note: Suffix "X" in the Cat. Nos. above represent a one or two-digit number.							
Note: (A) Crimp barrel sizes.							
Note: (1) Followed by -ST, -STFL, or -STFR.							
Note: (2) May be used at 600V where printed cirCuit board is conformal coated or equivalent to provide acceptable spacings at the solder pins.							
Note: (@) Input side (IDC) wire range is No. 24-16 AWG Cu. str.; Output side (pressure screw) is rated No. 26-10 AWG Cu. sol/str.							
Note: (@@) Input side (IDC) wire range is No. 24-14 AWG Cu. str.; Output side (pressure screw) is rated No. 26-10 AWG Cu. sol/str.							
QTS1.5/4 (1)	(1)	Cu	N/A	600	10	B, C	2(105)
QTS1.5/4-PE (1)	(1)	Cu	N/A	600	10	B, C	2(105)
QTS2.5/4 (2)	(2)	Cu	N/A	600	15	B, C	2(105)
QTS2.5/4-PE (2)	(2)	Cu	N/A	600	15	B, C	2(105)
Note: (1) Input side (IDC) wire range is No. 24-16 AWG Cu. Str.; Output side Cage Spring wire range is No. 24-10 AWG Cu. sol/str.							
Note: (2) Input side (IDC) wire range is No. 18-14 AWG Cu. Str.; Output side Cage Spring wire range is No. 24-10 AWG Cu. sol/str.							
FK-MC0.5(1)	28-20	Cu	N/A	150	4	B	2(105)
MC0.5(8)	—	Cu	N/A	125	4	B	2(105)
MCD0.5(8)	—	Cu	1	125	4	B	2(105)
MCDV0.5(8)	—	Cu	1	125	4	B	2(105)

MCV0.5(8)	—	Cu	N/A	125	4	B	2(105)
Note: (1) Followed by /1 or /2 digit number, followed by -ST, -2.5.							
Note: (8) Followed by /1 or /2 digit number, followed by -G, -G1 and -2.5, may be followed by THT, P14 THT, or THT PIN26.							
G5(1)	26-10	Cu	5-7	300#	30	B	2(105)
K2.5(2)	30-14	Cu	5-7	300	15	B, D	2(105)
K3(2)	28-12	Cu	5-7	600	20	B, C	2(105)
K4(2)	28-12	Cu	5-7	600	20	B, C	2(105)
K4-TG(2)	28-12	Cu	5-7	300	20	B, D	2(105)
K5(2)	26-10	Cu	5-7	600	30	B, D	2(105)
K10(2)	26-8	Cu	11-15	600	50	B, C	2(105)
K16, K16/E	24-6	Cu	11-15	600	65	B, C	2(105)
K25, K25/E	22-4	Cu	18-25	600	85	B, C	2(105)
MBK	30-14	Cu	5-7	300	15	B, D	2(105)
MBK2.5/E	30-12	Cu	5-7	300	20	B, D	2(105)
MBKK2.5, -PE	30-12	Cu	5-7	300	20	B, D	2(105)
MBKKB2.5, -PV	30-12	Cu	5-7	300	20	B, D	2(105)
MBK2.5/E-PE	30-12	Cu	5-7	—	—	B, D	2(105)
UGSK/S	26-8	Cu	11-15	600	50	B, C	2(105)
Note: (1) Followed by suffixes /2, /3, /4, /6, /12, /2B.							
Note: (2) May be followed by suffixes /E, /M.							
GTF76/230	26-8	Cu	11-15	250	50	B, C	2(105)
GTF76/48	26-8	Cu	11-15	250	50	B, C	2(105)
ST-BE	14-30	Cu	5-7	300	10	B, C	2(105)
ST-BE-VIERPOL	14-30	Cu	5-7	300	10	B, C	2(105)
ST-1N4007	14-30	Cu	5-7	300	1	B, C	2(105)
MBK3/E-Z-PE	30-12	Cu	5-7	—	—	B, D	2(105)
MBK3	28-12	Cu	5-7	600	20	B, C	2(105)
MBK5, MBK5/E	26-10	Cu	5-7	600	30	B, C	2(105)
MBK5/E-FS	26-10	Cu	5-7	300	5	B, D	2(105)
MBK5/E-FS/FS	26-10	Cu	—	300	—	B, D	2(105)

MBK10	26-8	Cu	11-15	600	50	B, C	2(105)
SSK5(3)	26-10	Cu	5-7	600	30	B, C	2(105)
SSK0525-TG(3)	28-12	Cu	5-7	300	20	B, D	2(105)
SSK/N0525-LB1(3)	28-12	Cu	5-7	600	20	B, C	2(105)
SSK110(3)	26-8	Cu	11-15	600	50	B, C	2(105)
SSK116(3)	24-6	Cu	11-15	600	65	B, C	2(105)
SSK125(3)	22-4	Cu	18-25	600	85	B, C	2(105)
SSK135(3)	18-2	Cu	20-50	600	115	B, C	2(105)
ST-Si(4)	—	Cu	—	300	10	B, D	2(105)
UDK3	30-12	Cu	5-7	300#	20	B, D	2(105)
UDK4	30-10	Cu	5-7	600#	30	B, D	2(105)
UDK4-ILA500	30-10	Cu	5-7	600	0.5	B, D	2(105)
UDK4-ILA1000	30-10	Cu	5-7	600	1	B, D	2(105)
UDK4-ULA(5)	30-10	Cu	5-7	600#	30	B, D	2(105)
URTK/S,URTK/S-Ben	26-8	Cu	11-15	300	50	B, D	2(105)
	26-8	Cu	11-15	300	50	B, D	2(105)

Note: (3) May be followed by suffix Kri.

Note: (4) May be followed by suffixes LA250, LED12, LED24, LED60, -UK4.

Note: (5) May be followed by suffixes -12RD/O-U, -12RT/O-U, -24RD/O-U, -24RT/O-U, -48RD/O-U, -48RT/O-U, -60RD/O-U, -60RT/O-U, 220, -/UK.

Note: # Limited amp rating at max voltage of 300v or 600v.

URTK/SP	26-8	Cu	1.5-1.8	300	45	B, D	2(105)
URTK/S-Ben 10, URTK/S-BEN 10-TK	26-8	Cu	1.1-1.8	600	50	B, D	2(105)
URTK/SS	28-12	Cu	5-7	300	20	B, D	2(105)
MTK(1)	28-12	Cu	5-7	300	10	B, D	2(105)
MTKD(2)	28-12	Cu	5-7	300	10	B, D	2(105)
OTTA 6-T/SB-P/P	N/A	Cu	1.5-1.8)/ Dis. Conn 1.2-1.4)	600	30	B, C	2(105), 5
OTTA 6-T/SB-P/P E	N/A	Cu	1.5-1.8)/ Dis. Conn 1.2-1.4)	600	30	B, C	2(105), 5
OTTAD 6/SB-P/P	N/A	Cu	1.5-1.8)/	600	30	B, C	2(105), 5

OTTAD 6/SB	26-10 (STR)	Cu	(1.5 -1.8) Nm	600	30	B, C	2(105)
OTTA 6-T/SB	26-10 (STR)	Cu	(1.5 -1.8) Nm Disconnect screw: (1.2- 1.4) Nm	600	30	B, C	2(105)
OTTA 6-P/P-HV	26-10 (STR)	Cu	(1.5 -1.8) Nm	600	30	B, C	2(105)
OTTA 6-HV	26-10 (STR)	Cu	(1.5 -1.8) Nm	600	30	B, C	2(105)
OTTA 6-PE-1	26-10 (STR)	Cu	(1.5 -1.8) Nm Fixing screw: (0.6- 0.8) Nm	N/A	N/A	B, C	2(105)
OTTA 6-PE	26-10 (STR)	Cu	(1.5 -1.8) Nm Fixing screw: (0.6- 0.8) Nm	N/A	N/A	B, C	2(105)
RBO 4-T/SB-P/P	N/A	Cu	1.5-1.8)/ Dis. Conn 1.2-1.4)	600	30	B, C	2(105), 5
RBO 4-T/SB-P/P E	N/A	Cu	1.5-1.8)/ Dis. Conn 1.2-1.4)	600	30	B, C	2(105), 5

Note: (1) With or without suffixes -E, -Loe/Loe, -Loel, -Loel/PR, -P/P, -D or -D/PP.

Note: (2) Followed by suffix -Cu/CuNI, -FE/CuNI, -NICR/CuNI, -NICR/NI, -NICRSI/NISI, -E-Cu/A-Cu or -S-Cu/E-Cu.

URDK6	26-8	Cu	15	300	50	B, C	2(105)
URTK6	26-8	Cu	15	300	50	B, C	2(105)
UGSK6	26-8	Cu	15	300	50	B, C	2(105)
BT 1.25(6)	26-16	Cu	10	600	0.6-1	B, C	2(105),5
BT 2.0(6)	26-14	Cu	15	600	1-1.3	B, C	2(105),5
BT 3.5(6)	26-10	Cu	30	600	1.4-2	B, C	2(105),5
BTO 1.25(6)	26-16	Cu	10	600	0.6-1	B, C	2(105),5
BTO 2.0(6)	26-14	Cu	15	600	1-1.3	B, C	2(105),5
BTO 3.5(6)	26-10	Cu	30	600	1.4-2	B, C	2(105),5
BT 14	20-6	Cu	60	600	3.6-3.7	B, C	2(105), 5
BT 14-F	20-6	Cu	60	600	3.6-3.7	B, C	2(105), 5
BTO 14	20-6	Cu	60	600	3.6-3.7	B, C	2(105), 5

BTO 14-F	20-6	Cu	60	600	3.6-3.7	B, C	2(105), 5
BTO 38	20-2	Cu	10-13.5 Nm	600	100	B, C	2(105), 5
BTO 38-F	20-2	Cu	10-13.5 Nm	600	100	B, C	2(105), 5
BT 5.5(6)	24-8	Cu	40	600	1.4 - 2.0	B, C	2(105),5
BT 5.5-F(6)	24-8	Cu	40	600	1.4 - 2.0	B, C	2(105),5
BTO 5.5(6)	24-8	Cu	40	600	1.4 - 2.0	B, C	2(105),5
BTO 5.5-F(6)	24-8	Cu	40	600	1.4 - 2.0	B, C	2(105),5
BTP 1.25(6)	26-16	Cu	10	300	—	B, C	2(105), 5
BTP 2.0(6)	26-14	Cu	15	600	—	B, C	2(105), 5
BTP 3.5(6)	26-12	Cu	20	600	—	B, C	2(105), 5
BTH 1.25(6)	26-16	Cu	10	300	—	B, C	2(105)
BTH 2.0(6)	26-14	Cu	15	600	—	B, C	2(105)
BTH 3.5(6)	26-12	Cu	20	600	—	B, C	2(105)
FK-MPT 0.5(A)	20-28	Cu	N/A	300	4	B, C	2(105)
FK-MPT 0.5(B)	—	Cu	N/A	300	4	B, C	2(105)
CPT0.5/X-M-3.5	—	Cu	N/A	300	4	B, C	2(105)
Note: (A) Followed by /1 or /2-digit number, w/wo -ST, followed by -3.5 w/wo -H.							
Note: (B) Followed by /1 or /2-digit number, followed by -IC or -ICA or -ICV or -ICVA and -3.5.							
Note: (6) May be followed by suffix -F.							
ZEC1.0(7)	26-16	Cu	N/A	300	8	D	2(105)
ZEC1.5(8)	26-14	Cu	N/A	300	10	B, D	2(105)
QC0.75(2)	22-18	Cu	N/A	300	7	B, C	2(105)
QC1(2)	16-20	Cu	N/A	300	10	B, C	2(105)
Note: (2) Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.08.							
Note: (7) Followed by /1 or /2 digit number, followed by -ST-3.5C1R1 and a 1 or 2 digit number.							
Note: (8) Followed by /1 or /2 digit number, followed by -ST-5.0 or -7.5 C1, followed by suffix C2R1 and a 1 or 2 digit number.							
PIK4 (2)	28-12	Cu	5-7	300	20 (3)	B, C	2(105)
PIK4-PE (2)	28-12	Cu	5-7	300	20 (3)	B, C	2(105)

PIK6 (1)	26-8	Cu	5-7	300	50	B, C	2(105)
PIK6-PE (1)	26-8	Cu	5-7	300	50	B, C	2(105)
UK-SI	28-12	Cu	5-7	300	10	B, C	2(105)

Note: (1) With Suffixes -L/L, -L/N, or -L/NT.

Note: (2) With Suffixes -L or /L, with or without Suffixes /L, /N, /NT, /NTB.

Note: (3) 25A max. factory-wiring only.

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
ME17.5 (1), ME22.5(1)	30-12	Cu	N/A	300	8	B, D	2(105)
ME MAX6.2 SC (4)	12-30	Cu	5-7	300	8	B, D	2(105)
ME MAX 6.2 SP (4)	12-24	Cu	—	300	8	B, D	2(105)
ME6.2 TBUS-2(6)	—	Cu	—	150	8	B, D	2(105)
ME17.5 TBUS(6)	—	Cu	—	150	8	B, D	2(105)
ME22.5 TBUS(6)	—	Cu	—	150	8	B, D	2(105)
PIT2.5(@@)	26-12 sol/str	Cu	N/A	600	20	B, C, D	2(105), 6(150 x150 x120)
PIT2.5-PE(@@)	26-12 sol/str	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PIT2.5-TWIN(@@)	26-12 sol/str	Cu	N/A	600	20	B, C, D	2(105), 6(150 x150 x120)
PIT2.5-TWIN-PE(@@)	26-12 sol/str	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PITO2.5(@@)	26-12 sol	Cu	N/A	600	20	B, C	2(105), 6(150 x150 x120)
FT 2.5	26-12 so	Cu	N/A	600	30	B, C	2(105)
PITO2.5-PE(@@)	26-12 sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
FT 2.5-PE	26-12 sol	Cu	N/A	N/A	N/A	B,C	2(105)
PITO2.5-TWIN(@@)	26-12 sol	Cu	N/A	600	20	B, C	2(105), 6(150 x150 x120)
FT 2.5-TWIN	26-12 sol	Cu	N/A	600	20	B, C	2(105)

PITO2.5-TWIN-PE(@@)	26-12 sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
FT 2.5-TWIN-PE	26-12 sol	Cu	N/A	N/A	N/A	B, C	2(105)
PIT2.5-QUATTRO(@@)	26-12 sol/str	Cu	N/A	600	20	B, C, D	2(105), 6(150 x150 x120)
PTTB or PITTB2.5(@@)	26-12 sol/str	Cu	N/A	300 600	20 5	B, C D	2(105), 6(150 x150 x120)
FTTB 2.5	26-12 sol/str	Cu	N/A	300	20	B, C	2(105)
FTTB 2.5	26-12 sol/str	Cu	N/A	600	5	D	2(105)
PTTB or PITTB2.5-PV(@@)	26-12 sol/str	Cu	N/A	300 600	20 5	B, C D	2(105), 6(150 x150 x120)
FTTB 2.5-PV	26-12 sol/str	Cu	N/A	300	20	B, C	2(105)
FTTB 2.5-PV	26-12 sol/str	Cu	N/A	600	5	D	2(105)
PITBTS2.5(@@)	26-12 sol/str	Cu	N/A	300 600	20 5	B, C D	2(105), 6(150 x150 x120)
PITO2.5-QUATTRO(@@)	26-12 sol	Cu	N/A	600	20	B, C	2(105), 6(150 x150 x120)
FT 2.5-QUATTRO	26-12 sol	Cu	N/A	600	20	B, C	2(105)
PIT2.5-QUATTRO-PE(@@)	26-12 sol/str	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PTTB or PITTB2.5-PE(@@)	26-12 sol/str	Cu	N/A	600	N/A	B, C, D	2(105), 6(150 x150 x120)
FTTB 2.5-PE	26-12 sol/str	Cu	N/A	600	N/A	B,C,D	2(105)
PITBTS2.5-PE(@@)	26-12 sol/str	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PITO2.5-QUATTRO-PE(@@)	26-12 sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
FT 2.5-QUATTRO-PE	26-12 sol	Cu	N/A	N/A	N/A	B, C	2(105)
PIT 2.5/1P(@@)	26-12 str/sol	Cu	N/A	600	20	B, C, D	2(105), 6(150 x150 x120)
PIT 2.5/1P-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PIT 2.5-TWIN/1P(@@)	26-12 str/sol	Cu	N/A	600	20	B, C, D	2(105), 6(150 x150 x120)

PIT 2.5-TWIN/1P-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PIT 2.5-QUATTRO/2P(@@)	26-12 str/sol	Cu	N/A	600	20	B, C, D	2(105), 6(150 x150 x120)
PIT 2.5-QUATTRO/2P-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
PITTB 2.5/2P(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
				600	5	D	2(105), 6 (6 x 6 x 4 3/4)
PITTB 2.5/2P-PV(@@)	26-12 str/sol	Cu	N/A	600	5	D	2(105), 6(150 x150 x120)
				300	20	B, C	2(105), 6 (6 x 6 x 4 3/4)
PITTB 2.5/2P-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 6(150 x150 x120)
SP-H 2.5 w suffixes	26-12 str/sol	Cu	N/A	300	20	B, C	2(105)
				600	5	D	2(105)
PP-H 2.5 w suffixes(@@)	26-12 str/sol	Cu	N/A	600	20	B, C, D	2(105)
PT or PIT 2.5-MT(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-TWIN-MT(@@)	26-12 str 24-12 sol	Cu	N/A	300	20 16	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-QUATTRO-MT(@@)	26-12 str 24-12 sol	Cu	N/A	300	20 16	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-TG(@@)	26-12 str 24-12 sol	Cu	N/A	300	20 16	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-TG (#)(@@)	26-12 str 24-12 sol	Cu	N/A	300	10	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-TWIN-TG(@@)	26-12 str 26-12 sol	Cu	N/A	300	20 16	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-TWIN-TG (#)(@@)	26-12 str 26-12 sol	Cu	N/A	300	10	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-QUATTRO-TG(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)

PT or PIT 2.5-QUATTRO-TG (#)(@@)	26-12 str/sol	Cu	N/A	300	10	B, C	2(105), 6(150 x150 x120)
PITTB 2.5-DIO/UL-UR(@@), PITTB2.5-DIO/0-U(@@), PITTB2.5-DIO/U-O(@@)	26-12 str/sol	Cu	N/A	300	20, 0.5(1)	B, C	2(105)
PITTB 2.5-2DIO/0-UL/UR-U(@@)L, PITTB2.5-2DIO-UL/0-UR(@@)	26-12 str/sol	Cu	N/A	300	20, 0.5(1)	B, C	2(105)
PITTB 2.5-LA 24RD(@@)	26-12 str/sol	Cu	N/A	30	20	B, C	2(105)
PITTB 2.5-LA 60RD(@@)	26-12 str/sol	Cu	N/A	60	20	B, C	2(105)
PITTB 2.5-LA 230(@@)	26-12 str/sol	Cu	N/A	250	20	B, C	2(105)
PITBTS 2.5-DIO/0-U(@@), PITBTS 2.5-DIO/U-0(@@)	26-12 str/sol	Cu	N/A	300	20,0.5 (1)	B, C	2(105)
PIT2.5-DIO/L-R(@@)(@@), PIT2.5-DIO/R-L(@@)	26-12 str/sol	Cu	N/A	300	20,0.5(1)	B, C	2(105)
PIT 2.5-TWIN-DIO/R-L(@@), PIT2.5-TWIN-DIO/L-R(@@)	26-12 str/sol	Cu	N/A	300	0.5(1)	B, C	2(105)
PIT 2.5-QUATTRO-DIO/R-L(@@), PIT 2.5-QUATTRO-DIO/L-R(@@)	26-12 str/sol	Cu	N/A	300	0.5(1)	B, C	2(105)
PITTB 2.5-L/N(@@), PTTB 2.5-L/N, FTTB 2.5-L/N	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PITTB 2.5-PE/L(@@), PTTB 2.5-PE/L	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 str/sol	Cu	N/A	N/A(2)	N/A(2)	B, C	2(105), 6(150 x150 x120)
PITTB 2.5-PE/N(@@), PTTB 2.5-PE/N	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 str/sol	Cu	N/A	N/A(2)	N/A(2)	B, C	2(105), 6(150 x150 x120)
PIT 2.5-3L, PT2.5-L/L/N(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-3PV(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PT or PIT 2.5-3PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
PIT2.5-PE-L/L(@@), PIT2.5-PE/L/N(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)

PIT 2.5/1P(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PIT 2.5/1.5-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
PIT 2.5-TWIN/1P(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PIT 2.5-TWIN/1P-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
PIT 2.5-QUATTRO/2P(@@)	26-12 str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
PIT 2.5-QUATTRO/2P-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
PITS2.5(@@)	26-12 str/sol	Cu	N/A	600	20	B, C	2(105), 4, 6(150 x150 x120)
PITS2.5-TWIN(@@)	26-12 str/sol	Cu	N/A	600	20	B, C	2(105), 4, 6(150 x150 x120)
PITS2.5-QUATTRO(@@)	26-12 str/sol	Cu	N/A	600	20	B, C	2(105), 4, 6(150 x150 x120)
PITS2.5-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PITS2.5-TWIN-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PITS2.5-QUATTRO-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 6(150 x150 x120)
PITI 2.5(@@)	26-12 str/sol	Cu	N/A	600	20	B, C	2(105), 4, 6(150 x150 x120)
PITI 2.5-L (-N)(@@)	26-12 str/sol	Cu	N/A	600	5	D	2(105), 4, 6(150 x150 x120)
				150	20	C	
				300	20	B	
PITI 2.5-L/L (-L/N)(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4
				150	20	C	
				300	10	D	
PITI 2.5-L/LT (-L/NT)(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4
				300	10	D	

PITI 2.5-L/LTB (-L/NTB)(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
					10	D	
PITI 2.5-L/TG(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				150	20	C	
				300	10	D	
PITI 2.5-L/LB(@@)	26-12 str/sol	Cu	N/A	300 150 300	20 20 10	B C D	2(105), 4, 6(150 x150 x120)
PITI 2.5-PE(@@)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 4, 6(150 x150 x120)
PTI 2.5-PE-L, PTI 2.5-PE-N, PTI 2.5-PE/L/L or PITI 2.5-PE/L/L(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				150	20	C	
				300	10	D	
				N/A	N/A	B, C, D	
PT 2.5/S-QUATTRO	28-12 str 28 sol	Cu	N/A	300	20	B,C	2(115), 4
				600	5	D	
PT 2.5/S-QUATTRO-CUS	28-12 str 28 sol	Cu	N/A	300	20	B,C	2(115), 4
				600	5	D	
PT 2.5/S-QUATTRO-PE	28-12 str 28 sol	Cu	N/A	N/A	N/A	B,C,D	2(115), 4
PT 2.5-PE/3L/2P	26-14str/sol	Cu	N/A	300 150	10 10	B,D C	2(115), 4
	26-14 str/sol	Cu	N/A	N/A	N/A	B,D C	2(115), 4
PT 2.5-PE/3L	26-12 str/sol	Cu	N/A	600	20	B, C	2(115), 4
	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(115), 4
PTI or PITI 2.5-PE/L/N(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				150	20	C	
				300	10	D	
				N/A	N/A	B, C, D	
PITI 2.5-PE/L/LB(@@)	26-12 str/sol	Cu	N/A	300	20(2)	B, C	2(105), 4, 6(150 x150 x120)
				N/A	N/A	B, C	
PTI 2.5-PE/L/LT, PTI 2.5-PE/L/NT or PITI 2.5-PE/L/NT(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				300	10	B, D	
				N/A	N/A	B, D	
PTI or PITI 2.5-PE/L/LTB(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				300	10	D	

				N/A	N/A	B, D	
PTI or PITI 2.5-PE/L/NTB(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				300	10	D	
				N/A	N/A	B, D	
PTI or PITI 2.5-PE/L/TG(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				150	20	C	
				300	10	D	
				N/A	N/A	B, C, D	
PITI 2.5-PE/L/LB(@@)	26-12 str/sol	Cu	N/A	300	20	B	2(105), 4, 6(150 x150 x120)
				300	10	D	
				N/A	N/A	B, D	
PITN 2.5(@@)	26-12 str/sol	Cu	N/A	600	20	B, C	2(105), 4, 6(150 x150 x120)
				600	5	D	
PTTB2.5-2DIO/UL-0/UR-0	26-12 str/sol	Cu	N/A	300	20 0.5(1)	B, C	2(105), 4
PTTB2.5-2DIO/0-UR/UL-UR	26-12 str/sol	Cu	N/A	300	20 0.5(1)	B, C	2(105), 4
PTTB 2.5-DIO/O-U, PTTB 2.5-DIO/U-O, PTTB 2.5-DIO/UL-UR, PTTB 2.5-2DIO/O-UL/UR-UL, PTTB 2.5-2DIO/UL-O/UR-O, PTTB 2.5-2DIO/UR-O/UR-UL, PTTB 2.5-2DIO/O-UL/O-UR, PTTB 2.5-2DIO/O-UR/UL-UR, PTTB 2.5-2DIO/OL-U/OR-U	26-12 str/sol	Cu	N/A	300	20 0.5(1)	B, C	2(105), 4
PTTB 2.5-LA 24	26-12 str/sol	Cu	N/A	30	20	B, C	2(105), 4
PTTB 2.5-LA 60	26-12 str/sol	Cu	N/A	60	20	B, C	2(105), 4
PTTB 2.5-LA 230	26-12 str/sol	Cu	N/A	250	20	B, C	2(105), 4
PTTBS2.5-LA24RD	26-12 str/sol	Cu	N/A	30	20	B, C	2(105), 4
PIT 2.5-L/LB	26-12	Cu	N/A	300 150 300	20 20 10	B C D	2(105), 4, 6(150 x150 x120)
PT 2.5, PTO 2.5 - MTB	26-12str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
				600	5	D	
PT 2.5, PTO 2.5-TWIN- MTB	26-12 str	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 sol			300	16	B, C	
	26-12 str/sol			600	5	D	
PT 2.5, PTO 2.5-QUATTRO- MTB	26-12 str	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 sol			300	16	B, C	

	26-12 str/sol			600	5	D	
PT 2.5, PTO 2.5 -TGB	26-12str/sol	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
				600	5	D	
PT 2.5, PTO 2.5-TWIN -TGB	26-12 str	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 sol			300	16	B, C	
	26-12 str/sol			600	5	D	
PT 2.5, PTO 2.5-QUATTRO-TGB	26-12 str	Cu	N/A	300	20	B, C	2(105), 6(150 x150 x120)
	26-12 sol			300	16	B, C	
	26-12 str/sol			600	5	D	
PT 2.5-QUATTRO-LA 24	26-12 str/sol	Cu	N/A	30	20	B, C	2(105), 4
PT 2.5-QUATTRO-LA 60	26-12 str/sol	Cu	N/A	60	20	B, C	2(105), 4
PT 2.5-QUATTRO-LA 230	26-12 str/sol	Cu	N/A	250	20	B, C	2(105), 4
PT2.5-4L/1P	26-12	Cu	N/A	300	10	B, C	2(105), 4, 6(150 x150 x120)
PT2.5-4L/2P	26-12	Cu	N/A	300	10	B, C	2(105), 4, 6(150 x150 x120)
CP-H2.5-4L w/wo -Z	—	Cu	N/A	300	10	B, C	2(105)
PT 1.5/S-MTD	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-TG	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-MT	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-TWIN-MTD	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-TWIN-TG	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-TWIN-MT	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-QUATTRO-MTD	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-QUATTRO-TG	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PT 1.5/S-QUATTRO-MT	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PTT 1.5/S-2L	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PTT 1.5/S-2TG	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PTT 1.5/S-2MT	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PTT 1.5/S-L/TG	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PTT 1.5/S-L/MT	26-16 str/sol	Cu	N/A	300	10	B, C	2(115), 4
PTT 2.5-2L	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTT 2.5-2TG	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTT 2.5-2MT	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4

PTT 2.5-L/TG	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTT 2.5-L/MT	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTTBS 2.5-2MTB	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTTBS 2.5-2TGB	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTTBS 2.5-MTB/TGB	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTTBS 2.5-TGB/MTB	26-12 str/sol	Cu	N/A	300	16	B, C	2(115), 4
PTTBS 2.5-TWIN	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTTBS 2.5-TWIN-PE	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(115)
PTTBS 2.5-TWIN-PV	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTTBS 2.5-TWIN/2P	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTTBS 2.5-TWIN/2P-PE	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(115)
PTTBS 2.5-TWIN/2P-PV	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTTBS 2.5-QUATTRO	26-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PTTBS 2.5-QUATTRO-PE	26-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(115)
PTTBS 2.5-QUATTRO-PV	26-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PTI 2.5 (1), PITI 2.5 (1)	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTI 2.5-PE (2), PITI 2.5-PE (2)	26-12 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(115)
PTI 4-PE/L/NT	20-8 sol/str	Cu	N/A	300	27	B	2(115)
	20-8 sol/str	Cu	N/A	300	10	D	2(115)
PTI 4-PE/L/LT	20-8 sol/str	Cu	N/A	300	27	B	2(115)
	20-8 sol/str	Cu	N/A	300	10	D	2(115)
PTI 4-PE/L/N	20-8 sol/str	Cu	N/A	300	27	B	2(115)
	20-8 sol/str	Cu	N/A	300	10	D	2(115)
PTI 4-PE/L/L	20-8 sol/str	Cu	N/A	300	27	B	2(115)
	20-8 sol/str	Cu	N/A	300	10	D	2(115)
PTI 4-L/N	20-8 sol/str	Cu	N/A	300	27	B	2(115)
	20-8 sol/str	Cu	N/A	300	10	D	2(115)
PTI 4-L/L	20-8 sol/str	Cu	N/A	300	27	B	2(115)
	20-8 sol/str	Cu	N/A	300	10	D	2(115)
PTTBS 2.5	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PTTBS 2.5-L/N	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PTTBS 2.5-PE	24-12 str/sol	Cu	N/A	N/A	N/A	B, C	2(115)
PTTBS 2.5-PE/L	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PTTBS 2.5-PV	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)

PTTBS 2.5-DIO/O-U	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PTTBS 2.5-DIO/U-O	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)
FTTBS 2.5	24-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PPC 2.5/n	26-12 str/sol	Cu	N/A	300	20	B, C	2(115)
PPC 2.5/n-L, PPC 2.5-NS/n-L	26-12 str/sol	Cu	N/A	300	20	B, C	2(115)
P-CO XL -w/wo XXX	28-18 str/sol	Cu	N/A	300	7	B, C	2(115)
PTS 4	24-10 str/sol	Cu	N/A	600	30	B,C	2(115)
PTS 4-PE	24-10 str/sol	Cu	N/A	600	N/A	B,C	2(115)
PTS 4-TWIN	24-10 str/sol	Cu	N/A	600	30	B,C	2(115)
PTS 4-TWIN-PE	24-10 str/sol	Cu	N/A	600	N/A	B,C	2(115)
PTS 4- QUATTRO	24-10 str/sol	Cu	N/A	600	30	B,C	2(115)
PTS 4- QUATTRO-PE	24-10 str/sol	Cu	N/A	600	N/A	B,C	2(115)
PT 4-TWIN/1P	24-10 str/sol	Cu	N/A	600	28	B,C	2(115)
PT 4-TWIN/1P-PE	24-10 str/sol	Cu	N/A	600	N/A	B,C	2(115)
PT 4-QUATTRO/2P	24-10 str/sol	Cu	N/A	600	28	B,C	2(115)
PT 4-QUATTRO/2P-PE	24-10 str/sol	Cu	N/A	600	N/A	B,C	2(115)
PT 4/S QUATTRO/1P	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
	26-12 str/sol	Cu	N/A	800	20	F	2(115)
PT 4-QUATTRO/3CP	24-10 str/sol	Cu	N/A	600	28	B, C	2(115)
	24-10 str/sol	Cu	N/A	800	28	F	2(115)
PT 4-QUATTRO/3CP-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C, D, F	2(115)
PTTBS 2.5/2P	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTTBS 2.5/2P-PE	26-12 str/sol	Cu	N/A	600	N/A	B, C	2(115)
PTTBS 2.5/2P-PV	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PP 2.5/1-M	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PP 2.5/1-R	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PP 2.5/1-L	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PP 2.5/n	26-12 str/sol	Cu	N/A	600	20	B, C	2(115)
PTTB 2.5-2DIO/U-OL/U-OR, PTTB 2.5-2DIO/OL-U/OR-U, FTTB 2.5-2DIO/U-OL/U-OR, FTTB 2.5-2DIO/OL-U/OR-U	26-12 str/sol	Cu	N/A	300	20 0.5(1)	B,C	2(115),4
PTTBS 4	24-10 str/sol	Cu	N/A	600	24	B, C	2(115), 4
PTTBS 4-PV	24-10 str/sol	Cu	N/a	600	24	B, C	2(115), 4
PTTBS 4-PE	24-10 str/sol	Cu	N/A	600	N/A	B, C	2(115), 4

PTTB 2.5/2P	26-12 str/sol	Cu	N/A	300	20	B, C	2(105)
				600	5	D	2(105)
PTTB 2.5/2P-PV	26-12 str/sol	Cu	N/A	300	20	B, C	2(105)
				600	5	D	2(105)
PTTB 2.5/2P-PE	26-12 str/sol	CU	N/A	N/A	N/A	B, C, D	2(105)
PT4-WE w/wo suffixes	24-10 sol/str	Cu	N/A	150	25	C	2(115),4
				300	25	B	
					10	D	
PTI 16/S	24 sol/str-4 str	Cu	N/A	300	10	B, C	2(115), 4
				600	5	D	
PTI 16/S-PE	24 sol/str-4 str	Cu	N/A	300	—	B, C	2(115), 4
				600	—	D	
PTN 16/S	24 sol/str-4 str	Cu	N/A	300	10	B, C	2(115), 4
				600	5	D	
PTU 35/4X6/6/2.5	14 sol/str-2 str(incoming side)	Cu	3.2-3.7nm	600	102	B, C	2(115),4
	20-10 sol/str(outgoing 1)	Cu	N/A	600	25.5	B, C	2(115),4
	26-12 sol/str(outgoing 2)	Cu	N/A	600	17	B, C	2(115),4
PTI 16-NLS-FI	20-4	Cu	N/A	600	70	B, C	2(115)
AGK PT 4X6/M10	20-8	Cu	N/A	1000	I/P - 100* O/P -50	C	2(115)
AGK PT 4X6/M12	20-8	Cu	N/A	1000	I/P - 100* O/P -50	C	2(115)
AGK PT 8X6/M10	20-8	Cu	N/A	1000	I/P - 100* O/P -50	C	2(115)
AGK PT 4X6/M10 GNYE	20-8	Cu	N/A	N/A	N/A	B, C	2(115)
AGK PT 8X6/M10 GYNE	20-8	Cu	N/A	N/A	N/A	B, C	2(115)
PT 2X10/9X4, FT 2X10/9X4	Input-20-8 AWG, Output-20-10 AWG	Cu	N/A	600	Input- 50, Output- 25	B,C	2(115)
				600	5	D	2(115)
HV M5/1	N/A	Cu	N/A	1000	76	C	2(115)
HV M5/1 NFF	24-4	Cu	3.6	600	76	B,C	2(115)
HV M6/1,HV M6/2	N/A	Cu	N/A	1000	125	C	2(115)
HV M6/1 NFF, HV M6/2 NFF	14-1	Cu	8	1000	125	C	2(115)
HV M8/1,HV M8/2	N/A	Cu	N/A	1000	150	C	2(115)

HV M8/1 NFF, HV M8/2 NFF	14-1/0	Cu	14.4	1000	150	C	2(115)
HV M10/1,HV M10/2	N/A	Cu	N/A	1000	269	C	2(115)
HV M10/1 NFF, HV M10/2 NFF	10-300 kcmil	Cu	30	1000	269	C	2(115)
HV M12/1	N/A	Cu	N/A	1000	269	C	2(115)
HV M12/1 NFF	10-300 kcmil	Cu	35.2	1000	269	C	2(115)
PTV 4	26-10	Cu	N/A	600	30	B,C	2(115)
PTV 4-PE	26-10	Cu	N/A	N/A	N/A	B,C	2(115)
PTV 4-TWIN	26-10	Cu	N/A	600	30	B,C	2(115)
PTV 4-TWIN-PE	26-10	Cu	N/A	N/A	N/A	B,C	2(115)
PTV 4-QUATTRO	26-10	Cu	N/A	600	30	B,C	2(115)
PTV 4-QUATTRO-PE	26-10	Cu	N/A	N/A	N/A	B,C	2(115)
PTV 4-MT	26-10	Cu	N/A	600	16	B,C	2(115)
PTV 4-TG	26-10	Cu	N/A	600	16	B,C	2(115)
PTV 4-HESI (5X20)	26-10	Cu	N/A	600	16	B,C	2(115)
PTV 4-HESILED 24 (5X20)	26-10	Cu	N/A	600	16	B,C	2(115)
PTV 4-HESILED 60 (5X20)	26-10	Cu	N/A	600	16	B,C	2(115)
PTV 4-HESILED/HESILA 250 (5X20)	26-10	Cu	N/A	600	16	B,C	2(115)
PTV 2.5-MT	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTV 2.5-TG	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTV 2.5-TWIN-MT	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTV 2.5-TWIN-TG	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTV 2.5-QUATTRO-MT	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTV 2.5-QUATTRO-TG	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTTBV 2.5	26-12	Cu	N/A	300	20	B,C	2(115)
	26-12	Cu	N/A	600	5	D	2(115)
PTTBV 2.5-PE	26-12	Cu	N/A	N/A	N/A	B,C, D	2(115)
PTTBV 2.5-PV	26-12	Cu	N/A	600	20	B,C	2(115)
	26-12	Cu	N/A	300	5	D	2(115)

PTTBV 4	26-10	Cu	N/A	600	28	B,C	2(115)
PTTBV 4-PV	26-10	Cu	N/A	600	28	B,C	2(115)
PTTBV 4-PE	26-10	Cu	N/A	N/A	N/A	B,C	2(115)
PTV 6	20-8	Cu	N/A	600	40	B,C	2(115)
	20-8	Cu	N/A	1000	40	F(3)	2(115)
PTV 6-PE	20-8	Cu	N/A	N/A	N/A	B,C,F(3)	2(115)
PTV 6-TWIN	20-8	Cu	N/A	600	40	B,C	2(115)
	20-8	Cu	N/A	1000	40	F(3)	2(115)
PTV 6-TWIN-PE	20-8	Cu	N/A	N/A	N/A	B,C,F(3)	2(115)
PTV 6-QUATTRO	20-8	Cu	N/A	600	40	B,C	2(115)
	20-8	Cu	N/A	1000	40	F(3)	2(115)
PTV 6-QUATTRO-PE	20-8	Cu	N/A	N/A	N/A	B,C,F(3)	2(115)
Note: (1) Current through Diode.							
Note: (2) Grounding terminal.							
Note: (3) Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification only.							
Note: (#) Cat. Nos. with Suffix -TG followed by Suffixes P-FU 5X20 and P-FU 6X32 followed by -5, LED 24-5, LED 60-5 or LA 250-5; Suffixes FP (5X20) with or without 24, 60, or 250.							
Note: * BOLT connection(M10, M12)							
(1) - w/wo suffixes -L, -N, -L/L, -L/N, -L/LT, -L/NT, -L/LTB, -L/NTB, -L/TG or -L/LB.							
(2) - w/wo suffixes -L, -N, -L/L, -L/N, -L/LT, -L/NT, -L/LTB, -L/NTB or -L/TG.							
EC4TR/2P, EC4TR/3P, EC4TR/4P, EC4TR/5P, EC4TR/6P, EC4TR/7P, EC4TR/8P, EC4TR/9P, EC4TR/10P, EC4TR, EC2.5PTR/2P, EC2.5PTR/3PEC2.5PTR/4P, EC2.5PTR/5P, EC2.5PTR/6P, EC2.5PTR/7P, EC2.5PTR/8P,EC2.5PTR/9P, EC2.5PTR/10P, EC2.5PTR	22-12	Cu	0.45	300	20	B, C, D	2(65), 4
EC6TR/2P, EC6TR/3P, EC6TR/4P, EC6TR/5P, EC6TR/6P, EC6TR/7P, EC6TR/8P, EC6TR/9P, EC6TR/10P, EC6TR, EC4PTR/2P, EC4PTR/3P, EC4PTR/4P, EC4PTR/5P, EC4PTR/6P, EC4PTR/7P, EC4PTR/8P, EC4PTR/9P, EC4PTR/10P, EC4PTR	20-10	Cu	0.8	300	30	B, C, D	2(65), 4
EC10TR/2P, EC10TR/3P, EC10TR/4P, EC10TR/5P, EC10TR/6P, EC10TR/7P, EC10TR/8P, EC10TR/9P, EC10TR/10P, EC10TR, EC6PTR/2P, EC6PTR/3P, EC6PTR/4P, EC6PTR/5P, EC6PTR/6P, EC6PTR/7P, EC6PTR/8P, EC6PTR/9P, EC6PTR/10P, EC6PTR	14-8	Cu	0.8	300	50	B, C, D	2(65), 4

EC16TR/2P, EC16TR/3P, EC16TR/4P, EC16TR/5P, EC16TR/6P, EC16TR/7P, EC16TR/8P, EC16TR/9P, EC16TR/10P, EC16TR, EC16PTR/2P, EC16PTR/3P, EC16PTR/4P, EC16PTR/5P, EC16PTR/6P, EC16PTR/7P, EC16PTR/8P, EC16PTR/9P, EC16PTR/10P, EC16PTR	10-6	Cu	1.1	300	55	B, C, D	2(65), 4
EC25TR/2P, EC25TR/3P, EC25TR/4P, EC25TR/5P, EC25TR/6P, EC25TR/7P, EC25TR/8P, EC25TR/9P, EC25TR/10P, EC25TR	8-4	Cu	1.7	600	85	B, C, D	2(65), 4

(1) Followed by Suffixes UT(L or R)BUS/5, or UT(L or R)BUS/10, and may be followed by AA to ZZ inclusive.

(2) Top terminals (MSTBT2.5, MKDSO2.5 blocks).

(3) Bottom terminals (MKCVR1.5 block).

(4) Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.

(5) Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.

(6) Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.

Cat. Nos.	Wire Sizes	WT	Torque In. Lb.	Volts	Amp	Use Group	CA
ST2.5	28-12	Cu	N/A	60	20	B, C	2(105)
ST2.5-PCB, ST2.5-PCBV Followed by /1 or /2 digit No. and by -G-5.2	—	Cu	N/A	300	15	B, C	2(105)
ST2.5-TWIN-PE	28-12	Cu	N/A	N/A	N/A	B, C	2(105)
ST2.5-QUATTRO, -U	28-12	Cu	N/A	600	20	B, C	2(105)
ST2.5-DIO/L-R, -DIO/R-L	28-12	Cu	N/A	300	1	B, C	2(105)
				600		D	
ST2.5-TWIN-DIO/L-R, -DIO/R-L	28-12	Cu	N/A	300	20(1)	B, C	2(105)
				600	5(1)	D	
ST2.5-QUATTRO-DIO/L-R, -DIO/R-L	28-12	Cu	N/A	300	20(1)	B, C	2(105)
				600	5(1)	D	
STTB2.5-LA24, -LA60	28-12	Cu	N/A	600	20	B, C	2(105)
STTB2.5	28-12	Cu	N/A	600	20	B, C	2(105)
STTB2.5-PV	28-12	Cu	N/A	600	20	B, C	2(105)
ST2.5-PE	28-12	Cu	N/A	N/A	N/A	B, C	2(105)
ST2.5-TWIN	28-12	Cu	N/A	600	20	B, C	2(105)
ST2.5-QUATTRO-PE	28-12	Cu	N/A	N/A	N/A	B, C	2(105)
STTB2.5-DIO/U-O	28-12	Cu	N/A	300	20(1)	B, C	2(105)
STTB2.5-DIO/O-U	28-12	Cu	N/A	300	20(1)	B, C	2(105)
STTB2.5-DIO/UL-UR	28-12	Cu	N/A	300	20(1)	B, C	2(105)

STTB2.5-2DIO/O-UL/UR-UL	28-12	Cu	N/A	300	20(1)	B, C	2(105)
STTB2.5-DIO/O-UL/O-UR	28-12	Cu	N/A	300	20(1)	B, C	2(105)
STTB2.5-LA230	28-12	Cu	N/A	300	20	B, C	2(105)
SP2.5/X, SPB2.5/X, w/wo Suffixes /1-L, /1-M, /1-R	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
SPDB2.5/X w/wo Suffixes /1-L, /1-M, /1-R	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
ST2.5/1P	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
ST2.5QUATTRO/2P/X	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
ST2.5-QUATTRO/4P, BU	N/A	Cu	N/A	600	20(2)	B, D	2(105)
STTB2.5/2P	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
STTB2.5/2P-PV	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
STTB2.5/2P-DIO/O-U	28-12	Cu	N/A	300	20(2)	B, D	2(105)
ST2.5/1P-PE	28-12	Cu	N/A	300/600	20(2)	B, C	2(105)
ST2.5-3L	28-12	Cu	N/A	600	20	B, C	2(105)
ST2.5-L/L/N	28-12	Cu	N/A	600	20	B, C	2(105)
ST2.5-3PV	28-12	Cu	N/A	600	20	B, C	2(105)
ST2.5-3PE	28-12	Cu	N/A	N/A	N/A	B, C	2(105)
ST2.5-PE/3L	28-12	Cu	N/A	600	20	B, C	2(105)
STTB2.5-PE	28-12	Cu	N/A	N/A	N/A	B, D	2(105)
ST2.5-QUATTRO/2P-PE	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
ST2.5-QUATTRO/4P-PE	N/A	Cu	N/A	N/A	N/A	B, D	2(105)
STTB2.5/2P-PE	28-12	Cu	N/A	300/600	20(2)	B, D	2(105)
ST2.5-PE/L/L, ST2.5-PE/L/N	28-12	Cu	N/A	300(3)	20(3)	B, C	2(105)
ST2.5-PE/2PV	28-12	Cu	N/A	300(3)	20(3)	B, C	2(105)
ST2.5-MT	28-12	Cu	N/A	300	16	B, C	2(105)
ST2.5-TWIN-MT	28-12	Cu	N/A	300	16	B, C	2(105)
ST2.5-QUATTRO-MT	28-12	Cu	N/A	300	16	B, C	2(105)
STTB2.5	28-12	Cu	N/A	300	20	B, C	2(105)
	28-12	Cu	N/A	600	5	D	2(105)
STTB2.5-PV	28-12	Cu	N/A	300	20	B, C	2(105)
	28-12	Cu	N/A	600	50	D	2(105)
STTB2.5-PE	28-12	Cu	N/A	N/A	N/A	B, D	2(105)
ST2.5/2P-PE	N/A	Cu	N/A	N/A	N/A	B, C	2(105)
ST2.5/2P	N/A	Cu	N/A	600	20	B, C	2(105)

[illegible]

Note: (2) 5A max. at 600V; 10A max. at 300V general industrial use.

STS2.5-MT	28-12	Cu	N/A	300	16	B, D	2(105)
STS2.5-TG	28-12	Cu	N/A	300	16	B, D	2(105)
STS2.5-TG(#)	28-12	Cu	N/A	300	10	B, C	2(105)
ST2.5-TG	28-12	Cu	N/A	300	16	B, D	2(105)
ST2.5-TG(#)	28-12	Cu	N/A	300	10	B, C	2(105)
ST2.5-TWIN-TG	28-12	Cu	N/A	300	16	B, D	2(105)
ST2.5-TWIN-TG(#),/1P	28-12	Cu	N/A	300	10	B, C	2(105)
ST2.5 QUATTRO-TG	28-12	Cu	N/A	300	20	B, D	2(105)
ST2.5 QUATTRO-TG(#)	28-12	Cu	N/A	300	10	B, C	2(105)
STTB2.5-L/N	28-12	Cu	N/A	300	16	B, D	2(105)
STTB2.5-PE/L	28-12	Cu	N/A	300	20	B, D	2(105)
				(3)	(3)		
STTB2.5-PE/N	28-12	Cu	N/A	300	20	B, D	2(105)
				(3)	(3)		
STI2.5, -BU	28-12	Cu	N/A	600	20	B, D	2(105)
STI2-5-PE	28-12	Cu	N/A	N/A	N/A	B, C	2(105)
STI2.5-L	28-12	Cu	N/A	150	20	B, C	2(105)
				/300	/10		
STI2.5-L/L	28-12	Cu	N/A	150	20	B, C	2(105)
				/300	/10		
STI2.5-L/N	28-12	Cu	N/A	150	20	B, C	2(105)
				/300	/10		
STI2.5-PE/L/L	28-12	Cu	N/A	150	20	B, C	2(105)
				/300	/10		
				(3)	(3)		
STI2.5-PE/L/N	28-12	Cu	N/A	150	20	B, C	2(105)
				/300	/10		
				(3)	(3)		
STI2.5-PE/L/NT	28-12	Cu	N/A	150	20	B, C	2(105)
				/300	/10		
				(3)	(3)		
STI2.5-PE/NTB	28-12	Cu	N/A	150	20	B, C	2(105)

				(3)	(3)		
STTB2.5-TWIN	28-12	Cu	N/A	300	20	B, D	2(105)
STTB2.5-TWIN-PV	28-12	Cu	N/A	300	20	B, D	2(105)
STTB2.5-TWIN-PE	28-12	Cu	N/A	N/A	N/A	B, D	2(105)
SC2.5, SC2.5-RZ, SC2.5/1-L, SC2.5-NS/1-L	28-12	Cu	N/A	300	20	B, D	2(105)
STI2.5-PE/LTB	28-12	Cu	N/A	150/300(3)	20/10(3)	B, D	2(105)
SPV2.5 w/wo Suffixes/1-L, /1-M, /1-R	26-12	Cu	N/A	600	20(2)	B, D	2(105)
SP2.5 f/b /1 or /2-difit No.	26-12	Cu	N/A	600	20(2)	B, D	2(105)
SPB2.5 f/b /1 or /2-difit No.	26-12	Cu	N/A	600	20(2)	B, D	2(105)
SPV2.5 f/b /1 or /2-difit No.	26-12	Cu	N/A	600	20(2)	B, D	2(105)
SPDB2.5 f/b /1 or /2-difit No.	26-12	Cu	N/A	600	20(2)	B, D	2(105)
Note: (2) Limited to 5A max. at 300V for industrial applications							
Note: (3) Ampere/voltage rating not applicable for lower level grounding terminals							
Note: (#) Cat. Nos. with Suffix -TG followed by Suffixes P-FU 5X20 and P-FU 6X32 followed by -5, LED 24-5, LED 60-5 or LA 250-5; Suffixes FP (5X20) with or without 24, 60, or 250.							

Cat. Nos.	Wire Sizes	WT	Torque In. Lb.	Volts	Amp	Use Group	CA
AKG4-GNIE	22-12	Cu	1.5-1.8 Nm	NA	NA	B, C	2(105)
AK4, AKG4	22-12	Cu	1.5-1.8 Nm	(1)	20	B, C	2(105)
	10	Cu	1.5-1.8 Nm	(1)	30	B, C	2(105)
AKG16	6-18	Cu	2.5-3.0 Nm	(1)	65	B, C	2(105)
AKG16-GNIE	6-18	Cu	2.5-3.0 Nm	NA	NA	B, C	2(105)
AKG35	2-18	Cu	5.6 Nm	(1)	115	B, C	2(105)
AKG35-GNIE	2-18	Cu	5.6 Nm	NA	NA	B, C	2(105)
Note: (1) The voltage rating depends on the fixing of the busbar and have to be considered in the end use application.							
QC0.5(1)-ST-3.81	24-20	Cu	N/A	300	6	B, C	2(105)
QC0.5(1)-STF-3.81	24-20	Cu	N/A	300	6	B, C	2(105)
STS2.5-TWIN, STS2.5, -BU STS2.5-QUATTRO	26-12	Cu	N/A	600	20	B, C	2(105)
STS2.5-TWIN-PE, STS2.5-PE STS2.5-QUATTRO-PE	26-12	Cu	N/A	—	—	B, C	2(105)
STS4-TWIN, STS4-QUATTRO	20-12	Cu	N/A	600	30	B, C	2(105)

STS4-TWIN-PE, STS4-QUATTRO-PE	20-12	Cu	N/A	—	—	B, C	2(105)
Note: (1) Followed by /1 or /2-digit number.							
ST6, STS6 w/suffixes - TWIN,	24-8	Cu	N/A	600	50	B, C	2(105)
ST6, STS6 w/Suffixes -PE, -TWIN-PE	24-8	Cu	N/A	N/A	N/A	C	2(105)
ST10	16-6	Cu	N/A	600	65	B, C	2(105)
ST10-TWIN	16-6	Cu	N/A	600	60	B, C	2(105), 4
ST10-PE	16-6	Cu	N/A	—	—	B, C	2(105)
ST10-TWIN-PE	16-6	Cu	N/A	—	—	B, C	2(105), 4
ST16	16-4	Cu	N/A	600	85	B, C	2(105)
ST16-TWIN	16-4	Cu	N/A	600	85	B, C	2(105), 4
ST16-PE	16-4	Cu	N/A	—	—	B, C	2(105)
ST16-TWIN-PE	16-4	Cu	N/A	—	—	B, C	2(105), 4
ST35	14-2	Cu	N/A	600	115	B, C	2(105)
ST35-PE	14-2	Cu	N/A	N/A	N/A	B, C	2(105)
STME6	24-8	Cu	N/A	600	30	B, C	2(105)
STMED6	24-8	Cu	N/A	600	30	B, C	2(105)
STMED6-PE	24-8	Cu	N/A	N/A	N/A	B, C	2(105)
STME6 HV	24-8	Cu	N/A	600	30	B, C	2(105),4
STME6-DIO P1000Y/R-L HV	24-8	Cu	N/A	600	5	B, C	2(105),4
STME6-DIO/R-L HV	24-8	Cu	N/A	600	5	B, C	2(105),4
STME6-DIO/L-R HV	24-8	Cu	N/A	600	5	B, C	2(105),4
PC6(1), PCu6(1)	20-8	Cu	11-15	600	50	B, C	2(115)
PC6(2), PCV6(2)	—	Cu	—	300	50	B, C	2(115)
LPC 6(3)	18-8	CU	N/A	600	35	B	2(105), 4
	18-8	CU	N/A	600	35	C	2(105), 4
	18-8	CU	N/A	600	35	F(+)	2(105), 4
LPCH 6(4)	Signal						
	24-16	CU	N/A	150	8	B	2(105), 4
	24-16	CU	N/A	50	8	C	2(105), 4
	24-16	CU	N/A	160	8	F(+)	2(105), 4
	Power						
	18-8	CU	N/A	600	35	B	2(105), 4

	18-8	CU	N/A	600	35	C	2(105), 4
	18-8	CU	N/A	600	35	F(+)	2(105), 4
PC 6(5), PCV 6 (7) (-G, -GL2 to GL8, -GU, -GL2U to GL8U, -G1U, -G1UL)-7.62	N/A	N/A	N/A	300	35	B	2(115)
	N/A	N/A	N/A	300	35	C	2(115)
	N/A	N/A	N/A	600	5	D	2(115)
	N/A	N/A	N/A	600	35	F(+)	2(115)
PCH 6(6)	Signal						
	N/A	N/A	N/A	300	8	B	2(115)
	N/A	N/A	N/A	50	8	C	2(115)
	N/A	N/A	N/A	50	8	D	2(115)
	N/A	N/A	N/A	160	8	F(+)	2(115)
	Power						
	N/A	N/A	N/A	300	35	B	2(115)
	N/A	N/A	N/A	300	35	C	2(115)
	N/A	N/A	N/A	300	10	D	2(115)
	N/A	N/A	N/A	600	5	D	2(115)
	N/A	N/A	N/A	600	35	F(+)	2(115)
Note: (+) Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification only.							
Note: (1) Followed by /1-digit number, and by suffix -ST, -STD, -STF, -SH, followed by -10.16, w/wo suffix RAE.							
Note: (2) Followed by /1-digit number, and by suffix -G or -GF, followed by -10.16, with or without suffix CODED.							
Note: (3) Followed by /2 to /9 followed by -ST-7.62. Followed by /2 to /9 followed by -STL followed by 2 to 9 followed by -7.62.							
Note: (4) Followed by /3 to /6 followed by +4 or +6 followed by -ST -7.62. Followed by /3 to /6 followed by +4 or +6 followed by -STL followed by 2 to 6 followed by -7.62.							
Note: (5) Followed by /2 to /9 followed by -G or -G1U, followed by -7.62. Followed by /2 to /9 followed by -GL or -G1UL followed by 2 to 9 followed by -7.62, may be followed by THR.							
Note: (6) Followed by /2 to /6 followed by +4 or +6 followed by -G or -G1U followed by -7.62. Followed by /3 to /6 followed by +4 or +6 followed by -GL or -G1UL followed by 2 to 6 followed by -7.62, may be followed by THR.							
Note: (7) Terminal Block Headers, Cat. No.: PCV 6/6-G-7.62 mated with Terminal Block Plug LPC 6/6-ST-7.62 have been used for testing purpose and are considered representative for all PCV 6 followed by /2 to /9 followed by -G or -GL followed by -7.62 models.							
SLKK5	26-10/	Cu	5-7	600	30	B, C	2(105)
	/26-12						
	gnd.						
TT-SLKK5, TT-SLKK5-S followed by suffixes/12, /24, /48, /60, /110 followed by suffix AC or DC	26-10 /26-12 gnd.	Cu	5-7	600	30	B, C	2(105)

FRONT-ZFL 1.5/D32	24-16	Cu	N/A	300	4	B, D	2(120)
ME17.5, ME22.5, ME35 ME45 suffixes UT(w/wo L or R), UT/FE, F-UT(w/wo L or R), or F-UTG(w/wo L or R), f/b suffixes BUS/5, BUS/10, BUS/5+2, BUS/10+2, w/wo suffixes AA-ZZ incl.	12-30	Cu	5-7	300 (Lower), 4.0 (Upper)	20	B, C	2(105)
ME17.5, ME22.5, ME35 ME45 suffixes OT-MSTBO-SET or OT-MKDSO-SET w/wo suffixes AA-ZZ incl.	12-30	Cu	5-7	300 (Lower), 4.0 (Upper)	20	B, C	2(105)
PT1.5 f/b by /1 or /2 digit No., may be f/b suffix -5.0, and by -H or -V or S	26-12	Cu	4.0	300	15(1)	B	2(105)
PT1.5 f/b by /1 or /2 digit No., by suffix -PVH may be f/b -5.0	26-12	Cu	4.0	300	1591)	B, D	2(105)
PTA1.5/X-3.5, w/wo -PIN3.5	26-16	Cu	2.2	300	10	B	2(105)
	26-16	Cu	2.2	300	10	D	2(105)
PTA1.5/X-5.0, w/wo -PIN3.5	26-12	Cu	4.0	300	15	B	2(105)
	26-12	Cu	4.0	300	16	B	2(105)
	26-12	Cu	4.0	300	10	D	2(105)
PST1.3 f/b /1 or /2 digit No., may be f/b -5.0	—	Cu	N/A	300	16	B, D	2(105)
PST1.3/X-5.0-SF	—	—	N/A	300	7	B, D	2(115)
PTDA 2.5/X-5.0	24-12 Str	Cu	N/A	300	20	B	2(105)
	24-14 Sol	Cu	N/A	300	15	B	2(105)
	24-12 Str 24-14 Sol	Cu	N/A	300	10	D	2(105)
	24-12 Str 24-14 Sol	Cu	N/A	150	15	D	2(105)
PTDA 2.5/X-5.0-RZ	24-12 Str	Cu	N/A	300	20	B	2(105)
	24-14 Sol	Cu	N/A	300	15	B	2(105)
	24-12 Str 24-14 Sol	Cu	N/A	300	15	C	2(105)

	24-12 Str 24-14 Sol	Cu	N/A	600	5	D	2(105)
PTDA 2.5/X-PH-5.0, w/wo RT, w/wo RTGY7038NZ	24-14	Cu	N/A	300	13.5	B	2(105)
	24-14	Cu	N/A	300	10	D	2(105)
PTDA 2.5/X-PH-5.0, w/wo RT, f/b -RZ	24-14	Cu	N/A	300	13.5	B	2(105)
	24-14	Cu	N/A	150	13.5	C	2(105)
	24-14	Cu	N/A	300	10	D	2(105)
PT1.5/X-3.5-H, -V	26-16	Cu	2.2	300	10	B, D	2(105)
PT1.5/X-PH-3.5	26-16	Cu	2.2	300	10	B, D	2(105)
PT1.5/X-PH-3.5-A	26-16	Cu	2.2	300	10	B, D	2(105)
PT1.5/X-PVH-3.5	26-16	Cu	2.2	300	10	B, D	2(105)
PT1.5/X-PVH-3.5-A	26-16	Cu	2.2	300	10	B, D	2(105)
PT1.5/X-5.0-H, -V	26-12	Cu	0.45	300	18	B	2(105), 4
	26-12	Cu	0.45	300	10	D	2(105), 4
PT2.5/X-5.0-H, -V, w/wo -S	20-12	Cu	4.4	300	20	B	2(105), 4
	20-12	Cu	4.4	300	10	D	2(105), 4
PT2.5/X-7.5-H, -V, w/wo -S	20-12	Cu	4.4	300	20	B	2(105), 4
	20-12	Cu	4.4	150	20	C	2(105), 4
	20-12	Cu	4.4	300	10	D	2(105), 4
PT2.5/X-PVH-5.0	26-16	Cu	4.4	300	10	B	2(105), 4
	26-16	Cu	4.4	300	10	D	2(105), 4
PST1.0/X- w/wo -H, may be f/b -3.5, f/b H, L	N/A	Cu	N/A	300	10	B, D	2(105)
PSTD1.3/X w/wo -H, may be f/b -5.0, may be f/b H, L	N/A	Cu	N/A	300	16 10	B D	2(105),4
PSTD1.0/X(1)	—	Cu	—	300	10	B,D	2(105)
PSTT1.3/X w/wo -H, f/b L, H (2)	N/A	Cu	N/A	300	16 10	B D	2(105), 4
PSTT1.0/X(1)	—	Cu	—	300	10	B, D	2(105)
PT1.5/X-PH-5.0 w/wo CLIP	28-14	Cu	3.1-3.5	300	10	B, D	2(105)
Note: (1) w/wo H, foll. by3.5, and by H, L, or S, and by a 1 or 2-digit no.							
Note: (2) w/wo H, foll. by5.0, and by H, L, or S, and by a 1 or 2-digit no.							
Note: (3) 16A max. for factory wiring only							
Note: (4) 10A max. at 300V for general industrial use							

PTDA1.5 f/b /1 or /2 digit No., by suffix -3.5	24-16	Cu	N/A	300	12,10	B, D	2(105)
PTDA1.5 f/b /1 or /2 digit No., f/b -3.5, f/b -RZ	24-16	Cu	N/A	300	12	B	2(105)
	24-16	Cu	N/A	300	10	D	2(105)
	24-16	Cu	N/A	150	12	C	2(105)
PTDA1.5 f/b /1 or /2 digit No., f/b -PH-3.5, w/wo RT	24-16	Cu	N/A	150	10	B	2(105)
PTDA1.5 f/b /1 or /2 digit No., by suffix -PH-3.5, w/wo -RT, f/b suffix -RZ	24-16	Cu	N/A	300	10	B, D	2(105)
PTS1.5/X-PH-5.0, w/wo CLIP	26-14	Cu	N/A	300	7	B, D	2(115)
UT2.5	26-12(2)	Cu	4-5	600	20	B, C	2(105), 4
UT2.5/1P	26-12(2)	Cu	5-7	300	20	B, C	2(105), 4
UT2.5 f/b -MT, -TG w/wo P/P, TMR	26-12(2)	Cu	4-5	300	16	B, C	2(105), 4
	26-12(2)	Cu	4-5	300	10	D	2(105), 4
UT2.5-MTS-EX	26-12(2)	Cu	4-5	300	16	B, C	2(105), 4
	26-12(2)	Cu	4-5	300	10	D	2(105), 4
UT2.5 -HESI w/wo -EX (5X20)	26-12(2)	Cu	4-5	300	10	B, C	2(105), 4
UT2.5 f/b -TG(#) w/wo P/P	26-12(2)	Cu	4-5	300	10	B, C	2(105), 4
UT2.5-MTD	26-12(2)	Cu	4-5	600	20	B, C	2(105), 4
UT2.5-MTD P/P	26-12(2)	Cu	4-5	300	20	B, C	2(105), 4
	26-12(2)	Cu	4-5	600	5	D	2(105), 4
UT2.5-MTD-DIO f/b /L-R, /R-L	26-12(2)	Cu	4-5	600	0.5	B, C	2(105), 4
UT2.5-MTD-PE	26-12(2)	Cu	4-5	N/A	N/A	B, C, D	2(105), 4
UT2.5-PE	26-12(2)	Cu	4-5	N/A	N/A	B, C, D	2(105), 4, 6(150x150x120)
UT2.5-QUATTRO	26-12	Cu	4-5	150	20	B, C	2(105), 4
UT2.5-QUATTRO-PE	26-12(2)	Cu	4-5	N/A	N/A	B, C, D	2(105), 4
UT2.5-TWIN	26-12(2)	Cu	4-5	150	20	B, C	2(105), 4
UT2.5-TWIN-PE	26-12(2)	Cu	4-5	N/A	N/A	B, C, D	2(105), 4
UT2.5-TWIN/1P	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)	Cu	4-5	150	20	C	2(105), 4
	26-12(2)	Cu	4-5	300	10	D	2(105), 4

UT2.5-TWIN/1P-PE	26-12(2)	Cu	4-5	N/A	N/A	B, C, D	2(105), 4
UT2.5-3L	26-12	Cu	4-5	300 600	20 5	B, C D	2(105), 4
UT2.5-3PV	26-12	Cu	4-5	300	20	B,C	2(105), 4
UT10-PE/S	20-6	Cu	13-15	N/A	N/A	B, C	2(105)
UT2.5-3L-LA24RD-O-M	26-12	Cu	4-5	300 600	20 5	B, C D	2(105), 4
UT2.5-3PE	26-12	Cu	4-5	N/A	N/A	B, C, D	2(105), 4
UT2.5-PE/L/L Grounding Level	26-12	Cu	4-5	300	20	B, C, D	2(105), 4
				600	5	D	
				N/A	N/A		
UT2.5-PE/L/N Grounding Level	26-12	Cu	4-5	300 600 N/A	20 5 N/A	B, C D	2(105), 4
UTI 2.5-L	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)			300	10	D	
UTI 2.5-L/LB	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)			300	10	D	
UTI 2.5 L/L, UTI 2.5 L/N	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)			300	10	D	
UTI 2.5-PE/L/NT	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)			300	10	D	
	26-12(2)			N/A	N/A	B, C, D	
UTI 2.5-PE/L/L UTI 2.5-PE/L/N	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)			300	10	D	
	26-12(2)			N/A	N/A	B, C, D	
UTI 2.5-PE/L/NTB	26-12(2)	Cu	4-5	300	20	B	2(105), 4
	26-12(2)			300	10	D	
	26-12(2)			N/A	N/A	B, C, D	
UTTB2.5 f/b -BE, - DIO/O-U,-DIO/U-O, - L/N, -LA230,-LA 24 RD, -LA 60 RD, -PV	26-12(2)	Cu	4-5	300	20	B, C	2(105), 4
		Cu	4-5	600	5	D	2(105), 4
UTTB2.5-DIO/UL-UR	26-12	Cu	4-5	300	20	B, C	2(105), 4
		Cu	4-5	600	5	D	2(105), 4
	26-12	Cu	4-5	300	0.5diodelevel	B, C	2(105), 4
		Cu	4-5	600	0.5diodelevel	D	2(105), 4
UTTB2.5-PE (/L, /N)	26-12	Cu	4-5	N/A	N/A	B, C, D	2(105), 4

UTTB2.5-2DIO/O-UL/O-UR	26-12	Cu	4-5	300	20	B, C	2(105), 4
		Cu	4-5	600	5	D	2(105), 4
UTTB2.5-2DIO/O-UL/UR-UL	26-12	Cu	4-5	300	20	B, C	2(105), 4
		Cu	4-5	600	5	D	2(105), 4
	26-12	Cu	4-5	300	0.5diodelevel	B, C	2(105), 4
		Cu	4-5	600	0.5diodelevel	D	2(105), 4
UTTB2.5/2P w/wo -PV	26-12(2)	Cu	4-5	300	20	B, C	2(105), 4
	26-12	Cu	4-5	600	5	D	2(105), 4
UTTB2.5/2P-PE	26-12(2)	Cu	4-5	N/A	N/A	B, C, D	2(105), 4
UPBV2.5 f/b /1-L, /1-M,/1-R, /X	26-12(2)	Cu	4-5	600	20	B, C	2(105), 4
	26-12(2)	Cu	4-5	600	5	D	2(105), 4
UT4	26-10(3)	Cu	5-7	600	30(1)	B, C	2(105), 4
UT4-CB	26-10(3)	Cu	5-7	300	30	B, C	2(105), 4
UT4-HEDI	26-10(3)	Cu	5-7	600	16	B, C	2(105), 4
UT4-HEDI-EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HEDI-P/P	26-10	Cu	5-7	600	16	B, C	2(105), 4
UT4-HEDI-P/P-EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESI (5X20)	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESI (5X20)-EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESILED24 (5X20)	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT 4-HESILED 24 (5X20) w/wo -EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT 4-HESILED 24 (5X20) 120KOHM w/wo -EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT 4-HESILED 24 (5X20) 820KOHM w/wo -EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT 4-HESILED 24-P/P w/wo -EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESILED60 (5X20)	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESILED60 (5X20)-EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESILA or HESILED 250 (5X20)	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
UT4-HESILA or HESILED 250 (5X20)-EX	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4

UT4-MT, UT4-MTL	26-10(3)	Cu	5-7	600	16	B, C	2(105), 4
UT4-MT-P/P, UT4-MTL-P/P	26-10(3)	Cu	5-7	300	16	B, C	2(105), 4
UT4-MTD	26-10(3)	Cu	5-7	600	30(1)	B, C	2(105), 4
UTMED4-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C	2(105), 4
UT4-MTD-DIO/L-R	26-10(3)	Cu	5-7	600	0.5	B, C	2(105), 4
UT4-MTD-DIO/L-R-P/P	26-10(3)	Cu	5-7	300	0.5	B, C	2(105), 4
UT4-MTD-DIO/R-L	26-10(3)	Cu	5-7	600	0.5	B, C	2(105), 4
UT4-MTD-DIO/R-L-P/P	26-10(3)	Cu	5-7	300	0.5	B, C	2(105), 4
UT4-MTD-BE	26-10(3)	Cu	5-7	300	0.5	B, C	2(105)
UT4-MTD-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4-MTD-PE/S	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UTMED4-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4-TWIN	26-10(3)	Cu	5-7	300	30	B, C	2(105), 4
UT4-TWIN-HV	26-10(3)	Cu	5-7	600	30	B, C	2(105), 4
UT4-QUATTRO-HV	26-10(3)	Cu	5-7	600	30	B, C	2(105)
UT4-TWIN f/b -MT, -TGw/wo P/P	26-10(3)	Cu	5-7	300	20	B	2(105), 4
	26-10(3)	Cu	5-7	150	20	C	2(105), 4
	26-10(3)	Cu	5-7	300	10	D	2(105), 4
UT4-TWIN f/b -TG (#) w/wo P/P	26-10(3)	Cu	5-7	300	10	B, C	2(105), 4
UT4-TWIN-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4-TWIN/1P	26-10(3)	Cu	5-7	300	30	B, C	2(105), 4
	26-10(3)	Cu	5-7	300	10	D	2(105), 4
UT4-TWIN/1P-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4/1P w/wo-H	26-10(3)	Cu	5-7	600	30	B, C	2(105), 4
UT4/1P w/wo-H f/b -PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/L-DIO/L-R P/P, UT 4-PE/L-DIO/R-L P/P	26-10(3)	Cu	5-7	600	0.5	B,C	2(105), 4
	26-10	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/MT P/P	26-10(3)	Cu	5-7	600	16	B, C	2(105), 4
	26-10	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/TG P/P	26-10(3)	Cu	5-7	600	16	B, C	2(105), 4
	26-10	Cu	5-7	N/A	N/A	B, C, D	2(105), 4

UT4-QUATTRO	26-10(3)	Cu	5-7	300	30	B, C	2(105), 4
UT4-QUATTRO f/b - MT, -TG w/wo P/P	26-10(3)	Cu	5-7	300	16	B	2(105), 4
	26-10(3)	Cu	5-7	150	16	C	2(105), 4
	26-10(3)	Cu	5-7	300	10	D	2(105), 4
UT4-QUATTRO f/b - MTL	26-10(3)	Cu	5-7	300	16	B	2(105), 4
	26-10(3)	Cu	5-7	150	16	C	2(105), 4
	26-10(3)	Cu	5-7	300	10	D	2(105), 4
UT4-QUATTRO f/b - TG (#) w/wo P/P	26-10(3)	Cu	5-7	300	10	B, C	2(105), 4
UT4-QUATTRO-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4-QUATTRO/2P	26-10(3)	Cu	5-7	300	30	B	2(105), 4
	26-10(3)	Cu	5-7	150	30	C	2(105), 4
	26-10(3)	Cu	5-7	300	10	D	2(105), 4
UT4-QUATTRO/2P-PE	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT4-TG w/wo P/P	26-10	Cu	5-7	600	16	B, C	2(105), 4
UT4-TG(#) w/wo P/P	26-10	Cu	5-7	300	10	B, C	2(105), 4
UT 4-PE/HEDI	26-10	Cu	5-7	600	16	B, C	2(105), 4
	26-10	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/HESI w/wo LED 24, LED 60, LA 250 f/b (5x20)	26-10(3)	Cu	5-7	600	10	B, C	2(105), 4
	26-10	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UTTB4 (-PV) (-L/N)	26-10(3)	Cu	5-7	300	30	B, C	2(105), 4
UTTB4 -HV	26-10(3)	Cu	5-7	600	30	B, C	2(105), 4
UTTB4-MT (P/P)	26-10(3)	Cu	5-7	300	30(6)	B, C	2(105), 4
	26-10(3)	Cu	5-7	600	5	D	2(105), 4
UTTB4-MT-P/P-LA24RD/O-U	26-10(3)	Cu	5-7	300	30(6)	B, C	2(105), 4
	26-10(3)	Cu	5-7	600	5	D	2(105), 4
UTTB4-PE (/L, /N)	26-10(3)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UTTB4-HV	26-10(3)	Cu	5-7	600	30	B, C, D	2(105), 4
UTTB4-TG (P/P)	26-10(3)	Cu	5-7	300	30(6)	B, C	2(105), 4
	26-10(3)	Cu	5-7	600	5	D	2(105), 4
UTTB4-TG(#) (P/P)	26-10(3)	Cu	5-7	300	10	B, C	2(105), 4
UT6 f/b -TG (#)	24-8(4)	Cu	13-15	300	10	B, C	2(105), 4
UP4 f/b /1-L, /1-M, /1-R, /X	26-10(3)	Cu	5-7	600	30	B, C	2(105), 4
UPBV4 f/b /1-L, /1-M, /1-R/X	26-10(3)	Cu	5-7	600	30	B, C	2(105), 4

UT2.5/1P-PE	26-12(2)	Cu	5-7	N/A	N/A	B, C, D	2(105), 4
UT6	24-8(4)	Cu	13-15	600	50	B, C	2(105), 4
UT6-HESI (6.3x32)	24-8	Cu	13-15	600	10(5)	B, C	2(105), 4
UT6-HESILA250 (6.3x32)	24-8	Cu	13-15	600	10(5)	B, C	2(105), 4
UT6-HESILED24 (6.3x32)	24-8	Cu	13-15	600	10(5)	B, C	2(105), 4
UT6-HESILED60 (6.3x32)	24-8	Cu	13-15	600	10(5)	B, C	2(105), 4
UT6 f/b -MT, MTL	24-8(4)	Cu	13-15	300	16	B, C	2(105), 4
	24-8(4)	Cu	13-15	600	5	D	2(105), 4
UT6-MT P/P, UT6-MTL P/P, UT6-TG P/P	24-8(4)	Cu	13-15	300	20	B, C	2(105), 4
	24-8(4)	Cu	13-15	600	5	D	2(105), 4
UT6-TG(#) P/P	24-8(4)	Cu	13-15	300	10	B, C	2(105), 4
UT6-PE	24-8(4)	Cu	13-15	N/A	N/A	B, C, D	2(105), 4
UT6-3L	24-8	Cu	1.5-1.8 Nm	600	40	B, C	2(105), 4
UTME6, UTMED6	24-8(4)	Cu	13-15	300	30	B, C	2(105), 4
	24-8(4)	Cu	13-15	600	5	D	2(105), 4
UTMED6-PE	24-8(4)	Cu	13-15	N/A	N/A	B, C, D	2(105), 4
UT10	20-6	Cu	13-15	600	65	B, C	2(105), 4
UT10-PE	20-6	Cu	13-15	N/A	N/A	B, C, D	2(105), 4
UT16	16-4(7)	Cu	2.3-3	600	85	B, C	2(105), 4
UT16-PE	16-4	Cu	2.3-3	N/A	N/A	B, C, D	2(105), 4
UT35	14-1/0(8)	Cu	3.2-3.7	600 1000	150	B, C	2(105), 4, 6(150x150x120)
UT35 IB	14-1/0	Cu	3.2-3.7	600	150	B	2(105), 4
		Cu	53-70	1000	150	C	2(105), 4
UT35-E/NS 35N	14-1/0	Cu	53-70	600 1000	150	B, C	2(105)
UT35-PE, UT35-PE IB	14-2	Cu	3.2-3.7	N/A	N/A	B, C	2(105),4
AGK4-UT10	26-10	Cu	5-7	600	30	B, C	2(105), 4
AGK4-UT16	26-10	Cu	5-7	600	30	B, C	2(105), 4
AGK4-UT35	26-10	Cu	5-7	600	30	B, C	2(105), 4
UTME4, UTME4 P/P	26-10	Cu	5-7	300, 600	25, 5	B, C D	2(105), 4
UTME4/1P	26-10	Cu	5-7	300, 600	25, 5	B, C D	2(105), 4

UTME4-CT/1P	26-10	Cu	5-7	300, 600	25, 5	B, C D	2(105), 4
UTMED4	26-10	Cu	5-7	300, 600	30, 5	B, C D	2(105), 4
UPCT4/2,UPCT4/3	26-10, 2# 26-12	Cu	5-7	300	25, 10	B, D	2(105), 4
UT 4-PE/L/L	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(middle) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/L/N	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(middle) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/L/MT	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(middle) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/L/TG	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(middle) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/L/HESI w/wo LED 24, LED 60, LED 250 f/b (5x20) w/wo 120KOHM	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(middle) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	N/A	N/A	B, C, D	2(105), 4
UT 4-PE/L/HEDI	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(middle) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	N/A	N/A	B, C, D	2(105), 4
UT 4-L/HESI (5x20) w/wo 120KOHM, UT 4-L/HESI LED 24 (5X20) w/wo 120KOHM , UT 4- L/HESI LED 60 (5X20) w/wo 120KOHM, UT 4-L/HESI 250 (5X20) w/wo 120KOHM, UT 4- L/HESI LED 250 (5X20) w/wo 120KOHM	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
UT 4-L/HEDI	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
UT 4-L	26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
UT 4-L/L	(upper) 26-10	Cu	0.6-0.8	300	16	B, C	2(105), 4
	(lower) 26-10	Cu	0.6-0.8	300	20	B, C	2(105), 4

UTT 2.5 f/b -2MT-P/P, -2TG-P/P	(upper) 26-12	Cu	0.5-0.6	300	16	B, C	2(105), 4
	(lower) 26-12	Cu	0.5-0.6	300	20	B, C	2(105), 4
UTTB 2.5 f/b -MT-P/P, -TG-P/P (6)	(upper) 26-12	Cu	0.5-0.6	300	16	B, C	2(105), 4
	(lower) 26-12	Cu	0.5-0.6	300	20	B, C	2(105), 4
Note: (@) 1 Amp field wiring, 2 Amp factory wiring.							
Note: (@@) 5 Amp field wiring, 6 Amp factory wiring.							
Note: (1) 40A max. for factory wiring							
Note: (2) Additional multiple wire combination rating of two No. 16-26 AWG Cu. str. wires (same size only) for field and factory wiring.							
Note: (3) Additional multiple wire combination rating of two No. 14-26 AWG Cu. str. wires (same size only) for field and factory wiring.							
Note: (4) Additional multiple wire combination rating of two No. 12-24 AWG Cu. str. wires (same size only) for field and factory wiring.							
Note: (5) 16A max. when used as a disconnect block (no fuse).							
Note: (6) 16A Current rating for disconnect upper level for Cat. Nos. UTTB4-TG (P/P), UTTB4-MT (P/P), UTTB4-MTP/PLA24RD/O-U, UTTB 2.5 f/b -MT-P/P, -TG-P/P.							
Note: (7) Additional multiple wire combination rating of four No. 14 AWG Cu. stranded wires for field and factory wiring.							
Note: (8) Additional multiple wire combination rating of six No. 14 AWG Cu. stranded wires for field and factory wiring.							
Note: (9) These Cat. Nos. have selected terminals approved as Protective Conductor Terminal Block which are marked accordingly. For these terminals the current and voltage ratings shall not be assigned. Remaining terminals have assigned electrical ratings, as specified.							
Note: (10) These Cat. Nos. have the bus bar terminals at the upper row. When these terminals are in open position, and not connected through the bus bars, the voltage rating for the upper row is 300V for Usage Group B only.							
Note: (11) These Cat. Nos. have the bus bar terminals at the upper row. When these terminals are in open position, and connected through the bus bars, the electrical rating for the upper row is 600V and 5A for Usage Group D.							
Note: (#) Cat. Nos. with Suffix -TG followed by Suffixes P-FU 5X20 followed by -5, LED 24-5, LED 60-5 or LED 250-5; Suffixes FP (5X20) with or without 24, 60, or 250. Cat. No. UT6-TG may be followed by P-FU 6.3X32, P-FU 6.3X32 LED 24, P-FU 6.3X32 LED 60, P-FU 6.3X32 LA 250							
DFK-PC16 f/b /1 or 2 digit No., -ST, -STF, -STF-SH, -STGF, -STGF-SH, -10.16 w/wo Suffix -EF and/or -RAE w/wo Suffix -EF and/or -RAE	20-6	Cu	15	600	55	B, C	2(120)
PC16 f/b /1 or 2 digit No., -ST, -STF, -STF-SH, -STGF, -STGF-SH, -STTL, -STFGP, -10.16, w/wo -RAE	20-6	Cu	15	600	55	B, C	2(120)
IPC16, DFK-IPC16 followed. by/1 or 2 digit No., -ST, -STF, -STF-SH, -STGF, -STGF-SH, -STFGP, -10.16w/wo -RAE	20-6	Cu	15	600	55	B, C	2(120)
PC6-16, DFK-PC6-16 f/b /1 or 2 digit No., -G, -G1, -GU, -G1U, -	N/A	Cu	N/A	300	66	B	2(120)
	N/A		N/A	300	66	C	

GF, -G1F, -GFU, -G1FU, w/wo -SH, and -10.16 w/wo-RAE							
	N/A		N/A	600	5	D	
PCV6-16, DFK-PCV6-16 f/b /1 or 2 digit No., -G, -G1, -GU, -G1U, -GF, -G1F, -GFU, -G1FU, w/wo -SH, and -10.16	N/A	Cu	N/A	300	66	B	2(120)
	N/A		N/A	300	66	C	
	N/A		N/A	600	5	D	
DFK-IPC16 f/b /1 or 2 digit No., -G, -GU, -GF, -GFU, w/wo -SH, and -10.16	N/A	Cu	N/A	300	55	B	2(120)
	N/A		N/A	300	55	C	
	N/A		N/A	600	5	D	
IPC16, IPCV16 f/b /1 or 2 digit No., by -G, -GF, -GU, -GFU	N/A	Cu	N/A	300	66	B	2(120)
	N/A		N/A	300	66	C	
	N/A		N/A	600	5	D	
DFK-IPCV16 f/b /1 or 2 digit No., -G, -GU, -GF, -GFU, w/wo -SH, and -10.16	N/A	Cu	N/A	300	55	B	2(120)
	N/A		N/A	300	55	C	
	N/A		N/A	600	5	D	
SPC16 followed by /one or two digit number, followed by Suffixes -ST, -STF, -STF-SH, or -STTL followed by -10.16	20-4	Cu	N/A	600	66	—	2(105)
ISPC16 followed by /one or two digit number, followed by Suffixes -ST, -STF or -STF-SH, followed by -10.16	20-4	Cu	N/A	600	66	—	2(105)
TPC16, followed by /one or two digit number, followed by -ST, -STF followed by -10.16	20-4	Cu	15	600	60	B, C, D	2(105)
QTC1.5, -MT, -TG, -QUATTRO, -TWIN, /1P	24-16	Cu	N/A	600	10	B, C	2(120)
QTC1.5-TG(#), /1P	24-16	Cu	N/A	300	10	B, C	2(120)
QTTCB1.5, -DIO/O-U, -PV, /2P, /2P-PV	24-16	Cu	N/A	600	10	B, C	2(120)
QTC1.5-PE, -QUATTRO-PE, -TWIN-PE, /1P-PE	24-16	Cu	N/A	N/A	N/A	B, C	2(120)
QTTCB1.5PE, QTTCB1.5/2P-PE	24-16	Cu	N/A	N/A	N/A	B, C	2(120)
QTC2.5, QTC2.5-TWIN	20-14	Cu	N/A	600	15	B, C	2(105)

QTC2.5-PE, QTC2.5-TWIN-PE	20-14	Cu	N/A	N/A	N/A	B, C	2(105)
QTC2.5-HESI (5X20), -HESILED 24, -HESILED 60, -HESILA OR HESILED 250	20-14	Cu	N/A	300	15	B, C	2(105)
QTC2.5-HEDI, -MT, -TG	20-14	Cu	N/A	300	15	B, C	2(105)
QTC2.5-TG(#)	20-14	Cu	N/A	300	10	B, C	2(105)
QP1.5 w/wo Suffixes/1-L, /1-M, /1-R	24-16	Cu	N/A	300/600	10/5	B, D	2(105)
QP1.5 f/b /1 or /2 digit No.	24-16	Cu	N/A	300/600	10	B, C	2(105)
Note: (#) Cat. Nos. with Suffix -TG followed by Suffixes P-FU 5X20 and P-FU 6X32 followed by -5, LED 24-5, LED 60-5 or AL 250-5; Suffixes FP (5X20) with or without 24, 60, or 250.							
ABS3/2, ABS3/6	24-14	Cu	4,5-5.3	300	15	B, C	2(105)
QTCS1.5, -BU, -TWIN	Input24-16; Output28-12	Cu	N/A	600	10	B, C	2(105)
QTTCBS1.5-BU, -PV(1)	Input24-16; Output28-12	Cu	N/A	300	10	B, C	2(105)
QTCu1.5-L, -BU, -TWIN(1)	Input 24-16; Output26-12	Cu	5-7	600	10	B, C	2(105)
QTTCBU1.5-BU-TWIN(1)	Input24-16; Output26-12	Cu	5-7	300	10	B, C	2(105)
QTCS1.5-PE	Input 24-16; Output 28-12	Cu	N/A	N/A	N/A	B, C	2(105)
QTCS1.5-TWIN-PE(1)	Input24-16; Output28-12	Cu	N/A	N/A	N/A	B, C	2(105)
QTTCBS1.5-PE	Input 24-16; Output28-12	Cu	N/A	N/A	N/A	B, C	2(105)
QTCu1.5-PE(1)	Input 24-16; Output26-12	Cu	0.6-0.8	N/A	N/A	B, C	2(105)
QTCu1.5-TWIN-PE(1)	Input 24-16; Output26-12	Cu	0.6-0.8	N/A	N/A	B, C	2(105)
QTTCBU1.5-PE	Input 24-16; Output26-12	Cu	0.6-0.8	N/A	N/A	B, C	2(105)
QTCS2.5/X, -BU, -TWIN	20-14 (Input);28-10 (Output)	Cu	N/A	600	15	B, C	2(105)
QCTS2.5-PE, -TWIN-PE	20-14(Input);28-10(Output)	Cu	N/A	N/A	N/A	B, C	2(105)
QTCu2.5/X, -BU, -TWIN(1)	20-14(Input);26-10(Output)	Cu	N/A input 0.6-0.8 output	600	15	B, C	2(105)

QTCU2.5-TWIN-MT (1)	20-14 sol/str (Input); 26-10(1) (output)	Cu	N/A input 0.6-0.8 output	300	15	B, C	2(105)
Note: (1) Multiple wire rating of Two No. 10-20 AWG Cu. same size wires for field and factory wiring.							
QTCu2.5/X-PE, -TWIN-PE	20-14(Input);26-10(Output)	Cu	5-7(Input)N/A(Output)	N/A	N/A	B, C	2(105)
DPB 2.5	24-12	Cu	N/A	300 / 600	20 / 5	B, C, D	2(105), 4
DT2.5/1P	24-12	Cu	N/A	600	20	B, C	2(105), 4
DT2.5/1P-PE	24-12	Cu	N/A	—	—	B, C	2(105), 4
DT2.5	24-12	Cu	N/A	600	20	B, C	2(105), 4
DT2.5-MT	24-12	Cu	N/A	300 / 600	16 / 5	B, C, D	2(105), 4
DT2.5-TG	24-12	Cu	N/A	300 / 600	16 / 5	B, C, D	2(105), 4
DT2.5-PE	24-12	Cu	N/A	—	—	B, C	2(105), 4
DT2.5-TWIN	24-12	Cu	N/A	600	20	B, C	2(105), 4
DT2.5-TWIN-MT	24-12	Cu	N/A	300 / 600	16 / 5	B, C, D	2(105), 4
DT2.5-TWIN-TG	24-12	Cu	N/A	300 / 600	16 / 5	B, C, D	2(105), 4
DT2.5-TWIN-PE	24-12	Cu	N/A	—	—	B, C	2(105), 4
DT2.5-QUATTRO	24-12	Cu	N/A	600	20	B, C	2(105), 4
DT2.5-QUATTRO-MT	24-12	Cu	N/A	300 / 600	16 / 5	B, C, D	2(105), 4
DT2.5-QUATTRO-TG	24-12	Cu	N/A	300 / 600	16 / 5	B, C, D	2(105), 4
DT2.5-QUATTRO-PE	24-12	Cu	N/A	—	—	B, C	2(105), 4
DT2.5-DIO/L-R	24-12	Cu	N/A	600	1	B, C	2(105), 4
DT2.5-DIO/R-L	24-12	Cu	N/A	600	1	B, C	2(105), 4
DT2.5-TWIN-DIO/L-R	24-12	Cu	N/A	600	1	B, C	2(105), 4
DT2.5-TWIN-DIO/R-L	24-12	Cu	N/A	600	1	B, C	2(105), 4
DT2.5-QUATTRO-DIO/L-R	24-12	Cu	N/A	600	1	B, C	2(105), 4
DT2.5-QUATTRO-DIO/R-L	24-12	Cu	N/A	600	1	B, C	2(105), 4
DT6/2.5-DREHSI (5x20)	20-8 Input; 24-12Output	Cu	—	600	10	B, C	2(105)
DT6/2.5-DREHSILED 24 (5x20)	2-08 Input; 24-12Output	Cu	—	600	10	B, C	2(105)
DT6/2.5-DREHSILA 250 (5x20)	20-8 Input; 24-12Output	Cu	—	600	10	B, C	2(105)
DTME6	24-8	Cu	—	300 600	30 5	B, C D	2(105)
DTMED6	24-8	Cu	—	600	30	B, C	2(105)

DTMED6-PE	24-8	Cu	—	N/A	N/A	B, C, D	2(105)
PITME6	24-8	Cu	—	300 600	30 5	B, C D	2(105)
PITMED6(@@)	24-8	Cu	—	600	30	B, C	2(105)
PITMED6-PE(@@)	24-8	Cu	—	N/A	N/A	B, C, D	2(105)
SPT1.5/X f/b -H-3.5, -V-3.5	24-16	Cu	N/A	300	10	B	2(105)
	24-16	Cu	N/A	300	10	D	2(105)
SPT-THR1.5/X f/b -H or -V-3.5, -H or -V-3.81	24-16	Cu	N/A	300	10	B	2(105), 4
	24-16	Cu	N/A	300	10	D	2(105), 4
SPT-THR1.5/X f/b -H or -V-5.0,-H or -V-5.08	24-16	Cu	N/A	300	10	B	2(105), 4
	24-16	Cu	N/A	300	10	D	2(105), 4
SPT-THR 2,5/X -H or -V, -5.0	24-12	CU	N/A	300	20	B	2(130),4
	24-12	CU	N/A	300	10	D	2(130),4
SPT-PS1.5/X f/b -H or -V-3.5, -H or -V-3.81	24-16	Cu	N/A	300	10	B	2(130), 4
	24-16	Cu	N/A	300	10	D	2(130), 4
SPT-PS1.5/X f/b -H or -V-5.0,-H or -V-5.08	24-16	Cu	N/A	300	10	B	2(130), 4
	24-16	Cu	N/A	300	10	D	2(130), 4
SPT-SMD1.5/X f/b -H or -V-3.5, -H or -V-3.81	24-16	Cu	N/A	300	10	B	2(105), 4
	24-16	Cu	N/A	300	10	D	2(105), 4
SPT-SMD1.5/X f/b -H or -V-5.0,-H or -V-5.08	24-16	Cu	N/A	300	10	B	2(105), 4
	24-16	Cu	N/A	300	10	D	2(105), 4
SPTS-SMD1.5/X f/b -3,5 f/b -H	24-16	Cu	N/A	300	10	B	2(105), 4
	24-16	Cu	N/A	300	10	D	2(105), 4
SPT2.5/X f/b -H-5.0, -V-5.0	24-12	Cu	N/A	300	20	B	2(105)
				150	20	C	
				150	15	D	
				300	10	D	
SPT5/X f/b -H-7.5, -V-7.5	24-8	Cu	N/A	300	36	B	2(105)
				150	36	C	
				300	10	D	
				600	5	D	
SPT5/X f/b -H-7.5, -V-7.5 f/b -ZB, -Z (3)	24-8	Cu	N/A	600	36	B	2(105)
	24-8	Cu	N/A	600	36	C	2(105)
SPT5/X f/b -V-7.5 f/b -ZM, f/b S-TUB*	24-8	Cu	N/A	300	36	B	2(105),4
	24-8	Cu	N/A	300	10	D	2(105),4
SPTAF 1 /X -3.5, f/b -IL, or EL	24-16	Cu	N/A	300	8	B	2(105),4

	24-16	Cu	N/A	300	8	D	2(105),4
SPTAF 1 /X -3.5, f/b - LL	24-18	Cu	N/A	300	8	B/D	2(105),4
SPTAF 1 /X -5.0, f/b - IL, or EL	24-16	Cu	N/A	300	8	B	2(105),4
	24-16	Cu	N/A	300	8	D	2(105),4
SPTAF 1 /X -5.0, f/b - LL	24-18	Cu	N/A	300	8	B/D	2(105),4
SPTA1/X f/b -3.5 w/wo -W/O T.SKT.	26-16	Cu	N/A	150	10	B	2(105)
	26-16	Cu	N/A	150	10	D	2(105)
SPTA1/X f/b -5,0 w/wo -W/O T.SKT.	26-16	Cu	N/A	300	10	B	2(105)
	26-16	Cu	N/A	300	10	D	2(105)
SPTA1.5/X-3.81	26-16	Cu	N/A	300	10	B	2(105)
SPTA1.5/X-5.08	26-16	Cu	N/A	300	10	B	2(105)
	26-16	Cu	N/A	300	10	D	2(105)
SPT16/X f/b -H-10.0, -V-10.0	20-4	Cu	N/A	300	66	B	2(105)
	20-4	Cu	N/A	300	66	C	2(105)
	20-4	Cu	N/A	300	10	D	2(105)
SPTA 16/X-10.0	18-4	Cu	N/A	300	66	B	2(105), 4
	18-4	Cu	N/A	150	66	C	2(105), 4
	18-4	Cu	N/A	300	10	D	2(105), 4
SPTA 16/X-10.0-CB f/b ZF or ZB	18-4	Cu	N/A	600	51	B, C	2(105), 4
SPTA 16/X-10.0 w/wo -CB f/b ZM	18-4	Cu	N/A	150	51	B, C	2(105), 4
SPTA 16/X -10.0-ZB, SPTA 16/X -10.0-ZF	18-4	Cu	N/A	600	51	B	2(105), 4
	18-4	Cu	N/A	600	51	C	2(105), 4
SPTA 16X -15.0-ZB f/b CB	18-4	Cu	N/A	600	51	B	2(105), 4
	18-4	Cu	N/A	600	51	C	2(105), 4
	18-4	Cu	N/A	1000	51	E	2(105), 4
SPTA 16/X-15.0-CB f/b ZF or ZB	18-4	Cu	N/A	600	51	B, C	2(105), 4
				1000	51	E	2(105), 4
SPTA 16/X-15.0 w/wo -CB f/b ZM	18-4	Cu	N/A	150	51	B, C	2(105), 4
SPT 16/X-H-10.0 f/b - ZB or -ZF, SPT 16/X-V-10.0 f/b -ZB, -ZF f/b PIN 4,6	20-4	Cu	N/A	600	66	B	2(105)
	20-4	Cu	N/A	600	66	C	2(105)
SPT 35/X-V-15.0	14-2	Cu	N/A	600	101	B	2(105), 4

	14-2	Cu	N/A	600	101	C	2(105), 4
	14-2	Cu	N/A	300	10	D	2(105), 4
SPT 35/X-V-15.0-Z	14-2	Cu	N/A	600	101	B	2(105), 4
SPT 35/X-V-15.0-F-Z	14-2	Cu	N/A	600	101	C	2(105), 4
SPTA5/X f/b -H-7.5, -V-7.5	24-8	Cu	N/A	150	35	B	2(105), 4
	24-8	Cu	N/A	150	35	C	2(105), 4
SPTA5/X f/b -H-7.5, -V-7.5 f/b -ZB, -ZF	24-8	Cu	N/A	600	33	B	2(105), 4
	24-8	Cu	N/A	600	33	C	2(105), 4
SPTD 1.5 followed by /one or digit number; followed by suffix -H, -HP, or -V; followed by suffix -3.5.	26-14	Cu	N/A	150	10	B	2(105), 4
RT 3	N/A	Cu	5-7	600	30	B, C	2(105)
RT 5	N/A	Cu	20-25	600	30	B, C	2(105)
RT 5-T	N/A	Cu	20-25 (2)	600	30	B, C	2(105)
RT 8	N/A	Cu	40-45	600	130	B, C	2(105)
RT 3-PE	N/A	Cu	5-7	N/A	N/A	B, C	2(105)
RT 5-PE	N/A	Cu	20-25	N/A	N/A	B, C	2(105)
RTO 3	N/A	Cu	5-7	600	30	B, C	2(105)
RTO 5	N/A	Cu	20-25	600	30	B, C	2(105)
RTO 5-T, RTO 5-T-TC	N/A	Cu	20-25 (2)	600	30	B, C	2(105)
RTO 8	N/A	Cu	40-45	600	130	B, C	2(105)
RTO 3-PE	N/A	Cu	5-7	N/A	N/A	B, C	2(105)
RT0 5-PE	N/A	Cu	20-25	N/A	N/A	B, C	2(105)
STIO2.5/3-2B/L	28-12	Cu	N/A	150	18	C	2(105)
		Cu	N/A	300	10	B, D	2(105)
STIO2.5/3-2B/L-LA24-RD (GN)/O-M	28-12	Cu	N/A	150	18	C	2(105)
		Cu	N/A	300	10	B, D	2(105)
STIO2.5/3-PE/B/L	28-12	Cu	N/A	150(3)	18(3)	C	2(105)
		Cu	N/A	300(3)	10(3)	B, D	2(105)
STIO2.5/3-PE/B/L-LA24-RD (GN)/O-M	28-12	Cu	N/A	150(3)	18(3)	C	2(105)
		Cu	N/A	300(3)	10(3)	B, D	2(105)
STIO2.5/3-PE/B/L-DIO/M-O	28-12	Cu	N/A	150(3)	18(3)	C	2(105)
		Cu	N/A	300(3)	10(3)	B, D	2(105)
STIO2.5/4-3B/L	28-12	Cu	N/A	150	18	C	2(105)

		Cu	N/A	300	10	B, D	2(105)
STIO2.5/4-3B/L-LA24-RD (GN)/O-M	28-12	Cu	N/A	150	18	C	2(105)
		Cu	N/A	300	10	B, D	2(105)
STIO2.5/4-PE/2B/L	28-12	Cu	N/A	150(3)	18(3)	C	2(105)
		Cu	N/A	300(3)	10(3)	B, D	2(105)
STIO2.5/4-PE/2B/L-LA24-RD (GN)/O-M	28-12	Cu	N/A	150(3)	18(3)	C	2(105)
		Cu	N/A	300(3)	10(3)	B, D	2(105)
STIO-IN2.5/3 OG	28-12	Cu	N/A	150	20	C	2(105)
		Cu	N/A	300	10	B, D	2(105)
STIO-IN2.5/3-PE OG	28-12	Cu	N/A	150(3)	20(3)	C	2(105)
		Cu	N/A	300(3)	10(3)	B, D	2(105)
STIO-IN2.5/4 OG	28-12	Cu	N/A	150	20	C	2(105)
		Cu	N/A	300	10	B, D	2(105)
STIO-IN2.5/4-PE OG	28-12	Cu	N/A	150(3)	20(3)	C	2(105)
		Cu	N/A	300(1)	10(3)	B, D	2(105)
RSC 4 may be followed by a one or two digit number	N/A	Cu	10-12	600	30	B, C	2(105)
RSC 4 -F, or -E, may be followed by a one or two digit number	N/A	Cu	10-12	600	30	B, C	2(105)
RSC 4 -SP/SP E, may be followed by a one or two digit number	N/A	Cu	10-12	600	30	B, C	2(105)
RSC 5 w/wo E may be followed by a one or two digit number	N/A	Cu	18-20	600	45	B, C	2(105)
RSC 5-F w/wo E may be followed by a one or two digit number	N/A	Cu	18-20	600	45	B, C	2(105)
RSC 5 -SP/SP E may be followed by a one or two digit number	N/A	Cu	18-20	600	45	B, C	2(105)
RSC 5-T w/wo E may be followed by a one or two digit number	N/A	Cu	18-20(1)	600	45	B, C	2(105)
RSC 5-T-F w/wo E may be followed by a one or two digit number	N/A	Cu	18-20(1)	600	45	B, C	2(105)
RBO 5 w/wo E may be followed by a one or two digit number	N/A	Cu	18-20	600	45	B, C	2(105)

RBO 5-F w/wo E may be followed by a one or two digit number	N/A	Cu	18-20	600	45	B, C	2(105)
RBO 5 w/wo Suffix SP/SP E may be followed by a one or two digit number	N/A	Cu	18-20	600	45	B, C	2(105)
RBO 5-T w/wo E may be followed by a one or two digit number	N/A	Cu	18-20(1)	600	45	B, C	2(105)
RBO 5-T-F w/wo E may be followed by a one or two digit number	N/A	Cu	18-20(1)	600	45	B, C	2(105)
RBO 8, may be followed by a one or two digit No.	N/A	Cu	15-20	600	175	B, C	2(105),5
RBO 8, may be followed by -WD, may be followed by a one or two digit No.	N/A	Cu	15-20	1000	175	C	2(105),5
RBO5 w/wo Suffix -T-B-HEX followed by a one or two digit number	N/A	Cu	28-33	600	41	B, C	2(105), 4
RBO6 w/wo Suffix -E, -F, or -F-E, may be followed by a -one or -2 digit number may be followed by -WD.	N/A	Cu	28-33	600	115	B, C	2(105), 4
RSC6 w/wo Suffix -E, -F, or -F-E followed by a one or two digit number	N/A	Cu	28-33	600	115	B, C	2(105), 4
PC35HC/X-STF-15.00, PC35HC/X-STF-SH-15.00	4-2 6-10 12-16	Cu	44 30 22	600	115	B, C	2(120), 4
PC35HC/X-GF-15.00, PC35HC/X-GF-SH-15.00	N/A	Cu	N/A	600	115	B, C	2(130)
PCV35HC/X-GF-15.00, PCV35HC/X-GF-SH-15.00	N/A	Cu	N/A	600	115	B, C	2(130)
Note: (1) May be followed by /one or two digit number; followed by suffix -3.5 or -5.0; may be followed by suffix -W/O T.SKT.							
Note: (2) Screw torque for disconnect is 13-16 in-lbs.							
Note: (3) SPT5 vertical type may be followed by suffix S-TUB							
STU 10/4x2.5	Input 20-8 Output 28-12	Cu	13-16	600	Input 50A, Output20A/pole, 50A max total	B, C	2(105), 6(150x150x120)

PTSM 0.5, f/b /one or /two digit number, and by suffixes -P, and 2.5, may be followed by suffix -PI, -PL , may be followed by suffix WH or BK	26-20	Cu	N/A	150	6 (5A for -PI and -PL suffixes)	B	2(105), 4
PTCM 0.5 followed by /one or two digit number followed by suffix -PL followed by suffix -2.5	22-18 str	Cu	N/A	150	6(3)	B, D	2(105)
PTCM 0.5 followed by /one or two digit number followed by suffix -P followed by suffix -2.5	22-18 str	Cu	N/A	150	6(3)	B, D	2(105)
PTCM 0.5 followed by /one or two digit number followed by suffix -PI followed by suffix -2.5	22-18 str	Cu	N/A	150	5(4)	B, D	2(105)
PTPM 0.2, f/b /one or /two digit number; f/b Suffix -P-2.5; may be f/b Suffix AU. PTPM 0.2, PTPM 0.4 f/b /one or /two digit number, f/b -P-2.5 PA CAT5	26(1)	Cu	N/A	50	2	B, D	2(105)
PTPM 0.4, f/b /one or /two digit number; f/b Suffix -P-2.5; may be f/b Suffix AU. PTPM 0.2, PTPM 0.4 f/b /one or /two digit number, f/b -P-2.5 PA CAT5	24-22(1)	Cu	N/A	50	3	B, D	2(105)
PTSM 0.5 followed by /one or /two digit number; followed by -HH, -HH0, -HH1, -HHI, -HHI0, -HHI1, -HVO, HTB, or -HV; followed -2.5; followed by -THR or -SMD; may be followed by WH or BK, may be followed by R.	—	—	N/A	150	6	B	2(105)
PTQ 0.3/2 f/b -2.5, may be f/b -L, f/b THR, f/b R	24(2) str only	Cu	N/A	150	2	B	2(105)
ICC20-H/3L5.0, ICC20-H/3R5.0, ICC25-H/4L5.0, ICC25-H/4R5.0. (5)	N/A	N/A	N/A	300	16	B	2(115),4
	N/A	N/A	N/A	150	15(6)	D	2(115),4
	N/A	N/A	N/A	300	10(6)	D	2(115),4

Note: (1) - Type Wiring - R/C Appliance Wiring Material (AVLV2), Style 20276 multi-conductor cable. Individual conductors have approximately 0.006 in. thermoplastic insulation.

Note: (2) - Type Wiring - R/C Appliance Wiring Material (AVLV2), Style 1061, approximately 0.009 in. SRPVC Insulated Wire.

Note: (3) - Current rating only with header cat. no. PTSM0.5/-HH/HV/HTB/PI-2,5-THR/SMD.

Note: (4) - Current rating only with header cat. no. PTSM0.5/-PL/-HHI-2.5.

Note: (5) - Types ICC20 and ICC25 covered by this Report are multi pole Terminal Blocks Headers intended for use with Terminal Block Plug Model MSTBT 2.5HC and PSPT 2.5 that are manufactured by Phoenix Contact GmbH & Co Kg and recognized under File No. E60425, Volume 1, Section 60. The ratings shall be adjusted to the plugs ratings.

Note: (6) - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.

PTSA1.5 followed by /1 or /2 digit number, by Suffix -3.5, and by -F or -Z, may be followed by HT.	24-16	Cu	N/A	300	5	B, D	2(105)
PTSA0.5 followed by /1 or /2 digit number, by Suffix -2.5, and by -F or -Z, may be followed by HT.	26-20	Cu	N/A	300	1	B, D	2(105)
PTSM0.5 followed by /1 or /2 digit number, followed by -2.5, followed by -H or -V, followed by THR or SMD, may be followed by WH or BK, may be followed by L, and may be followed by R.	26-20	Cu	N/A	150	5	B	2(105)
PTS1.5 f/b /one or two digit number, -5.0-H may be followed by NO TP	26-14	Cu	N/A	300	15 (16A for factory)	B, D	2(105), 4
PTS1.5 f/b /one or two digit number, -7.5-H may be followed by NO TP	26-14	Cu	N/A	300	15 (16A for factory)	B, D	2(105), 4
PTSA1.5/X-3.5 followed by -F or -Z followed by THR or HT	24-16	Cu	N/A	300	8	B, D	2(105), 4
PIT4, PTO 4 (@@)	24-10 str/sol	Cu	2	600	30	B, C	2(105), 4, 6(150 x150 x120)
FT 4	24-10 str/sol	Cu	2	600	30	B, C	2(105), 4
PIT 4-PE, PTO 4-PE(@@)	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
FT 4-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4

PIT 4-TWIN, PTO 4-TWIN(@@)	24-10 str/sol	Cu	N/A	600	30	B, C	2(105), 4, 6(150 x150 x120)
FT 4-TWIN	24-10 str/sol	Cu	N/A	600	30	B, C	2(105), 4
PIT 4-TWIN-PE (@@)	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
FT 4-TWIN-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4
PIT 4-QUATTRO (@@)	24-10 str/sol	Cu	N/A	600	30	B, C	2(105), 4, 6(150 x150 x120)
FT 4-QUATTRO	24-10 str/sol	Cu	N/A	600	30	B, C	2(105), 4
PIT 4-QUATTRO-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
FT 4-QUATTRO-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4
PITTB 4(@@)	24-10 str/sol	Cu	N/A	300	28	B, C	2(105), 4, 6(150 x150 x120)
	24-10 str/sol	Cu	N/A	600	5	D	2(105), 4, 6(150 x150 x120)
FTTBTB 4	24-10 str/sol	Cu	N/A	300	28	B, C	2(105), 4
FTTBTB 4	24-10 str/sol	Cu	N/A	600	5	D	2(105), 4
PITTB 4-PV(@@)	24-10 str/sol	Cu	N/A	300	30	B, C	2(105), 4, 6(150 x150 x120)
	24-10 str/sol	Cu	N/A	600	5	D	2(105), 4, 6(150 x150 x120)
FTTB 4-PV	24-10 str/sol	Cu	N/A	300	30	B, C	2(105), 4
FTTB 4-PV	24-10 str/sol	Cu	N/A	600	5	D	2(105), 4
PITTB 4-PE(@@)	24-10 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 4, 6(150 x150 x120)
FTTB 4-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C, D	
PT 4-PE/3L	24-10 str/sol	Cu	N/A	600	28	B, C	2(115), 4
	24-10 str/sol	Cu	N/A	600	28	B, C	2(115), 4
	24-10 str/sol	Cu	N/A	600	28	B, C	2(115), 4
	24-10 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(115), 4
PIT 4-FSI/F(@@)	24-10 str/sol	Cu	N/A	300	15/7.5 (2)	B,C	2(105)
PIT 4-FSI/F-LED 12(@@)	24-10 str/sol	Cu	N/A	12	15/7.5 (2)	B,C	2(105)
PIT 4-FSI/F-LED 24(@@)	24-10 str/sol	Cu	N/A	24	15/7.5 (2)	B, C	2(105)
PIT 4-FSI/F-LED (#) (@@)	24-10 str/sol	Cu	N/A	(#)	15/7.5 (2)	B, C	2(105)
PIT 4-DIO 1N5408/L- R(@@)	24-10 str/sol	Cu	N/A	600	1.5	B, C	2(105)

PIT 4-DIO 1N5408/R-L(@@)	24-10 str/sol	Cu	N/A	600	1.5	B, C	2(105)
PIT 4-QUATTRO-DIO 1N5408/L-R(@@)	24-10 str/sol	Cu	N/A	600	1.5	B, C	2(105)
PIT 4-QUATTRO-DIO 1N5408/R-L(@@)	24-10 str/sol	Cu	N/A	600	1.5	B, C	2(105)
PIT 4-HESI(5X20) (@@)	24-10 str/sol	Cu	N/A	300	6.3	B, C	2(105)
PIT 4-HESILED 24 (5X20)(@@)	24-10 str/sol	Cu	N/A	30	6.3	B, C	2(105)
PIT 4-HESILED 60 (5X20)(@@)	24-10 str/sol	Cu	N/A	60	6.3	B, C	2(105)
PIT 4-HESILA 250 (5X20)(@@)	24-10 str/sol	Cu	N/A	250	6.3	B, C	2(105)
PIT 4-MT(@@)	24-10 str/sol	Cu	N/A	300	20	B, C	2(105), 4, 6(150 x150 x120)
PIT 4-TG(@@)	24-10 str/sol	Cu	N/A	600	20	B, C	2(105), 4, 6(150 x150 x120)
PITME 4(@@)	24-10 str/sol	Cu	N/A	300	26	B, C	2(105), 4, 6(150 x150 x120)
PITMED 4(@@)	24-10 str/sol	Cu	N/A	300	26	B, C	2(105), 4, 6(150 x150 x120)
PTTB4L 1000	24-10 str/sol	Cu	N/A	1000	30	E	2(105), 4, 6(150 x150 x120)
PTMED 4-PE	24-10 str/sol	Cu	N/A	N/A	N/A	B, C	2(105)
PIT 6; FT 6(@@)	20-8 sol/str	Cu	N/A	600	40	B, C	2(105), 4, 6(150 x150 x120)
PT 6	20-8 sol/str	Cu	N/A	600	40	B, C	2(105), 4, 6(150 x150 x120)
PIT 6-PE(@@); FT 6-PE	20-8 sol/str	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PT 6-PE	20-8 sol/str	Cu	N/A	N/A	N/A	B, C, D	2(105), 4, 6(150 x150 x120)
PT10	20-6 str/sol	Cu	N/A	600	60	B, C	2(105), 4, 6(150 x150 x120)
PT10-TWIN	20-6 str/sol	Cu	N/A	600	60	B, C	2(105), 4, 6(150 x150 x120)
PT10-PE	20-6 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PT10-TWIN-PE	20-6 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PT10-M5	20-6(1)	Cu	N/A	300	30	B, C	2(105), 4, 6(150 x150 x120)
	14-8(2)			150	10	D	
PT 16 N, PT 16 TWIN N	20-4 str/sol	Cu	N/A	600	85	B, C	2(105)

PT 16 N-PE, PT 16-TWIN N-PE	20-4 str/sol	Cu	N/A	600		B, C	2(105)
FT 6-TWIN	20-8 str/sol	Cu	N/A	600	40	B	2(105), 4, 6(150 x150 x120)
PT 6-TWIN	20-8 str/sol	Cu	N/A	600	40	B,C	2(105), 4, 6(150 x150 x120)
FT 6-TWIN-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PT 6-TWIN-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 4, 6(150 x150 x120)
FT 6-QUATTRO	20-8 str/sol	Cu	N/A	600	40	B, C	2(105), 4, 6(150 x150 x120)
PT 6-QUATTRO	20-8 str/sol	Cu	N/A	600	40	B, C	2(105), 4, 6(150 x150 x120)
FT 6-QUATTRO-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PT 6-QUATTRO-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105), 4, 6(150 x150 x120)
PT 6/1P	20-8 str/sol	Cu	N/A	600	40	B, C	2(105), 4, 6(150 x150 x120)
PT 6/1P-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PPC 6-NS/1-L	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PPC 6/1-L	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PPC 6/1-L	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PT 6-QUATTRO/2P	20-8 str/sol	Cu	N/A	600	40	B, C	2(105), 4, 6(150 x150 x120)
PT 6-QUATTRO/2P-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C	2(105), 4, 6(150 x150 x120)
PTME 6 HV	20-8 str/sol	Cu	N/A	600	30	B, C	2(105)
PTME 6-DIO/L-R(R-L)HV	20-8 str/sol	Cu	N/A	600	10	B, C	2(105)
PTME 6-CT/1P	20-8 str/sol	Cu	N/A	300	30	B, C	2(105)
				600	5	D	
PTMED 6-CT/1P	20-8 str/sol	Cu	N/A	300	30	B, C	2(105)
				600	5	D	
PTME 6/1P	20-8 str/sol	Cu	N/A	300	30	B, C	2(105)
				600	5	D	
PTMED 6-CT/1P-PE	20-8 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(105)
PP-H 6/1	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PP-H 6/1-L	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)

PP-H 6/2...10	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PP-H 6/1-M	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PP-H 6/1-R	20-8 str/sol	Cu	N/A	600	40	B, C	2(105)
PPCT 6/2 (Suffixes 2-10)	20-8 str/sol	Cu	N/A	300	30	B, C	2(105)
				600	5	D	
PT 2.5-HEXA/3P	26-12 str/sol	Cu	N/A	300	20	B, C	2(105)
PT 2.5-HEXA/3P-PE	26-12 str/sol	Cu	N/A	300	—	B, C	2(105)
PT4/1P	24-10	Cu	N/A	600	28	C	2(105)
PT4/1P-PE	24-10	Cu	N/A	N/A	N/A	C	2(105)
PT 4-MT	24-10 str/sol	Cu	N/A	300	20	B	
				300	20	C	
PT4-TG	24-10 str/sol	Cu	N/A	300	20	B	2(115)
				300	20	C	
PT 4-FSI/F	24-10 str/sol	Cu	N/A	300	15	B, C	2(115)
				150	15	B, C	
PT 4-FSI/F-LED 12	24-10 str/sol	Cu	N/A	300	15	B, C	2(115)
				150	15	B, C	
PT 4-FSI/F-LED 24	24-10 str/sol	Cu	N/A	300	15	B, C	2(115)
				150	15	B, C	
PT 4-FSI/F-LED 70	24-10 str/sol	Cu	N/A	300	15	B, C	2(115)
				150	15	B, C	
PT 4-HESI (5X20)	24 - 10	Cu	N/A	300	6.3	B	2(115)
				300	6.3	C	
PT 4-HESILED24 (5X20)	24 - 10	Cu	N/A	300	6.3	B	2(115)
				300	6.3	C	
PT 4-HESILED 60(5X20)	24 - 10	Cu	N/A	300	6.3	B	2(115)
				300	6.3	C	
PT 4-HESILA OR HESILED 250 (5X20)	24 - 10	Cu	N/A	300	6.3	B	2(115)
				300	6.3	C	
PT 4-DIO 1N 5408/L-R	24-10	Cu	N/A	600	1.5	B,C,D	2(115)
PT 4-DIO 1N 5408/R-L	24-10	Cu	N/A	600	1.5	B,C,D	2(115)
PT 4-QUATTRO-DIO 1N 5408/L-R	24-10	Cu	N/A	600	1.5	B,C,D	2(115)
PT 4-QUATTRO-DIO 1N 5408/R-L	24-10	Cu	N/A	600	1.5	B,C,D	2(115)
PT 4-QUATTRO	24-10	Cu	N/A	600	30	B,C	2(115)
		Cu	N/A	600	5	D	2(115)
PP-H4/1	24-10	Cu	N/A	600	28	C	2(105)
PP-H4/2 through 15	24-10	Cu	N/A	600	28	C	2(105)

PP-H4/1-L, -1-M, -1/R	24-10	Cu	N/A	600	28	C	2(105)
PTRV 4	26-14 str/sol	Cu	N/A	300	10	D	2(115)
PTRV 4-PV	26-14 str/sol	Cu	N/A	300	10	D	2(115)
PTRV 8	26-14 str/sol	Cu	N/A	300	10	D	2(115)
PTRV 8-PV	26-14 str/sol	Cu	N/A	300	10	D	2(115)
FTRV 4	26-14 str/sol	Cu	N/A	300	10	D	2(115)
FTRV 4-PV	26-14 str/sol	Cu	N/A	300	10	D	2(115)
FTRV 8	26-14 str/sol	Cu	N/A	300	10	D	2(115)
FTRV 8-PV	26-14 str/sol	Cu	N/A	300	10	D	2(115)
PTC 2.5-MT	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-TWIN-MT	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-QUATTRO-MT	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-TG	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-TWIN-TG	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-QUATTRO-TG	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-MTD	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 2.5-TWIN-MTD	24-12 str/sol	Cu	N/A	300	10	D	2(115)
				150	15	D	
PTC 4-HESILA 250 (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
PTC 4-HESI (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
PTC 4-HESILED 24 (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
PTC 4-HESILED 60 (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
FTC 4-HESI (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
FTC 4-HESILED 24 (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4

FTC 4-HESILED 60 (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
FTC 4-HESILA 250 (5X20)	24-10 str/sol	Cu	N/A	300	6.3	B,C	2(120).4
PTRVB 4-PV	26-14 str/sol	Cu	N/A	300	10	B,D	2(115)
FTRVB 4-PV	26-14 str/sol	Cu	N/A	300	10	B,D	2(115)
PTRVB 8-PV	26-14 str/sol	Cu	N/A	300	10	B,D	2(115)
FTRVB 8-PV	26-14 str/sol	Cu	N/A	300	10	B,D	2(115)
PTRVB 4-FI	12-10 str/sol	Cu	N/A	300	25	B,D	2(115)
	26-14 str/sol				10		
FTRVB 4-FI	12-10 str/sol	Cu	N/A	300	25	B,D	2(115)
	26-14 str/sol				10		
PTRVB 8-FI	12-10 str/sol	Cu	N/A	300	25	B,D	2(115)
	26-14 str/sol				10		
FTRVB 8-FI	12-10 str/sol	Cu	N/A	300	25	B,D	2(115)
	26-14 str/sol				10		
PTRVB 4-PE	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(115)
FTRVB 4-PE	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2(115)
LAK 4/5	20-10 sol/str	Cu	N/A	600	30	C	2(115)
LAK 4/10	20-10 sol/str	Cu	N/A	600	30	C	2(115)
LAK 16/5	14sol/str- 6 str	Cu	N/A	600	55	C	2(115)
LAK 16/10	14 sol/str- 6 str	Cu	N/A	600	55	C	2(115)
PTTB 4-HESI (5X20)	24-10 sol/str	Cu	—	300	U :6.3	B,C	2(115)
					L : 20		
				600	5	D	
PTTB 4-HESILED 24 (5X20)	24-10 sol/str	Cu	—	300	U :6.3	B,C	2(115)
					L : 20		
				600	5	D	
PTTB 4-HESILED 60 (5X20)	24-10 sol/str	Cu	—	300	U :6.3	B,C	2(115)
					L : 20		
				600	5	D	
PTTB 4-HESILED OR HESILA 250 (5X20)	24-10 sol/str	Cu	—	300	U :6.3	B,C	2(115)
					L : 20		
				600	5	D	
PTTB 4-TG	24-10 sol/str	Cu	—	300	U :16	B,C	2(115)

					L : 20		
				600	5	D	
PTTB 4-MT	24-10 sol/str	Cu	—	300	U :16	B,C	2(115)
					L : 20		
				600	5	D	
PT 4-L	24-10 sol/str	Cu	—	300	20	B,C	2(115)
				600	5	D	
PT 4-L/L	24-10 sol/str	Cu	—	300	U : 16	B,C	2(115)
					L : 20		
				600	5	D	
PT 4-PE/L/L	24-10 sol/str	Cu	—	300	U : 16	B,C	2(115)
					L : 20		
				600	PE : NA	D	
					5		
PT 4-PE/L/N	24-10 sol/str	Cu	—	300	U : 16	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-L/HESI (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
				600	5	D	
PT 4-L/HESILED 24 (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
				600	5	D	
PT 4-L/HESILED 60 (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
				600	5	D	
PT 4-L/HESILED OR HESILA 250 (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
				600	5	D	
PT 4-PE/L/TG	24-10 sol/str	Cu	—	300	U : 16	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	

PT 4-PE/L/MT	24-10 sol/str	Cu	—	300	U : 16	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-PE/L/HESI (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-PE/L/HESILED 24 (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-PE/L/HESILED 60 (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-PE/L/HESILED OR HESILA 250 (5x20)	24-10 sol/str	Cu	—	300	U : 6.3	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-PE/L/HEDI	24-10 sol/str	Cu	—	300	U : 16	B,C	2(115)
					L : 20		
					PE : NA		
				600	5	D	
PT 4-HEDI	24-10 sol/str	Cu	—	300	16	B,C	2(115)
				600	5	D	
PT 6-HESILED 60 (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESI (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESI-EX (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESILED 24 (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	

PT 6-HESILED 250 (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESILED EX (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESILED 24-EX (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESILED 60-EX (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT 6-HESILED 250-EX (6.3X32)	20 sol/str-8 str	Cu	—	300	10	B,C	2(115)
				600	5	D	
PT6-FSI/C	20 sol/str-8 str	Cu	—	300	25	B,C	2(115)
				600	5	D	
PT6-FSI/C-LED12	20 sol/str-8 str	Cu	—	300	25	B,C	2(115)
				600	5	D	
PT6-FSI/C-LED24	20 sol/str-8 str	Cu	—	300	25	B,C	2(115)
				600	5	D	
PT6-FSI/C-LED48	20 sol/str-8 str	Cu	—	300	25	B,C	2(115)
				600	5	D	
PT 6-DREHSI (5X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
PT 6-DREHSILED 24 (5X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
PT 6-DREHSILED 60 (5X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
PT 6-DREHSILA 250 (5X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
PT 6 DREHSI (6.3X32)	20-8 str/sol	Cu	N/A	600	20	B, C	2(115)
PT 6 DREHSILED 24 (6.3X32)	20-8 str/sol	Cu	N/A	600	20	B, C	2(115)
PT 6 DREHSILED 60 (6.3X32)	20-8 str/sol	Cu	N/A	600	20	B, C	2(115)
PT 6 DREHSILA 250 (6.3X32)	20-8 str/sol	Cu	N/A	600	20	B, C	2(115)
FT 6-DREHSI (5X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
FT 6-DREHSILED 24 95X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
FT 6-DREHSILA 250 (5X20)	20-8 str/sol	Cu	—	600	10	B, C	2(115)
PT 6-T P/P HV	20 - 10 str/sol	Cu	N/A	600	30	B, C	2(115)

				600	5	D	2(115)
PTU 35/4x10	14 sol/str-3 str (screw connection)	Cu	—	600	86	B, C	2(115)
	20 sol/str-8 str (spring connection)	Cu	3.2-3.7 NM	600	36	B, C	2(115)
FTU 35/4x10	14 sol/str-3 str (screw connection)	Cu	—	600	86	B, C	2(115)
	20 sol/str-8 str (spring connection)	Cu	3.2-3.7 NM	600	36	B, C	2(115)
Note: (1) Outside terminal							
Note: (2) Inside Terminal							
U is for upper level, L is for lower level, PE is for grounding level							
PIT 1.5/S(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PIT 1.5/S-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105)
PIT 1.5/S-TWIN(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PIT 1.5/S-TWIN-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C	2 (105)
PIT 1.5/S-QUATTRO(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PIT 1.5/S-QUATTRO-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105)
PIT 1.5/S-QUATTRO-U(@@)	26-14 str/sol	Cu	N/A	300	15	B	2 (105)
				150	15	C	
				300	10	D	
PT 1.5/S/2P	N/A	Cu	N/A	300 600	15 5	B, C D	2 (105)
PT 1.5/S/2P-PE	N/A	Cu	N/A	N/A	N/A	B, C, D	2 (105)
PT 1.5/S/4P	N/A	Cu	N/A	300 600	15 5	B, C D	2 (105)
PT 1.5/S/4P-PV	N/A	Cu	N/A	300 600	15 5	B, C D	2 (105)
PT 1.5/S/4P-PE	N/A	Cu	N/A	N/A	N/A	B, C, ,D	2 (105)
PITTB 1.5/S(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PITTB 1.5/S-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105)
PITTB 1.5/S-PV(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)

PITTB 1.5/S-L/N(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PITTB 1.5/S- PE/L(@@)	26-14 str/sol	Cu	N/A	300	15	B, C	2 (105)
				600	5	D	
				N/A	N/A	B, C, D	
PITTB 1.5/S- PE/N(@@)	26-14 str/sol	Cu	N/A	300	15	B, C	2 (105)
				600	5	D	
				N/A	N/A	B, C, D	
PIT 1.5/S-3L(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PIT 1.5/S-3PV(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PIT 1.5/S-3PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105)
PIT 1.5/S- 3PE/L/N(@@)	26-14 str/sol	Cu	N/A	300	15	B, C	2 (105)
				600	5	D	
				N/A	N/A	B, C, D	
PIT 1.5/S- 3PE/L/L(@@)	26-14 str/sol	Cu	N/A	300	15	B, C	2 (105)
				600	5	D	
				N/A	N/A	B, C, D	
PITS 1.5/S(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PITS 1.5/S-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105)
PITS 1.5/S- TWIN(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105)
PITS 1.5/S-TWIN- PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PITS 1.5/S- QUATTRO(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITS 1.5/S- QUATTRO-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PITTBS 1.5/S(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITTBS 1.5/S- PV(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITTBS 1.5/S-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C	2 (105), 4
PIT 1.5/S/1P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PIT 1.5/S/1P-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PIT 1.5/S- TWIN/1P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4

PIT 1.5/S-TWIN/1P-PE	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PIT 1.5/S-QUATTRO/2P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B,C D	2 (105), 4
PIT 1.5/S-QUATTRO/2P-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PITTB 1.5/S/2P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITTB 1.5/S/2P-PV(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITTB 1.5/S/2P-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PP-H 1.5/S/1	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PP-H 1.5/S/1 followed By /1 or /2 digit number	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PP-H 1.5/S/1-L	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PP-H 1.5/S/1-M	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PP-H 1.5/S/1-R	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PPC 1.5/S/1	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PPC 1.5/S followed by /1 or/2 digit number	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PPC 1.5/S/1-L	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PPC 1.5/S/-NS/1-L	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITS 1.5/S/1P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITS 1.5/S /1P-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PITS 1.5/S-TWIN/1P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITS 1.5/S-TWIN/1P-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PITTBs 1.5/S/2P(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITTBs 1.5/S/2P-PV(@@)	26-14 str/sol	Cu	N/A	300 600	15 5	B, C D	2 (105), 4
PITTBs 1.5/S/2P-PE(@@)	26-14 str/sol	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4

PTIO 1.5/S/3	26-14	Cu	N/A	300	15	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 1.5/S/4	26-14	Cu	N/A	300	15	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 1.5/S/5	26-14	Cu	N/A	300	15	B	2(105), 4
PTIO 1.5/S/5	26-14	Cu	N/A	150	15	C	2(105), 4
PTIO 1.5/S/5	26-14	Cu	N/A	500	15	F(+)	2(105), 4
PTIO 1.5/S/5-PE	26-14	Cu	N/A	300	15	B	2(105), 4
PTIO 1.5/S/5-PE	26-14	Cu	N/A	150	15	C	2(105), 4
PTIO 1.5/S/5-PE	26-14	Cu	N/A	500	15	F(+)	2(105), 4
PTIO 1.5/S/5-PE	26-14	Cu	N/A	300	N/A (1)	B,C,D	2(105), 4
PTIO 1.5/S/3-LED 24 RD	26-14	Cu	N/A	300	15	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 1.5/S/3-LED 24 GN	26-14	Cu	N/A	300	15	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 1.5/S/3-L-R1K8/O-M	26-14	Cu	NA	50	15	C	2 (105), 4
PTIO 1.5/S/4-LED 24 RD	26-14	Cu	N/A	300	15	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 1.5/S/4-LED 24 GN	26-14	Cu	N/A	300	15	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 2.5/3 OG	24-12	Cu	N/A	300	16	B	2 (105), 4
				150	15	C	
				300	10	D	
PTIO 1.5/S/3-PE	26-14	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PTIO-IN 2.5/3 OG	26-14	Cu	N/A	300 150 300	10 16 10	B, C, D	2 (105), 4
PTIO 1.5/S/4-PE	26-14	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4
PTIO-IN2.5/4-PE OG	24-12	Cu	N/A	N/A	N/A	B, C, D	2 (105), 4

PTS 1.5/S-3L/3P, PTS 1.5/S-3PV/3P	26-14	Cu	2	300	13	B,C	2(105), 4
				600	5	D	2(105), 4
PTS 1.5/S-3PE/3P	26-14	Cu	2	N/A	N/A	B,C	2(105), 4
PTS 1.5/S-PE/L/L/3P, PTS 1,5/S-PE/L/N/3P	26-14	Cu	2	300	13	B,C	2(105), 4
				600	5	D	2(105), 4
				N/A	N/A	B,C	2(105), 4
PTS 1.5/S-PE/L/L/3P , PTS 1,5/S-PE/L/N/3P (PE Level)	26-14	Cu	2	N/A	N/A	B,C	2(105), 4
PLA 5/X-7.5, PLH 5/X-7.5	24-10	Cu	N/A	300 600	27 5	B, C D	2(115), 4
PLA 5/X-7.5-ZB, PLA 5/X-7.5-ZF, PLH 5/X-7.5-ZB, PLH 5/X-7.5-ZF	24-10	Cu	N/A	600	27	B, C	2(115), 4
HW 16/2-STO-7,2	16-6, Str	Cu	1.8	300	30 Note A	B D	2 (115), #1
SDC 2.5 (##)	24-12	Cu	N/A	300	12 10	B D	2(115)
SDC 2.5 (##) one pole	24-12	Cu	N/A	600	12	C	2(115),4
	24-12	Cu	N/A	250	12	F(+)	2(115),4
SDDC 1, 5 (##)	24-16	Cu	N/A	300	8	B, D	2(115), 4
	24-16	Cu	N/A	250	8	F(+)	2(115),4
CDDC 2.5 + CDC-MP 0,14-0,5 (##)	26-20	Cu	N/A	300	5	B	2(115),4
	26-20	Cu	N/A	300	5	D	2(115),4
CDDC 2.5 + CDC-MP 0,5-1,5 (##)	20-16	Cu	N/A	300	10	B	2(115),4
	20-16	Cu	N/A	300	10	D	2(115),4
CDDC 2.5 + CDC-MP 1,5-2,5 (##)	16-12	Cu	N/A	300	12	B	2(115),4
	16-12	Cu	N/A	150	12	D	2(115),4
	16-12	Cu	N/A	300	10	D	2(115),4
	16-12	Cu	N/A	250	12	F(+)	2(115),4
CDDC 1.5 + CDC-MP 0,14-0,5 (##)	26-20	Cu	N/A	150	5	B	2(115),4
	26-20	Cu	N/A	300	5	D	2(115),4
CDDC 1.5 + CDC-MP 0,5-1,5 (##)	20-16	Cu	N/A	150	8	B	2(115),4
	20-16	Cu	N/A	300	8	D	2(115),4

Note: A These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.

Note: (#) - May vary from 0 to 300 to indicate value of voltage rating

Note: (##) followed by/one or two digit number, followed by Suffix -PV, followed by Suffix -5.0, followed by -ZB or -ZF, may be followed by 1 to 30 character alphanumeric suffix (any combination of letters and/ or numbers) indicating optional alternate poles, colors, partial assemblies, coding and laser prints.

Note: (+) Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification only.

Note: (**) - May be followed by P-FU 6.3X32, P-FU 6.3X32 LED 24, P-FU 6.3X32 LED 60, P-FU 6.3X32 LA 250.

DMC1.5, DMCV1.5 (Note AA)	N/A	Cu	N/A	300 50	8	B, D C	2(130), 4
DMC1.5, DMCV1.5 (Note AA)	N/A	Cu	N/A	300	8	D	2(130), 4
DMC1.5/X f/b -G1, - G1F f/b -3.5 w/wo - LR, AU f/b P35 w/wo THR (1).	N/A	Cu	N/A	150	8	B	2(130), 4
	N/A	Cu	N/A	300	8	D	2(130), 4
DMCV1.5/X f/b -G1, - G1F f/b -3.5 w/wo - LR, AU f/b P35 w/wo THR (1).	N/A	Cu	N/A	300	8	B	2(130), 4
	N/A	Cu	N/A	300	8	D	2(130), 4
DFMC1.5(Note BB)	24-16	Cu	N/A	300	8	B,D	2(115), 4

Note: AA Followed by /one or two digit number followed by -G1, -G1F followed by -3.5 with or without --LR or AU followed by P20, P26, P34, PXX, w/wo THR.

PXX - Designates free solder-pin length below insulation body in mm.

Note: BB Followed by /one or two digit number followed by -ST, -STF followed by -3.5 with or without -LR.

Note: (1). Models DMC1.5/X, DMCV1.5/X followed by suffixes can be mated with Terminal Block Plugs, Model No. DFMC 1.5/X-ST-3.5.

CB 1/6-2/4 PT-BE	Input 20-10 str/sol	Cu	N/A	300 600	16 5	B, C D	2(105), 4
	Output 24-12 str/sol			300 600	16 5	B, C D	
	Signal 26-16 str/sol			300 600	2 2	B, C D	
CB 1/10-1/10 UT-BE	Line/Load 14- 10 Sol/Str	Cu	1.5-1.8	277Vac, 50Vdc	16	B	2(105), 4
	Signals 26-16 Sol/Str	Cu	0.5-0.6	277Vac, 50Vdc	1	B	2(105), 4
USST4	24-10	Cu	5-7	300 600	30 5	B, C D	2(105), 4
USST 4-MT	24-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
				600	5	D	
USST 4-MT-P/P	24-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
				600	5	D	
USST 4-TG	24-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
				600	5	D	
USST 4-TG-P/P	24-10	Cu	0.6-0.8	300	20	B, C	2(105), 4
				600	5	D	

USST6	24-10	Cu	13-16	300 600	30 5	B, C D	2(105), 4
USST6-T	24-10	Cu	13-16	300 600	30 5	B, C D	2(105), 4
USST6-T/SB w/wo -P	24-10	Cu	13-16	300 600	30 5	B, C D	2(105), 4
USSTD6	24-10	Cu	13-16	300 600	30 5	B, C D	2(105), 4
USST10	20-6	Cu	13-16	300 600	65 5	B, C D	2(105), 4
USST 6-T/SB HV	20-8	Cu	1.5-1.8 Nm	600	50	B, C	2(105), 4
					5	D	
USSTD 6 HV	20-8	Cu	1.5-1.8 Nm	600	50	B, C	2(105), 4
					5	D	
UT 6-T/SP	20-8	Cu	13-16	600	50	B, C	2(105)
UTD 6/SP	20-8	Cu	13-16	600	50	B, C	2(105)
USST 6-T/SP	20-8	Cu	13-16	600	50	B, C	2(105)
USSTD 6/SP	20-8	Cu	13-16	600	50	B, C	2(105)
UT6/1P	24-8	Cu	13-16	600	40	B, C	2(105), 4
UT6/1P-PE	24-8	Cu	13-16	600	40	B, C	2(105), 4
UT6-QUATTRO/2P	24-8	Cu	13-16	N/A	N/A	B, C, D	2(105), 4
UT6-QUATTRO/2P-PE	24-8	Cu	13-16	600	40	B, C	2(105), 4
UP6/1-L	24-8	Cu	13-16	N/A	N/A	B, C, D	2(105), 4
UP6/1-M	24-8	Cu	5-7	600	40	B, C	2(105), 4
UP6/1-R	24-8	Cu	5-7	600	40	B, C	2(105), 4
UP6/2...10	24-8	Cu	5-7	600	40	B, C	2(105), 4
UT6/1P	24-8	Cu	5-7	600	40	B, C	2(105), 4

1. The mating terminal block as tabulated below is evaluated for capacity of Current-carrying. These devices have not been evaluated to make or break the flow of Current. It is intended for disconnect use only. These devices are not evaluated for use with any other mating connectors.

Cat. No.	Mating Part Cat. No.
HW 16/2-STO-7,2	SJ018-2PZW-A

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
FKDSO2.5 /2, /3 or /4 f/b suffix -L or -R	24-14 Sol/str	Cu	N/A	300	10	B, D	2(105)

FKDSO 2.5HV followed by /3, followed by suffix -L or -R, followed by 7.5	30-14 sol/str	Cu	N/A	300 600	10 5	B, C D	2(105)
Type FKDSO 2.5 followed by /1, /2, /3 or /4 followed by suffix -L1 or -R1	24-12 sol/str	Cu	N/A	300 150 300	20 15 10	B D D	2(105)
MUT2.5	24-12	Cu	4-5	300	20	B, C	2(115)
MUT2.5-PE	24-12	Cu	4-5	N/A	N/A	B, C	2(115)
MUT4	24-10	Cu	5-7	300	30	B, C	2(115)
MUT4-PE	24-10	Cu	5-7	N/A	N/A	B, C	2(115)
FASTCON-PRO-SC	24-12	Cu	4.4- 5.3	300	6	B, D	2(115)
FASTCON-PRO-PT	24-12	Cu	N/A	300	6	B, D	2(115)
PWR-DIS-TMSTB/2-IT-5.08 (AA)	18-6	Cu	1-2 N-m	600	55	B, C	2(105),
PWR-DIS-TMSTB/4-IT-7.62 (AA)	18-6	Cu	1-2 N-m	600	55	B, C	2(105)
PWR-DIS-TPC5/4-IT-7.62 (AA)	18-6	Cu	1-2 N-m	600	55	B, C	2(105)
PWR-DIS-TPC5/2-IT-7.62	18-6	Cu	1-2 N-m	600	55	B, C	2(105)
PWR-DIS-TMSTB/2-ST-5.08 (AA)	—	—	—	600	70	B, C	2(105)
PWR-DIS-TMSTB/2-ST-7.62 (AA)	—	—	—	600	70	B, C	2(105)
PWR-DIS-TPC5/2-ST-7.62 (AA)	—	—	—	600	70	B, C	2(105)
PWR-DIS-BUSBAR/1-52.5 (AA)	—	—	—	600	70	B, C	2(105)
PWR-DIS-BUSBAR/1-85.0 (AA)	—	—	—	600	70	B, C	2(105)
PWR-DIS-BUSBAR/1-100.0 (AA)	—	—	—	600	70	B, C	2(105)
PWR-DIS-BUSBAR/2-220 (AA)	—	—	—	600	70	B, C	2(105)
Note: (AA) PWR-DIS terminal block Kits, Cat. Nos. K5700 100mm Control Power KIT; K5700 100mm Busbar Replacement; K5700 220mm Busbar Replacement; K5700 Family DC INPUT CONN KIT; K5500; K5500 FR3 input connector set; K5500 FR1,2 input connector set; K5500 FR3 AC Bus Connector; K5500 FR3 DC Bus Connector; K5500 FR3 control power conn.; K5500 FR3 AC,DC Bus Connector; K5500 FR3 AC,control conn.,K5500 FR3 DC,control conn., K5500 FR3 AC,DC,control conn; K5500 FR1,2 AC bus connector; K5500 FR1,2 DC bus connector; K5500 FR1,2 control power con; K5500 FR1,2 AC,DC bus conn; K5500 FR1,2 AC control conn; K5500 FR1,2 DC control conn; K5500 FR1,2 AC,DC,control con; CONKIT,MIDRANGE,BUS BAR,SM and CONKIT,MIDRANGE,BUS BAR,LG; CONKIT,K5500,CAP,MODULE consists of POWER-DIS terminal blocks and MC 1.5/2-ST-3.81 BK terminal block, packaged in kit form. PWR-DIS Kits consist of multiple PWR-DIS terminal blocks of above Cat. No. and rating, packaged in kit form.							
MPT1.5/S	26-14	Cu	N/A	300 600	15 5	B, C D	2(105), 4
MPT1.5/S-PE	26-14	Cu	N/A	N/A	N/A	B, C D	2(105), 4
MPT1.5/S-1P	26-14	Cu	N/A	300 600	15 5	B, C D	2(105), 4

MPT1.5/S-1P-PE	24-10	Cu	N/A	N/A	N/A	B, C, D	2(105), 4
MPT2.5	26-12	Cu	N/A	300 600	20 5	B, C, D	2(105), 4
MPT2.5-PE	26-12	Cu	N/A	N/A	N/A	B, C, D	2(105), 4
MP nX1.5	26-14	Cu	N/A	300	15	B, C	2(105), 4
			N/A	150	15	D	2(105), 4
MPI nX1.5	26-14	Cu	N/A	300	15	B, C	2(105), 4
			N/A	150	15	D	2(105), 4
MPI nX1.5-F	26-14	Cu	N/A	300	15	B, C	2(105), 4
			N/A	150	15	D	2(105), 4
MP nX1.5-RZ	26-14	Cu	N/A	300	15	B, C	2(105), 4
			N/A	150	15	D	2(105), 4
PTFIX nX2.5, PTFIX nX2.5-NS35, TFIX nX2.5-NS15A, PTFIX nX2.5-NS35A, PTFIX nX2.5-G	26-12	Cu	N/A	300	20	B, C	2(115)
				600	5	D	
PTFIX nX2.5-GNYE, PTFIX nX2.5-NS35-GNYE, PTFIX nX2.5-NS15A-GNYE, PTFIX nX2.5-NS35A-GNYE, PTFIX nX2.5-G-GNYE	26-12	Cu	N/A	N/A	N/A	B,C,D	2(115)
PTFIX 2X2.5	26-12	Cu	N/A	300	20	B, C	2(115), 4
				600	5	D	
PTFIX 2X2.5-GNYE	26-12	Cu	N/A	N/A	N/A	B,C,D	2(115)
PTFIX 6/nX2.5, PTFIX 6/nX2.5-NS35, PTFIX 6/nX2.5-NS15A, PTFIX 6/nX2.5-NS35A, PTFIX 6/nX2.5-G	20-8	Cu	N/A	300	50	B, C	2(115)
	26-12			600		D	
	20-8				5		
	26-12						
PTFIX 6/nX2.5-GNYE, PTFIX 6/nX2.5-NS35-GNYE, PTFIX 6/nX2.5-NS15A-GNYE, PTFIX 6/nX2.5-NS35A-GNYE, PTFIX 6/nX2.5-G-GNYE	20-8	Cu	N/A	N/A	N/A	B,C,D	2(115)
	26-12						
PTFIX nX4, PTFIX nX4-NS35, PTFIX nX4-NS35A, PTFIX nX4-G	24-10	Cu	N/A	600	32	B,C	2(115)
PTFIX nX4-GNYE, PTFIX nX4-NS35-GNYE, PTFIX nX4-NS35A-GNYE, PTFIX nX4-G-GNYE	24-10	Cu	N/A	N/A	N/A	B,C	2(115)

PTFIX 10/nX4, PTFIX 10/nX4-NS35, PTFIX 10/nX4-NS35A, PTFIX 10/nX4-G	10: 20-8	Cu	N/A	600	50	B,C	2(115)
	nX4: 24-10	Cu	N/A	600	32	B,C	2(115)
PTFIX 10/nX4-GNYE, PTFIX 10/nX4-NS35-GNYE, PTFIX 10/nX4-NS35A-GNYE, PTFIX 10/nX4-G-GNYE	10: 20-8	Cu	N/A	N/A	N/A	B,C	2(115)
	nX4: 24-10						
PTFIX n X 1.5, PTFIX n X 1.5-NS15A, PTFIX n X 1.5-NS35AD, PTFIX n X 1.5-RZF, PTFIX n X 1.5-NS35, PTFIX n X 1.5-G, PTFIX n X 1.5-F	26-12	Cu	N/A	300	20	B	2(115)
				150	20	C	2(115)
				300	10	D	2(115)
PTFIX 4/n X 1.5, PTFIX 4/n X 1.5-NS15A, PTFIX 4/n X 1.5-NS35AD, PTFIX 4/n X 1.5-RZF, PTFIX 4/n X 1.5-NS35, PTFIX 4/n X 1.5-G, PTFIX 4/n X 1.5-F	INPUT 24-10 OUTPUT 26-12	Cu	N/A	300	INUPUT:30, OUTPUT:20	B	2(115)
				150	INUPUT:30, OUTPUT:20	C	2(115)
				300	10	D	2(115)
PTFIX n X 10/S, PTFIX n X 10/S-NS35, PTFIX n X 10/S-NS35A, PTFIX n X 10/S-G, PTFIX n X 10/S-F, PTFIX n X 10/S-GNYE, PTFIX n X 10/S-NS35-GNYE, PTFIX n X 10/S-NS35A-GNYE, PTFIX n X 10/S-G-GNYE, PTFIX n X 10/S-F-GNYE	20-6	Cu	N/A	N/A	N/A	B,C,D	2(115)
PTVFIX nX2.5PTVFIX nX2.5-NS 35PTVFIX nX2.5-NS 35APT PTVFIX nX2.5-NS 35A FIXPTVFIX nX2.5-NS 15PTVFIX nX2.5-NS 15APT PTVFIX nX2.5-NS 15A FIXPTVFIX nX2.5-FPTVFIX nX2.5-G	26-12	Cu	N/A	300	20	B, C	2(115)
				600	5	D	2(115)
PTVFIX 6/nX2.5PTVFIX 6/nX2.5-NS 35PTVFIX 6/nX2.5-NS 35APT PTVFIX 6/nX2.5-NS 35A FIXPTVFIX 6/nX2.5-NS 15PTVFIX 6/nX2.5-NS 15APT PTVFIX 6/nX2.5-NS 15A FIXPTVFIX 6/nX2.5-FPTVFIX 6/nX2.5-G	6sqmm: 20-82.5sqmm: 26-12	Cu	N/A	300	40(6 sq mm), 20 (2.5 sq mm)	B, C	2(115)
				600	5	D	2(115)
PTFIX n/6X 2.5-TG-NS35,PTFIX n/6X 2.5-TG-NS35APT PTFIX n/6X 2.5-TG-NS15A,PTFIX n/6X 2.5-TG-FPTFIX n/6X2.5-MT-NS35,PTFIX n/6X2.5-MT-NS35A,PTFIX n/6X2.5-MT-NS15A,PTFIX n/6X2.5-MT-F,PTFIX n/6X2.5-MTL-NS35,PTFIX n/6X2.5-MTL-NS35A,PTFIX n/6X2.5-MTL-NS15A,PTFIX n/6X2.5-MTL-F,PTFIX n/6X2.5-TG, PTFIX n/6X2.5-MT, PTFIX n/6X2.5-MTL	Input: 20 – 8 Output: 26 – 12	Cu	N/A	300	45	B, C	2(115)
				600	5	D	2(115)
				400	45	F	2(115)
PTFIX 10/nX4-SI (5X20), PTFIX 10/nX4-SILED 250 (5X20), PTFIX 10/nX4-SILED 60 (5X20), PTFIX 10/nX4-SILED 24 (5X20) w or w/o NS35/ NS35A/ NS15A/-F	10: 20 – 8	Cu	N/A	300	Input: 40 Output: 6 X 6.3	B	2(115)
	nx4: 24 – 10			250		F(+)	2(115)

Note: (+) Ratings associated with Usage Group F are based on Overvoltage Category III and are applicable to USR certification

Notes: (1) Ratings associated with surge arresters are based on overvoltage category III and are applicable to 100 kV system only.

Cat. No.	Suitable Conductors Kcmil/AWG		OverCurrent Protection Fuse Required Class/Max Amp Rating							SCCR RMS Sym A	Max Volts
	Line	Load	J	L	T	RK1	RK5	G	CC		
PT or PIT 2.5, PT or PIT 2.5-TWINn, PT or PIT 2.5-QUATTRO, PT or PIT 2.5-PE, PT or PIT 2.5-TWIN-PE, PT or PIT 2.5-QUATTRO-PE	14 - 12 Str.	14 - 12 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PTTBor PITTB 2.5, PTTB or PITTB 2.5-LN, PTTB or PITTB 2.5-PE/L, PTTB or PITTB 2.5-PE/N, PTTB or PITTB 2.5-PV, PTTB or PITTB 2.5-PE	14 - 12 Str.	14 - 12 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT or PIT 2.5-3PV, PT or PIT 2.5-3-PE	14 - 12 Str.	14 - 12 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT or PIT 2.5-MT, PT or PIT 2.5-TWIN-MT, PT or PIT 2.5-QUATTRO-MT, PT or PIT 2.5-TG, PT 2.5-TWIN-TG, PT or PIT 2.5-QUATTRO-TG, PT or PIT 2.5-QUATTRO-MTB	14 -12 Str.	14 - 12 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PTI or PITI 2.5-PE followed by -L, -N, -L/L, -L/N, -L/LT, -L/NT, -L/LTB, -L/NTB or -L/TG	14 - 12 Str.	14 - 12 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT 4, PT 4 TWIN, PT 4-QUATTRO, PT 4-PE, PT 4-TWIN-PE, PT 4 QUATTRO-PE	14 - 10 Str.	14 - 10 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PTTB 4, PTTB 4-PV, PTTB 4-PE	14 - 10 Str.	14 - 10 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT 4-MT, PT 4-TG	14 - 10 Str.	14 - 10 Str.	35	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT 6, PT 6-TWIN, PT 6-QUATTRO, PT 6-PE, PT 6-TWIN-PE, PT 6-QUATTRO-PE	14 - 8 Str.	14 - 8 Str.	60	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT 6-QUATTRO/2P, PT 6-QUATTRO/2P-PE	14 - 8 Str.	14 - 8 Str.	60	—	—	—	—	30	30	100 kA	600 ac 3 ph
PT 10, PT 10-TWIN, PT 10-PE, PT 10-TWIN-PE	14 - 6 Str.	14 - 6 Str.	60	—	—	—	—	30	30	100 kA	600 ac 3ph
STU 10/4x2.5	8	(2)12w(1)16	100	—	100	60	30	60	30	100 kA	600 v
U 2.5 PE	14	14	100	—	100	60	30	60	30	100 kA	N/A

UT 35	1/0	1/0	400	—	400	200	100	60	30	100 kA	600 v
-------	-----	-----	-----	---	-----	-----	-----	----	----	-----------	----------

Cat. No.	Suitable Conductors kcmil/AWG		OverCurrent Protection Fuse Required Class/Max Amp Rating						SCCR, RMS Sym, kA	Volts Max
	Line	Load	J	T	RK1	RK5	G	CC		
ST 1.5	14 Cu	14 Cu	60	60	—	—	30	30	100	300
ST 1.5 PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
ST 1.5 QUATTRO	14 Cu	14 Cu	60	60	—	—	30	30	100	300
ST 1.5-QUATTRO-PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
ST 1.5-TWIN	14 Cu	14 Cu	60	60	—	—	30	30	100	300
ST 1.5-TWIN PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
STTB 1.5	14 Cu	14 Cu	60	60	—	—	30	30	100	300
STTB 1.5PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
QTC 2.5-HEDI	14 Cu	14 Cu	60	60	—	—	30	30	100	300
QTC 2.5-MT	14 Cu	14 Cu	60	60	—	—	30	30	100	300
QTC 2.5-TG	14 Cu	14 Cu	60	60	—	—	30	30	100	300
QTC 2.5	14 Cu	14 Cu	60	60	—	—	30	30	100	600
QTC 2.5-PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
QTC 2.5-TWIN	14 Cu	14 Cu	60	60	—	—	30	30	100	600
QTC 2.5-TWIN PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
QTCS 2.5	14 Cu	14 Cu	60	60	—	—	30	30	100	600
QTCS 2.5 PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
QTCS 2.5-TWIN	14 Cu	14 Cu	60	60	—	—	30	30	100	600
QTCS 2.5-TWIN PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
QTCu 2.5	14 Cu	14 Cu	60	60	—	—	30	30	100	600
QTCu 2.5-PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
QTCu 2.5-TWIN	14 Cu	14 Cu	60	60	—	—	30	30	100	600
QTCu 2.5-TWIN PE	14 Cu	14 Cu	60	60	—	—	30	30	100	N/A
UT 2.5	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
UT 2.5 PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
UT 2.5-QUATTRO	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	150
UT 2.5-QUATTRO-PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
UT 2.5-TWIN	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	150

UT 2.5-TWIN-PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
UTTB 2.5	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
UTTB 2.5 PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
UTTB 2.5-PV	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
ST 2.5 MT	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
ST 2.5 QUATTRO-MT	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
ST 2.5 QUATTRO-TG	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
ST 2.5 TG	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
ST 2.5 TWIN MT	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
ST 2.5 TWIN TG	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
ST 2.5-3PV	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
ST 2.5-3L	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
ST 2.5-3PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
ST 2.5	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
ST 2.5 PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
ST 2.5-QUATTRO	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
ST 2.5-QUATTRO PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
ST 2.5-TWIN	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
ST 2.5-TWIN-PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
STU 2.5-TWIN	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
STU 2.5-TWIN-PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
STTB 2.5	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	600
STTB 2.5-PE	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	N/A
STTB 2.5-TWIN	14-12 Cu	14-12 Cu	60	60	—	—	30	30	100	300
UT 4-HEDI	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-HEDI BU	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-HEDI-P/P	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-MT	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-MT-P/P	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-TG	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-TG-P/P	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UTTB4-TG	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4 CB	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600

UT 4-MTD	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UT 4-MTD-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UT 4-MTD-PE/S	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UT 4-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UT 4-QUATTRO	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	150
UT 4-QUATTRO-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UT 4-TWIN	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	150
UT 4-TWIN-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UTTB 4	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UTTB 4-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UTTB 4-PV	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
ST 4	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
ST 4-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
ST 4-TWIN	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
ST 4-TWIN-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
ST 4-QUATTRO	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
ST 4-QUATTRO-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
STTB 4	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
STTB 4-PV	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
STTB 4-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
STU 4-TWIN	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
STU 4-TWIN-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
ST 4-MT	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
ST 4-TG	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UDK 4	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UDK 4-PE	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	N/A
UDK 4-TG	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UDK 4-MTK	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UDK 4-MTK-P/P	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UK 5N	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UKK 5	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	600
UKK 5-MTKD	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UKK 5-MTKD-P/P	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UKK 5-MTK	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300

UKK 5-MTK-P/P	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UKK 5-T	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UKK 5-TG	14-10 Cu	14-10 Cu	60	60	—	—	30	30	100	300
UK 6N	14-8 Cu	14-8 Cu	100	100	30	30	60	30	100	600
UT 6	14-8 Cu	14-8 Cu	100	100	30	30	60	30	100	600
UT 6-PE	14-8 Cu	14-8 Cu	100	100	30	30	60	30	100	N/A
ST 6	14-8 Cu	14-8 Cu	100	100	30	30	60	30	100	600
ST 6-PE	14-8 Cu	14-8 Cu	100	100	30	30	60	30	100	N/A
UT10	14-6 Cu	14-6 Cu	100	100	30	30	60	30	100	600
UT 10-PE	14-6 Cu	14-6 Cu	100	100	30	30	60	30	100	N/A
UT 10-P/P	14-6 Cu	14-6 Cu	100	100	30	30	60	30	100	600
ST 10	14-6 Cu	14-6 Cu	100	100	30	30	60	30	100	600
ST 10-PE	14-6 Cu	14-6 Cu	100	100	30	30	60	30	100	N/A
UT 16	14-4 Cu	14-4 Cu	100	100	30	30	60	30	100	600
UT 16-PE	14-4 Cu	14-4 Cu	100	100	30	30	60	30	100	N/A
ST 16	14-4 Cu	14-4 Cu	100	100	30	30	60	30	100	600
ST 16-PE	14-4 Cu	14-4 Cu	100	100	30	30	60	30	100	N/A
UT 35	14-1/0 Cu	14-1/0 Cu	200	200	100	30	60	30	100	600
UT 35-PE	14-1/0 Cu	14-1/0 Cu	200	200	100	30	60	30	100	N/A
ST 35	14-2 Cu	14-2 Cu	200	200	100	30	60	30	100	600
ST 35-PE	14-2 Cu	14-2 Cu	200	200	100	30	60	30	100	N/A
UKH 25	6-4 Cu	6-4 Cu	30	30	—	—	30	30	100	600
UKH 50	6-1/0 Cu	6-1/0 Cu	200	200	100	30	60	30	100	600
UKH 50-IB	6-1/0 Cu	6-1/0 Cu	200	200	100	30	60	30	100	600
UKH 95	2-4/0 Cu	2-4/0 Cu	200	200	100	30	60	30	100	600
UKH 95	2-4/0	2-4/0 Cu	400	400	200	100	60	30	100	600
UKH 240	2/0-500 kcmil Cu	2/0-500 kcmil Cu	200	200	100	30	60	30	100	600
UKH 240	2/0-500 kcmil	2/0-500 kcmil Cu	400	400	200	100	60	30	100	600
UKH 70 (1)	6-3/0	6-3/0	200	200	100	30	60	30	100	600
UHV 50 (1)	6-1/0	6-1/0	200	200	100	30	60	30	100	600
UKH 70/4X10	For 70: 4 to 3/0; For 4x10: 16 to 6	For 70: 4 to 3/0; For 4x10: 16 to 6	200	200	100	30	60	30	100	600
UHV 95 (1)	2-4/0	2-4/0	400	400	200	100	60	30	100	600
UHV 150 (1)	2-300 kcmil	2-300 kcmil	400	400	200	100	60	30	100	600
UHV 240 (1)	2/0-500 kcmil	2/0-500 kcmil	400	400	200	100	60	30	100	600

USLKG 50	6-1/0 Cu	6-1/0 Cu	100	100	60	30	60	30	100	N/A
USLKG 50-IB	6-1/0 Cu	6-1/0 Cu	100	100	60	30	60	30	100	N/A
USLKG 95	2-4/0 Cu	2-4/0 Cu	200	200	200	60	60	30	100	N/A
RT5, RT5-PE, RTO 5, RTO 5-PE	14-10	14-10	100	100	60	30	60	30	100	600
RT8, RTO 8	14-1	14-1	200	200	100	30	60	30	100	600
RSC 5	14-8	14-8	100	100	60	30	60	30	100	600
RSC 6	12-2	12-2	200	200	100	30	60	30	100	600
RBO 8-HC, RBO 8	8-2/0	8-2/0	200	200	100	30	60	30	100	600
RBO 10, RBO 10-FE, RBO 10-HC, RBO 10-HC-FE	10-350 kcmil	10-350 kcmil	400	400	200	100	60	30	100	600
RBO 12, RBO 12-FE, RBO 12-HC, RBO 12-HC-FE	8-600 kcmil	8-600 kcmil	400	400	200	100	60	30	100	600
RBO 16, RBO 16-FE, RBO 16-HC, RBO 16-HC-FE	4-1000 kcmil	4-1000 kcmil	600	600	400	200	60	30	100	600
PTPOWER 35, PTPOWER 35-F, PTPOWER 35-PE	2-14 AWG	2-14 AWG	100	100	60	30	60	30	100	600
PTPOWER 95, PTPOWER 95-F, PTPOWER 95-F-P, PTPOWER 95 P, PTPOWER 95-PE	4-4/0 AWG	4-4/0 AWG	200	200	100	30	60	30	100	600
PT POWER 150, PTPOWER 150 P, PTPOWER 150-F	1/0-300 kcmil	1/0-300 kcmil	400	400	200	100	60	30	100	600
PT 16 N, PT 16 N-PE, PT 16-TWIN N, PT 16-TWIN N-PE	14-4	14-4	60	60	30	—	50	30	100	600
Note: (1) Followed by suffixes -M8, -M10, -M12, -M16, -AS or KH, additionally followed by suffixed /M8, /M10, /M12, /M16, /AS, or /KH.										

Cat. No.	Suitable Conductors kcmil/AWG		OverCurrent Protection [Circuit Breaker] [Self-protected Combination Motor Controller] Required			SCCR, RMS Sym, kA	Volts Max
	Line	Load	Mfr	Type	Max Amp		
PT6	14-8 Str.	14-8 Str.	Mitsubishi	NV50-SVFU (20A 120-240V 30MA)	20	14	240 ac 3 ph
	14-8 Str.	14-8 Str.	Mitsubishi	NV50-SVFU (30A 120-240V 30MA)	30	14	240 ac 3 ph
PT6/1P With PP-H6 Plug	14-8 Str.	14-8 Str.	Mitsubishi	NV50-SVFU (5A, 10A, 15A, 20A 120-240V 30MA)	20	14	240 ac 3 ph
	14-8 Str.	14-8 Str.	Mitsubishi	NV50-SVFU (5A, 10A, 15A, 20A, 30A 120-240V 30MA)	30	14	240 ac 3 ph
USLKG 95	2-4/0 Str	2-4/0 Str	Siemens	3VA52..	250	65	480
UKH 95	2-4/0 Str	2-4/0 Str	Siemens	3VA52..	250	65	480

UT 2,5, UT 2,5-PE	14-12 Str	14-12 Str	Siemens	3V2711.., 3RV2811..	15	65	480
	14-12 Str	14-12 Str	Siemens	3V2721.., 3RV2821..	22	50	480
UT 2,5, UT 2,5-PE	14-12 Str	14-12 Str	Siemens	3RV2011.., 3RV2021..	25	65	480
UT 4, UT 4-PE, UT 4-QUATTRO-HV, UT 4-TWIN-HV	14-10 Str	14-10 Str	Siemens	3V2711.., 3RV2811..	15	65	480
	14-10 Str	14-10 Str	Siemens	3V2721.., 3RV2821..	22	50	480
UT 4, UT 4-PE, UT 4-QUATTRO-HV, UT 4-TWIN-HV	14-10 Str	14-10 Str	Siemens	3RV2011.., 3RV2021..	25	65	480
UT 10, UT 10-PE	14-6 Str	14-6 Str	Siemens	3V2721.., 3RV2821..	22	50	480
	14-6 Str	14-6 Str	Siemens	3VA51..	60	65	480
UT 10, UT 10-PE	14-6 Str	14-6 Str	Siemens	3RV2031.., 3RV2032..	52	65	480
UT 6, UT 6-PE	14-8 Str	14-8 Str	Siemens	3V2721.., 3RV2821..	22	50	480
UT 6, UT 6-PE	14-8 Str	14-8 Str	Siemens	3RV2011.., 3RV2021..	32	50	480
	14-8 Str	14-8 Str	Siemens	3RV2011.., 3RV2021..	25	65	480
UT 16, UT 16-PE	14-4 Str	14-4 Str	Siemens	3RV2742..	70	65	480
	14-4 Str	14-4 Str	Siemens	3VA51..	125	65	480
UT 16, UT 16-PE	14-4 Str	14-4 Str	Siemens	3RV2041.., 3RV2042..	100	65	480
UT 35, UT 35-PE	14-1/0 Str	14-1/0 Str	Siemens	3VA51..	125	65	480
UT 35, UT 35-PE	14-1/0 Str	14-1/0 Str	Siemens	3RV2041.., 3RV2042..	100	65	480
PT 2.5, PT 2.5-TWIN, PT 2.5-QUATTRO, PT 2.5-PE, PT 2.5-TWIN-PE, PT 2.5-QUATTRO-PE	14-12 Str	14-12 Str	Siemens	3RV2721.., 3RV2821..	22	50	480
PT 2.5, PT 2.5-TWIN, PT 2.5-QUATTRO, PT 2.5-PE, PT 2.5-TWIN-PE, PT 2.5-QUATTRO-PE	14-12 Str	14-12 Str	Siemens	3V2711.., 3RV2811..	15	65	480
PT 2.5, PT 2.5-TWIN, PT 2.5-QUATTRO, PT 2.5-PE, PT 2.5-TWIN-PE, PT 2.5-QUATTRO-PE	14-12 Str	14-12 Str	Siemens	3RV2011.., 3RV2021..	25	65	480

PT 4, PT 4-TWIN, PT 4-QUATTRO, PT 4-PE, PT 4-TWIN-PE, PT 4-QUATTRO-PE	14-10 Str	14-10 Str	Siemens	3RV2721.. 3RV2821..	22	50	480
PT 4, PT 4-TWIN, PT 4-QUATTRO, PT 4-PE, PT 4-TWIN-PE, PT 4-QUATTRO-PE	14-10 Str	14-10 Str	Siemens	3V2711.. 3RV2811..	15	65	480
PT 4, PT 4-TWIN, PT 4-QUATTRO, PT 4-PE, PT 4-TWIN-PE, PT 4-QUATTRO-PE	14-10 Str	14-10 Str	Siemens	3RV2011.. 3RV2021..	25	65	480
PT 6, PT 6-TWIN, PT 6-QUATTRO, PT 6-PE, PT 6-TWIN-PE, PT 6-QUATTRO-PE	14-8 Str	14-8 Str	Siemens	3RV2721.. 3RV2821..	22	50	480
PT 6, PT 6-TWIN, PT 6-QUATTRO, PT 6-PE, PT 6-TWIN-PE, PT 6-QUATTRO-PE	14-8 Str	14-8 Str	Siemens	3RV2021..	32	50	480
PT 10, PT 10-TWIN, PT 10-PE, PT 10-TWIN-PE	14-6 Str	14-6 Str	Siemens	3RV2721.., 3RV2821..	22	50	480
	14-6 Str	14-6 Str	Siemens	3VA51..	22	65	480
PT 10, PT 10-TWIN, PT 10-PE, PT 10-TWIN-PE	14-6 Str	14-6 Str	Siemens	3RV2031.. 3RV2032..	52	65	480
PT 16 N, PT 16-TWIN N, PT 16 N-PE, PT 16-TWIN N-PE	14-4 Str	14-4 Str	Siemens	3RV2742	70	65	480
PT 16 N, PT 16-TWIN N, PT 16 N-PE, PT 16-TWIN N-PE	14-4 Str	14-4 Str	Siemens	3VA51..	125	65	480
PT 16 N, PT 16-TWIN N, PT 16 N-PE, PT 16-TWIN N-PE	14-4 Str	14-4 Str	Siemens	3RV2041.., 3RV2042..	100	65	480
PTPOWER 35, PTPOWER 35-F, PTPOWER 35-PE	14-2 Str	14-2 Str	Siemens	3VA51..	125	65	480
PTPOWER 50, PTPOWER 50P, PTPOWER 50-F, PTPOWER 50-PE PTPOWER 50P-F	8-1/0 Str	8-1/0 Str	Siemens	3VA51..	125	65	480
PTPOWER 35, PTPOWER 35-F, PTPOWER 35-PE	14-2 Str	14-2 Str	Siemens	3RV2041.., 3RV2042..	100	65	480
PTPOWER 50, PTPOWER 50P, PTPOWER 50-F, PTPOWER 50-PE PTPOWER 50P-F	8-1/0 Str	8-1/0 Str	Siemens	3RV2041.., 3RV2042..	100	65	480

PTPOWER 95, PTPOWER 95-F, PTPOWER 95-F-P, PTPOWER 95 P, PTPOWER 95-PE	4-4/0 Str	4-4/0 Str	Siemens	3VA52..	250	65	480
--	--------------	--------------	---------	---------	-----	----	-----

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
PRC 3-FT-MPCB-HW	—	—	—	300	20	B	2 (115)
					Note A	D	
PHW-PC-FC-PL4-3 8.5-14.5	16-12, Str/Sol	Cu	—	300	20	B, C	2 (115), #1
HW-PC-FT20-C4-3	16-14, Str/Sol	Cu	—	300	20	B, C	2 (115), #1
MCDN, followed by 1.5, followed by /12, followed by -G1U, followed by -3,5, followed by RN, followed by P26, followed by THR, followed by 2CP.	—	—	—	160	8	B	2 (130)
					Note A	D	
DFK, followed by -MSTB, followed by 2,5, followed by /, followed by 2 thru 24, followed by -STF, followed by -5,08, followed by -LR.	24~12, SOL/STR	Cu	0.6	300	12	B	2 (115), 4
					Note A	D	
Note: A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.							

#1 The terminal blocks as tabulated below consist of two halves with plug consisting of the push-in type (wire secured by spring type action) terminals and header consisting of the soldering terminals. These devices have not been evaluated to make or break the flow of current. These devices are not evaluated for use with any other mating connectors.

Cat. No.	Wire Range AWG	Wire Type	FW	TQ Lb-in	V	A	UG	CA
PT 10-MTL KNIFE, PT 10-MT, PT 10-TG	20-6	Cu	2	NA	300	20	B,C	2 (115)
					600	5	D	2 (115)
PT 10-FSI/C, PT 10-FSI/C-LED 12, PT 10-FSI/C-LED 24, PT 10-FSI/C-LED 48	20-6	Cu	2	NA	300	30	B,C	2 (115)
					600	5	D	2 (115)
PT 10-HESI (6.3X32), PT 10-HESILED 24 (6.3X32) PT 10-HESILED 250 (6.3X32)	20-6	Cu	2	NA	300	10	B,C	2 (115)

					600	5	D	2 (115)
--	--	--	--	--	-----	---	---	------------

Cat. No.	Wire Range	Wire Type	TQ Lb In.	V	A	UG	CA
FKC 2.5 HC/ 8-ST NGFT JUMP	12-26	Cu	--	300	20	B, D	2 (105)

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
PT 2.5 / FT 2.5	26 - 12 str/sol	Cu	N/A	300	20	B, C	2 (115)
				600	5	D	2 (115)
PT 2.5-MT / FT 2.5-MT	26 - 12 str/sol	Cu	N/A	300	20	B, C	2 (115)
				600	5	D	2 (115)
PT 2.5-TG / FT 2.5-TG	26 - 12 str/sol	Cu	N/A	300	20	B, C	2 (115)
				600	5	D	2 (115)
PT 2.5-MTB / FT 2.5-MTB	26 - 12 str/sol	Cu	N/A	300	20	B, C	2 (115)
				600	5	D	2 (115)
PT 2.5-TGB / FT 2.5-TGB	26 - 12 str/sol	Cu	N/A	300	20	B, C	2 (115)
				600	5	D	2 (115)
PT 2.5-TWIN-MT / FT 2.5-TWIN-MT	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5-TWIN-TG / FT 2.5-TWIN-TG	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5-TWIN-MTB / FT 2.5-TWIN-MTB	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5-TWIN-TGB / FT 2.5-TWIN-TGB	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5-QUATTRO-MT / FT 2.5-QUATTRO-MT	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)

	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5- QUATTRO-TG / FT 2.5- QUATTRO-TG	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5- QUATTRO-MTB / FT 2.5- QUATTRO-MTB	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
PT 2.5-QUATTRO-TGB / FT 2.5-QUATTRO-TGB	26 - 12 str	Cu	N/A	300	20	B, C	2 (115)
	26 - 12 sol				16	B, C	2 (115)
	26 - 12 str/sol			600	5	D	2 (115)
UT 4-L/HESI (5x20) /DIO/U-OL, UT 4-L/HESILED 24 (5X20) /DIO/U-OL, UT 4-L/HESILED 60 (5X20) /DIO/U-OL, UT 4-L/HESILA 250 (5X20) /DIO/U-OL, UT 4-L/HESILED 250 (5X20) /DIO/U-OL, UT 4-L/HESI (5x20) /DIO/O-UL, UT 4-L/HESILED 24 (5X20) /DIO/ O-UL, UT 4-L/HESILED 60 (5X20) /DIO/ O-UL, UT 4-L/HESILA 250 (5X20) /DIO/ O-UL, UT 4-L/HESILED 250 (5X20) /DIO/ O-UL	(Upper) 26 - 10	Cu	(0.6-0.8) 5-7	300	16	B, C	2(105), 4
	(Lower) 26- 10	Cu	(0.6-0.8) 5-7	300	20	B, C	2(105), 4
P-FU 5X20	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20-5	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20-LED 24	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LED 24 120KOHM	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LED 24-5	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LED 24-5 120 KOHM	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LED 60	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LED 60-5	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LA 250	NA	NA	NA	300	10	B,C,D	2(105), 4
P-FU 5X20 LED 250-5	NA	NA	NA	300	10	B,C,D	2(105), 4
FP (5X20)	NA	NA	NA	300	10	B,C,D	2(105), 4

FP (5X20) 24, 60, 250	NA	NA	NA	300	10	B,C,D	2(105), 4
BTFE 6-3, may be followed by /x, nU, AUX, /x nU, /x AUX, nU AUX, /x nU AUX	20-10 Str/Sol	Cu	1-1.3 Nm	300	30	B, C	2(105)
				600	5	D	2(105)
FTP-3F, may be followed by /x, nU, /x nU***	N/A	N/A	N/A	300	30	B, C	2(105)
				600	5	D	2(105)
FBP-3F, may be followed by /x, nU, AUX, /X nU, /X AUX, nU AUX, /X nU AUX***	N/A	N/A	N/A	N/A	N/A	N/A	2(105),4
*** FTP-3F, may be followed by /x, nU, /x nU and FBP-3F, may be followed by /x, nU, AUX, /x nU, /x AUX, nU AUX, /x nU AUX are plugs. They always used with main articles BTFE 6-3, may be followed by /x, nU, AUX, /x nU, /x AUX, nU AUX, /x nU AUX. They are not used as standalone articles.							

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
C-HW-CBC-CF-M5Z2L-10-35-2.	8-2, STR	CU	2	26.5	300	125	B, C	2(115)
						Note A	D	
C-HW-CBC-FT-CM-B-M6H1L-2.	8-2, STR	CU	2	26.5	300	125	B, C	2(120), 5
						Note A	D	
PC 10/ 2-STL-8,5-52A-WS	8-6 AWG, Str	CU	2	1.4 - 1.5	72	52	B	2(115), #1
						Note A	D	
PC 10/ 2-GL-7,2-52A	—	—	1	—	72	52	B	2(115), #1
						Note A	D	

#1 The terminal blocks as tabulated below consist of two halves with plug consisting of the pressure wire terminals and the header consisting of the soldering terminals. These devices as tabulated below are not evaluated for use with any other mating connectors.

Plug	Header
PC 10/ 2-STL-8,5-52A-WS	PC 10/ 2-GL-7,2-52A

Note:

Some models have been transferred from file E469679.

(1) Followed by /1-digit number, and by Suffix -ST, -STD, -STF or -SH, followed by -10.16, w/wo suffix RAE.

(1) With or without suffixes BK, BU or GNYE.

(1) 16A max. for factory-wiring only.

(2) Followed by /1-digit number, and by Suffix -G or -GF, followed by -10.16, with or without Suffix CODED.

(3) Ampere and voltage rating not applicable for lower level grounding terminals.

(4) 5A max. at 600V (Limited VA, industrial use).

(5) 15 lb.-in. torque for No. 6 AWG only. 11-15 lb.-in. for all other wire sizes.

All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

/X denotes one or two digit number.

(#) Feedthrough levels - 600; gndg. level-N/A

(##) Feedthrough level - 30; gndg. level N/A

All Cat. Nos. in reports dated 4-27-1977/3-31-1987/10-11-1993/10-11-1993/10-12-1993/10-13-1993 which provide pressure screw terminals may have Suffix H0L, H1L, SO1 or Z1L denoting combination Phillips/slotted head screws) added to end of Cat. No.

(@@) All PIT(S), PITB(S), PITI, PITO Series may have the optional letter "I" removed in the Cat. No. Ex.- PT, PITB(S), PTO, etc

Marking: Company name, trademarks ,  and Recognized Component Mark for Canada , on the product or on the smallest unit container in which the product is packaged. Catalog designation, maximum voltage, wire range, and amp rating appear on the device or in or on the carton.

Last Updated on 2022-09-03

Der Umstand, dass der Name oder das Produkt eines Unternehmens in dieser Datenbank aufgeführt ist, garantiert nicht, dass die Herstellung der jeweiligen Produkte dem Follow-Up-Service von UL unterliegt. Nur Produkte mit UL-Zeichen gelten als zertifiziert und sind vom Follow-Up-Service von UL abgedeckt. Prüfen Sie daher stets, ob ein Produkt das UL-Zeichen trägt.

UL gestattet die Weiterverwendung der im Online-Zertifizierungsverzeichnis enthaltenen Materialien unter den folgenden Bedingungen: 1. Alle Anleitungen, Baugruppen, Konstruktionen, Designs, Systeme und/oder Zertifizierungen (Dateien) müssen vollständig und auf nicht irreführende Weise ohne Manipulation der Daten (oder Zeichnungen) dargestellt werden. 2. Bei Weiterverwendung von Materialien muss der Vermerk „Aus dem Online-Zertifizierungsverzeichnis mit Genehmigung von UL nachgedruckt“ stets mit angegeben werden. Darüber hinaus muss das nachgedruckte Material einen Urheberrechtsvermerk in folgendem Format enthalten: "© 2022 UL LLC"