

CERTIFICATE OF COMPLIANCE

Certificate Number E60425
Report Reference E60425-19870331
Date 2021-December-30

Issued to: PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8
Blomberg 32825 DE

This is to certify that
representative samples of TERMINAL BLOCKS - COMPONENT
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 1059 TERMINAL BLOCKS
CAN/CSA C22.2 No. 158-10 TERMINAL BLOCKS

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E60425
Report Reference E60425-19870331
Date 2021-December-30

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Component Terminal Blocks

Types GMKDS 3, GMKDSP3, GSMKDS 3, followed by one or two digit number; may be followed by -7.62

Type MKDSF 3 followed by /one or two digit number, with or without S01, may be followed by -5.08

Type MKDSFW3 followed by /one or two digit number

Type MKDSP 3 followed by /one or two digit number, may be followed by -5.08

Types SMKDS, SMKDSFU followed by Suffixes 1.5, 2.5, 3, 5, followed by /one or two digit number may be followed by -5.08, -6.35 or -9.5; may be followed by HT BK

Type SMKDSP1.5 followed by a 1 or 2-digit number, with or without -5.08

Types DFLK-D37 Sub, DFLK-D50 Sub followed by /B, or /S

Types DFLK-D followed by one or two-digit number, and by Sub/B, or Sub/S. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>