

Certificate of Compliance

Certificate Number(s):

UL-US-L60425-6187161-
31013991-13
UL-US-2351610-10
UL-US-2354495-9
UL-US-2354496-9
UL-US-2354497-9

Report Reference:

E60425-19931013

Issue Date:

2026-01-20

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstrasse 8, Blomberg, 32825, DE

This certificate confirms that representative samples of:
XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-L60425-6187161-31013991-13, UL-US-2351610-10, UL-US-2354495-9, UL-US-2354496-9, UL-US-2354497-9
Report reference: E60425-19931013
Issue Date: 2026-01-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): GSMSTB 2.5 followed by /one or two digit number, followed by Suffix -ST, STF or STFS59, may be followed by or 7.62.

Terminal Blocks - Component

Model(s): GMSTBA, Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBP Suffixes -ST, w/wo -7.62 w/wo RDB All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GCCA Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffixes -G, -GF may be followed by -15.24, may be followed by -1, -2, -LA, -R, -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMVSTBW 2.5, followed by /one- or two-digit number, followed by Suffix HV, and Suffixes -ST or ST 7.62 or /8-STGY3XEB2. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBVA followed by Suffix 2.5, followed by /one or two digit number, followed by -G or -GF, may be followed by 15.24, may be followed by -1, -2, -LA -R or -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBT 2.5 HV/ followed by one-digit number followed by suffix -ST followed by suffix -7.25. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBO 2.5 HV/, followed by one-digit number, followed by suffix -GL, -GR, followed by suffix -7.25, may be followed by THR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GFKC 2.5 followed by /one- or two-digit number, by Suffix -ST, -STF, or -STF-SH followed by -7.5 or -7.62, may be followed by RDB or RAE. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBT 2.5 HV/3-ST-7.25 KMGY PA2, GMSTB, Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffix -GU, GMSTB, Suffixes 2.5, followed by /one or two-digit number., Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R or -HT, may be followed by -LR., GMVSTBR, Suffixes 2.5, followed by /one or two-digit number, Suffixes -ST or -STF, followed by -7.62., GMVSTBW, Suffixes 2.5, followed by /one or two-digit number, Suffixes -ST or -STF, followed by -7.62., GMVSTBR, Suffixes 2.5, followed by /one or two-digit number, Suffixes -HV, followed by -ST or -ST.7.62 or /8-STGY3XEB2., GMSTBV, Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffix -GU., GFKIC2.5 f/X f/b -ST, STF, -STF-SH - f/b -7.5, -7.62, GMSTB, Suffixes 2.5, followed by HCV, followed by / one or two digit number, Suffixes -ST, w/wo -7.62 w/wo RDB., GMSTB, Suffixes 2.5, followed by /one or two-digit number, Suffixes -ST, w/wo -15.24, -1, -2., GMSTBAS2.5/4-G-7.62, GMVSTBR, Suffixes 2.5, followed by HC, followed by / one or two digit number, Suffixes -ST or -STF, followed by -7.62., GMSTB, Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffixes -ST, w/wo -15.24, -1, -2., GMVSTBW, Suffixes 2.5, followed by HC, followed by / one or two digit number Suffixes -ST or -STF, followed by -7.62., GMSTB, f/X f/b -ST, STF, f/b -7.5, -7.62, w/wo RDB., GMVSTBR 2.5, f/X w/wo-ST, f/b -7.62, f/b -PA13 SO, GFKC2.5 HC f/X f/b -ST, STF, f/b -7.5, -7.62, w/wo RDB, RAE All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-L60425-6187161-31013991-13, UL-US-2351610-10, UL-US-2354495-9, UL-US-2354496-9, UL-US-2354497-9
Report reference: E60425-19931013
Issue Date: 2026-01-20

Model(s): GMSTBO 2.5 HV/3, followed by –GL or –GR, followed by -7.25 THR, followed by PA1.3. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTB ,Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GCCA, Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBV, Suffixes 2.5, followed by /one or two-digit number. Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R or -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBVA , Suffixes 2.5, followed by /one or two-digit number., GMSTB, Suffixes 2.5, followed by /one or two-digit number, Suffixes -G, -GF or -GU, may be followed by -7.62 or -15.24, may be followed by -1, -2, -LA, -R, -HT, may be followed by -LR, may be followed by 24MM. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTB ,Suffixes 2.5, followed by /one or two-digit number. Suffixes -ST or -STF, followed by -7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBP, Suffixes 2.5, followed by /one or two-digit number. Suffixes -ST, w/wo -15.24, -1, -2. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBV Suffixes 2.5, may be followed by HC, followed by / one or two digit number ,Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBA Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R or -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTB 2.5 f/x HV/X f/b -ST, f/b 7.62, w/wo RDB, w/wo LR, w/wo 2 digit no, w/wo AU. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBHK, UGMSTBHK followed by Suffix 2.5, followed by /10 G, may be followed by 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): FRONT-GMSTB followed by Suffix 2.5, followed by /one- or two-digit number, followed by Suffix ST or STF., followed by 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBVA followed by Suffix 2.5, with Suffix HC, followed by /one or two digit number, followed by -G or -GF or -GU, may be followed by 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBV ,Suffixes 2.5, followed by /one or two-digit number, Suffixes -G, -GF or -GU, may be followed by -7.62 or -15.24, may be followed by -1, -2, -LA, -R, -HT, may be followed by -LR, may be followed by 24MM. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



Certificate of Compliance

Certificate Number(s):

UL-CA-L60425-6189161-
31013991-13
UL-CA-2344896-9
UL-CA-2347396-9
UL-CA-2347397-9
UL-CA-2347398-9

Report Reference:

E60425-19931013

Issue Date:

2026-01-20

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstrasse 8, Blomberg, 32825, DE

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-L60425-6189161-31013991-13, UL-CA-2344896-9, UL-CA-2347396-9, UL-CA-2347397-9, UL-CA-2347398-9
Report reference: E60425-19931013
Issue Date: 2026-01-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): GSMSTB 2.5 followed by /one or two digit number, followed by Suffix -ST, STF or STFS59, may be followed by or 7.62.

Terminal Blocks - Component

Model(s): GMSTBA, Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBP Suffixes -ST, w/wo -7.62 w/wo RDB All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GCCA Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffixes -G, -GF may be followed by -15.24, may be followed by -1, -2, -LA, -R, -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMVSTBW 2.5, followed by /one- or two-digit number, followed by Suffix HV, and Suffixes -ST or ST 7.62 or /8-STGY3XEB2. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBVA followed by Suffix 2.5, followed by /one or two digit number, followed by -G or -GF, may be followed by 15.24, may be followed by -1, -2, -LA -R or -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBT 2.5 HV/ followed by one-digit number followed by suffix -ST followed by suffix -7.25. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBO 2.5 HV/, followed by one-digit number, followed by suffix -GL, -GR, followed by suffix -7.25, may be followed by THR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GFKC 2.5 followed by /one- or two-digit number, by Suffix -ST, -STF, or -STF-SH followed by -7.5 or -7.62, may be followed by RDB or RAE. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBT 2.5 HV/3-ST-7.25 KMGY PA2, GMSTB, Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffix -GU, GMSTB, Suffixes 2.5, followed by /one or two-digit number., Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R or -HT, may be followed by -LR., GFKIC2.5 f/X f/b -ST, STF, -STF-SH - f/b -7.5, -7.62, GMVSTBR, Suffixes 2.5, followed by /one or two-digit number, Suffixes -ST or -STF, followed by -7.62., GMVSTBW, Suffixes 2.5, followed by /one or two-digit number, Suffixes -ST or -STF, followed by -7.62., GMVSTBR, Suffixes 2.5, followed by /one or two-digit number, Suffixes -HV, followed by -ST or -ST.7.62 or /8-STGY3XEB2., GMSTBV, Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffix -GU., GFKC2.5 HC f/X f/b -ST, STF, f/b -7.5, -7.62, w/wo RDB, RAE, GMSTB, Suffixes 2.5, followed by HCV, followed by / one or two digit number, Suffixes -ST, w/wo -7.62 w/wo RDB., GMSTB, Suffixes 2.5, followed by /one or two-digit number, Suffixes -ST, w/wo -15.24, -1, -2., GMSTBAS2.5/4-G-7.62, GMVSTBR, Suffixes 2.5, followed by HC, followed by / one or two digit number, Suffixes -ST or -STF, followed by -7.62., GMSTB, Suffixes 2.5, may be followed by HC, followed by / one or two digit number, Suffixes -ST, w/wo -15.24, -1, -2., GMVSTBW, Suffixes 2.5, followed by HC, followed by /

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-L60425-6189161-31013991-13, UL-CA-2344896-9, UL-CA-2347396-9, UL-CA-2347397-9, UL-CA-2347398-9
Report reference: E60425-19931013
Issue Date: 2026-01-20

one or two digit number Suffixes -ST or -STF, followed by -7.62., GMSTB, f/X f/b -ST, STF, f/b -7.5, -7.62, w/wo RDB., GMVSTBR 2.5 , f/X w/wo-ST, f/b-7.62, f/b -PA13 SO All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBO 2.5 HV/3, followed by -GL or -GR, followed by -7.25 THR, followed by PA1.3. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTB , Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GCCA, Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBV, Suffixes 2.5, followed by /one or two-digit number. Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R or -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBVA , Suffixes 2.5, followed by /one or two-digit number., GMSTB, Suffixes 2.5, followed by /one or two-digit number, Suffixes -G, -GF or -GU, may be followed by -7.62 or -15.24, may be followed by -1, -2, -LA, -R, -HT, may be followed by -LR, may be followed by 24MM. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTB , Suffixes 2.5, followed by /one or two-digit number. Suffixes -ST or -STF, followed by -7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBP, Suffixes 2.5, followed by /one or two-digit number. Suffixes -ST, w/wo -15.24, -1, -2. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBV Suffixes 2.5, may be followed by HC, followed by / one or two digit number , Suffixes -G or -GF or -GU may be followed by - 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBA Suffixes 2.5, may be followed by HC, followed by / one or two digit number. Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R or -HT, may be followed by -LR. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTB 2.5 f/x HV/X f/b -ST, f/b 7.62, w/wo RDB, w/wo LR, w/wo 2 digit no, w/wo AU. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBHK, UGMSTBHK followed by Suffix 2.5, followed by /10 G, may be followed by 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): FRONT-GMSTB followed by Suffix 2.5, followed by /one- or two-digit number, followed by Suffix ST or STF., followed by 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBVA followed by Suffix 2.5, with Suffix HC, followed by /one or two digit number, followed by -G or -GF or -GU, may be followed by 7.62. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.

Model(s): GMSTBV , Suffixes 2.5, followed by /one or two-digit number, Suffixes -G, -GF or -GU, may be followed by -7.62 or -15.24, may be followed by -1, -2, -LA, -R, -HT, may be followed by -LR, may be followed by 24MM. All cat. nos. having pressure screws may be followed by Suffix H0L, H1L or Z1L.