

Certificate of Compliance

Certificate Number:

UL-US-L60425-6187159-
11013991-13

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:
XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-6187159-11013991-13
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-6187159-11013991-13
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-6187159-11013991-13
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-6187159-11013991-13
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): CC, CCA, CCVA, CCV (1)(13)

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number	UL-US-L60425-6187159-11013991-13
Report reference	E60425-19931011
Date	2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L *Suffixes - G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX*

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FKC2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FKC2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKCOR2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2., MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

© 2025 UL LLC. All rights reserved.
Form-ULID-019496 – ver 1.0

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L60425-6187159-11013991-13
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBT2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409491-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409491-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409491-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409491-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409491-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409491-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409491-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409492-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409492-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409492-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409492-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409492-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409492-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409492-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409493-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409493-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409493-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409493-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409493-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409493-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409493-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409494-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409494-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409494-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409494-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409494-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409494-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409494-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409495-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409495-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409495-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409495-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409495-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409495-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409495-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409496-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409496-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409496-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409496-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409496-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409496-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409496-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409497-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409497-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409497-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409497-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409497-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409497-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409497-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409498-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409498-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409498-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409498-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409498-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409498-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409498-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409499-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409499-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409499-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409499-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409499-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409499-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409499-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409500-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409500-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409500-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409500-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409500-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409500-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409500-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-US-2409501-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409501-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409501-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409501-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409501-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409501-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FKC2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FKC2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2409501-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-L60425-6189159-
11013991-11

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-6189159-11013991-11
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-6189159-11013991-11
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-6189159-11013991-11
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-6189159-11013991-11
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): CC, CCA, CCVA, CCV (1)(13)

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters,



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-6189159-11013991-11
Report reference E60425-19931011
Date 2025-12-15

designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FKCT2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKCOR2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G,



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L60425-6189159-11013991-11
Report reference E60425-19931011
Date 2025-12-15

GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408277-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408277-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408277-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408277-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408277-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408277-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408277-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408278-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Owner



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408278-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408278-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408278-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408278-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408278-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408278-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408279-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408279-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408279-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408279-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408279-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408279-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408279-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408280-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408280-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408280-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408280-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408280-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408280-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408280-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408281-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408281-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408281-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408281-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408281-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408281-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408281-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408282-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

**PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany**

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408282-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408282-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408282-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408282-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408282-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408282-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408283-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Owner



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408283-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408283-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408283-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408283-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408283-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408283-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408284-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408284-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408284-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408284-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408284-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408284-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408284-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408285-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408285-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408285-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408285-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408285-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408285-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408285-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408286-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408286-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by /one or two digit number, followed by -ST, -STD, -STF, -STE, -STGF, -STB or -STZ, may be followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX, NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408286-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by/one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by/one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408286-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, -10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408286-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by/one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by/one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408286-5
Report reference E60425-19931011
Date 2025-12-15

variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKOW2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408286-5
Report reference E60425-19931011
Date 2025-12-15

GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2408287-5

Report Reference:

E60425-19931011

Issue Date:

2025-12-15

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8 Blomberg 32825
Germany

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Terminal Blocks

Model(s): TB 4-L-HESILA 250 (5X20) EI, TB 4-L-HESILED 24 (5X20) EI, TB 4-L-HESILED 60 (5X20) EI
Model(s): TB-EE-UTF 2.5, TB-EE-UTF 2.5-HESI (5X20), TB-EE-UTF 2.5-HESILA250 (5X20), TB-EE-UTF 2.5-HESILED 24 (5X20), TB-EE-UTF 2.5-MT All cat. nos. may be followed additional suffixes (any combination of letters, symbols (-, / etc.), space and/or numbers) designating non-electrical variations such as color, customer identification, packaging or plating options.

Model(s): MSTB2.5 followed by /2, followed by Suffix -STFL-5.08, or -GFL-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, CCA followed by Suffix 2.5, CCV followed by Suffix 2.5 followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB2.5 followed by /one or two digit number, followed by Suffix -ST-5.08 and by BGH1L SO1. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): EMSTB2.5, EMSTBA2.5, EMSTBV2.5, EMSTBVA2.5 followed by /one or two digit number, followed by Suffix -G or -GF, may be followed by -5.08, -10.16, may be followed by -LR, EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC followed by Suffix 2.5, followed by /one or /two digit number, CCV followed by Suffix 2.5, followed by /one or /two digit number followed by GSF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FKC, FKCOR, FKCOV, FKCS, FKCT, FKCVR, FKCVW, FKIC, FKICS followed by Suffix 2.5 with or without HC, followed by/one or two digit number, followed by -ST, -STD, -STF, -STEH, -STGF, -STB or -STZ, may followed by Suffix -5.08, -10.16 may be followed by RDB and/or NZ:EH, may be followed by -LR, -RF, -RN, -A, -EX,



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

NGFT-JUMP or -NGFT SAPP. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, GF, GL, GR, GFL, or GFR, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), followed by -5.08, may be followed by -LR, -RN, followed by P14 THR, P20 THR, P26THR. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): CC, CCA, CCV, CCVA followed by Suffix 2.5, followed by /one or /two digit number, followed by -G, -GF, may be followed by color code (BK, GN, RD, BU or any other color abbreviation), may be followed by -LR, followed by P14 THR, P20 THR, P26 THR or NGFT SAPH. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB, DFK-MSTBA, DFK-MSTBVA followed by Suffix 2.5, followed by /one or two digit number, followed by Suffix -G, or -GF, with or without Suffix WW1x1, followed by Suffix -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TFKC followed by Suffix 2.5, may be followed by HC, followed by /one or two digit number, followed by -ST or -STF, followed by -5.08, may be followed by RDB, may be followed by -LR, AU, or EX. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTBA followed by Suffix 2.5, with or without HC, followed by /one or two digit number, followed by -G, -GF -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TMSTBP followed by Suffix 2.5, with or without HC, followed by /one or two digit number, followed by -ST, or -STF, followed -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTBVAL, MSTBVL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): A-MSTBV, A-MSTBVA, MSTBA, MSTBAG, MSTBV, MSTBVA, MSTBVAG, MSTBVW, MSTBW followed by Suffix 2.5, with or without Suffixes HC and/or L, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAL followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MSTB, MSTBP, MSTBT followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, followed by Suffix -ST, -STF or -STZ, followed by -5.08, -10.16-1, 10.16-2, may be followed by RDB, may be followed by -AB, -AU, -LR, -SO, P+F, -DOM, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -GL, or -GR, followed by -5.08, followed by P+F2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MDSTB, MDSTBV, MDSTBVA, MDSTBVH, MDSTBVHA, MDSTBW followed by Suffix 2.5, followed by one or two digit number, followed by -G, -GF, -GFL, -GFR, -GL, -GR or -G1, followed by -5.08, -10.16-1, or -10.16-2. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB, SMSTBA followed by Suffix 2.5, followed by one or two digit number, followed by -G, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY, or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): SMSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF, followed by -5.08, -10.16-1, or -10.16-2, may be followed by -AU, -BK, -ABGY or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FRONT-MSTB followed by Suffix 2.5, followed by one or two digit number, followed by -ST, -STF or STF1, followed by -5.08, -10.16-1, or -10.16-2, may be followed by RDB, may be followed by -AU, -BK, -ABGY, EMC or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTB followed by Suffix 2.5, with or without Suffixes HC, followed by one or two digit number, followed by -G, -GB, -G0.5, -GF, -GFSO or -GEH, followed by -5.08, -10.16 with or without -1 or -2, may be followed by -RN, -LA, -LAB/RD, -LR, -KM with or without -H, -R, -AU, -BK, -ABGY, -4.45, -6.03, -THT, with or without PXX or combinations thereof.

Model(s): MVSTBN, MVSTBR, MVSTBW followed by Suffix 2.5, with or without Suffix HC, followed by one or two digit number, may be followed by -one or two digit number, followed by -ST, or -STF, followed by -5.08, -10.16 with or without -1, or -2, may be followed by -KM, -GY, -AU, -BK, -ABGY, DOM or combinations thereof. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -ST-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): TVMSTB 2.5/ followed by one or two digit number followed by -STF-5.08. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MVSTBR ASI/ 4-ST-5.08, MVSTBW ASI/ 4-ST-5.08 may be followed by RDB, may be followed by suffix -KM, -AU, -MS, -BK, -ABGY, SO, PA, S or SI, RF, RN. Cat. No. having pressure screws may be followed by Suffix H0L, H1L or Z1L. May be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Component terminal blocks



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): TB4-L-HESI-(5X20) EI (Lower Level), TB4-L-HESI-(5X20) EI (Upper Level) *All cat. nos. may be followed additional suffixes (any combination of letters, symbols (-, / etc.), space and/or numbers) designating non-electrical variations such as color, customer identification, packaging or plating options.*

Terminal Blocks - Component

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX, -THT

Model(s): CCDN2.5 f/b/one or two digit number, f/b -G1, -G1F, w/wo -5.08 and/orbP26 THR, MSTB 2,5 HC/4-GF EMC, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBO2.5, followed by /2, /3 or /4 followed by G1PL or G1PR *All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.*

Model(s): TB 2.5 EI, TB 2.5 I, TB 2.5-B-PE-EC, TB 2.5-B-PE-I, TB10 EC, TB10 EI, TB10 I, TB10 TWIN I, TB10-PE EB, TB10-PE EC, TB10-PE I, TB16 C, TB16 ECH, TB16 EI, TB16 I, TB16 C HI, TB16-PE ECH, TB16-PE EI, TB16-PE I, TB2.5 B I, TB2.5 EC, TB2.5 PE-EB, TB2.5 PE-EC, TB2.5 PE-I, TB2.5-2L EI, TB2.5-2L I, TB2.5-2L-BCP/2P I, TB2.5-3L I, TB2.5-3L-LA 24RD/O-M I, TB2.5-3L-LA 24RD/U-O I, TB2.5-3PV I, TB2.5-BCP/2P I, TB2.5-BCVP/1P I, TB2.5-L/L/TG I, TB2.5-L/LB I, TB2.5-L/LB-PV I, TB2.5-PE/3L I, TB2.5-QUATTRO EI, TB2.5-Quattro I, TB2.5-TWIN EI, TB2.5-TWIN I, TB3 I, TB3-PE I, TB35 ECH, TB35 EI, TB35 I, TB35 C HI, TB35-PE ECH, TB35-PE EI, TB35-PE I, TB4-2L EI, TB4-2L I, TB4-2L-HESI (5x20) I lower level, TB4-2L-HESI (5x20) I upper level, TB4-2L-HESILA 250 (5x20) I lower level, TB4-2L-HESILA 250 (5x20) I upper level, TB4-2L-HESILED 24 (5x20) I lower level, TB4-2L-HESILED 24 (5x20) I upper level, TB4-2L-HESILED 60 (5x20) I lower level, TB4-2L-HESILED 60 (5x20) I upper level, TB4-EB, TB4-EC, TB4-EI, TB4-I, TB4-HEDI EI, TB4-HEDI I, TB4-HEDI I MS, TB4-HESI (5X20)EI, TB4-HESI (5X20)I, TB4-HESI (5X20) I MS, TB4-HESILA250 (5X20) EI, TB4-HESILA250 (5X20) I, TB4-HESILA250 (5X20) I MS /TB 4-HESILA 250 (5X20) I ZK, TB4-HESILED24 (5X20) EI, TB4-HESILED24 (5X20) I, TB4-HESILED24 (5X20) I MS /TB 4-HESILED 24 (5X20) I ZK, TB4-HESILED60 (5X20) EI, TB4-HESILED60 (5X20) I, TB4-HESILED60 (5X20), I MS, TB4-L/LB I, TB4-L/LB-PV I, TB4-MT EI, TB4-MT I, TB4-MT N I TB4-MT N I ZK, TB4-MT-P/P EI, TB4-MT-P/P I, TB4-MTD I, TB4-PE EB, TB4-PE EC, TB4-PE I, TB4-PE/3L I, TB4-QUATTRO EC, TB4-QUATTRO EI, TB4-QUATTRO I, TB4-QUATTRO I MS, TB4-TG EI, TB4-TG I, TB4-TG-P/P EI, TB4-TG-P/P I, TB4-TWIN EI, TB4-TWIN I, TB50 I, TB6 EB, TB6 EC, TB6 EI, TB6 I, TB6 RTK N, TB6 RTK, TB6 RTK I, TB6 RTK EI, TB6 RTK I MS, TB6-PE EB, TB6-PE EC, TB6-PE I, TB6-T EI, TB6-T I, TB6-T-NP I, TB70 I, TBD6 EI, TBD 6 I, TBI35CHI, TBIO2.5 I, TBIO2.5-2L I, TBIO2.5-LA 24RD/O-M I, TBIO2.5-LA 24RD/U-O I, TBIO2.5-PE I, TBIO2.5-PE/L/L I, TBIO2.5-PE/L/TG I, TBIO2.5-PE/TG I, USLKG 35 N, UT 16-PE/S, UT 35-PE/S *All cat. nos. may be followed additional suffixes (any combination of letters, symbols (-, / etc.), space and/or numbers) designating non-electrical variations such as color, customer identification, packaging or plating options.*

Model(s): TB16 EI *All cat. nos. may be followed additional suffixes (any combination of letters, symbols (-, / etc.), space and/or numbers) designating non-electrical variations such as color, customer identification, packaging or plating options.USR only for alternate construction with lower toque rating.*

Model(s): MSTBVA Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, Suffixes -ST, -STD, or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -KM, -AU, -LR, -BK, -DOM and/or -ABGY, -THT

Model(s): MSTBV Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L, Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, With or without suffixes HC and/or L Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -LR, -BK, -ABGY, -445, -6.03, May be followed by PXX

Model(s): MSTB2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX X replaces a one or two digit number All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFK-MSTB2.5/X f/b -G, -GF, DFK-MSTB2.5/X f/b -G, -GF f/b -10-1, -10-2, EMSTB2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBV2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, EMSTBVA2.5/X f/b -G, -GF, followed by -5.08, with or without -RN, FK2.5/X f/b -ST, -STF, -STZ, -STB w/w -5.08, FK2.5HC/X f/b -ST, -STF, -STZ, FKCN2.5 w/wo HC /X f/b -ST-5.08, -STF- 5.08, FKCOR2.5/X, FKCOR2.5/X followed by -ST, -STF, -5.08 with or without -LR, FKCS2.5/X f/b -ST, -STF, -STZ, FKCS2.5HC/X f/b -ST, -STF, -STZ, FKCT2.5/X f/b -ST, -STF, -STZ, may be f/b by -LIFT, FKCT2.5HC/X f/b -ST, -STF, -STZ, FKCV2.5/X f/b -ST, -STF, -STZ, FKCV2.5HC/X f/b -ST, -STF, -STZ, FKCVW2.5/X f/b -ST, -STF, -STZ, FKCVW2.5HC/X f/b -ST, -STF, -STZ, FKIC2.5/X f/b -ST, -STF, -STZ, FKIC2.5/X-TB, FKIC2.5HC/X f/b -ST, -STF, -STZ, FKICS2.5/X f/b -ST, -STF, -STZ, FKICS2.5HC/X f/b -ST, -STF, -STZ, FRONT-MSTB2.5/X f/b -ST, -STF, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTB2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5 w/wo -HC /X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, followed by -5.08, 10-1, or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBV2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING and/or -10-2, MDSTBVA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVH2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBVHA2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 f/b 10-1, 10-2 w/wo -HT, W/OPENING, MDSTBW2.5/X f/b -G, -GF, -GL, -GFL, -GR, -GFR, -G1 w/wo -HT, W/OPENING and/or -10-2, MSTB2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5/X f/b -ST, -STF, -STZ, MSTB2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTB2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTB2.5HC/X f/b -ST, -STF, -STZ, MSTBA2.5/X f/b -G, GF, GB, -GU, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, PXX, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAG2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBAGKL2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBP2.5/X f/b -ST, -STF, -STZ, MSTBP2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MSTBP2.5HC/X f/b -ST, -STF, -STZ, MSTBT2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2 w/wo P+F, MSTBT2.5/X f/b -ST, -STF, -STZ, w/wo RDB, w/wo P+F, MSTBT2.5HC/X f/b -ST, -STF, -STZ w/wo P+F, MSTBTP 2.5, f/b -ST, -STF, -STZ, w/wo RDB, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBV2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5/X f/b -G, GF,



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2408287-5
Report reference E60425-19931011
Date 2025-12-15

GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVA2.5HC/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVAG2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBVW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH f/b -10-1, -10-2 w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MSTBW2.5/X f/b -G, GF, GB, -G0.5, -GEH w/wo -RN, -LA, -LAB/RD, -KM w/wo -H, -R, -THT, MVSTBN2.5/X f/b -ST, -STF, -STZ, MVSTBN2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBN2.5HC/X f/b -ST, -STF, -STZ, MVSTBR2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBR2.5/X f/b -ST, -STF, -STZ, w/wo RDB, MVSTBR2.5HC/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ, MVSTBW2.5/X f/b -ST, -STF, -STZ f/b 10-1, 10-2, MVSTBW2.5HC/X f/b -ST, -STF, -STZ, PSPT2.5/X-ST (/X is followed by /2, /3 or /4), QC1.5/X f/b -ST, -STF, SMSTB2.5/X-G, SMSTB2.5/X-G f/b -10-1, 10-2, SMSTB2.5/X-ST, SMSTB2.5/X-ST f/b 10-1, 10-2, SMSTBA2.5/X-G, SMSTBA2.5/X-G f/b -10-1, 10-2, TMSTBP2.5/X f/b -ST, -STF f/b 10-1, 10-2 w/wo P+F, TMSTBP2.5/X f/b -ST, -STF w/wo P+F, TVFKC1.5/X-ST, w/wo RDB, TVFKCL1.5/X-ST X replaces a one or two digit number .All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBT2.5HC followed by /2, /3 or /4 followed by -STP, may be followed by BK SZS. All cat. nos. with pressure screws maybe followed by Suffix H0L, H1L or Z1L. All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): MSTBAG, Suffix 2.5, followed by /one or two digit number, MSTBV, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX

Model(s): MSTBA, Suffix 2.5, followed by /one or two digit number with or without suffixes HC and/or L, Suffixes -G, -G.05, -GB, -GF, GU, -GFSO or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -LR, -BK, -ABGY, -445, -THT, -6.03, May be followed by PXX



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.