

Certificate of Compliance

Certificate Number(s):

UL-US-2408776-9
UL-US-2408775-10
UL-US-2408774-9
UL-US-2408773-9
UL-US-2408772-9
UL-US-2408770-9
UL-US-2408769-8
UL-US-2408768-9
UL-US-2408767-9
UL-US-2408765-9
UL-US-L60425-6187193-82101102-15

Report Reference:

E60425-20110128

Issue Date:

2026-06-01

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8, Blomberg, 32825, DE

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2408776-9, UL-US-2408775-10, UL-US-2408774-9, UL-US-2408773-9, UL-US-2408772-9, UL-US-2408770-9, UL-US-2408769-8, UL-US-2408768-9, UL-US-2408767-9, UL-US-2408765-9, UL-US-L60425-6187193-82101102-15
Report reference: E60425-20110128
Issue Date: 2026-06-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standard(s): UL 1059, Edition 6, Issue Date 2024-12-11

Terminal Blocks

Model(s): MC1.5HP/X, MCV1.5HP/X f/b -G -GF, -GL, -GEF, -GFL, -GSF, -GR, -GFR, -GO, -GW f/b -3.5, -3.81, -5.08 w/o -RN w/wo color-code w/wo P14, P20, P26, AU w/wo THT, THR

Model(s): MC1.5 or MCV1.5 or IMC1.5 or IMCV1.5 followed by /one or /two digit number followed by -G, -GU, -GF, -GL, -GFL, -GR, -GEF, -GFR, -GSF, -GO, -GW followed by -3.5, -3.81, -5.08, may be followed by -LR, with or without -RN, with or without two-digit color-code (GY, -GN, OG and others), with or without P14, P20, P26, PXX, AU with or without THT, THR, CPXX, SOX or R.

Model(s): SMC1.5, followed by /one or two digit number followed by -G, followed by -3.5, followed by P26, followed by THR, followed by R44.

Terminal Blocks - Component

Model(s): IMC1.5/X-G-3.5, IMCV1.5/X-G-3.5

Model(s): MC1.5 followed by /one or two-digit number followed by -ST, -STF, -ST1, ST1F, -STZ, -STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13, -STZF followed by -3.5, -3.81, -5.08, may be followed by -LR.

Model(s): MC1.5 followed by /one or /two digit number followed by -G, -GU, -GF, -GL, -GFL, -GR, -GEF, -GFR, -GSF, -GO, -GW followed by -3.5, -3.81, -5.08, may be followed by -LR, with or without -RN, with or without two-digit color-code (GY, -GN, OG and others), with or without P14, P20, P26, AU with or without THT, THR, CPXX, SOX or R.

Model(s): MCD1.5/, MCD1.5/X, MCDV1.5/X followed by /one or two digit number followed by -G, G1, -G2, -GF, -G1F, -G1W followed by -3.5, -3.81 with or without P20, P26, with or without HT, THR, TR, S01, or PIN2.

Model(s): MCDN1.5, MCDNV1.5 followed by /one or two digit number followed by -G1 followed by -3.5, -3.81 followed by P14THR, P26THR, RNP14THR, RNP26THR.

Model(s): MCVU1.5 followed by /one or two digit number followed by -GFD-3.81.

Model(s): MCVDU1.5 followed by /one or two digit number followed by -G followed by -3.5, -3.81.

Model(s): EMC1.5, EMCV1.5 followed by /one or two digit number followed by -G, GF followed by -3.5, -3.81.

Model(s): SMC1.5 followed by /one or two digit number followed by -G, -GF followed by -3.81 with or without HT or CPXX, XX.

Model(s): MCVK1.5 followed by /one or two digit number followed by -G, -GF followed by -3.81.

Model(s): DFK-MC1.5 followed by /one or two digit number followed by -GF followed by -3.81.

Model(s): DMC1.5 followed by /one or two digit number, followed by -G1, -G1F, -G2 or -G2F, followed by -3.5 with or without -LR or AU, followed by PXX, w/wo THR.

Model(s): DMCV1.5 followed by /one or two digit number, followed by -G1, -G1F, -G2 or -G2F, followed by -3.5 with or without -LR or AU, followed by PXX, w/wo THR. Models DMC1.5/X, DMCV1.5/X followed by suffixes can be mated with Terminal Block Plugs, Model No. DFMC 1.5/X-ST-3.5.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2408776-9, UL-US-2408775-10, UL-US-2408774-9, UL-US-2408773-9, UL-US-2408772-9, UL-US-2408770-9, UL-US-2408769-8, UL-US-2408768-9, UL-US-2408767-9, UL-US-2408765-9, UL-US-L60425-6187193-82101102-15
Report reference: E60425-20110128
Issue Date: 2026-06-01

Model(s): FRONT-MC1.5 followed by /one or two-digit number followed by -ST, -STF followed by -3.81, may be followed by SOX (X is a one digit number).

Model(s): MCVR1.5, MCVW1.5 followed by /one or two-digit number followed by -ST, -STF, -STFL, -STFR followed by -3.5, -3.81.

Model(s): MCC1 followed by /one or two-digit number followed by -STZ, -STZF followed by -3.81.

Model(s): MCC0.5 followed by /one or two-digit number followed by -ST, followed by -2.54

Model(s): IMC1.5 followed by /one or two digit number followed by -ST, -STGF followed by -3.81.

Certificate of Compliance

Certificate Number(s):

UL-CA-2407717-9
UL-CA-2407716-10
UL-CA-2407715-9
UL-CA-2407714-9
UL-CA-2407713-8
UL-CA-2407712-9
UL-CA-2407711-8
UL-CA-2407709-8
UL-CA-2407708-9
UL-CA-2407710-9
UL-CA-L60425-6189193-
82101102-13

Report Reference:

E60425-20110128

Issue Date:

2026-06-01

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8, Blomberg, 32825, DE

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-2407717-9, UL-CA-2407716-10, UL-CA-2407715-9, UL-CA-2407714-9, UL-CA-2407713-8, UL-CA-2407712-9, UL-CA-2407711-8, UL-CA-2407709-8, UL-CA-2407708-9, UL-CA-2407710-9, UL-CA-L60425-6189193-82101102-13
Report reference: E60425-20110128
Issue Date: 2026-06-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standard(s): CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Terminal Blocks

Model(s): MC1.5HP/X, MCV1.5HP/X f/b -G -GF, -GL, -GEF, -GFL, -GSF, -GR, -GFR, -GO, -GW f/b -3.5, -3.81, -5.08 w/o -RN w/wo color-code w/wo P14, P20, P26, AU w/wo THT, THR

Model(s): MC1.5 or MCV1.5 or IMC1.5 or IMCV1.5 followed by /one or /two digit number followed by -G, -GU, -GF, -GL, -GFL, -GR, -GEF, -GFR, -GSF, -GO, -GW followed by -3.5, -3.81, -5.08, may be followed by -LR, with or without -RN, with or without two-digit color-code (GY, -GN, OG and others), with or without P14, P20, P26, PXX, AU with or without THT, THR, CPXX, SOX or R.

Model(s): SMC1.5, followed by /one or two digit number followed by -G, followed by -3.5, followed by P26, followed by THR, followed by R44.

Terminal Blocks - Component

Model(s): IMC1.5/X-G-3.5, IMCV1.5/X-G-3.5

Model(s): MC1.5 followed by /one or two-digit number followed by -ST, -STF, -ST1, ST1F, -STZ, -STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13, -STZF followed by -3.5, -3.81, -5.08, may be followed by -LR.

Model(s): IMC1.5, IMCV1.5, MC1.5, MCV1.5 followed by /one or /two digit number followed by -G, -GU, -GF, -GL, -GFL, -GR, -GEF, -GFR, -GSF, -GO, -GW followed by -3.5, -3.81, -5.08, may be followed by -LR, with or without -RN, with or without two-digit color-code (GY, -GN, OG and others), with or without P14, P20, P26, AU with or without THT, THR, CPXX, SOX or R.

Model(s): MCD1.5/, MCDB1.5/X, MCDV1.5/X followed by /one or two digit number followed by -G, G1, -G2, -GF, -G1F, -G1W followed by -3.5, -3.81 with or without P20, P26, with or without HT, THR, TR, S01, or PIN2.

Model(s): MCDN1.5, MCDNV1.5 followed by /one or two digit number followed by -G1 followed by -3.5, -3.81 followed by P14THR, P26THR, RNP14THR, RNP26THR.

Model(s): MCVU1.5 followed by /one or two digit number followed by -GFD-3.81.

Model(s): MCVDU1.5 followed by /one or two digit number followed by -G followed by -3.5, -3.81.

Model(s): EMC1.5, EMCV1.5 followed by /one or two digit number followed by -G, GF followed by -3.5, -3.81.

Model(s): SMC1.5 followed by /one or two digit number followed by -G, -GF followed by -3.81 with or without HT or CPXX, XX.

Model(s): MCVK1.5 followed by /one or two digit number followed by -G, -GF followed by -3.81.

Model(s): DFK-MC1.5 followed by /one or two digit number followed by -GF followed by -3.81.

Model(s): DMC1.5, DMCV1.5 followed by /one or two digit number, followed by -G1, -G1F, -G2 or -G2F, followed by -3.5 with or without -LR or AU, followed by PXX, w/wo THR.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-2407717-9, UL-CA-2407716-10, UL-CA-2407715-9, UL-CA-2407714-9, UL-CA-2407713-8, UL-CA-2407712-9, UL-CA-2407711-8, UL-CA-2407709-8, UL-CA-2407708-9, UL-CA-2407710-9, UL-CA-L60425-6189193-82101102-13
Report reference: E60425-20110128
Issue Date: 2026-06-01

Model(s): DMCV1.5 followed by /one or two digit number, followed by –G1, –G1F, –G2 or –G2F, followed by -3.5 with or without –LR or AU, followed by PXX, w/wo THR. Models DMC1.5/X, DMCV1.5/X followed by suffixes can be mated with Terminal Block Plugs, Model No. DFMC 1.5/X-ST-3.5.

Model(s): FRONT-MC1.5 followed by /one or two-digit number followed by -ST, -STF followed by -3.81, may be followed by SOX (X is a one digit number).

Model(s): MCVR1.5, MCVW1.5 followed by /one or two-digit number followed by -ST, -STF, -STFL, -STFR followed by -3.5, -3.81.

Model(s): MCC1 followed by /one or two-digit number followed by -STZ, -STZF followed by -3.81.

Model(s): MCC0.5 followed by /one or two-digit number followed by –ST, followed by -2.54

Model(s): MCC0.5 followed by /one or two-digit number followed by –ST, followed by -2.54, may be followed by 1 to 30 character alphanumeric suffix (any combination of letters and/ or numbers) indicating optional alternate poles, colors, coding and laser prints.

Model(s): IMC1.5 followed by/one or two digit number followed by –ST, -STGF followed by -3.81.