

CERTIFICATE OF COMPLIANCE

Certificate Number 20180321-E468743
Report Reference E468743-20180321
Issue Date 2018-MARCH-21

Issued to: PHOENIX CONTACT GMBH & CO KG
FLACHSMARKTSTRASSE 8
32825 BLOMBERG GERMANY

**This is to certify that
representative samples of**

MULTI-POINT INTERCONNECTION POWER CABLE
ASSEMBLIES FOR INDUSTRIAL MACHINERY
See Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

SU 2237, Outline Of Investigation for Multi-Point
Interconnection Power Cable.
CSA C22.2 No. 182.3-16, Special Use Attachment Plugs,
Receptacles and Connectors.

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20180321-E468743
Report Reference E468743-20180321
Issue Date 2018-MARCH-21

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Power Cable Assembly – Power Cable Assemblies- Cat. Nos. Types SAC-3P, SAC-4P; may be followed by suffix -M12; followed by suffixes (-)MST, MRT, (-)MSS or MRS; followed by suffix /M,M; followed by suffix -###; may be followed by suffix /M12; followed by suffixes (/)FST, (/)FRT, /FSS OR /FRS, may be followed by suffix PE; may be followed by suffix SH

Male Cable Fitting – Cat. Nos. Types SAC-3P, SAC-4P; followed by suffix -M12; followed by suffixes MST, MRT, MSS or MRS; followed by suffix /M,M; followed by suffix -###; may be followed by suffix PE; may be followed by suffix SH.

Female Cable Fitting - Cat. Nos. Types SAC-3P, SAC-4P; followed by suffix -M,M; followed by suffix -###; followed by suffix /M12; followed by suffixes FST, FRT, FSS or FRS; may be followed by suffix PE; may be followed by suffix SH.

Where ### = PVC or PUR, Where -M, M = cable length in meters

All cat. nos. may be followed additional suffixes (any combination of letters, symbols and/or numbers) designating non-electrical variations such as color, customer identification, packaging or plating options.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

