



Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.



Recommended PCB



General Information:

- Simplified representation, exemplary shown in gray
- Tolerances, apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- When using this connection technology in housing systems from Phoenix Contact see the appropriate documentation.
-  Restricted area
- General tolerances PCB:
dimensions ≤ 30 : $\pm 0,1/R \pm 0,2/\pm 1^\circ$
dimensions > 30 : $\pm 0,15/R \pm 0,2/\pm 1^\circ$
symmetry: 0,2
- Web: www.phoenixcontact.com

Additional Information

A. Marking area

B. PCB $t=1,6 \pm 0,2$

Pos.	QTY	Description	Material
1	1	HOUSING	PA
2	1	COVER	PA
3	4	SPRING OPENER	PBT
4	4	SPRING	STL
5	4	SOLDER PIN	Cu alloy



page 1 of 1

document-no. / ri
00602917 / 05

article-no.
1012225

date
20.10.2025

document-type
TECDOC 2D_Productdrawing

description

FKDSO 2,5/ 4-L KMGY BD:5-8

scale
2:1

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]