

Certificate of Compliance

Certificate Number(s):

UL-US-2597339-1
UL-US-2569875-5
UL-US-L60425-6187154-
60302991-11
UL-US-2569877-5
UL-US-2569874-4
UL-US-2569878-5
UL-US-2569879-5
UL-US-2569876-5

Report Reference:

E60425-19920306

Issue Date:

2026-05-29

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8, Blomberg, 32825, DE

This certificate confirms that representative samples of:

XCFR2 - Terminal Blocks - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1059, Edition 6, Issue Date 2024-12-11

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2597339-1, UL-US-2569875-5, UL-US-L60425-6187154-60302991-11, UL-US-2569877-5, UL-US-2569874-4, UL-US-2569878-5, UL-US-2569879-5, UL-US-2569876-5
Report reference: E60425-19920306
Issue Date: 2026-05-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standard(s): UL 1059, Edition 6, Issue Date 2024-12-11

Component terminal blocks

Model(s): FMC0.5 followed by /one or two digit number followed by –ST-2.54 may be followed by suffix C and an one or two digit number

Terminal Blocks - Component

Model(s): FK-MCP1.5/X f/b -ST, -STF, -STZ, -STZ1, -STZ2, -STZ3, -STZF, -STW, -STZW f/b -3.5, w/wo -LR, FMCD1.5/X f/b -ST-3.5, -STF-3.5, IMC1.5/X-G-3.5, IMC1.5/X-G-3.81, IMCV1.5/X-G-3.5, IMCV1.5/X-G-3.81, MC0.5/X, MCV0.5/X f/b -G-2.54 f/b P14, P20, P26 f/b THR, SMD f/b R24, R44, R56, R72 w/wo CX, PSC1.5(/3 or /5)-F, PSC1.5(/3 or /5)-M, -PE, TFMC1.5/X f/b -ST or -STF and by -3.5

Model(s): FMC0.5/X-ST-2.54 w/wo CX, IDC0.3/X-3.81 All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DMC0.5, DMCV0.5 followed by /one or two digit number followed by –G1, –G1SH or G1SHL, followed by -2.54 followed by P14, P20, P26 followed by THR or SMD, followed by R24, R44, R56, R72 may be followed by suffix C and an one or two digit number.

Model(s): DFMC1.5 followed by /one or two digit number followed by –ST, -STF followed by -3.5 with or without AU, -LR or T.SKT

All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, customer identification, packaging or plating options, omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFMC0.5 followed by /one or two digit number followed by –ST-2.54 may be followed by suffix –RF or C and an one or two digit number

Model(s): IFMC1.5 followed by /one or two digit number, -ST, –STF, -STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13, -STFZ1, -STFZ2, -STFZ3, -STFZ4, -STFZ11, -STFZ12, -STFZ13 and -3.5 or -3.81, may be followed by –RF or –RN.

Model(s): FMC1.5 followed by /one or two digit number, -ST, –STF, -STZxx, -STFZxx and -3.5 or -3.81, may be followed by –RF or –RN.

All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, customer identification, packaging or plating options, omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): FMCOW1.5 followed by /one or two digit number, followed by -ST or -STF, followed by -3.5, maybe followed by -LR.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2597339-1, UL-US-2569875-5, UL-US-L60425-6187154-60302991-11, UL-US-2569877-5, UL-US-2569874-4, UL-US-2569878-5, UL-US-2569879-5, UL-US-2569876-5
Report reference: E60425-19920306
Issue Date: 2026-05-29

Model(s): FMCOR1.5 followed by /one or two digit number, followed by -ST or -STF, followed by -3.5.

Model(s): DMCC0.5 followed by /one or two digit number, followed by -ST, may be followed by -SH 7,0, -SHL 4,8 or -SHL 7,0, followed by -2.54, maybe followed by 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) indicating optional alternate poles, colors, coding and laser prints.

Model(s): FK-MCP1.5 followed by/one or two-digit number, -ST, -STF, -STZ, -STZ1, -STZ2, -STZ3, -STZF, -STW or STZW and -3.5 or -3.81, may be followed by -LR or BUGY or SOX.

Certificate of Compliance

Certificate Number(s):

UL-CA-2571410-1
UL-CA-2551404-6
UL-CA-L60425-6189154-
60302991-11
UL-CA-2551403-4
UL-CA-2551405-4
UL-CA-2551406-5
UL-CA-2551408-5
UL-CA-2551407-5

Report Reference:

E60425-19920306

Issue Date:

2026-05-29

Issued to:

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8, Blomberg, 32825, DE

This certificate confirms that representative samples of:

XCFR8 - Terminal Blocks Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-2571410-1, UL-CA-2551404-6, UL-CA-L60425-6189154-60302991-11, UL-CA-2551403-4, UL-CA-2551405-4, UL-CA-2551406-5, UL-CA-2551408-5, UL-CA-2551407-5
Report reference: E60425-19920306
Issue Date: 2026-05-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standard(s): CSA C22.2 No. 158, Edition 4, Issue Date 2023-02, Revision Date 2025-03

Component terminal blocks

Model(s): FMC0.5 followed by /one or two digit number followed by -ST-2.54 may be followed by suffix C and an one or two digit number

Terminal Blocks - Component

Model(s): FK-MCP1.5/X f/b -ST, -STF, -STZ, -STZ1, -STZ2, -STZ3, -STZF, -STW, -STZW f/b -3.5, w/wo -LR, FMCD1.5/X f/b -ST-3.5, -STF-3.5, IMC1.5/X-G-3.5, IMC1.5/X-G-3.81, IMCV1.5/X-G-3.5, IMCV1.5/X-G-3.81, MC0.5/X, MCV0.5/X f/b -G-2.54 f/b P14, P20, P26 f/b THR, SMD f/b R24, R44, R56, R72 w/wo CX, PSC1.5(/3 or /5)-F, PSC1.5(/3 or /5)-M, -PE, TFMC1.5/X f/b -ST or -STF and by -3.5

Model(s): IDC0.3/X-3.81 All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, Customer identification, packaging or plating options, coded variations (by adding or removing parts) or omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DMC0.5, DMCV0.5 followed by /one or two digit number followed by -G1, -G1SH or G1SHL, followed by -2.54 followed by P14, P20, P26 followed by THR or SMD, followed by R24, R44, R56, R72 may be followed by suffix C and an one or two digit number.

Model(s): DFMC1.5 followed by /one or two digit number followed by -ST, -STF followed by -3.5 with or without AU, -LR or T.SKT

All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, customer identification, packaging or plating options, omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Model(s): DFMC0.5 followed by /one or two digit number followed by -ST-2.54 may be followed by suffix -RF or C and an one or two digit number

Model(s): IFMC1.5 followed by /one or two digit number, -ST, -STF, -STZ1, -STZ2, -STZ3, -STZ4, -STZ11, -STZ12, -STZ13, -STFZ1, -STFZ2, -STFZ3, -STFZ4, -STFZ11, -STFZ12, -STFZ13 and -3.5 or -3.81, may be followed by -RF or -RN.

Model(s): FMC1.5 followed by /one or two digit number, -ST, -STF, -STZxx, -STFZxx and -3.5 or -3.81, may be followed by -RF or -RN.

All Cat. Nos. may be followed by a 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) with or without spaces between characters, designating nonelectrical variations such as color, customer identification, packaging or plating options, omitting terminals from single or multiple alternating poles. Terminal blocks may not be shipped with all terminals removed.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-2571410-1, UL-CA-2551404-6, UL-CA-L60425-6189154-60302991-11, UL-CA-2551403-4, UL-CA-2551405-4, UL-CA-2551406-5, UL-CA-2551408-5, UL-CA-2551407-5
Report reference: E60425-19920306
Issue Date: 2026-05-29

Model(s): FMCOW1.5 followed by /one or two digit number, followed by -ST or -STF, followed by -3.5, maybe followed by -LR.

Model(s): FMCOR1.5 followed by /one or two digit number, followed by -ST or -STF, followed by -3.5.

Model(s): DMCC0.5 followed by /one or two digit number, followed by -ST, may be followed by -SH 7,0, -SHL 4,8 or -SHL 7,0, followed by -2.54, maybe followed by 1 to 30 character alphanumeric suffix (any combination of letters and/or numbers) indicating optional alternate poles, colors, coding and laser prints.

Model(s): FK-MCP1.5 followed by /one or two-digit number, -ST, -STF, -STZ, -STZ1, -STZ2, -STZ3, -STZF, -STW or STZW and -3.5 or -3.81, may be followed by -LR or BUGY or SOX.