

CERTIFICATE OF COMPLIANCE

Certificate Number E468743
Report Reference E468743-20190917
Date 2023-January-27

Issued to: PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8
Blomberg 32825 DE

**This is to certify that
representative samples of**

MULTI-POINT INTERCONNECTION POWER CABLE
ASSEMBLIES FOR INDUSTRIAL MACHINERY -
COMPONENT

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
component requirements in the Standard(s) indicated on
this Certificate. UL Recognized components are incomplete
in certain constructional features or restricted in
performance capabilities and are intended for installation in
complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: See Addendum Page for Standard(s)

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark.
Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified
and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E468743
Report Reference E468743-20190917
Date 2023-January-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Female Panel Mounts - Cat. Nos. Types SACC; followed by suffixes DSI, E or CI; followed by suffix M12; followed by suffixes FSS or FST; followed by suffixes 4CON, 4P, 3CON or 3P; followed by suffixes M16, M16XL or blank; followed by suffixes L180 or -M,M; may be followed by suffixes TOR, THR, SCO, PE or SH

Female SMD Soldering - Cat. Nos. Types SACC; followed by suffixes CIP or CI; followed by suffix M12; followed by suffix FST; followed by suffixes 4CON, 4P, 3CON or 3P; followed by suffix SMD; may be followed by suffix SH.

Male Panel Mounts - Cat. Nos. Types SACC; followed by suffixes MCI, DSI, E or CI; may be followed by suffix M12; followed by suffixes MSS or MST; followed by suffix 4CON, 4P 3 CON or 3P; may be followed by suffixes M16, M16XL or blank; followed by suffixes L180 or -M,M; may be followed by suffixes TOR, THR, SCO, PE or SH.

Male SMD Soldering - Cat. Nos. Types SACC; followed by suffixes CIP or CI; followed by suffix M12; followed by suffix MST; followed by suffixes 4CON, 4P, 3CON or 3P; followed by suffix SMD; may be followed by suffix SH.

All cat. nos. may be followed additional suffixes (any combination of letters, symbols and/or numbers) designating non-electrical variations such as color, customer identification, packaging or plating options.

All cat. nos. may be followed additional suffix 'X' indicating use of new contact type.

Standard(s):

UL 2237, Multi-Point Interconnection Power Cable Assemblies for Industrial Machinery.
CSA C22.2 No. 182.3, Special Use Attachment Plugs, Receptacles and Connectors.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>