

CERTIFICATE OF COMPLIANCE

Certificate Number 20190410-E468743
Report Reference E468743-20190308
Issue Date 2019-APRIL-10

Issued to: PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstrasse 8
32825 Blomberg GERMANY

**This certificate confirms that
representative samples of**

MULTI-POINT INTERCONNECTION POWER CABLE
ASSEMBLIES FOR INDUSTRIAL MACHINERY
See Addendum Page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 2237, Multi-Point Interconnection Power Cable
Assemblies for Industrial Machinery
CAN/CSA C22.2 No. 182.3-16, Special Use Attachment
Plugs, Receptacles and Connectors.

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190410-E468743
Report Reference E468743-20190308
Issue Date 2019-APRIL-10

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Cable Assemblies, Series QPD Cat. Nos:

- Type QPD H 4PE1.5 with or without 4X7-10 or 4X9-14, followed by suffix BK.
- Type QPD H 4PE2.5 with or without suffix 4X6-11 or 4X9-16, followed by suffix BK or GY.
- Type QPD H 4PE6.0 with or without 4X9-14 or 4X12-20, followed by suffix BK or GY.
- Type QPD P 4PE1.5 with or without 7-10 or 9-14, followed by suffix BK.
- Type QPD P 5X1.5 with or without 7-10 or 9-14, followed by suffix BK.
- Type QPD P 4PE2.5 followed by suffix 6-11 or 9-16, followed by suffix BK or GY.
- Type QPD P 4PE6.0 with or without 9-14 or 12-20, followed by suffix BK, BKBK or GY.
- Type QPD C 4PE1.5 with or without 1X7-10 or 2X5-10 or 1X9-14 or 2X9-14, followed by suffix BK.
- Type QPD C 4PE2.5 with suffix 1X6-11 or 2X6-11 or 1X9-16 or 2X9-16, followed by suffix BK or GY.
- Type QPD C 4PE6.0 with suffix 1X9-14 or 2X9-14 or 1X12-20 or 2X12-20, followed by suffix BK or GY.
- Type QPD N 4PE1.5 with or without suffix 7-10 or 9-14, followed by suffix BK or GY.
- Type QPD N 4PE2.5 with or without suffix 6-11 or 9-16, followed by suffix BK or GY.
- Type QPD N 4PE6.0 with or without suffix 9-14 or 12-20, followed by suffix BK or GY.

Panel feed-through connector, Series QPD Cat. Nos:

- Type QPD W 4PE1.5 with or without 7-10 or 9-14 or 6-11, followed by suffix M25, may be followed by suffix 0.5 or 1.0 or FC, followed by suffix BK.
- Type QPD W 4PE1.5 with or without suffix 5-10 or 9-14 or 6-11, followed by suffix M25; followed by suffix DT, followed by BK, GY or WH, may be followed by ELED or NOR.
- Type QPD W 5X1.5 with or without 7-10 or 9-14, may be followed by suffix M25, may be followed by suffix 0.25, followed by suffix BK B-S.
- Type QPD W 4PE2.5 with or without suffix 6-11 or 9-16 or 7-14, followed by suffix M20 or M25; followed by suffix 0.5, 1.0 or FC or DT, followed by BK, GY or WH, may be followed by ELED or NOR.
- Type QPD W 4PE6.0 with or without 9-14 or 12-20, may be followed by suffix M25, may be followed by suffix 0.5 or 1.0, followed by suffix BK or GY.
- Type QPD CW 4PE2.5 with suffix 1X6-11 or 2X6-11 or 1X9-16 or 2X9-16, followed by suffix BK or GY.

T-distributor connector, Series QPD Cat. Nos:

- Type QPD T 4PE1.5 with or without 2X7-10 or 3X7-10 or 2X9-14 or 3X9-14, followed by suffix BK.
- Type QPD T 4PE2.5 followed by suffix BK.
- Type QPD T 4PE may be followed by suffix 2X6-11, 2X9-16, 3X6-11 or 3X9-16, followed by BK or GY.
- Type QPD T 4PE6.0 with or without suffix 3X9-14 or 2X9-14 or 3X12-20 or 2X12-20, followed by suffix BK or GY.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

