

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Primary-switched power supply unit, ESSENTIAL POWER, Screw connection, DIN rail mounting, input: 1-phase, output: 24 V DC / 5 A, Adjustable from 24 V DC ... 28 V DC

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1234302 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | ***** |
| Product key | CMPG13 |
| GTIN | 4063151338336 |
| Weight per piece (including packing) | 710 g |
| Weight per piece (excluding packing) | 657 g |
| Customs tariff number | 85044095 |
| Country of origin | CN |

Technical data

Input data

AC operation

| | |
|--|--|
| Supply system configuration | TN, TT, IT (PE) |
| Nominal input voltage range | 100 V AC ... 240 V AC |
| Input voltage range | 110 V AC ... 240 V AC $\pm 10\%$ ($P_N = 120\text{ W}$) |
| | 100 V AC ... 109 V AC -15% ... $+10\%$ ($P_N = 100\text{ W}$) |
| Typical national grid voltage | 120 V AC |
| | 230 V AC |
| Voltage type of supply voltage | AC |
| Inrush current | typ. 43 A (at 25 °C) |
| Inrush current integral (I^2t) | typ. 0.7 A ² s |
| Frequency range (f_N) | 50 Hz ... 60 Hz $\pm 10\%$ |
| Mains buffering time | typ. 15 ms (120 V AC) |
| | typ. 42 ms (230 V AC) |
| Current consumption | max. 2 A |
| | max. 1.5 A |
| | typ. 1.3 A (110 V AC (120 W)) |
| | typ. 0.6 A (240 V AC (120 W)) |
| | typ. 1.2 A (100 V AC (100 W)) |
| Protective circuit | typ. 1.1 A (109 V AC (100 W)) |
| | Transient protection; Varistor |
| Switch-on time | typ. 1 s |
| Device mains fuse | 3.15 A internal (device protection), fast-blow |
| Recommended breaker for input protection | 10 A ... 16 A (Characteristic B, C, D, K or comparable) |
| Discharge current to PE | < 3.5 mA |

Output data

| | |
|---|---|
| Efficiency | typ. 87 % (120 V AC) |
| | typ. 88 % (230 V AC) |
| Nominal output voltage | 24 V DC |
| Setting range of the output voltage (U_{Set}) | 24 V DC ... 28 V DC (> 24 V DC, constant capacity restricted) |
| Nominal output current (I_N) | max. 5 A ($P_N = 120\text{ W}$) |
| | max. 4.16 A ($P_N = 100\text{ W}$) |
| Short-circuit-proof | yes |
| No-load proof | yes |
| Crest factor | typ. 1.5 (120 V AC) |
| | typ. 1.5 (230 V AC) |
| Output power (P_N) | 120 W (240 V AC) |
| | 100 W (100 V AC) |
| Connection in parallel | yes, for increasing power and redundancy with diode |
| Connection in series | yes, for increased output voltage |

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit










1234302

<https://www.phoenixcontact.com/in/products/1234302>

| | |
|--|--|
| Feedback voltage resistance | ≤ 35 V DC |
| Protection against overvoltage at the output (OVP) | ≤ 35 V DC |
| Residual ripple | typ. 70 mV _{PP} (with nominal values) |
| Control deviation | < 2 % (change in load, static 10 % ... 90 %) |
| | < 4 % (change in load, dynamic 10 % ... 90 %) |
| | < 0.1 % (change in input voltage ±10 %) |
| Rise time | < 2 s (U _{Out} = 10 % ... 90 %) |
| Minimum no-load power dissipation | < 1 W (120 V AC) |
| Maximum no-load power dissipation | < 1 W (230 V AC) |
| Minimum nominal load power dissipation | < 20 W (120 V AC) |
| Power loss nominal load max. | < 16 W (230 V AC) |
| Integrated fuse protection | no |

Connection data

Input

| | |
|----------------|--|
| Position | 1.x |
| Identification | 1.1 (       FS L), 1.3 (N) |

Conductor connection

| | |
|--|---|
| Connection method | Screw connection |
| rigid | 0.5 mm ² ... 2.5 mm ² |
| flexible | 0.5 mm ² ... 2.5 mm ² |
| flexible with ferrule without plastic sleeve | 0.5 mm ² ... 2.5 mm ² |
| flexible with ferrule with plastic sleeve | 0.5 mm ² ... 2.5 mm ² |
| rigid (AWG) | 20 ... 14 (Cu) |
| Stripping length | 6.5 mm |
| Tightening torque | 0.5 Nm ... 0.6 Nm |
| | 5 lb _F -in. ... 7 lb _F -in. |
| Drive form screw head | Slotted L |

Output

| | |
|----------------|----------------------------|
| Position | 2.x |
| Identification | 2.1, 2.2 (+), 2.3, 2.4 (-) |

Conductor connection

| | |
|--|---|
| Connection method | Screw connection |
| rigid | 1 mm ² ... 2.5 mm ² |
| flexible | 1 mm ² ... 2.5 mm ² |
| flexible with ferrule without plastic sleeve | 1 mm ² ... 2.5 mm ² |
| flexible with ferrule with plastic sleeve | 1 mm ² ... 2.5 mm ² |
| rigid (AWG) | 17 ... 14 (Cu) |
| Stripping length | 6.5 mm |
| Tightening torque | 0.5 Nm ... 0.6 Nm |
| | 5 lb _F -in. ... 7 lb _F -in. |
| Drive form screw head | Slotted L |

1234302

<https://www.phoenixcontact.com/in/products/1234302>

Signaling

LED signaling

| | |
|-----------------------|--|
| Types of signaling | LED DC OK – signal state operation ($U_N = 24 \text{ V DC}$, $I_{Out} = I_N$) |
| Function | Visual operating state display |
| Color | green |
| LED off | Supply voltage input AC not present (Off) |
| LED on (green), DC OK | $U_{OUT} > 15 \text{ V}$ (On (green), DC OK) |

Electrical properties

| | |
|---------------------------------|--------------------------|
| Number of phases | 1.00 |
| Insulation voltage input/output | 4 kV AC (type test) |
| | 3 kV AC (routine test) |
| Insulation voltage input / PE | 3.5 kV AC (type test) |
| | 2.4 kV AC (routine test) |

Product properties

| | |
|-------------------------|---------------------|
| Product type | Power supply |
| Product family | ESSENTIAL POWER |
| MTBF (Telcordia SR-332) | > 2470000 h (25 °C) |
| | > 2000000 h (40 °C) |
| | > 1840000 h (45°C) |

Insulation characteristics

| | |
|---------------------|---|
| Protection class | I |
| Degree of pollution | 2 |

Life expectancy (electrolytic capacitors)

| | |
|-----------------|----------|
| Current | 5 A |
| Temperature | 40 °C |
| Time | 24000 h |
| Additional text | 120 V AC |

Life expectancy (electrolytic capacitors)

| | |
|-----------------|----------|
| Current | 5 A |
| Temperature | 30 °C |
| Time | 48000 h |
| Additional text | 120 V AC |

Life expectancy (electrolytic capacitors)

| | |
|-----------------|----------|
| Current | 5 A |
| Temperature | 40 °C |
| Time | 32000 h |
| Additional text | 230 V AC |

Life expectancy (electrolytic capacitors)

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

| | |
|-----------------|----------|
| Current | 5 A |
| Temperature | 30 °C |
| Time | 64000 h |
| Additional text | 230 V AC |

Dimensions

Item dimensions

| | |
|--------|--------|
| Width | 40 mm |
| Height | 124 mm |
| Depth | 125 mm |

Installation dimensions

| | |
|----------------------------------|---------------|
| Installation distance right/left | 10 mm / 10 mm |
| Installation distance top/bottom | 30 mm / 30 mm |

Mounting

| | |
|-------------------------|--|
| Mounting type | DIN rail mounting |
| Assembly instructions | alignable: 0 mm horizontally, 30 mm vertically |
| Mounting position | horizontal DIN rail NS 35, EN 60715 |
| With protective coating | No |

Material specifications

| | |
|----------------------|---|
| Housing material | Metal |
| Hood version | Stainless steel |
| Side element version | Aluminum |
| Foot latch material | Sheet steel, zinc-plated |
| Housing material | Aluminum (AlMg3) / sheet steel, zinc-plated |

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -20 °C ... 70 °C (Derating >45°C: 2.5%/K) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Maximum altitude | ≤ 5000 m (> 2000 m, Derating: 10 %/1000 m) |
| Climatic class | 3K22 (in accordance with EN 60721-3-3) |
| Max. permissible relative humidity (operation) | ≤ 95 % (at 25 °C, non-condensing) |
| Shock (operation) | 15 ms, 15 g, per spatial direction (IEC 60068-2-27) |
| Vibration (operation) | 10 Hz ... 50 Hz, amplitude ±0.2 mm 50 Hz to 150 Hz, 2.3 g, 90 min. |

Standards and regulations

Overvoltage category

| | |
|------------|---------------|
| EN 61010-1 | II (≤ 3000 m) |
|------------|---------------|

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

Electrical safety

| | |
|--------------------------|------------------------|
| Standard designation | Electrical safety |
| Standards/specifications | IEC 61010-2-201 (SELV) |

Safety for measurement, control, and laboratory equipment

| | |
|--------------------------|---|
| Standard designation | Safety for equipment for measurement, control, and laboratory use |
| Standards/specifications | IEC 61010-1 |

Protective extra-low voltage

| | |
|--------------------------|------------------------------|
| Standard designation | Protective extra-low voltage |
| Standards/specifications | IEC 61010-1 (SELV) |
| | IEC 61010-2-201 (PELV) |

Limitation of harmonic line currents

| | |
|--------------------------|--------------------------------------|
| Standard designation | Limitation of harmonic line currents |
| Standards/specifications | EN 61000-3-2 |

Mains voltage dips

| | |
|--------------------------|---|
| Standard designation | Requirement of the semiconductor industry with regard to mains voltage dips |
| Standards/specifications | SEMI F47 - 0706 (120 V AC) |

Approvals

UL

| | |
|----------------|---------------------------|
| Identification | UL/C-UL Listed UL 61010-1 |
|----------------|---------------------------|

UL

| | |
|----------------|-------------------------------|
| Identification | UL/C-UL Listed UL 61010-2-201 |
|----------------|-------------------------------|

CB scheme

| | |
|----------------|--|
| Identification | CB scheme (IEC 61010-1, IEC 61010-2-201) |
|----------------|--|

EMC data

| | |
|-------------------------------------|--|
| Low Voltage Directive | Conformance with Low Voltage Directive 2014/35/EC |
| Interference emission | Interference emission in accordance with EN 61000-6-3 (residential and commercial) and EN 61000-6-4 (industrial) |
| EMC requirements for noise immunity | EN 61000-6-2 |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |
| Conducted noise emission | EN 55016 |
| | EN 61000-6-3 (Class B) |
| Noise emission | EN 55016 |
| | EN 61000-6-3 (Class B) |

Harmonic currents

| | |
|-----------------------|------------------------|
| Standards/regulations | EN 61000-3-2 |
| | EN 61000-3-2 (Class A) |

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

| | |
|----------------------------|------------------------------------|
| Frequency range | 0 kHz ... 2 kHz |
| Electrostatic discharge | |
| Standards/regulations | EN 61000-4-2 |
| Electrostatic discharge | |
| Contact discharge | 6 kV (Test Level 3) |
| Discharge in air | 8 kV (Test Level 3) |
| Comments | Criterion A |
| Electromagnetic HF field | |
| Standards/regulations | EN 61000-4-3 |
| Electromagnetic HF field | |
| Frequency range | 80 MHz ... 1 GHz |
| Test field strength | 10 V/m (Test Level 3) |
| Frequency range | 1 GHz ... 6 GHz |
| Test field strength | 10 V/m (Test Level 3) |
| Frequency range | 2 GHz ... 3 GHz |
| Test field strength | 1 V/m (Test Level 3) |
| Comments | Criterion A |
| Fast transients (burst) | |
| Standards/regulations | EN 61000-4-4 |
| Fast transients (burst) | |
| Input | 4 kV (Test Level 4 - asymmetrical) |
| Output | 2 kV (Test Level 3 - asymmetrical) |
| Comments | Criterion A |
| Surge voltage load (surge) | |
| Standards/regulations | EN 61000-4-5 |
| Input | 2 kV (Test Level 3 - symmetrical) |
| | 4 kV (Test Level 4 - asymmetrical) |
| Output | 1 kV (Test Level 2 - symmetrical) |
| | 2 kV (Test Level 3 - asymmetrical) |
| Comments | Criterion A |
| Conducted interference | |
| Standards/regulations | EN 61000-4-6 |
| Conducted interference | |
| Input/Output | asymmetrical |
| Frequency range | 0.15 MHz ... 80 MHz |
| Comments | Criterion A |
| Voltage | 10 V (Test Level 3) |
| Voltage dips | |

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>


| | |
|-----------------------|---------------|
| Standards/regulations | EN 61000-4-11 |
| Voltage | 230 V AC |
| Frequency | 50 Hz |
| Voltage dip | 70 % |
| Number of periods | 25 periods |
| Comments | Criterion A |
| Voltage dip | 40 % |
| Number of periods | 12 periods |
| Comments | Criterion A |
| Voltage dip | 0 % |
| Number of periods | 1 period |
| Comments | Criterion A |

Criteria

| | |
|-------------|--|
| Criterion A | Normal operating behavior within the specified limits. |
| Criterion B | Temporary impairment to operational behavior that is corrected by the device itself. |


Drawings

Diagram



Output power Installation altitude

Diagram



Efficiency


PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302


<https://www.phoenixcontact.com/in/products/1234302>

Diagram



Input current/output current


Dimensional drawing



Device dimensions (dimensions in mm)

Schematic diagram

Housing



Test sections, insulation voltage


PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302


<https://www.phoenixcontact.com/in/products/1234302>

Block diagram



Block diagram

Diagram




Power factor

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>



Device dimensions (dimensions in mm)

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/1234302>



IECEE CB Scheme

Approval ID: DE 2-039094



cULus Listed

Approval ID: E123528-20230401

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27040701 |
| ECLASS-12.0 | 27040701 |
| ECLASS-13.0 | 27040701 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002540 |
|----------|----------|

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

Environmental product compliance

REACH SVHC

Lead 7439-92-1

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

Accessories

UNO-DIODE/5-24DC/2X10/1X20 - Redundancy module

2905489

<https://www.phoenixcontact.com/in/products/2905489>



Redundancy module, 5 V - 24 V DC, 2 x 10 A, 1 x 20 A.

TRIO2-DIODE/12-24DC/2X10/1X20 - Redundancy module

2907380

<https://www.phoenixcontact.com/in/products/2907380>



Redundancy module, 12 V - 24 V DC, 2 x 10 A, 1 x 20 A

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

PLT-EE-T3-230AC-R - Type 3 surge protection device

1249060

<https://www.phoenixcontact.com/in/products/1249060>




Type 3 surge protection, consisting of protective plug and base element with screw connection, with integrated status indicator and remote signaling for single-phase power supply networks. Nominal voltage: 230 V AC

PLT-SEC-T3-230-FM - Type 3 surge protection device

2905229

<https://www.phoenixcontact.com/in/products/2905229>



Pluggable device protection, according to type 3/class III, for 1-phase power supply networks with separate N and PE (3-conductor system: L1, N, PE), with integrated surge-proof fuse and remote indication contact. Also suitable for DC applications.

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

CBMC E4 24DC/1-4A NO - Electronic circuit breaker

2906031

<https://www.phoenixcontact.com/in/products/2906031>



Multi-channel electronic circuit breaker for protecting four loads at 24 V DC in the event of overload and short circuit. With electronic locking of the set nominal currents. For installation on DIN rails.

CBMC E4 24DC/1-10A NO - Electronic circuit breaker

2906032

<https://www.phoenixcontact.com/in/products/2906032>



Multi-channel electronic circuit breaker for protecting four loads at 24 V DC in the event of overload and short circuit. With electronic locking of the set nominal currents. For installation on DIN rails.

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

CBMC E4 24DC/1-4A+ IOL - Electronic circuit breaker

2910410

<https://www.phoenixcontact.com/in/products/2910410>



Multi-channel electronic circuit breaker with IO-Link interface for protecting four loads at 24 V DC in the event of overload and short circuit. With electronic locking of the set nominal currents. For installation on DIN rails.

CBMC E4 24DC/1-10A IOL - Electronic circuit breaker

2910411

<https://www.phoenixcontact.com/in/products/2910411>



Multi-channel electronic circuit breaker with IO-Link interface for protecting four loads at 24 V DC in the event of overload and short circuit. With electronic locking of the set nominal currents. For installation on DIN rails.

PS-EE-2G/1AC/24DC/120W/SC - Power supply unit



1234302

<https://www.phoenixcontact.com/in/products/1234302>

CBM E4 24DC/0.5-10A NO-R - Electronic circuit breaker

2905743

<https://www.phoenixcontact.com/in/products/2905743>



Multi-channel, electronic circuit breaker with active current limitation for protecting four loads at 24 V DC in the event of overload and short circuit. With nominal current assistant and electronic locking of the set nominal currents. For installation on DIN rails.

CBM E8 24DC/0.5-10A NO-R - Electronic circuit breaker

2905744

<https://www.phoenixcontact.com/in/products/2905744>



Multi-channel, electronic circuit breaker with active current limitation for protecting eight loads at 24 V DC in the event of overload and short circuit. With nominal current assistant and electronic locking of the set nominal currents. For installation on DIN rails.

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in